



## 3M™ Specialty Tape Solutions

### 3M™ Vinyl Tape 471

Solve a variety of challenges, including floor and safety marking, color coding and industrial applications with our durable 3M™ Vinyl Tape 471. Designed to resist wear, scrapes and moisture, this long-lasting tape is available in an array of vivid colors, as well as transparent.

#### Key Characteristics

- “Color throughout” resists scrapes, wear and weathering
- Colors available to help implement the 5S system
- Clean removal
- Extreme conformability and dead stretch means tape stays locked in place
- Chemical resistant
- Wide variety of vivid colors

#### Use For

- Durable marking of aisles and corridors in factories, warehouses, hospitals and retail spaces
- Marking of safety hazards on walls, stairs and pipes
- Fine line paint masking
- Sealing
- High visibility splicing
- Decorative trim
- Surface protection



#### Technical Parameters

<b>Adhesive</b>	Rubber
<b>Backing</b>	Vinyl
<b>Backing Thickness</b>	4.1 mils (0.10mm)
<b>Total Thickness</b>	5.2 mils (0.13mm)
<b>Temperature Use Range</b>	40°F to 170°F (4°C to 77°C)

\* To meet your safety requirements, consider 3M™ Safety Stripe Tapes 5700 and 5702.

# Specialty Six

Bringing better ideas to the surface  
with a wide variety of tape solutions.

3M™ Specialty Tape Solutions meeting application challenges for appliances, aerospace, automotive, construction, MRO, electronics, commercial transport, marine and more.

	<b>3M™ Aluminum Foil Tape 425</b>		<b>3M™ Polyester Tape 850</b>
	<b>3M™ Vinyl Tape 471</b>		<b>3M™ PTFE Film Tape 5490</b>
	<b>3M™ Glass Cloth Tape 361</b>		<b>3M™ UHMW-PE Tape 5423</b>

For more information, call **1-800-362-3550** or visit **3M.com/IATD**



**3M Industrial Adhesives and Tapes Division**  
3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
Phone 800-362-3550  
Fax 877-369-2923  
Web 3M.com/IATD

**Product Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. **Warranty, Limited Remedy and Disclaimer:** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M is a trademark of 3M. © 3M 2017. All rights reserved. Please recycle. Printed in USA. 70-0716-9835-4 3/2017