

Scotch®

High-Tack Box Sealing Tape 311+

Extreme performance. Everyday use.

- ✓ Extreme temperatures
- ✓ Highly recycled corrugated boxes
- ✓ General purpose, medium-duty box sealing for palletized shipments



3M
TM

Scotch® High-Tack Box Sealing Tape 311+

Great for medium-duty and everyday packaging applications — box sealing, splicing, tabbing, bag closures, and palletized shipments.



Food and Beverage



Ecommerce




General Industrial



Manufacturing

- Excellent performance over broad temperature ranges — including freezer and refrigeration temperatures of 20°F to 50°F (-6.6°C to 10°C).
- Adheres to a variety of surfaces, including on corrugated boxes with over 70% recycled content.
- Quick, easy application by hand, manual dispensers or 3M-Matic™ Case Sealers.
- Available in 48mm and 72mm widths.



Fiber Pull Test

Measures how much paper fiber the tape pulls off the box upon removal. The higher percent fiber pull, the stronger the tape bond is to the box. The following tapes tested were applied and pulled at 20°F (-6.6°C).



Product	3M Material ID	UPC	Size	Color	Tape Structure (Backing/Adhesive)	Adhesion to Steel oz./in. (N/100 mm)	Tensile Strength lbs./in. (N/100 mm)	Elongation at Break (%)	Backing Thickness mils (mm)	Total Thickness mils (mm)	Rolls/Case
ASTM Test Method						D-3330	D-3759	D-3759	D-3652	D-3652	
Scotch® High-Tack Box Sealing Tape											
311+	7100179523	50051128001610	48mm x 50m	Clear	Polypropylene/Acrylic	38 (42)	25 (438)	125	1.1 (.028)	2.05 (.052)	36
	7010306820	50051128000248	48mm x 100m								6
	7100253856	50638060536365	48mm x 914m								24
	7010355076	50051128001153	48mm x 1500m								4
	7100253843	50638060536358	72mm x 100m								36
	7010405992	50051128000279	72mm x 914m								6
	7010411725	50051128001405	72mm x 1500m								24
	7100179459	50051128001627	48mm x 100m								4
	7010506927	50051128001634	48mm x 914m								36
	7100179433	50051128001603	72mm x 100m								6
7010506928	50051128001641	72mm x 914m	24								
				Tan	Polypropylene/Acrylic	38 (42)	25 (438)	125	1.1 (.028)	2.05 (.052)	4



3M Closure and Masking Systems Division
3M Center, Building 220-3W
St. Paul, MN 55144-1000

Phone 800-362-3550
Fax 877-369-2923
Web 3M.com/packaging

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Scotch is a registered trademark of 3M. 3M, 3M-Matic and the Plaid are trademarks of 3M.
© 3M 2022. All rights reserved. Please recycle.