

# Hexagon Sockets for hexagonal screws

for internal square 3/8" or 1/2"

IEC 60900 DIN EN 60900

98



98 37 17  
⚡ 1000 V ○  $\frac{3}{8}$ "



98 47 17  
⚡ 1000 V ○  $\frac{1}{2}$ "



- > for metric hexagonal head screws
- > chrome plated
- > chrome vanadium steel

Product Number	Packaging	↔ Inch mm		Width across flats S Inch mm	dia. of effective tool side d max. Inch mm	Square drive Inch	⚖ lbs
98 37 10		1 21/32 42	⚡ 1000 V ○ $\frac{3}{8}$ "	25/64 10.0	47/64 18.7	3/8	0.07
98 37 11		1 21/32 43		7/16 11.0	25/32 20.0	3/8	0.08
98 37 12		1 3/4 44		15/32 12.0	53/64 21.2	3/8	0.09
98 37 13		1 49/64 45		1/2 13.0	57/64 22.5	3/8	0.09
98 37 14		1 13/16 46		35/64 14.0	15/16 23.7	3/8	0.10
98 37 16		1 13/16 46		5/8 16.0	1 1/32 26.2	3/8	0.12
98 37 17		1 13/16 46		43/64 17.0	1 5/64 27.5	3/8	0.12
98 37 19		1 59/64 49		3/4 19.0	1 3/16 30.0	3/8	0.14
98 47 10		2 1/8 54		⚡ 1000 V ○ $\frac{1}{2}$ "	25/64 10.0	3/4 19.5	1/2
98 47 11		2 1/8 54	7/16 11.0		13/16 20.7	1/2	0.15
98 47 12		2 11/64 55	15/32 12.0		29/32 23.0	1/2	0.14
98 47 13		2 11/64 55	1/2 13.0		29/32 23.2	1/2	0.15
98 47 14		2 11/64 55	35/64 14.0		31/32 24.5	1/2	0.16
98 47 16		2 11/64 55	5/8 16.0		1 1/16 26.9	1/2	0.19
98 47 17		2 11/64 55	43/64 17.0		1 7/64 28.2	1/2	0.18
98 47 18		2 11/64 55	45/64 18.0		1 9/64 29.0	1/2	0.19
98 47 19		2 1/8 54	3/4 19.0		1 13/64 30.7	1/2	0.22
98 47 22		2 9/32 58	55/64 22.0		1 23/64 34.5	1/2	0.28
98 47 24		2 13/32 61	15/16 24.0		1 29/64 37.0	1/2	0.34
98 47 27		2 31/64 63	1 1/16 27.0	1 19/32 41.0	1/2	0.42	