

3M™ Secure Click™ Half Facepiece Reusable Respirator Series HF-800

Description

The 3M™ Secure Click™ Half Facepiece Reusable Respirator HF-800 Series helps provide protection against certain airborne contaminants. For use with 3M Secure Click™ particulate filters and gas/vapor cartridges. Dual flow cartridges are designed for easy breathing.

Key Features

- Speaking diaphragm is designed to help provide easier communication while you work
- Dual flow cartridges and filters are designed for easy breathing
- Push button seal check helps provide improved confidence in respirator fit
- Quick, simple cartridge/filter connection
- Lower profile system designed for improved compatibility with face shields and weld shields
- Faceseal designed to sit lower on the nose bridge to help improve eyewear compatibility



Facepiece Options

Model	Size	Approximate Weight (grams)
HF-801SD	Small	186 g
HF-802SD	Medium	187 g
HF-803SD	Large	194 g

Approvals

HF-800 Series half facepieces are NIOSH approved for use with D8000 Series cartridges, D3000 Series filters, D9000 Series hardcase filters, and D7000 Series filters against a variety of gases, vapors, and particulate hazards.



Use




When properly fitted and used, these respirators may be used in contaminant concentrations up to 10 times the Permissible Exposure Limit (PEL) with approved 3M cartridges and filters. Not for use in environments that are immediately dangerous to life or health (IDLH) or in oxygen deficient environments.

Materials

Part	Material
Face seal	Silicone Rubber
Fascia	Thermoplastic
Inhalation/Exhalation Valve	Silicone Rubber
Speaking Diaphragm	Thermoplastic, Silicone Rubber, and Polyimide Film
Straps	Synthetic Fiber
Buckles	Thermoplastic

Spare Parts and Accessories

Part Number	Description	Image
HF-800-04	Head Harness Assembly, SD Version, 5/cs	
HF-800-02	Inhale/Exhale Valve, 10/cs	

HF-800-05	Speaking Diaphragm, 5/cs	
HF-800-03	Quantitative Fit Test Adapter Kit, 1/cs	
D701	Filter Retainer, 100/cs	

Secure Click™ Cartridges

Part #	Description	Particulates	OV	SD	HC	CI	CD	HF	HS	AM/MA	FM ¹	MV ²	Ozone ³
D8001	OV		X										X
D8002	AG			X	X	X	X	X	X				
D8003	OV/AG		X	X	X	X		X	X				
D8004	AM/MA									X			
D8005	FM/OV		X								X		
D8006	MG/V		X	X	X	X	X	X	X	X	X		
D8009	MV/MG		X	X	X	X	X	X	X	X	X	X	
D80921	OV/P100	X	X										X
D80923	OV/AG/P100	X	X	X	X	X		X	X				
D80926	MG-V/P100	X	X	X	X	X	X	X	X	X	X		
D80929	MV/MG/P100	X	X	X	X	X	X	X	X	X	X	X	

OV = Organic vapors	CD = Chlorine dioxide	FM = Formaldehyde
SD = Sulfur dioxide	HF = Hydrogen fluoride	MV = Mercury vapor
HC = Hydrogen chloride	HS = Hydrogen sulfide	AG = Acid gas
CI = Chlorine	AM/MA = Ammonia/Methylamine	MG-V = Multi Gas - Vapor

¹Half facepiece respirators cannot be used unless appropriate eye protection is also worn.

²3M™ Secure Click D8009 and D80929 cartridges must be discarded within 50 hours of use against mercury vapor; or according to service life for other gas/vapor, or when odors of vapors or gases become noticeable, whichever occurs first.

³3M recommended for ozone up to 1ppm for up to 40 hours

Secure Click™ Filters

Part #	Particulate Filter Class			HF	Ozone ¹	Nuisance OV ²	Nuisance AG ³
	N95	P95	P100				
D3071		X					
D3076HF		X		X			X
D3078		X				X	X
D3091			X				
D3096			X				X
D3097			X		X	X	
D7N11	X						
D7P71		X					
D9093			X				
D9093C			X	X		X	X

3M Personal Safety Division

¹D3097 is 3M recommended for use against up to 1ppm ozone for up to 8 hours. Not NIOSH approved for ozone.

²Nuisance level refers to concentrations not exceeding the OSHA PEL or applicable government occupational exposure limits, whichever is lower.

HF = Hydrogen fluoride

OV = Organic vapors

AG = Acid gases

 **WARNING**



This product helps protect against certain airborne contaminants. **Misuse may result in sickness or death.** For correct use, consult supervisor, *User Instructions* or call 3M in U.S.A., 1-800-243-4630. In Canada, call Technical Service at 1-800-267-4414.



Personal Safety Division
3M Center, Building 235-2W-70
St. Paul, MN 55144-1000

3M PSD products are occupational use only.

3M Canada
P.O. Box 5757
London, Ontario
N6A 4T1

In United States of America
Technical Service 1-800-243-4630
Customer Service 1-800-328-1667
3M.com/workersafety

In Canada
Technical Service 1-800-267-4414
Customer Service 1-800-364-3577
3M.ca/Safety

© 3M 2024. All rights reserved.
3M and Secure Click are trademarks of
3M Company and its affiliates.

Used under license in Canada. All
other trademarks are property of their
respective owners.
Please recycle.