

3M[™] Tabbing Tape 5400

Technical Data Sheet



Description

3M™ Tabbing Tape 5400 is a clear, heat-bondable film that provides a strong bond to many polyolefin release liners found on most 3M™ Acrylic Foam and 3M™ Acrylic Plus Tapes (non-silicone versions). Used in conjunction with heat-bond tab application equipment, 3M Tabbing Tape 5400 provides a reliable means of liner removal in a production environment.

Physical Properties and Typical Performance Characteristics

Color	Clear
Approximate Thickness	0.10 mm (0.004 in)
Tensile Strength, M.D. Break	3.4 kgf/cm width (19.0 lbs/in width)
Elongation at Breakage, M.D. Break	80%
Area Factor	10.4m²/kg (7300 in²/lb)
Tear Strength (Elmendorf) M.D.	70.0 grams/ply
Thermal Use Temperature range	149°-204°C, (300-399°F) 0.2 to 2.0 seconds, .07 to 4.2 kgf/cm² (10-60 psi)

Shelf Life

36 months from date of manufacture when stored at 4°C–38°C (40°F–100°F) and 0–95% relative humidity (RH). The optimum storage conditions are 22°C (72°F) and 50% relative humidity.

Regulatory Information

To obtain published IMDS ID numbers, email requests to 3M-IMDSrequest@mmm.com.

Technical Data Sheet 3M™ Tabbing Tape 5400

2

Contact Information

The information provided in this technical document is intended as a guide for this product. For more information or help in selecting a 3M product for an application, please contact your 3M technical service representative or call 1-800-328-1684.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive and Aerospace Solutions Division 3M Center St. Paul, MN 55144-1000 1-800-328-1684 3M.com/autosolutions