Rapidaptor Bit Holders





- Rapidaptor technology for rapid bit change
- Rapidaptor universal holder with ring magnet for bits with 1/4" hexagon drive
- 1/4" hexagon drive

Rapidaptor universal holder for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173). The Rapidaptor allows mounting the bits without using the sleeve. The bit is removed by simply pushing it forward - for lightning-fast bit changes, even with just one hand. The strong permanent magnet holds the bits firmly. 1/4" hexagonal, suitable for screwdriver machines with mounting as per DIN ISO 1173-F 6.3.

Rapidaptor Bit Holders

H Were Be 4 TOOL Rel

Magnetic

Rapidaptor holder

Chuck-all



The Rapidaptor quick-release chucks hold 1/4" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Bitholders, magnetic, for easier

application of the screw

Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.



Rapid bit change without needing

any additional tools. One-hand

operation with a freely spinning

sleeve for simplified guidance of

the tool. Also available in a

BiTorsion design.

Rapid-spin

The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for 1/4" applications e.g. in combination with the Wera Zyklop Ratchets.

Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Further versions in this product family:

		L ▼	L ▼	0	Ø
	inch	mm	inch	inch	mm
05052503001	1/4"	75	3"	1/4"	15.0