



|                        |                |                               |           |
|------------------------|----------------|-------------------------------|-----------|
| <b>EAN:</b>            | 4013288226846  | <b>Size:</b>                  | 89x7x6 mm |
| <b>Part number:</b>    | 05060515001    | <b>Weight:</b>                | 19 g      |
| <b>Article number:</b> | 867/4 TORX® HF | <b>Country of origin:</b>     | CZ        |
|                        |                | <b>Customs tariff number:</b> | 82079030  |

- For TORX® socket screws
- Holding function for recessed TORX® screws
- Also suitable for Würth ASSY screws as well as Altenloh SPAX T-STAR plus screws
- 1/4" hexagon drive (Wera connecting series 1)
- With Take it easy tool finder: colour coding by size

Premium bits for TORX® socket screws. The TORX® HF (HF = holding function) tools developed by Wera stand out with the geometric optimization of the original TORX® profile. The clamping force resulting from the seating stress between the tip and the screw profile keeps the screws securely on the tool! Also suitable for Würth ASSY screws as well as Altenloh SPAX T-STAR plus screws. Take it easy tool finder with colour coding by size. 1/4" hexagonal, suitable for holding tools as per DIN ISO 1173-F 6.3.

#### Web link

Wera - 867/4 TORX® HF  
05060515001 - 4013288226846


Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**Holding function for recessed TORX® screws**




The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

**Take it easy tool finder system**







Depending on their size, the 867 TORX® HF bits have different coloured bands with size stamping which make the required bit quickly accessible.

**Also for ASSY and SPAX T-STAR plus screws**



The Wera 867/4 TX HF bits are also suitable for Würth ASSY screws as well as Altenloh SPAX T-STAR plus screws.

**Further versions in this product family:**

|                           |  |  |  |  |
|---------------------------|---|---|---|---|
|                           |   | mm  | inch  | mm  |
| 05060505001               | TX 8  | 50  | 2"  | 3.0   |
| 05060506001               | TX 10   | 50  | 2"  | 4.0   |
| 05060507001               | TX 15   | 50  | 2"  | 4.0   |
| 05060508001               | TX 20   | 50  | 2"  | 4.5   |
| 05060509001               | TX 25   | 50  | 2"  | 6.0   |
| 05060510001               | TX 30   | 50  | 2"  | 6.0   |
| 05060511001 <sup>1)</sup> | TX 40   | 50  | 2"  | -   |

1) Pound-thru hexagonal; no Take it easy.

**Web link**

Wera - 867/4 TORX® HF  
05060515001 - 4013288226846

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de