7400 series Kraftform Torque screwdrivers, with factory pre-set value (0.3-3.0 Nm) and Rapidaptor quick-release chuck, handle size 105 mm, 7460 x 0.3 Nm x 0.3-1.2 Nm

Size:

Weight:

number:

Country of origin:

Customs tariff

Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value













- Factory pre-set torque screwdriver with Rapidaptor quick-release chuck
- Only adjustable with an extra tool

EAN:

Part number:

Article number:

- Suitable for bits with 1/4" hex head drive
- Rapidaptor technology for rapid bit change

4013288102911

7400 pre-set, 105 mm

05074715001

- Distinct signal when pre-set value is reached
- Multi-component Kraftform handle for high working speeds

Wera torque screwdrivers. With a factory pre-set torque value set to the smallest scale value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed with an extra tool within the measuring range (re-calibration kit can be ordered with the code number 05137001001). Afterwards you can check the set value using an off-the-shelf torque tester. Unlimited loosening torque for slackening stuck screws. Rapidaptor quick-release technology for rapid bit changes. Suitable for bits with a 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173). Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Please note: 1 Ncm = 0.01 Nm.

155x37x37 mm

180 g

82054000

CZ


7400 series Kraftform Torque screwdrivers, with factory pre-set value (0.3-3.0 Nm) and Rapidaptor quick-release chuck, handle size 105 mm, 7460 x 0.3 Nm x 0.3-1.2 Nm

Pre-set, adjustable torque

Wera Be 4 TOOL Rebel

Versatile

Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value



Wera torque screwdrivers. With a factory pre-set torque value set to the smallest scale value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed with an extra tool within the measuring range (re-calibration kit can be ordered with the code number 05137001001). Afterwards you can check the set value using an off-the-shelf torque tester.



Unlimited torque

Unlimited torque for loosening seized screws.



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

Web link https://products.wera.de/en/torque_tools_series_7400_kraftform_torque_screwdrivers_with_a_factory_pre-set_measurement_value_7400_pre-set__105_mm.html

7400 series Kraftform Torque screwdrivers, with factory pre-set value (0.3-3.0 Nm) and Rapidaptor quick-release chuck, handle size 105 mm, 7460 x 0.3 Nm x 0.3-1.2 Nm



Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value

Chuck-all

Rapid-in and self-lock

Rapid-out

Kraftform



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After а long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

Further versions in this product family:

| | | | | +++ ++++ | | ∏ ▲ U v | ∏ ▲ U v |
|---------------------------|----------|------|-----|-------------------|-----|------------|------------|
| | art. no. | inch | Nm | Nm | mm | mm | inch |
| 05074715001 ¹⁾ | 7460 | 1/4" | 0.3 | 0.3-1.2 | 105 | 155 | 6" |
| 050747160011) | 7461 | 1/4" | 1.2 | 1.2-3.0 | 105 | 155 | 6" |

1) The preset torque can be changed. However, this requires the use of special tools and Torque Test Equipment. Please contact the Wera Torque Service.