

Kraftform 100 iS/7 set 2 Screwdriver set Kraftform Plus series 100. Partly with reduced blade diameter, 7 pieces



| | | | |
|------------------------|--------------------------|-------------------------------|---------------|
| EAN: | 4013288218155 | Size: | 275x175x60 mm |
| Part number: | 05136022001 | Weight: | 843 g |
| Article number: | Kraftform 100 iS/7 Set 2 | Country of origin: | CZ |
| | | Customs tariff number: | 82054000 |

- 6-piece VDE screwdriver set in compact, textile box with Wera 2go compatibility
- Insulated tools, blades partly with reduced diameter for safe working at up to 1,000 Volt
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Take it easy tool finder: colour coding according to profile and size
- With Wera bottle opener

6-piece VDE screwdriver set, includes some tools with reduced blade diameters and integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated. Kraftform Plus handle for comfortable ergonomic screwdriving, which avoids blisters and calluses. Hard handle zones for high working speeds, while soft handle zones guarantee high torque transfer. Take it easy tool finder with colour coding and size stamping - for easy and fast location of the required tool. The anti-roll protection avoids bits from annoying rolling away in the workplace. Plus iconic Wera bottle opener.

Web link

Wera - Kraftform 100 iS/7 Set 2
05136022001 - 4013288218155



Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Kraftform 100 iS/7 set 2 Screwdriver set Kraftform Plus series 100. Partly with reduced blade diameter, 7 pieces



Suitable for Wera 2go




The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



Suitable for docking with the Wera 2go system.

VDE-insulated screwdriver with reduced blade diameter



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

Individually tested



Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

Impact strength test




Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces - resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

"Take it easy" Tool Finder



Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.

Convenient



Plus iconic Wera bottle opener.



Web link


Wera - Kraftform 100 iS/7 Set 2
05136022001 - 4013288218155

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de




Set contents:


162 iS PH VDE Insulated screwdriver with reduced blade diameter for Phillips screws, PH 1 x 80 mm

| | | | |
|---|-------------|----|---------------|
|  | 05006450001 | 1x | PH 1 x 80 mm |
|  | 05006451001 | 1x | PH 2 x 100 mm |




160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws, 0.6 x 3.5 x 100 mm


| | | | |
|---|-------------|----|--------------------|
|  | 05006440001 | 1x | 0.6 x 3.5 x 100 mm |
|  | 05006442001 | 1x | 1 x 5.5 x 125 mm |
|  | 05006441001 | 1x | 0.8 x 4 x 100 mm |



160 i VDE Insulated screwdriver for slotted screws, 0.4 x 2.5 x 80 mm

| | | | |
|---|---------------------------|----|-------------------|
|  | 05006100001 ¹⁾ | 1x | 0.4 x 2.5 x 80 mm |
|---|---------------------------|----|-------------------|

1) without Lasertip



Bottleopener red/yellow, 145

1x 145



Hook and Loop Fastener Strip 240, 50 x 240 mm

1x 50 x 240 mm



Web link