

PRO[®] DUCT 110

General Purpose Duct Tape



Technical Data Sheet

Pro[®] Duct 110 is a general purpose duct tape used for a wide variety of applications.

Features & Benefits:

- Easy to apply
- Conforms well to irregular surfaces
- Handles easily
- Good tensile strength, adhesion and tack
- Economically priced
- Resists twisting & curling

Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Polyethylene coated cloth
- ⇒ Thickness: 9 mils
- ⇒ Tensile strength: 24 lbs. per inch
- ⇒ Elongation: 20%
- ⇒ Adhesion to steel: 70 oz./in
- ⇒ Colors: Silver, Black, Tan, Brown, Red, Olive Drab, White, Blue, Green, Yellow, Burgundy
- ⇒ Service Temperature Range: 40°F to 200°F
- ⇒ Low VOC Content

Application:

Pro[®] Duct 110 is used for general repair and general purpose abatement and contractor uses. Pro[®] Duct 110 is commonly used for bundling, patching, mending, carton sealing, book repair and color coding.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.