


SPECIFICATIONS LED WALL LAMP Input Voltage 100-120V ~ 60Hz Input Current 0.5A 0.5A 0.38A 0.58A 45W 55W 55W 70W Rated Power Luminous Flux 5500lm 4000lm 6200lm 5500lm Model BDD100-3 BDL40-3 BDB100-3 BDB36-3 Input Voltage 100-120V ~ 60Hz 0.35A 0.83A 0.83A 0.3A Input Current 40W 100W Rated Power 4000lm 9000lm CCT 6500K CRI ≥80 Power Factor ≥0.9 L₇₀B₅₀ lifetime 30000hours L₇₀B₅₀ @ 25° Beam Angle -20-40°C/-4°F-104°F SUITABLE FOR WET LOCATIONS Luminaire Locatio





NOTE:

Before beginning assembly of product, make sure all parts are present. Compare parts with parts list. If any part is missing or damaged, do not attempt to assemble the product. Estimated Assembly Time:30-60 minutes.

Recommended to be installed on the ground above 2.5m (8.2 ft) and no higher

Product appearance may vary from image shown.

TOOLS REQUIRED (not included



WARNING:

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

CAUTION:

PLEASE MAKE SURE YOUR WALL SWITCH AND POWER AT MAIN CIRCUIT BREAKER BOTH ARE OFF.

IF IN DOUBT ABOUT ELECTRICAL INSTALLATION, CONSULT A LICENSED ELECTRICIAN.

PREPARATION

RISK OF SHOCK:

BEFORE BEGINNING INSTALLATION, TURN OFF ELECTRICITY AT THE CIRCUIT BREAKER BOX OR THE MAIN FUSE BOX.

BE SURE TO USE WIRE NUTS/CONNECTORS RATED FOR THE CORRECT GAUGE AND NUMBER OF WIRES USED.


MAKE SURE THERE ARE NO EXPOSED WIRE BUNDLES OUTSIDE THE WIRE NUT/CONNECTOR (IF APPLICABLE). BE CAREFUL NOT TO DAMAGE OR CUT THE WIRE INSULA-TION (COVERING) DURING INSTALLATION. DO NOT LET THE **WIRES TOUCH ANY SHARP EDGES.**

WARNING:

DO NOT CONNECT THIS LIGHT FIXTURE TO AN UNGROUNDED ELECTRICAL SYSTEM. ATTACH GROUND FIXTURE WIRE TO EITHER GREEN GROUND SCREW ON MOUNTING PLATE OR THE GROUND WIRE IN THE OUTLET BOX.

INSTALLING THIS LIGHT IN AN UNGROUNDED ELECTRICAL SYSTEM MAY CAUSE THE METAL PARTS OF THE LIGHT TO CARRY CURRENT IF ANY WIRES OR WIRE CONNECTIONS ARE DAMAGED OR LOOSE. IN THIS CASE, ANYONE WHO TOUCHES THE LIGHT WILL RECEIVE AN ELECTRIC SHOCK, RESULTING IN INJURY OR DEATH.

INSTALLATION STEPS FOR WET LOCATION, MAKE SURE FILL FULL THE GAP OF EVA GASKET AND MOUNTING



nnaught Road West, Sai Wan Hong Kong rrer/Hersteller: MDH LIGHTING LTD 292 Strovolos Avenue, 2048 Strovolo Made in China

(€

(€