

CLEANING SEALING & AFTERCARE

EXTERNAL STONE SEALER TECHNICAL DATA SHEET

REF: 36/5/1 FEBRUARY 2021



LTP EXTERNAL STONE SEALER

Water-based impregnating sealer

For exterior use

Moisture-repellent and stain resistant. Delicately enhances appearance. Helps prevent moss and mould formation. Protects against weathering and efflorescence. UV Resistant and non-yellowing. Breathable. Suitable for use on all types of external masonry including natural and artificial stone, limestone, sandstone, slate, brick and concrete paving.

Directions for use:

Preparation New surfaces: Ensure surface to be treated is as clean and as dry as possible. If necessary, first wash surfaces down with a dilute solution of **LTP Grimex** (1:10). Scrub well using a white pad. Rinse well and leave overnight to dry.

Preparation Older surfaces: Remove blackspot, algae, mildew and stains from detritus use **LTP Blackspot & Algae Remover**. Apply to surfaces undiluted and leave for up to 5 hours. Rinse and leave to dry.

Sealing: Shake bottle well before use. Apply evenly to the surface using a foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is completely saturated. Remove any residual sealer if still visible after one hour.

Coverage (M² per coat)

	1ltr	5ltr
Lower porosity surfaces	15m ²	75m ²
Higher porosity surfaces	7.5m ²	37.5m ²

Aftercare:

Routinely sweep surfaces to keep them free from organic matter. Surfaces can be washed on a regular basis with **LTP Waxwash**.

Storage information:

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 2 years for un-opened containers.

Other:

Dried on over applied sealer can be removed by wiping up undried solution after 1 hour. If excess is left to dry and is still visible: Use soap and water and gently scrub with a white nylon scrubber, rinse and leave to dry.

On higher porosity surfaces, sufficient sealer should be applied until treated surfaces are fully saturated. Do not apply when surface temperatures are under 5°C or over 25°C. Clean application tools and brushes with water after use.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound.

Health, Safety & Environmental:

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5)

Keep out of reach of children.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN UK

