

ViziPrint®

Impress Clear

Our optically clear printable window film is designed for trouble-free installation of graphics on glass surfaces. ViziPrint® Impress Clear utilises a low tack hybrid adhesive technology that creates a strong bond in both high and low temperatures without leaving residue behind. This adhesion technology also eliminates bubbling and is unaffected by moisture. Since it uses a mechanical bond to gently adhere images to windows, the glass stays clear and graphics stay bright whenever ViziPrint® Impress Clear is re-positioned and re-applied. The film is ideal for high quality decals, signage and retail window advertising.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE


Product Code: VPI & VPI-SEL

UV	SEL		
100	125	Optically Clear	<input type="checkbox"/>
micron	micron	PET	Gloss



	UV	SEL
	UV	(Eco) Solvent Latex UV

 **Hybrid Adhesive Technology**

 Widths up to 1524mm

3 YEARS DURABILITY INTERIOR **6** MONTHS DURABILITY EXTERIOR

BEAUTIFUL OPTICALLY CLEAR GRAPHICS



APPLICATIONS

- Smooth Flat Surfaces
- Retail Displays
- Window Graphics
- Decals & Stickers

Certified for HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at hp.com/go/mediasolutionslocator



DRYTAC®
ADHESIVE SCIENCE

ViziPrint®

Impress Clear

ViziPrint® Impress Clear is an optically clear PET film with hybrid adhesive technology that is protected by a clear, 1 side siliconised release liner. Its proprietary adhesion technology creates a strong bond in both high and low temperatures without leaving residue behind, eliminates bubbling and is unaffected by moisture. ViziPrint® Impress Clear can be re-positioned and re-applied multiple times, and removes cleanly up to 3 years after installation.

- IDEAL FOR APPLICATIONS ON GLASS AND OTHER SMOOTH, FLAT SURFACES *surfaces.*
- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- CAN BE USED ON ELECTRONIC EQUIPMENT, SUCH AS TV SCREENS, IPAD/TABLET DISPLAYS AND COMPUTER MONITORS, AS WELL AS REFRIGERATORS, GLASS DISPLAY CASES.
- REVERSE PRINTABLE FOR INSIDE MOUNTING OF WINDOW ADVERTISEMENTS.

INSTALLATION RECOMMENDATION

Wet or dry installation will work for ViziPrint® Impress Clear. Please see ViziPrint® Impress Clear installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Optically Clear PET
Adhesive	Hybrid Adhesive Technology
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

	ViziPrint Impress Clear UV	ViziPrint Impress Clear SEL
Film Thickness	4 mil (100µ)	5 mil (125µ)
Outdoor Durability	6 months	
Application Temperature	>23°F (-5°C)	
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PRINTING RECOMMENDATIONS

- Handle material with care prior to printing; use gloves to avoid finger prints.
- Printing temperature should be 59-86°F (15-30°C) with 30-60% humidity.
- Set printer to highest print setting for optimal print quality.
If mounting on glass or backlit substrates, evaluate colour density of the print on a window or in transmitted light.

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com