





### Specifications

	ltem	UCJV300-160	UCJV150-160		
Print head		On-demand piezo head			
Print resolution		300 dpi, 600 dpi, 900 dpi, 1,200 dpi			
Max. print width		1,610 mm (63.4 in)			
Max. media width		1,620 mm (63.8 in)			
Ink	Туре	LED-UV ink LUS-170			
	Color	4C (C, M, Y, K) 7C (C, M, Y, K, Lc, Lm, W)	4C (C, M, Y, K)		
	Capacity	1 L (Bottle	1 L (Bottle supply)		
Media thickness		1.0 mm or less			
Media roll weight		40 kg (88.2 lb) or less			
Media roll outer diameter		1 == = :::::: (=	arphi250 mm (9.8 in) or less		
Cut speed		Max.300 mm/s (420 mm/s in 45 degrees direction)			
Cut pressure		10 - 450 gf			
Cutter types		Eccentric cutter, Blade for small character, Blade for reflective sheet			
		Blade for fluorescent sheet, Blade for PVC with low-pressure			
Interface		USB2.0 / Ethernet 1000 BASE-T			
		VCCI Class A / FCC Class A / Compliant with UL 60950-1, ETL /			
Safety stando	ard	CE Marking (EMC, Low Voltage, Machinery Directive), RoHS/			
		CB Report / REACH • ENERGY STAR / RCM			
Power supply		Single phase (AC100 - 120/200 - 240 V±10%, 50/60 Hz±1 Hz) x2			
Power consumption		AC100V : 1.44 kW / AC200 V : 1.92 kW x 2 or less			
Operational environment	Temperature	20 - 30 degC (68 - 86 degF)			
	Humidity	35-65% Rh (Non condensing)			
	Recommended temperature	20 -25 degC (68 - 77 degF)			
	Temperature gradient	±10 degC (±50 degF)/h or less			
	Dust level	Equivalent to normal office level			
Outside dimension (W x D x H)		2,900 x 776 x 1,475 mm (114.2 x 30.6 x 58.1 in)			
Weight		188 kg (414.5 lb)	183 kg (403.4 lb)		

#### Supplies

1 1				
Product name	Color	Item code	Remarks	
	Cyan	LUS17-C-BA		
	Magenta	LUS17-M-BA		
LED-UV ink	Yellow	LUS17-Y-BA		
LUS-170	Black	LUS17-K-BA	1L bottle	
LU3-1/U	White	LUS17-W-BA		
	Light Cyan	LUS17-LC-BA		
	Light Magenta	LUS17-LM-BA		

Newly upgraded RIP software with higher functionality and more user-friendliness
RASTER LINK 5 PLUS
Added useful functions  ID Cutl for consecutive cutting Multi layers print for wider expressiveness  Braille print for easy operation of braille print.
PDF including transparent effect is applicable.  PDF data image with transparent effect is faithfully printable as the original.

contact us for more information 01772 250207 sales@granthams.co.uk


samples and private demonstrations available upon request

SIGN











Excellent model focused to UV-LED printing technology and Print & Cut function with high cost-performance. It can meet various demands of customers quickly.







# *UCJV300-160* UCJV150-160

UV-LED print enhancing the work


efficiency

Leading the Future of Sign Graphics through

UV Innovation

# Immediate processing and deliver are available by UV-LED.

With the UV ink property of immediate curing upon UV light irradiation no drying time is required. The post-processing and sign applying are possible instantly. Required time for production is saved to be possible to undertake even an order of tight scheduled work. It is immune from ink blocking while printing by multi layers or using white ink. There is no necessity to mind media stains nor to attend by operator.




4 layers print


enabling a new

advertisement expression






High speed! UV-LED print by max. print speed 25.8 sqm/h



### Possible to print the wider range of materials! Broadening application.

UV ink is printable to PVC and tarpaulin which are compatible with solvent, as well good matching with fabric, non specified ink-receiving paper and PET. More varied applications with UC|V300-160 due to mountable white ink.







## Design is changing with backlight, [Day & Night Printing]

print\*. [Day & Night Printing], a visible design change is presented by backlighting of 4 layers print of [Color]+[Black]+[White]+[Color]. A proposal of highly designed sign can be put forward without any retouches of current simple light box but just ON/OFF of internal lamp. It can make a graphic change or an illumination of specified area etc.





[Back light ON]



# The pre-check of final image is possible by [RasterLink6Plus]

The final image of 4 layers print is available on the monitor of Illustrator operation by [RasterLink Tools], the Plug-in tool of Adobe Illustrator of Mimaki RIP software [RasterLink6Plus]. The check of ON/OFF image of inside lighting before print is available by the monitor of PC. It saves retry of print to reduce



[ID Cut] can help to cut easily even for multiple types data of small lot of each. [ID Cut] is to print together ID (Barcode) for recognition of cutting details and

stickers and car wrapping film by one unit only.


Immediate materializing an image idea by

Print & Cut

Ecology

by the newly developed ink

then cut data of every print data is readable to start cutting automatically Then with this function, cutting starts without any respective cutting order by



[UC]V300/150-160] is equipped with cutting function of high performance and high efficiency to be able to make labels,

### Continuous registration mark detection

Continuous reading of registration marks arranged on the RIP an revision of cutting position based on the read marks for accurate c

#### Print & Cut without registration marks

Cutting is available without registration marks for minimum loss

### Intermediate registration mark detection

For a correct cut of long outline by multiple corrections of position



Mimaki's print technology in pursuit of essential beauty

Business solution

# [MAPS4\*] to reduce banding

MAPS function makes the banding less visible b where the banding is conspicuous while printing It can reduce generation of banding and unever



#### Mimaki Waveform Control Technology for high quality print

By Mimaki's originally advanced ink discharging control, jetting ink drops in straight with almost a perfect circle dots to accomplish high accuracy dot placement to the media. Thanks to apply UV ink of instant curing, very fine line for maps can








#### [NRS\*] maintains the productivity

[NRS] is mounted as when a problem occurs in some nozzles, other nozzles will take place to continue to print. Without the stop operating of wait of arrival of service staff, the productivity is maintained.

# Preventing print failure by [NCU\*]

Mimaki original system [NCU] is mounted to check the nozzle status automatically. When a nozzle clogging is found, auto cleaning is executed to eliminate it. If it does not help. NRS performs to recover the nozzle automatically to restart the print.



#### not interfering Newly developed ink, [LUS-170] adaptive to environment, generates hardly VOC and can cure without the by continuous running

is based on most strict global standard of chemical substance diffusion, assuring the product propert conforms to schools and medical facilities. It is surely considered to environment and safety

Newly developed environmentally friendly UV ink, [LUS-170]



which allows stable printing Mounted [MCT] of periodical white ink circulation suppressing the sedimental

tion of pigment. Preventing the ink trouble and it supports stable printing from starting of printer. Moreover MCT can contributes to the control of ink waste too, to be effective environmentally and economically.