

119 Lurgan Ave, Suite C Shippensburg, PA 17257 PHONE: 717.300.1311

EMAIL: i@needrubbernow.com www.americanmaterialsupply.com





## ADHESIVE BACKED NEOPRENE RUBBER

NAME: NEOPRENE W/PSA ONE SIDE

RUBBER: POLYCHLOROPRENE -- ADHESIVE: ACRYLIC

Fuel Resistance: GOOD Tear Resistance: GREAT Solvent Resistance: GREAT

Oil Resistance: GOOD

Aging Weather / Sunlight: EXCELLENT

<<<< RESISTANCE

40-70 DUROMETER

Tensile Strength: 800 psi

Elongation Max: 250%

ADHESIVE: 3 MIL - 5 MIL TOTAL WITH

ADESIVE: ACRYLIC

Rubber Temperature: -20 F° to 180 F°

Adhesive Temperature: -30 F° to 200 F°

<<<< TEMPERATURE

## **ADHESIVE IS CLEAR**

\*\*\*Our rubber products are blended of various polymers formulated to meet stated physical specifications.

Recommendations made by American Material Supply in its product literature relating to applications of the rubber are believed to be reliable, but we make no warranty of results to be obtained since the conditions of the end application by Buyer and others are beyond American Material Supply's control.\*\*\*