



# 1808 TELEPHONE ENTRY SYSTEM



IDEAL FOR RESIDENTIAL AND SMALL COMMERCIAL  
OR APARTMENT APPLICATIONS



surface mount



surface mount with built in  
directory/message window

- Provides visitor access control in residential or commercial applications
- Visitors use the 1808 to communicate with a resident, who can then grant or deny them access from their touch-tone phone
- Provides service for up to 1000 residents
- Programmable directory codes can be set from 1 to 4 digits
- 2 year limited factory warranty



**flash entry codes**  
allow entry on a single day only, then  
automatically deactivate themselves



**dtmf tone output**  
useable with PBX, KSU and telephone  
systems with auto-attendants



**led lighting**  
illuminates keypad and directory



**modular design**  
makes installation and service easy



# 1808 TELEPHONE ENTRY SYSTEM

## 1808 Surface

with and without directory/message window

11" W x 7.5" H x 6.5" D

(27.9cm W x 19cm H x 16.5cm D)



1808	PHONE # MEMORY	ENTRY CODES	DEVICE CODES	RELAYS	DIRECTORY	ELEVATOR CONTROL	PROGRAMMING OPTIONS	OPTIONS	TRANSACTION BUFFER
<b>Surface Mount</b>	1000	1000 (4-digit) 6 (5-digit)	N/A	2	-	-	System Keypad or Touch-Tone Telephone	-	-
<b>Surface w/Directory</b>	1000	1000 (4-digit) 6 (5-digit)	N/A	2	Paper	-	System Keypad or Touch-Tone Telephone	-	-

## Technical Features

### Mechanical

- Stainless steel faceplate
- Galvanized steel sub-plate
- Metal keypad
- Offset speaker holes for protection
- Hands free voice operation (Optional handset available on surface mount style only)
- Surface mount with lighted key pad

### Electrical

- 16 VAC (power transformer included)
- Full Duplex voice communication
- Stores up to 1000 phone numbers, 10 area codes
- Programmable directory codes (1 to 4 digits)
- 10 & 11 digit dialing capability
- DTMF tone output allows for use with PBX and auto-attendant type phone systems
- Four-digit entry codes (1000)
- Five-digit entry codes (6)
- Built-in clock / calendar provides automatic relay activation
- Entry code time zones
- Hold open time zones (4)
- Flash entry codes (8)
- Time zone restrictions on selected entry codes
- Two relays to control two entry points
- Two special inputs can be programmed for relay activation or dial-out function

### Miscellaneous

- Environmental: 10°F to 145°F (-12°C to 62°C)
- Available with small built-in directory (not lighted)
- Camera Ready: Optional B&W or Color CCTV camera\*  
\*may require additional CCTV equipment
- Shipping weight approximately 15-20 Lbs (6.8-9 kg)



FCC (US) DUF6VT-12874-0T-0  
DOC (CAN) 1736 4507 A



Access Control Solutions since 1948

Distributed by:

### MEMBER:



### DOORKING®, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.  
Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2012 All Rights Reserved. Product specifications may change without notice.  
Rev. 9/12