



SWING GATE OPERATOR

700_{LBS} CAPACITY

NEW



RESIDENTIAL
CLASS I VEHICULAR SWING GATE OPERATOR



- Convenient Fuse Access
- High Voltage L.E.D. Status Indicators
- Convenient Power Switch
- E-Z Set-up 115V/230V

Quick Release Handle for Manual Operation

- New "VFlex" Control Board**
- Diagnostics, Settings, and Status Display
 - Conveniently Labeled Enclosure
 - Ergonomically Located

Battery Included: True Battery Back-up

Convenient J-Box for High Voltage Wiring

Built-In Heater:

- Cold Weather Operation Down to -20°F



COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for the Viking wireless expansion products.



PROTECTION

- Multi-Layer Corrosion Protection
- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder coating



INTEGRATED HEATER

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



BATTERY BACKUP INCLUDED

- Standard Battery Backup provides 400 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.



SOLAR SMART

- Power Saving technology minimizes current draw while at standby.



LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps.
- On board surge protection monitoring.



DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	...24 VDC
Main Power Source Options	...115 / 230 VAC Single Phase 24 AC/DC Solar Compatible
Battery	...12 VDC x 2
Max Gate Capacity	...700 lbs / 14'
Operating Speed	...13-16 seconds per 90°
Battery Backup	...400 full continuous duty cycles (600 lbs)
Maximum Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 20° F to + 160° F

WARRANTY:
5 YEAR RESIDENTIAL

- VIKING WIRELESS**
- SOLAR EFFICIENT OPERATION**



www.vikingaccess.com • 800 908 0884