Sapphire Infrared Transmitter IRT-60











Sapphire Pendant infrared transmitter/microphone with rechargeable Lithium-ion battery and unidirectional microphone for true voice reproduction and excellent feedback suppression.

Specifications

1			i cuture
	Transmitter Carrier Transmission Frequencies Channel Switchable A or B Transmitting Diodes Modulation Pilot Tone Frequency Peak Deviation Operating Range Battery Discharge Indicator Blue Purple Red Flashing Red Battery Used Battery Used Battery Life External Power Charger Transmission Angle User Controls	Field Switchable Six FM Wide-Band 32.768 KHz ± 25KHz 1,500 Ft ² . 60 Ft. Line of Sight	 Elegant Only 1.4 Long life Recharg Battery I Back li Moment Backligh Push "or Channel Three ler (HIGH, N Auxiliary Low pro Wear with
	Power Switch (Push) Mute Switch (Push)	On/Off On/Off	Matrix, Fo Receiver//
	Mic Switch (3 position) Aux. Vol/Gain Channel Select External Aux Input Dimensions (H x W x D) Weight	Normal, - 3db, -6dB Increase, Decrease (A or B) in battery compartment 3.5mm Stereo Line Level 3 in x 1 ¼ in x ¾ in 1.4 oz including battery	SecurityTeacheraux-mic

Features

- Design
- 4 oz. including battery
- e "Lithium ion" battery
- geable via micro USB cable
- level indicator light under power switch
- itary mute button, ht blinks in mute mode
- on/off" power
- el A or B selectable
- evel mic volume switch MID, LOW) Normal, - 3db, -6dB
- y input (3.5mm)
- ofile clip for mounting
- ith a lanyard or directly to neckline collar

witch features only function with orum232, Maxim III and Spectrum III Amplifier/

- Alert activation
- Priority over aux/line inputs
- input volume Up-Down



