# G-170 S

#### G-170 Gravity Enduro Suspension - 170mm

SRP £2,399



	Colour	Matt Blue with Orange/Denim/Sky				
	Sizes Available	S,M,L,XL				
	Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts				
	Fork	RockShox Yari RC, 27.5", 170mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate				
	Rear Shock	RockShox Deluxe R, Fast Black Coating, Adjustable Rebound				
	Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing				
	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 148mm Boost Through Axle, 32 Hole				
	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole				
	Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples				
	Rims	WTB STp i29 Rims with TCS System, Pinned Joint, Tubeless Ready				
	Tyres	WTB Convict TCS System Light High Grip 27.5 X 2.5" Folding Front, WTB Riddler TCS System Light Fast Rolling 27.5" X 2.4" Folding Rear				
	Shift Levers	SRAM GX, MMX Clamp, 11 Speed				
	Front Derailleur	N/A				
	Rear Derailleur	SRAM GX, 11 Speed Alloy				
	Cassette	SRAM NX-1130, 11-42, 11 Speed				
	Chain	SRAM PC-1110, 11 Speed				
	Crankset	SRAM Descendant 6K GXP, X-SYNC 2, Direct Mount 30T Chainring, 11 Speed				
	<b>Bottom Bracket</b>	SRAM GXP XR, BSA 73mm				
	Seatpost	Whyte drop.it, 30.9mm, 125mm on S, 150mm Travel on M & L, 170mm XL, Paddle Remote				
	Seat	Whyte Custom Dual Density, Triple Panel Design				
	Bar	Whyte Custom Alloy 6061, 35mm Bar Bore, 15mm Rise, 780mm Wide				
	Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm				
	Grips	Whyte Lock-on V Grip				
	Front Brakes	SRAM Guide R, 4 Pots, 200mm Rotor (180mm on the S)				
	Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing				
	Brake Levers	SRAM Guide R, MMX Matchmaker				
	Pedals	None				
<b>√</b>	Indicates an upgra	ade or improvement over last years model				
<b>✓</b>	Indicates an upgra	ade or improvement over the model below				

The all new G-170 frame takes everything we learnt from the G-160 and improves it. From the oversize hardware on our main pivot complete with Enduro bearings, to the new Flat Mount dropout, the G-170 is literally built to handle anything you throw at it.

The S is loaded with the very latest developments in Enduro/Trail bikes. WTB i29mm rims combined with TCS front and rear specific tyres help to give neutral handling without too much drag.

The G-170 has extra width built into the rear chainstays to allow the rider to fully exploit the future developments in wide high volume tyres but maintain mud clearance.

Dropout Code	DROPWHQ4SR		
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	230mm		
Weight	15Kg		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	75.83	582.9	333.5	839.5
M	65	75.5	602.7	333.5	843.5
L	65	75.19	627.5	333.5	848.5
XL	65	74.9	652.3	333.5	848.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1195.6	Chain Stay 430	Seat Post 30.9	Head Tube	
		<u> </u>			Tube
S	1195.6	430	30.9	110	Tube 406.4

# **G-170C RS**

#### G-170 Gravity Enduro Suspension - 170mm

SRP £3,799



		Colour	Matt Granite with Orange/Blue			
		Sizes Available	M,L			
	Frame  Fork  Rear Shock		Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts			
			RockShox Lyrik RC, 27.5", 170mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate			
			RockShox Deluxe RT3, Fast Black Coating, Adjustable Rebound and Compression			
	<b>√</b>	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings			
	<b>√</b>	Rear Hub	Whyte Cartridge Sealed Bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole			
		Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole			
		Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples			
	<b>√</b>	Rims	WTB STs i29 Rims with TCS System, Sleeve Joint, Tubeless Ready			
	✓ Tyres ✓ Shift Levers		Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear			
			SRAM GX Eagle, MMX Clamp, 12 Speed			
		Front Derailleur	N/A			
	<b>√</b>	Rear Derailleur	SRAM GX Eagle, 12 Speed			
	<b>√</b>	Cassette	SRAM XG-1275 Eagle 10-50, 12 Speed			
	$\checkmark$	Chain	SRAM GX Eagle, Black, 12 Speed			
	<b>√</b>	Crankset	SRAM Descendent Carbon Eagle GXP, X-SYNC 2, Direct Mount 32T Chainring, 12 Speed			
		Bottom Bracket	SRAM GXP XR, BSA 73mm			
		Seatpost	RockShox Reverb Stealth 150mm, 30.9mm, MMX			
	$\checkmark$	Seat	Whyte Custom Dual Density, Triple Panel Design			
		Bar	Whyte Custom Alloy 6061, 35mm Bar Bore, 15mm Rise, 780mm Wide			
		Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm			
		Grips	Whyte Lock-on V Grip			
		Front Brakes	SRAM Guide R, 4 Pots, 200mm Rotor			
		Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing			
		Brake Levers	SRAM Guide R, MMX Matchmaker			
		Pedals	None			
<b>√</b>		Indicates an upgr	ade or improvement over last years model			

Indicates an upgrade or improvement over the model below

The RS uses the same highly developed frame as the Works bike which our team race on. The parts are picked to make the most of this frame - from RockShox suspension to the brand new Eagle GX groupset, the RS is everything a modern long travel bike should be.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its clever open front triangle design it is possible to fit various option of rear shock including coil shocks but still carry a full size water bottle.

The G-170 has extra width built into the rear chainstays to allow the rider to fully exploit the future developments in wide high volume tyres but maintain mud clearance.

Dropout Code	DROPWHQ4SR		
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	230mm		
Weight	14Kg		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	65	75.5	602.7	333.5	843.5
L	65	75.19	627.5	333.5	848.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	1215.6	430	30.9	120	431.8
L	1240.6	430	30.9	130	457.2

# G-170C WORKS

#### **G-170 Gravity Enduro Suspension - 170mm**

SRP £5,499



		Colour	Matt Lime with Eucalyptus/Olive
		Sizes Available	M,L
		Frame	Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
	<b>√</b>	Fork	RockShox Lyrik, RCT3, 27.5", 170mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
	<b>√</b>	Rear Shock	RockShox Super Deluxe Debonair, RT3, Fast Black Coating, Adjustable Rebound and 2-postion Compression
		Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
	<b>√</b>	Rear Hub	Hope Pro 4, Stainless Steel Cartridge Sealed bearing, 12mm X 148mm Boost Through Axle XD Driver Free Hub, 28 Hole
	<b>√</b>	Front Hub	Hope Pro 4, Stainless Steel Cartridge sealed Bearing, 15mm x 110mm Boost Through Axle, 28 Hole
	<b>√</b>	Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless Steel, Brass Nipples
	<b>√</b>	Rims	Whyte 30mm Carbon Hookless, 28H, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included
		Tyres	Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear
	$\checkmark$	Shift Levers	SRAM X01 Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
	<b>√</b>	Rear Derailleur	SRAM X01 Eagle, 12 Speed
	$\checkmark$	Cassette	SRAM XG-1295 Eagle, 10-50, 12 Speed
		Chain	SRAM GX Eagle, Black, 12 Speed
	<b>√</b>	Crankset	SRAM X01 Carbon Eagle GXP, X-SYNC 2 Direct Mount 34T Chainring, 12 Speed
	$\checkmark$	<b>Bottom Bracket</b>	SRAM GXP Team, BSA 73mm
	$\checkmark$	Seatpost	RockShox Reverb Stealth 150, 30.9mm, MMX with X1 Remote
		Seat	Whyte Custom Team, with Lightweight Foam, CrMo Rails, Triple Panel Design
	$\checkmark$	Bar	RaceFace SIXC Carbon, 35mm Bar Bore, 20mm Rise, 820mm Wide
	$\checkmark$	Stem	RaceFace Turbine 35mm Bar Bore, 40mm
		Grips	Whyte Lock-on V Grip
	<b>√</b>	Front Brakes	SRAM Guide RSC, 4 Pots, 200mm Rotor
	<b>√</b>	Rear Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing
	<b>√</b>	Brake Levers	SRAM Guide RSC, MMX Matchmaker
_		Pedals	None
		Indicates an upgra	ade or improvement over last years model
		1	

Indicates an upgrade or improvement over the model below

This bike will not only be raced by our Gravity Enduro team - it was actually designed in conjunction with them. Their input to the geometry, combined with the new carbon front triangle and oversize hardware, adds up to a very stiff and capable chassis.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its clever open front triangle design it is possible to fit various option of rear shock including coil shocks but still carry a full size water bottle.

The G-170 has extra width built into the rear chainstays to allow the rider to fully exploit the future developments in wide high volume tyres but maintain mud clearance.

Dropout Code	DROPWHQ4SR		
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	230mm		
Weight	13.8Kg		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	65	75.5	602.7	333.5	843.5
L	65	75.19	627.5	333.5	848.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	1215.6	430	30.9	120	431.8
L	1240.6	430	30.9	130	457.2

# S-150 S

#### S-150 Trail/Enduro Suspension - 150mm

SRP £2,850



	Colour	Matt Blue with Orange/Denim/Sky			
	Sizes Available	S,M,L,XL			
	Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, ISCG 5 Tabs, alloy symmetrical SCR rear Triangle, 148mm Boost dropouts			
	Fork	RockShox Revelation RC 29", 150mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate			
	Rear Shock	RockShox Deluxe RT Debonair, Fast Black Coating, Adjustable Rebound and 2 Position Compression			
	Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing			
	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole			
	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole			
	Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples			
	Rims	WTB STp i29 Rims with TCS System, Pinned Joint, Tubeless Ready			
	Tyres	Maxxis High Roller II TR, 29" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection Front, Maxxis Crossmark II TR, 29" X 2.25" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear			
	Shift Levers	SRAM GX Eagle MMX Clamp, 12 Speed			
	Front Derailleur	N/A			
	Rear Derailleur	SRAM GX Eagle, 12 Speed			
	Cassette	SRAM PG-1275 Eagle, 10-50, 12 Speed			
	Chain	SRAM GX Eagle, 12 Speed			
	Crankset	SRAM GX Eagle, X-SYNC 2 Direct Mount 32T, Boost 12 Speed			
	<b>Bottom Bracket</b>	SRAM GXP XR, BSA 73mm			
	Seatpost	RockShox Reverb Stealth 125mm on S, 150mm on M & L, 170mm on XL, 30.9mm, MMX			
	Seat	Whyte Custom Dual Density, Triple Panel Design			
	Bar	Whyte Custom Alloy 6061, 15mm Rise, 760mm Wide (30mm Rise, 780mm Wide on the XL)			
	Stem	Whyte Gravity Stem, 40mm S&M, 50mm L&XL			
	Grips	Whyte Lock-on V Grip			
	Front Brakes	SRAM Level TL, 180mm Rotor (200mm on the XL)			
	Rear Brakes	SRAM Level TL, 170mm Rotor (180mm on the XL), Internal Routing			
	Brake Levers	SRAM Level TL, MMX Matchmaker			
	Pedals	None			
<b>√</b>	Indicates an upgr	ade or improvement over last years model			

Indicates an upgrade or improvement over the model below

Latest generation Whyte geometry, 150mm of travel and 29er wheels make this trail bike fast and controllable in every situation. A wide main pivot with oversize hardware is a perfect way to get the power down.

The S-150 was built unashamedly around the SRAM Eagle concept. With Eagle tech now available at GX level the S-150 S makes the most of the huge 500% gear range - both in the speed it climbs and the ability to get pedal strokes in, as well as a big top gear for the descents.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. For 2018 Whyte will launch wheel kits that are ready to switch into your bike in the time it takes to go back to your car and change the Eagle cassette.

Dropout Code	DROPWHQ4SR	
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)	
Reducer Bush Widths	25mm x 8mm, no hardware at the rear	
Eye to Eye Length	210mm	
Weight	14.5Kg	

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	65.6	74.7	620.7	335	816
L	65.6	74.5	640.1	335	816
XL	65.6	74.3	659.6	335	816
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	1211.6	435	30.9	110	431.8
L	1231.6	435	30.9	120	457.2
XL	1251.6	435	30.9	130	482.6

## **S-150C RS**

#### S-150 Trail/Enduro Suspension - 150mm

SRP £3,850



	Colour	Matt Granite with Lime/Olive
	Sizes Available	M,L,XL
<b>✓</b>	Frame	Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<b>√</b>	Fork	RockShox Pike RC, 29°, 150mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
	Rear Shock	RockShox Deluxe RT Debonair, Fast Black Coating, Adjustable Rebound and 2 Position Compression
	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
<b>√</b>	Rear Hub	Whyte Cartridge Sealed Bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Throug Axle, 32 Hole
	Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
	Rims	WTB STp i29 Rims with TCS System, Pinned Joint, Tubeless Ready
	Tyres	Maxxis High Roller II TR, 29" X 2.3" 60TPI 3C(Maxx Terra) Folding Bea EXO Sidewall Protection Front, Maxxis Crossmark II TR, 29" X 2.25" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear
	Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
	Front Derailleur	N/A
	Rear Derailleur	SRAM GX Eagle, 12 Speed
	Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
	Chain	SRAM GX Eagle, 12 Speed
<b>√</b>	Crankset	SRAM Descendant Carbon Eagle GXP, X-SYNC 2, Direct Mount 32T Chainring, 12 Speed
	<b>Bottom Bracket</b>	SRAM GXP XR, BSA 73mm
	Seatpost	RockShox Reverb Stealth 150mm on M & L, 170mm on XL, 30.9mm, MMX
	Seat	Whyte Custom Dual Density, Triple Panel Design
	Bar	Whyte Custom Alloy 6061, 15mm Rise, 760mm Wide (30mm Rise, 780mm Wide on the XL)
	Stem	Whyte Gravity Stem, 40mm M, 50mm L&XL
	Grips	Whyte Lock-on V Grip
<b>√</b>	Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor (200mm on XL)
	Rear Brakes	SRAM Guide R, 4 Pots, 170mm Rotor (180mm on XL), Internal Routin
<b>√</b>	icai biaces	
<b>√</b>	Brake Levers	SRAM Guide R, MMX Matchmaker

Indicates an upgrade or improvement over last years model
Indicates an upgrade or improvement over the model below

With its all-new sculpted carbon front triangle the RS certainly looks the part. Add Eagle GX, the brand new Rockshox Pike and Deluxe suspension and you've got the fastest trail bike we've ever made.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. For 2018 Whyte will launch wheel kits that are ready to switch into your bike in the time it takes to go back to your car and change the Eagle cassette. There's a choice of Carbon or Alloy wheel kits.

Maxxis 3C compound is peerless in the level of front end grip it provides. The 29mm wide rims create a stable bead platform for these tyres so you can push them right to the limit

Dropout Code	DROPWHQ4SR		
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	210mm		
Weight	13.9Kg		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	65.6	74.7	620.7	335	816
L	65.6	74.5	640.1	335	816
XL	65.6	74.3	659.6	335	816
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1211.6	435	30.9	110	431.8
L	1231.6	435	30.9	120	457.2
XL	1251.6	435	30.9	130	482.6

### **S-150C WORKS**

#### S-150 Trail/Enduro Suspension - 150mm

SRP £5,499



	Colour	Matt Lime with Eucalyptus/Olive
	Sizes Available	M,L,XL
Frame		Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<b>/</b>	Fork	RockShox Pike RCT3, 29°, 150mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
	Rear Shock	RockShox Deluxe RT3 Debonair, Fast Black Coating, Adjustable Rebound and 3 Position Compression
	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
/	Rear Hub	Hope Pro 4, Stainless Steel Cartridge Sealed Bearing, 12mm X 148mm Boost Through Axle XD Driver Free Hub, 28 Hole
/	Front Hub	Hope Pro 4, Stainless Steel Cartridge Sealed Bearing, 15mm x 110mm Boost Through Axle, 28 Hole
/	Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless Steel, Brass Nipples
/	Rims	Whyte 30mm Carbon Hookless, 28H, Tubeless Ready, 3M Rim strip with Tubeless Valves Included
	Tyres	Maxxis High Roller II TR, 29" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead EXO Sidewall Protection Front, Maxxis Crossmark II TR, 29" X 2.25" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear
	Shift Levers	SRAM XX1 Eagle, MMX Clamp, 12 Speed
	Front Derailleur	N/A
/	Rear Derailleur	SRAM XX1 Eagle, 12 Speed
/	Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
	Chain	SRAM GX Eagle, 12 Speed
/	Crankset	SRAM XX1 Carbon Eagle GXP, X-SYNC 2, 34T Direct Mount Boost Chainring, 12 Speed
	<b>Bottom Bracket</b>	SRAM GXP Team, BSA 73mm
/	Seatpost	RockShox Reverb Stealth 150mm on M & L, 170mm on XL, 30.9mm, MMX with X1 Remote
/	Seat	Whyte Custom Team, with lightweight Foam, CrMo Rails, Triple Panel Design
	Bar	RaceFace SIXC Carbon, 35mm Bar Bore, 20mm Rise X 800mm Wide
	Stem	Whyte Gravity 35mm Bar Bore, 40mm M, 50mm L&XL
	Grips	Whyte Lock-on V Grip
	Front Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor (200mm on XL)
	Rear Brakes	SRAM Guide RSC, 4 Pots, 180mm CLX 2pcs Rotor
	Brake Levers	SRAM Guide RSC, MMX Matchmaker
-	Pedals	None

Indicates an upgrade or improvement over last years model
Indicates an upgrade or improvement over the model below

Our Whyte Enduro team have a secret weapon in 2018 - the S-150 Works is their "out the box" race bike for the more all-round events. Already there have been wins at the Master's National Championships and we are sure this is just the beginning for this great all-round bike.

There is a wish list spec on the Works, but standouts must include the 30mm hookless Whyte carbon rims hand laced onto Hope Pro4 hubs, the XX1 Reverb, under the bar paddle lever and the RockShox suspension.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. For 2018 Whyte will launch wheel kits that are ready to switch into your bike in the time it takes to go back to your car and change the Eagle cassette. The Carbon 35mm hookless rims are even colour matched to the Works paint finish.

Dropout Code	DROPWHQ4SD		
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	210mm		
Weight	13.3Kg		

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	М	65.6	74.7	620.7	335	816
	L	65.6	74.5	640.1	335	816
	XL	65.6	74.3	659.6	335	816
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	M	1211.6	435	30.9	110	431.8
	L	1231.6	435	30.9	120	457.2
1						

# T-130 SR

#### T-130 Trail Suspension - 130mm

SRP £2,250



	Colour	Matt Lime with Eucalyptus/Magenta				
	Sizes Available	XS,S,M,L.XL				
	Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, Alloy Symmetrical SCS Rear Triangle, 148mm Boost Dropouts, Shimano Direct Mount Hanger				
<b>√</b>	Fork	Fox Rhythm 34, 27.5°, 130mm Travel, Grip Sweep-Adjust Damper, Tapered Steerer, Black Coating, 110mm x 15mm Boost E-Thru Axle				
	Rear Shock	Fox Float DPS Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol				
	Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing				
<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole				
<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole				
	Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples				
	Rims	WTB STp i29 29mm Wide, TCS System, 32 Hole				
<b>✓</b>	Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra), EXD Sidewall Protection Front, Maxxis Crossmark II TR 27.5 X 2.25" EXO Sidewall Protection, Rear				
	Shift Levers	Shimano SLX M7000, I-Spec B, 11 Speed, Black				
	Front Derailleur	N/A				
	Rear Derailleur	Shimano SLX M7000, Shadow Plus, Direct Mount, 11 Speed				
$\checkmark$	Cassette	Sunrace CSMX8, 11-46, Alloy Spider 7075 46t, 11 Speed				
	Chain	Shimano HG601, 11 Speed				
	Crankset	RaceFace Ride, Direct Mount 32T, Boost, 11 Speed				
	<b>Bottom Bracket</b>	RaceFace BSA, 73mm				
	Seatpost	Whyte drop.it, 30.9, 125mm Travel on XS & S, 150mm Travel on M,L & XL, Paddle Remote				
$\checkmark$	Seat	Whyte Custom Dual Density, Triple Panel Design				
	Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)				
	Stem	Whyte Gravity Stem, 40mm XS/S, 50mm M/L				
	Grips	Whyte Lock-on V Grip				
	Front Brakes	TRP Slate T4, Four Pot Front, I-spec, 160mm Rotor (180mm on M,L&XL)				
	Rear Brakes	TRP Slate T2, Two Pot, I-spec, 160mm Rotor (180mm on L&XL), Internal Routing				
	Brake Levers	TRP Slate, I-Spec B				
	Pedals	None				
<b>✓</b>	Indicates an upgr	ade or improvement over last years model				

Indicates an upgrade or improvement over the model below

The T-130 SR is new for 2018. It's available from XS to XL and brings the very latest MTB features to a more affordable price point.

WTB STp i29 rims and TR Maxxis tyres give a Tubeless ready wheelset which, when combined with the Fox Rhythm 34 fork and Fox Float DPS double chamber rear shock, give the SR the ability to tame your favourite trails.

Frame size specific Whyte, drop.it, seat posts give each size of rider the perfect ride high and travel for their bike.

Dropout Code	DROPWHQ4SD		
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm		
Eye to Eye Length	216mm		
Weight	14.3Kg		

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
ſ	XS	67	74	571.7	331	761
ſ	S	67	73.7	591.4	331	763
ſ	М	67	73.5	611.1	331	766
ſ	L	67	73.3	631	331	776
	XL	67	73.2	650.7	331	786
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	XS	1116.5	420	30.9	100	368.3
Ī	S	1136.5	420	30.9	107	406.4
ſ	М	1156.5	420	30.9	115	431.8
Ī	L	1176.5	420	30.9	120	457.2
	XL	1196.5	420	30.9	130	482.6

## T-130 S

#### T-130 Trail Suspension - 130mm

SRP £2,750



		Colour	Matt Blue with Orange/Denim/Sky
		Sizes Available	XS,S,M,L,XL
		Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<b>√</b>	<b>√</b>	Fork	RockShox Revelation RC, 27.5", 130mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
		Rear Shock	RockShox Monarch Debonair, RT, Fast Black Coating, Adjustable Rebound and Compression
		Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
		Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
	<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
		Rims	WTB STp i29 29mm Wide, TCS System, 32 Hole
		Tyres	WTB Vigilante, Light High Grip TCS System 27.5" X 2.3", 60TPI Front, Trail Boss, TCS System, Light Fast Rolling 27.5" X 2.4", 60TPI Rear
$\checkmark$	$\checkmark$	Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
<b>V</b>	<b>V</b>	Rear Derailleur	SRAM GX Eagle, 12 Speed
$\checkmark$	$\checkmark$	Cassette	SRAM PG-1275 Eagle, 10-50, 12 Speed
$\checkmark$	$\checkmark$	Chain	SRAM GX Eagle, 12 Speed
<b>√</b>	<b>√</b>	Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, Boost, 12 Speed
	$\checkmark$	Bottom Bracket	SRAM GXP XR, BSA, 73mm
		Seatpost	RockShox Reverb Stealth 125mm on S, 150mm on M & L, 170mm on XL, 30.9mm, MMX
	$\checkmark$	Seat	Whyte Custom Dual Density, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
<b>V</b>		Grips	Whyte Lock-on V Grip
$\checkmark$	<b>√</b>	Front Brakes	SRAM Level TL, 180mm Rotor
$\sqrt{}$	<b>√</b>	Rear Brakes	SRAM Level TL, 160mm Rotor (170mm on XL), Internal Routing
$\sqrt{}$	<b>√</b>	Brake Levers	SRAM Level TL, MMX Matchmaker
		Pedals	None
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

The T-130 S features our "multi award winning" SCR single ring specific frame with mega-stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

To further improve the hugely popular T-130 S for 2018 this bike gets Eagle GX. This evolutionary groupset give the rider a massive 500% gear range allowing Whyte to increase the chain ring size without sacrificing the lower gearing size.

The T-130 S also gets a suspension upgrade for this season. The all new Rockshox Revelation RC is a ground up design based on the brand new Pike fork. This Trail fork brings new levels of lightweight stiffness and balance to the award wining T-130 S.

Dropout Code	DROPWHQ4SR		
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)		
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm		
Eye to Eye Length	216mm		
Weight	14.1Kg		

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67	74	571.7	331	761
S	67	73.7	591.4	331	763
М	67	73.5	611.1	331	766
L	67	73.3	631	331	776
XL	67	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1116.5	420	30.9	100	368.3
S	1136.5	420	30.9	107	406.4
М	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

# T-130 RS

#### T-130 Trail Suspension - 130mm

SRP £3,150



		Colour	Matt Granite with Lime/Magenta
		Sizes Available	S,M,L,XL
		Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, Alloy Symmetrical SCS Rear Triangle, 148mm Boost Dropouts, Shimano Direct Mount Hanger
<b>✓</b>	<b>√</b>	Fork	Fox Float Performance Elite 34, 27.5°, 130mm Travel with 3-Pos FIT 4 Damper, Tapered Steerer, Black Coating, 110mm x 15mm Boost E-Thru Axle
		Rear Shock	Fox Float DPS Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol
		Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
	<b>√</b>	Rear Hub	Hope Pro 4 with StSt Bearings, 11 Speed Shimano Freehub, 12mm X 148mm Boost Through Axle, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
	$\checkmark$	Spokes	DT Swiss Champion 2.0mm, Brass Nipples
		Rims	WTB STs i29, 29mm Wide, TCS System, Sleeved Joint, 32 Hole
		Tyres	WTB Vigilante, Light High Grip TCS System 27.5" X 2.3", 60TPI Folding Front, Trail Boss, TCS System Light Fast Rolling 27.5" X 2.4", 60TPI Folding Rear
		Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
		Front Derailleur	N/A
		Rear Derailleur	Shimano XT M8000, Shadow Plus, Direct Mount, 11 Speed
		Cassette	Shimano XT M8000, 11-46, 11 Speed
		Chain	Shimano HG601, 11 Speed
		Crankset	RaceFace Turbine Clinch, Direct Mount 32T Chainring, 30mm Alloy Boost Axle, 11 Speed
	$\checkmark$	Bottom Bracket	RaceFace BSA, 73mm
		Seatpost	RockShox Reverb Stealth 125mm on S, 150mm on M & L, 170mm on XL, 30.9mm
		Seat	Whyte Custom Dual Density, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
$\checkmark$		Grips	Whyte Lock-on V Grip
	<b>√</b>	Front Brakes	Shimano XT M8000, 180mm Rotor (200mm on XL)
	<b>/</b>	Rear Brakes	Shimano XT M8000, 160mm Rotor (180mm on XL), Internal Routing
	<b>V</b>	Brake Levers	Shimano XT M8000, I-spec II
		Pedals	None
<b>✓</b>		Indicates an upgra	ade or improvement over last years model

Indicates an upgrade or improvement over the model below

The T-130 RS features our "multi award winning" SCR single ring specific frame with mega-stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

The T-130 RS gets a big suspension upgrade in 2018 using the Fox 34 Performance Elite fork with its highly acclaimed FIT-4 damper.

Whyte hubs are laced to WTB STs i29 29mm wide rims with WTB high air volume tyres to allow you to exploit even more speed and fun out of the T-130's geometry.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	14Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67	73.7	591.4	331	763
М	67	73.5	611.1	331	766
L	67	73.3	631	331	776
XL	67	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
M L	1156.5 1176.5	420 420	30.9 30.9	115 120	431.8 457.2

## **T-130C RS**

#### T-130 Trail Suspension - 130mm

SRP £3,799



		Colour	Matt Lime with Eucalyptus/Olive
		Sizes Available	M,L,XL
	<b>✓</b>	Frame	Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System with Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<b>✓</b>	<b>√</b>	Fork	RockShox Pike RC, 27.5", 130mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
		Rear Shock	RockShox Monarch Debonair, RT, Fast Black Coating, Adjustable Rebound and Compression
	<b>√</b>	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
<b>√</b>	<b>√</b>	Rear Hub	Whyte Cartridge Sealed Bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
		Spokes	DT Swiss Champion 2.0mm, Brass Nipples
	<b>√</b>	Rims	RaceFace AR-30, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
	<b>✓</b>	Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra), EXO Sidewall Protection Front, Maxxis Crossmark II TR 27.5 X 2.25" EXO Sidewall Protection, Rear
	<b>\</b>	Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
<b>/</b>	<b>√</b>	Rear Derailleur	SRAM GX Eagle, 12 Speed
<b>/</b>	<b>√</b>	Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
<b>/</b>	<b>V</b>	Chain	SRAM GX Eagle, Silver, 12 Speed
<b>√</b>	<b>√</b>	Crankset	SRAM Descendant Carbon Eagle, X-SYNC 2, Direct Mount 34T Boost, 12 Speed
		Bottom Bracket	SRAM GXP XR, BSA, 73mm
		Seatpost	RockShox Reverb Stealth 125mm on S, 150mm on M & L, 170mm on XL, 30.9mm, MMX
		Seat	Whyte Custom Dual Density, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm M, 50mm L/XL
<b>/</b>		Grips	Whyte Lock-on V Grip
	<b>V</b>	Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor
	<b>√</b>	Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor (170mm on XL), Internal Routing
	<b>√</b>	Brake Levers	SRAM Guide RS, MMX Matchmaker
		Pedals	None

Indicates an upgrade or improvement over last years model
Indicates an upgrade or improvement over the model below

The T-130 C RS features our "5/5 award winning" single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

SRAM's all-new Eagle GX 12 speed drive-train is used on the T-130 C RS. This evolutionary groupset gives a massive 10-50 gear spread cassette, allowing the chainring to be increased to 34t, giving both top and bottom range improvement.

RaceFace AR-30, 30mm wide, sleeved joint, UST Tubeless rims are combined with Maxxis TR tyres to give exceptional levels of control. Boost 148mm rear and 110mm front hubs have 10mm wide flange spacing creating a stiffer wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	67	73.5	611.1	331	766
L	67	73.3	631	331	776
XL	67	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

### **T-130C WORKS**

T-130 Trail Suspension - 130mm

SRP £5,499



		Colour	Matt Granite with Silver/Grey
		Sizes Available	M.L.XL
		Frame	Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System with Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<u> </u>	<b>√</b>	Fork	RockShox Pike RCT-3, 27.5", 130mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
	<b>√</b>	Rear Shock	RockShox Monarch Debonair, RT3, Fast Black Coating, Adjustable Rebound and Compression
		Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
/	<b>√</b>	Rear Hub	Hope Pro 4, Stainless Steel Cartridge Sealed Bearing, 12mm X 148mm Boost Through Axle XD Driver Free Hub, 28 Hole
/	<b>√</b>	Front Hub	Hope Pro 4, Stainless Steel Cartridge Sealed Bearing, 15mm x 110mm Boost Through Axle, 28 Hole
<u> </u>	<b>√</b>	Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless Steel, Brass Nipples
	<b>√</b>	Rims	Whyte 30mm Carbon Hookless, Tubeless Ready, 3M Rim Strip with Tubeless Valves included, 28 Hole
		Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terral, EXO Sidewall Protection Front, Maxxis Crossmark II TR 27.5 X 2.25" EXO Sidewall Protection, Rear
/	<b>√</b>	Shift Levers	SRAM XX1 Eagle Gold, MMX Clamp, 12 Speed
		Front Derailleur	N/A
/	<b>√</b>	Rear Derailleur	SRAM XX1 Eagle Gold, 12 Speed
/	<b>√</b>	Cassette	SRAM XG-1299 Eagle Gold, 10-50, 12 Speed
/	<b>√</b>	Chain	SRAM XX1 Eagle Gold, 12 Speed
		Crankset	
	<b>√</b>		SRAM XX1 Eagle Gold Carbon, X-SYNC 2, Direct Mount 34T Boost, 12 Speed
	<b>√</b>	Bottom Bracket	SRAM GXP Team, BSA, 73mm
/	<b>√</b>	Seatpost	RockShox Reverb Stealth 150mm on M & L, 170mm on XL, 30.9mm, MMX with X1 remote
/	<b>✓</b>	Seat	Whyte Custom Team, with Lightweight Foam, CrMo Rails, Triple Panel Design
/	<b>√</b>	Bar	RaceFace, NEXT R Carbon, 35 Dia, 20mm Rise x 780mm Wide
/	<b>\</b>	Stem	Whyte Gravity 35mm Stem, 40mm M, 50mm L/XL
/		Grips	Whyte Lock-on V Grip
	<b>/</b>	Front Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor
	/	Rear Brakes	SRAM Guide RSC, 4 Pots, 160mm Rotor (170mm on XL), Internal
	<b>V</b>		Routing

Indicates an upgrade or improvement over last years model
Indicates an upgrade or improvement over the model below

Pedals

The T-130 C Works gets a wish list spec built around SRAM's evolutionary Eagle drive chain which comes in the top spec XX1 Gold version. With X-Dome cassette technology and Hard Chrome™coating on both the chain and cassette, shifting and wear resistance have never been better.

The T-130 C Works features our "5/5 award winning" single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

The Works comes with Whyte's own 30mm wide hookless carbon tubeless ready rims laced onto Hope Pro4 hubs with DT Swiss spokes and brass nipples. This build gives both lightweight and security when pushing the Works to the limit.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	12.9Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
ļ	М	67	73.5	611.1	331	766
	L	67	73.3	631	331	776
1	XL	67	73.2	650.7	331	786
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
ł	М	1156.5	420	30.9	115	431.8
1	L	1176.5	420	30.9	120	457.2
1	XL	1196.5	420	30.9	130	482.6

#### Trail/Enduro Hardtail - 900 Series - 130mm

SRP £1,350



	Colour	Matt Lime with Eucalyptus/Olive
	Sizes Available	S,M,L,XL
	Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Get A Grip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
<b>✓</b>	Fork	RockShox Recon RL Gold 27.5", 130mm Travel, Fast Black Coating, Solo Air, Adjustable Compression and Rebound, Tapered Steerer, 110mm X 15mm Boost, Maxle Lite
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Caged Lower Bearing 1.5", 1 1.8" Caged Upper Bearings
<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
	Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
	Rims	WTB STp i29 TCS System, Tubeless Ready, 32 Hole
<b>√</b>	Tyres	Maxxis Forekaster TR, 27.5" x 2.6" 60 TPI 3C (Maxx Terra) Folding Bead, EXO Sidewall Protection Front & Rear
	Shift Levers	SRAM NX, 11 Speed
	Front Derailleur	N/A
	Rear Derailleur	SRAM NX, 11 Speed
	Cassette	SRAM PG-1130, 11-42, 11 Speed
	Chain	SRAM PC-1110, 11 Speed
<b>√</b>	Crankset	SRAM NX, X-SYNC Direct Mount 30T, Boost 11 Speed
	Bottom Bracket	SRAM GXP, 73mm
	Seatpost	Whyte 20mm Offset, 30.9mm x 400mm (350mm on Small & Med), 6061 Alloy, 2 Bolt Clamp, Adjuster
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
	Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
<b>/</b>	Grips	Whyte Lock-on V Grip
	Front Brakes	SRAM Level, 180mm Rotor (200mm on XL)
	Rear Brakes	SRAM Level, 160mm Rotor (180mm on XL), Internal Routing
	Brake Levers	SRAM Level
	Pedals	None
<b>✓</b>	Indicates an upgr	ade or improvement over last years model
<b>✓</b>	Indicates an upgr	ade or improvement over the model below
$\overline{}$		

With the 901 it's all about the geometry - it will make you feel more confident in all situations than any hardtail you've ever ridden. With it's BBX frame there is the easy option to upgrade to a Whyte Drop.it seat post.

The award winning 901 features the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

For 2018 the 901 rides on high air volume 2.6" Maxxis Forekaster tyres which combine with the WTB STP i29 rims to create more comfort, more control and more fun!

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	73	621	297.5	788.5
М	65	73	639	297.5	793.5
L	65	73	658	297.5	819.5
XL	65	73	677	297.5	825.5
					6 .
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1161	Chain Stay 430	Seat Post 30.9	Head Tube 120	
		<u> </u>			Tube
S	1161	430	30.9	120	Tube 406.4

#### Trail/Enduro Hardtail - 900 Series - 130mm

SRP £1,699



		Colour	Matt Blue with Orange/Denim/Sky
		Sizes Available	S,M,L,XL
	<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
<b>√</b>	<b>√</b>	Fork	RockShox Revelation RC 27.5", 130mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
		Rear Shock	N/A
	<b>√</b>	Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
		Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
<b>√</b>		Front Hub	Alloy, Double Sealed, Cartridge Bearing Hub, 15mm X 110mm Boost Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
$\checkmark$	<b>√</b>	Rims	WTB STp i35 TCS System, Pinned Joint, Tubeless Ready, 32 Hole
<b>√</b>	<b>✓</b>	Tyres	Maxxis High Roller II TR, 27.5" X 2.8" 120TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection Front, Maxxis Rekon TR, 27.5" X 2.8" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear
	<b>V</b>	Shift Levers	SRAM GX, 11 Speed
		Front Derailleur	N/A
	<b>√</b>	Rear Derailleur	SRAM GX, 11 Speed
		Cassette	SRAM PG-1130, 11-42, 11 Speed
		Chain	SRAM PC-1110, 11 Speed
<b>√</b>	<b>√</b>	Crankset	SRAM Descendant K6, X-SYNC 2, Direct Mount 32T, Boost 11/12 Speed
		Bottom Bracket	SRAM GXP, 73mm
		Seatpost	Whyte drop.it Post with Paddle Remote, 30.9mm X 420mm, 150mm Travel
<b>V</b>	<b>V</b>	Seat	Whyte Custom, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
<b>/</b>		Grips	Whyte Lock-on V Grip
	<b>√</b>	Front Brakes	SRAM Level T, 180mm Rotor (200mm on XL)
	<b>√</b>	Rear Brakes	SRAM Level T, 160mm Rotor (180mm on XL), Internal Routing
	<b>\</b>	Brake Levers	SRAM Level T, Matchmaker
		Pedals	None
<b>/</b>		Indicates an upgra	ade or improvement over last years model

Indicates an upgrade or improvement over the model below

The 2018 905 defines the modern Trail Hardtail. Its stripped back SCR frame, the all new RockShox Revelation fork and the  $2.8^{\prime\prime}$  tyres make this the best 905 Whyte have ever built.

The new 2018 905 brings ideas directly from our Whyte Enduro team, from the thicker V-Grips to the use of 170mm cranks to bring the rider 5mm closer to the ground without compromising pedal clearance.

WTB STp i35 35mm wide TCS rims combined with Maxxis 2.8" high volume TR 3C compounds create more comfort, more grip and more fun!

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	73	620	297.5	788.5
М	65	73	638.3	297.5	793.5
L	65	73	657	297.5	819.5
XL	65	73	675.4	297.5	825.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1167	Chain Stay 430	Seat Post 30.9	Head Tube	
		<u> </u>			Tube
S	1167	430	30.9	120	Tube 408.4

#### Trail/Enduro Hardtail - 900 Series - 130mm

SRP £2,150



		Colour	Matt Granite with Grey/Bronze
		Sizes Available	S,M,L,XL
		Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
	<b>✓</b>	Fork	Fox Float Performance 34, 27.5", 130mm Travel with GRIP 3-Pos Damper, Tapered Steerer, Black Coating and 110mm X 15mm Boost, E-Thru Axle
		Rear Shock	N/A
		Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
<b>√</b>	<b>√</b>	Rear Hub	Hope PRO4 with Stainless Steel Bearings, 12mm X 148mm Boost Through Axle, XD Driver, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 110mm Boost Through Axle, 32 Hole
$\checkmark$	<b>√</b>	Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
<b>√</b>	<b>√</b>	Rims	WTB STs i35 Rims with TCS System, Sleeve Joint, Tubeless Ready
<b>√</b>		Tyres	Maxxis High Roller II TR, 27.5" X 2.8" 120TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection Front, Maxxis Rekon TR, 27.5" X 2.8" 60TPI Dual TLR, Folding Bead, EXO Sidewall Protection Rear
$\checkmark$	<b>√</b>	Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
		Front Derailleur	N/A
$\checkmark$	<b>√</b>	Rear Derailleur	SRAM GX Eagle, 12 Speed
$\checkmark$	$\checkmark$	Cassette	SRAM XG-1275 Eagle 10-50, 12 Speed
$\checkmark$	<b>√</b>	Chain	SRAM GX Eagle, 12 Speed
$\checkmark$	$\checkmark$	Crankset	SRAM GX Eagle, X-SYNC 2 Direct Mount 34T, Boost 12 Speed
$\checkmark$		<b>Bottom Bracket</b>	SRAM GXP, 73mm
		Seatpost	Whyte drop.it Post with Paddle Remote, 30.9mm X 420mm, 150mm Travel
$\checkmark$		Seat	Whyte Custom, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
<b>V</b>		Grips	Whyte Lock-on V Grip
<b>√</b>	<b>√</b>	Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor (20mm on XL)
$\checkmark$	<b>√</b>	Rear Brakes	SRAM Guide R, 4 Pots, 160mm Rotor (180mm on XL), Internal Routing
<b>√</b>	<b>√</b>	Brake Levers	SRAM Guide R, MMX Matchmaker
		Pedals	None

Indicates an upgrade or improvement over last years model Indicates an upgrade or improvement over the model below

Our top-end trail hardtail is dripping with lust-worthy components such as SRAM's revolutionary Eagle GX groupset, Fox suspension and a Hope Pro 4 rear hub.

WTB STp i35 35mm wide TCS rims combined with Maxxis 2.8" high volume TR 3C compounds create more comfort, more grip and more fun!

The new 2018 909 brings ideas directly from our Whyte Enduro team, from the thicker V-Grips to the use of 170mm cranks to bring the rider 5mm closer to the ground without compromising pedal clearance.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	73	620	297.5	788.5
M	65	73	638.3	297.5	793.5
L	65	73	657	297.5	819.5
XL	65	73	675.4	297.5	825.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1167	Chain Stay 430	Seat Post 30.9	Head Tube	
		<u> </u>			Tube
S	1167	430	30.9	120	Tube 408.4

#### Youth 26er Trail Hardtail - 400 Series - 100mm

#### **SRP** £599



	·				
Colour	Matt Lime with Eucalyptus/Olive				
Sizes Available	13"				
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System				
Fork	Suntour, XCR, 100mm Travel, 32mm, HYDRO Lock-out, Air Spring, Adjustable Rebound, Post Mount				
Rear Shock	N/A				
Headset	FSA No.10, Semi Integrated, Caged Bearings				
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole				
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole				
Spokes	2.0mm, Black Stainless with Brass Nipples				
Rims	Whyte Trail-403, 28 Hole				
Tyres	WTB Bronson Race, 26" X 2.1" Front, WTB Riddler, 26" X 1.95" Rear				
Shift Levers	Shimano Altus SL-M310, 9 Speed Trigger Shifter				
Front Derailleur	N/A				
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed				
Cassette	Sunrace 9 Speed, ED Black 11-40T				
Chain	KMC, 9 Speed				
Crankset	28T Narrow/Wide Chainring, 165mm Crank Length				
Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge Bearings				
Seatpost	Whyte 20mm Offset, 30.9mm x 300mm, 6061 Alloy, 2 Bolt Clamp				
Seat	Whyte Custom				
Bar	Whyte Riser Bar 30mm Rise DB, 31.8mm, 640mm Wide				
Stem	Whyte Custom, 45mm S, M, 60mm L & XL				
Grips	Whyte Lock-on V Grip				
Front Brakes	Promax Solve, 160mm Rotor				
Rear Brakes	Promax Solve, 160mm Rotor, Internal Routing				
Brake Levers	Promax Solve, Short Reach				
Pedals	Fibre Reinforced Composite Platform				
Indicates an upgr	ade or improvement over last years model				
✓ Indicates an upgr	rade or improvement over the model below				
	Fork  Rear Shock  Headset Rear Hub Front Hub Spokes Rims Tyres Shift Levers Front Derailleur Cassette Chain Crankset Bottom Bracket Seatpost Seat Bar Stem Grips Front Brakes Rear Brakes Brake Levers Pedals Indicates an upgr				

We've broken the mould with our kids bikes. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

For 2018 Whyte has specced a trigger shifter, which will help with the transition to an adult bike.

The 403 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74	540.1	297.5	706.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1022.9	400	30.9	100	331

### **Youth 26er Trail Hardtail - 400 Series - 100mm SRP** £950



	_	i e	
		Colour	Matt Blue with Orange/Denim/Sky
		Sizes Available	13"
<b>✓</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
<b>√</b>	<b>√</b>	Fork	SR Epixon, 100mm Travel, Black Alloy Stanchions, Alloy Steerer, Hydro Lockout, Air Spring, Adjustable Rebound
		Rear Shock	N/A
		Headset	FSA No.10, Semi Integrated, Caged Bearings
		Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
		Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
		Spokes	2.0mm, Black Stainless with Brass Nipples
		Rims	Whyte Trail-405, 28 Hole
	<b>√</b>	Tyres	WTB Bronson Race, 26" X 2.1", 60TPl Folding Front, WTB Riddler, 26" X 1.95" Rear
$\checkmark$	$\checkmark$	Shift Levers	SRAM NX, 11 Speed, Trigger Shifter
		Front Derailleur	N/A
	<b>√</b>	Rear Derailleur	SRAM NX, 11 Speed
	<b>\</b>	Cassette	SRAM GX-1130, 13-42, 11 Speed
	<b>√</b>	Chain	SRAM PC-1130, 11 Speed
<b>√</b>	<b>√</b>	Crankset	SRAM NX Power Spline, X-SYNC Direct Mount 28T Chainring, 11 Speed Alloy, 165mm Crank Arms
		Bottom Bracket	SRAM Power Spline, 73mm
		Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
	<b>√</b>	Seat	Whyte Custom
	$\checkmark$	Bar	Whyte Riser Bar 30mm Rise, 31,8mm, 680mm Wide
	$\checkmark$	Stem	Whyte Gravity, 40mm
L		Grips	Whyte Lock-on V Grip
	<b>√</b>	Front Brakes	Tektro Auriga, 160mm Rotor
	<b>V</b>	Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
	<b>V</b>	Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
<b>✓</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

We've broken the mould with our kids bikes. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

With SRAM NX 1 by 11 spec and a trigger shifter the 405 really is a scaled down version of our award winning 900 series bikes. We have specced a XSYNC Direct Mount chainring so multiple chainrings are available to tune this bike to the size of the rider.

The 405 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWH9
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11.9Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
1	13"	68.5	74	540.1	297.5	706.5
1	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	13"	1022.9	400	30.9	100	331

#### Trail Hardtail - 800 Series - 120mm

#### **SRP** £899



	Colour	Matt Granite with Lime/Grey
	Sizes Available	S,M,L,XL
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
	Fork	RockShox 30 Silver 27.5", 120mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
$  \checkmark  $	Rims	Whyte Trail-21, Sleeve Joint, Offset Rims, 32 Hole
	Tyres	Maxxis Ardent Wire 27.5" x 2.25" Front, Maxxis Crossmark II Wire 27.5" x 2.25" Rear
$\checkmark$	Shift Levers	Shimano Deore SL-M6000, 10 Speed
	Front Derailleur	N/A
$\checkmark$	Rear Derailleur	Shimano Deore RD-M6000, Shadow Plus
$\checkmark$	Cassette	Sunrace CSMS3, 11-42, 10 Speed
$\checkmark$	Chain	Shimano HG-54, 10 Speed
$\checkmark$	Crankset	FSA Alpha Drive 1X, Forged Cranks, Narrow Wide 30T Chainring
$  \checkmark  $	Bottom Bracket	FSA Square Taper, 73mm
	Seatpost	Whyte 20mm Offset, 30.9mm x 350mm Small & Med 400mm Large & X Large, 6061 Alloy, 2 Bolt Clamp, Adjuster
	Seat	Whyte Custom
$\checkmark$	Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\checkmark$	Stem	Whyte Custom, 35mm S, 45mm M & L, 60mm XL
$\checkmark$	Grips	Whyte Lock-on V Grip
	Front Brakes	Tektro Auriga, 180mm Rotor (160mm on S)
	Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
	Brake Levers	Tektro Auriga
	Pedals	Fibre Reinforced Composite Platform
<b>✓</b>	Indicates an upgra	ade or improvement over last years model
<b>√</b>	Indicates an upgra	ade or improvement over the model below

Our aluminium hardtails have always offered a fine blend of fun, control and speed. For 2018 the line has upgraded to a dedicated SCR frame. Not needing inner chainring clearance means our engineers are able to further reduce the length of the chainstays for improved agility and a more dynamic ride.

The 800 Series frame is brand new for 2018, using the very latest Whyte geometry, based around a longer top tube, a short stem and wide 740mm bar. The 800 series bikes also feature a 120mm travel fork, for trail-bike levels of performance.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	66.5	74	604	303.5	789
ſ	М	66.5	74	623	303.5	807
	L	66.5	74	641	303.5	832
ſ	XL	66.5	74	660	303.5	861
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
ſ	S	1137.5	425	30.9	115	406
	М	1157.5	425	30.9	125	444
Ī	L	1177.5	425	30.9	135	482.6
ſ	XL	1197.5	425	30.9	145	533

#### Trail Hardtail - 800 Series - 120mm

**SRP** £899



	Colour	Matt Magenta with Black/Purple
	Sizes Available	XS,S,M
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
	Fork	RockShox 30 Silver 27.5", 120mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Caged Lower Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
	Rims	Whyte Trail-21, Sleeve Joint, Offset Rims, 32 Hole
	Tyres	Maxxis Ardent Wire 27.5" x 2.25" Front, Maxxis Crossmark II Wire 27.5" x 2.25" Rear
$\checkmark$	Shift Levers	Shimano Deore SL-M6000, 10 Speed
	Front Derailleur	N/A
$\checkmark$	Rear Derailleur	Shimano Deore RD-M6000, Shadow Plus
$\checkmark$	Cassette	Sunrace CSMS3, 11-42, 10 Speed
$\checkmark$	Chain	Shimano HG-54, 10 Speed
$\checkmark$	Crankset	FSA Alpha Drive 1X, Forged Cranks, Narrow Wide 30T Chainring
$\checkmark$	<b>Bottom Bracket</b>	FSA Square Taper, 73mm
	Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
	Seat	Whyte Custom, Triple Panel Design
<b>√</b>	Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\checkmark$	Stem	Whyte Custom, 35mm XS & S, 45mm M
$\checkmark$	Grips	Whyte Lock-on V Grip
	Front Brakes	Tektro Auriga, 160mm Rotor
	Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
	Brake Levers	Tektro Auriga
	Pedals	Fibre Reinforced Composite Platform
✓	Indicates an upgr	ade or improvement over last years model
✓	Indicates an upgr	ade or improvement over the model below

The 802 is available in the XS size, and all sizes have more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

The 800 Series frame is brand new for 2018, using the very latest Whyte geometry, based around a longer top tube, a short stem and wide 740mm bar. The 800 series bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

Our aluminium hardtails have always offered a fine blend of fun, control and speed. For 2018 the line has upgraded to a dedicated SCR frame. Not needing inner chainring clearance means our engineers are able to further reduce the length of the chainstays for improved agility and a more dynamic ride.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	XS	66.5	74	580	303.5	786
	S	66.5	74	599	303.5	794
	М	66.5	74	618	303.5	814
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
1	XS	1112.5	425	30.9	107	381
١	S	1132.5	425	30.9	115	406
	М	1163	425	30.9	125	444

#### Trail Hardtail - 800 Series - 120mm

#### **SRP** £999



	_	i .	
		Colour	Matt Lime with Eucalyptus/Olive
		Sizes Available	S,M,L,XL
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
<b>√</b>	<b>✓</b>	Fork	RockShox Recon Silver RL 27.5", 130mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer, 110mm X 15mm Boost, Maxle Lite
		Rear Shock	N/A
		Headset	FSA No. 57B, Caged Bearings 1.5" Lower, 1 1.8" Upper Bearings
<b>_</b>	<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
<b>√</b>	<b>√</b>	Front Hub	Alloy, Double Seal Cartridge Bearings, 15 X 110mm Boost, Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
<b>√</b>	<b>√</b>	Rims	WTB STp i25 TCS System, Tubeless Ready, 32 Hole
	<b>√</b>	Tyres	Maxxis Ardent TR 27.5" x 2.25" Front, Maxxis Crossmark II TR 27.5" x 2.25" Rear
$\checkmark$		Shift Levers	Shimano Deore SL-M6000, 10 Speed
		Front Derailleur	N/A
<b>V</b>		Rear Derailleur	Shimano Deore RD-M6000, Shadow Plus
<b>V</b>	<b>V</b>	Cassette	Shimano CS-HG500, 11-42, 10 Speed
<b>V</b>		Chain	Shimano HG-54, 10 Speed
$\checkmark$	<b>√</b>	Crankset	Whyte Forged cranks, Direct Mount 32T Narrow Wide Chainring
<b>V</b>	<b>V</b>	<b>Bottom Bracket</b>	BSA, 73mm
		Seatpost	Whyte 20mm Offset, 30.9mm x 350mm Small & Med 400mm Large & X Large, 6061 Alloy, 2 Bolt Clamp, Adjuster
		Seat	Whyte Custom, Triple Panel Design
$\checkmark$		Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\checkmark$		Stem	Whyte Custom, 35mm S, 45mm M & L, 60mm XL
$\checkmark$		Grips	Whyte Lock-on V Grip
		Front Brakes	Tektro Auriga, 180mm Rotor (160mm on S)
		Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

The 800 Series frame is brand new for 2018, using the very latest Whyte geometry, based around a longer top tube, a short stem and wide 740mm bar.

The BBX internal cable routing keeps cables clean and clear of grime whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine. It also allows the rider to easily upgrade to the new Whyte Drop.it dropper post.

WTB STP i25 TCS System rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	789
М	66.5	74	623	303.5	807
L	66.5	74	641	303.5	832
XL	66.5	74	660	303.5	861
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1137.5	425	30.9	115	406
M	1157.5	425	30.9	125	444
L	1177.5	425	30.9	135	482.6
XL	1197.5	425	30.9	145	533



		Colour	Matt Granite with Grey/Blue
		Sizes Available	XS,S,M
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
<b>√</b>	<b>√</b>	Fork	RockShox Judy TK 27.5", 120mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer, 110mm X 15mm Boost Maxle Lite
		Rear Shock	N/A
		Headset	FSA No. 57B Orbit ZS, Caged Lower Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
$\checkmark$	<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
<b>√</b>	<b>√</b>	Front Hub	Alloy, Double Seal Cartridge Bearings, 15 X 110mm Boost, Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
$\checkmark$	<b>√</b>	Rims	WTB STp i25 TCS System, Tubeless Ready, 32 Hole
<b>√</b>	<b>√</b>	Tyres	Maxxis Ardent TR 27.5" x 2.25" Front, Maxxis Crossmark II TR 27.5" x 2.25" Rear
		Shift Levers	Shimano Deore SL-M6000, 10 Speed
		Front Derailleur	N/A
$\checkmark$		Rear Derailleur	Shimano Deore RD-M6000, Shadow Plus
$\checkmark$	<b>V</b>	Cassette	Shimano CS-HG500, 11-42t, 10 Speed
$\checkmark$		Chain	Shimano HG-54, 10 Speed
$\checkmark$	<b>√</b>	Crankset	Whyte Forged cranks, Direct Mount 30T Narrow Wide Chainring
$\checkmark$	$\checkmark$	<b>Bottom Bracket</b>	BSA, 73mm
		Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
		Seat	Whyte Custom, Triple Panel Design
$\checkmark$		Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\sqrt{}$		Stem	Whyte Custom, 35mm XS & S, 45mm M
$\checkmark$		Grips	Whyte Lock-on V Grip
		Front Brakes	Tektro Auriga, 160mm Rotor
		Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
<b>✓</b>		Indicates an upgr	ade or improvement over last years model
	1	l	

✓ Indicates an upgrade or improvement over the model below

The 806 is available in the XS size, and all sizes have more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

The 806 uses the brand new Deore M6000 Shimano groupset This 1 by 10 set up uses the latest Shadow Plus clutch rear derailleur combined with a Whyte 2pcs chainset with narrow-wide chain ring for perfect chain control.

WTB STP i25 TCS System rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74	580	303.5	786
S	66.5	74	599	303.5	794
М	66.5	74	618	303.5	814
G.			6 . 5 .		Seat
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Tube
XS	Wheelbase	Chain Stay 425	30.9	107	Tube 381
		<u> </u>			

#### Sports Hardtail - 600 Series - 100mm

#### SRP £599



	Colour	Matt Lime with Eucalyptus/Olive
	Sizes Available	S,M,L,XL
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
	Fork	Suntour XCM-LO Hydro Lockout / 100mm Travel Fixed Rebound Damping
	Rear Shock	N/A
	Headset	FSA No.10, Semi Integrated, Caged Bearings
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
<b>√</b>	Rims	Whyte Trail 20, 32 Hole
	Tyres	WTB Ranger Wire 27.5" x 2.25"
<b>√</b>	Shift Levers	Shimano Altus SL-M2000, 9 Speed
$\checkmark$	Front Derailleur	Shimano Altus FD-M2000, 9 Speed
$\checkmark$	Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
	Cassette	Shimano CS-HG-200, 11-36, 9 Speed
	Chain	Shimano CN-HG53
$\checkmark$	Crankset	Shimano FC-MT100, 40-30-22, 9 Speed
	<b>Bottom Bracket</b>	JIS Square Interface, BB-7420ST, Cartridge, 73mm
	Seatpost	Whyte 12mm Offset, 30.9mm x 350mm (400mm on L&XL) 6061 Alloy, 2 Bolt Clamp
$  \checkmark  $	Seat	Whyte Custom
	Bar	Whyte Riser Bar 30mm Rise, 31.8mm, 740mm Wide
$\checkmark$	Stem	Whyte Custom, S, 45mm M,L,XL, 60mm
$ \checkmark $	Grips	Whyte Lock-on V Grip
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Rear Brakes	Tektro HD-M285, 160mm Rotor, Internal Routing
	Brake Levers	Tektro HD-M285
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
<b>✓</b>	Indicates an upgr	ade or improvement over the model below

The Whyte design team given the 600 series the "Trail" treatment in 2018. A longer frame, wider 740mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips make these the most trail-ready bikes in this price category.

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

The frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	14Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	74	604.8	303.5	778.5
M	68.5	74	623.8	303.5	796.5
L	68.5	74	642.8	303.5	821.5
XL	68.5	74	661.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
					Tube
S	1124	435	30.9	115	406
S M	1124 1144	435 435	30.9 30.9	115 125	1
_					406



	Colour	Matt Blue with Orange/Magenta
	Sizes Available	XS,S,M
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
	Fork	Suntour XCM-LO Hydro Lockout / 100mm Travel Fixed Rebound Damping
	Rear Shock	N/A
	Headset	FSA No.10, Semi Integrated, Caged Bearings
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Trail 20, 32 Hole
	Tyres	WTB Ranger Wire 27.5" x 2.25"
	Shift Levers	Shimano Altus SL-M2000, 9 Speed
	Front Derailleur	Shimano Altus FD-M2000, 9 Speed
	Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
	Cassette	Shimano CS-HG-200, 11-36, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-MT100, 40-30-22, 9 Speed
	Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge, 73mm
	Seatpost	Whyte 12mm Offset, 30.9mm x 350mm (400mm on L) 6061 Alloy, 2 Bolt Clamp
$\checkmark$	Seat	Whyte Custom
$\checkmark$	Bar	Whyte Riser Bar 30mm Rise, 31.8mm, 720mm Wide
$\checkmark$	Stem	Whyte Custom, XS,S, 35mm L 45mm
$ \checkmark $	Grips	Whyte Lock-on V Grip
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Rear Brakes	Tektro HD-M285, 160mm Rotor, Internal Routing
	Brake Levers	Tektro HD-M285
	Pedals	Fibre Reinforced Composite Platform
✓	Indicates an upgr	ade or improvement over last years model
V	Indicates an upgra	ade or improvement over the model below

Our Compact MTBs feature shorter geometry and components to better fit a smaller rider. The 604 may be our entry level model, but with carefully chosen parts and an exceptional frame it remains distinctly Whyte.

Whyte design team have taken the 604 and given it the "Trail" treatment in 2018. A wider 720mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips make this a trail-ready package at a great price.

The frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74	581	303.5	764
S	68.5	74	600	303.5	783.5
M	68.5	74	619	303.5	803.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1099.1	435	30.9	107	381
S	1119.1	435	30.9	115	406
М	1139.1	435	30.9	125	444

#### Sports Hardtail - 600 Series - 100mm

#### **SRP** £750



		Colour	Matt Granite with Orange/Blue
		Sizes Available	S,M,L,XL
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
	<b>√</b>	Fork	RockShox XC-30 27.5", 100mm Travel, Adjustable Rebound, Turnkey Lockout
		Rear Shock	N/A
		Headset	FSA No.10, Semi Integrated, Caged Bearings
		Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
		Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
		Spokes	2.0mm PG Spokes with Brass Nipples
$\checkmark$		Rims	Whyte Trail 20, 32 Hole
$\checkmark$		Tyres	WTB Ranger Wire 27.5" x 2.25"
	<b>√</b>	Shift Levers	Shimano Acera SL-M3000, 9 Speed
	$\checkmark$	Front Derailleur	Shimano Acera FD-M3000, 9 Speed
	$\checkmark$	Rear Derailleur	Shimano Acera RD-M3000-SGS Shadow, 9 Speed
$\checkmark$		Cassette	Shimano CS-HG-200, 11-36, 9 Speed
		Chain	KMC. 9 Speed
$\checkmark$	$\checkmark$	Crankset	Shimano FC-M3000-B2, 36-22, 9 Speed
	$\checkmark$	Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge, 73mm
		Seatpost	Whyte 12mm Offset, 30.9mm 6061 Alloy, 2 Bolt Clamp
$\checkmark$		Seat	Whyte Custom
$\checkmark$		Bar	Whyte Riser Bar 30mm Rise, 31.8mm, 740mm Wide
$\checkmark$		Stem	Whyte Custom, S, 45mm M,L,XL, 60mm
$\checkmark$		Grips	Whyte Lock-on V Grip
	<b>V</b>	Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
	<b>√</b>	Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
	<b>√</b>	Brake Levers	Tektro Auriga, HD-M290
		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

The Whyte design team given the 600 series the "Trail" treatment in 2018. A longer frame, wider 740mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips make these the most trail-ready bikes in this price category.

The frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

2018 sees the 605 fitted with Shimano's all new 2 by 9 drive-train. This Full Shimano groupset will give the rider years of trouble-free riding.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	74	604.8	303.5	778.5
M	68.5	74	623.8	303.5	796.5
L	68.5	74	642.8	303.5	821.5
XL	68.5	74	661.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
					Tube
S	1124	435	30.9	115	406
S M	1124 1144	435 435	30.9 30.9	115 125	1
_					406

**SRP** £950



	Colour	Matt Lime with Eucalyptus/Olive
	Sizes Available	S,M,L,XL
<b>√</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
	Fork	SR Suntour Raidon 32, 120mm Travel, Alloy Tapered Steerer, Adjustable Rebound and Lockout, 100mm X 15mm Through Axle
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Caged Lower Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy, Cup & Cone, Double Seal, 15mm X 100mm Through Axle, 32 Hole
	Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
	Rims	Whyte Trail-21, Offset, Sleeve Joint, 29", 32 Hole
	Tyres	Maxxis Ardent 60TPI, 29"x 2.25" Front, Maxxis Crossmark II 60TPI, 29" x 2.25" Rear
$\checkmark$	Shift Levers	Shimano, Deore M6000, 10 Speed
	Front Derailleur	N/A
$\checkmark$	Rear Derailleur	Shimano Deore M6000, Shadow Plus
$\checkmark$	Cassette	SunRace CSMS3, 11-42, 10 Speed
$\checkmark$	Chain	Shimano HG-54, 10 Speed
$\checkmark$	Crankset	FSA Alpha Drive 1X, Forged Cranks, Narrow Wide 28T Chainring
	<b>Bottom Bracket</b>	FSA Square Taper, 73mm
	Seatpost	Whyte 20mm Offset, 30.9mm x 400mm (350mm on Small), 6061 Alloy, 2 Bolt Clamp, Adjuster
	Seat	Whyte Custom, Triple Panel Design
$\checkmark$	Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\checkmark$	Stem	Whyte Custom, 45mm S & M, 60mm L & XL
	Grips	Whyte Lock-on V Grip
	Front Brakes	Tektro Auriga, 180mm Rotor
	Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
	Brake Levers	Tektro Auriga
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
<b>✓</b>	Indicates an upgr	ade or improvement over the model below

Our Alloy 29er hardtail frame is further developed for 2018 with a dedicated SCR frame. Not needing inner chainring clearance means our engineers are able to further reduce the length of the chainstays for improved agility and a more dynamic ride.

A clever combination of 10 speed drive-train parts allows Whyte to bring SCR technology to a much wider group of riders. In only a matter of years this technology has trickled down to make it more affordable and the "go to" spec for a British Trail bike.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5°	75.5	609	305	810
M	66.5°	76.5	628.3	305	820
L	66.5°	77.5	647.6	305	846
XL	66.5°	78.5	665.4	305	860
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1146.5	425	30.9	110	406.4
M	1166.5	425	30.9	115	444.5
L	1186.5	425	30.9	120	495.7
XL	1206.5	425	30.9	135	533.4

#### Trail Hardtail 29er - 120mm

**SRP** £1,150



			Mark Conservatible Place (Parrier (Obs.
		Colour	Matt Orange with Blue/Denim/Sky
		Sizes Available	S,M,L,XL
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
	<b>√</b>	Fork	RockShox Recon Sliver RL 29", Solo Air, 120mm Travel, Alloy Tapered Steerer, Lock out and Rebound, 110 X 15mm Boost, Maxle
		Rear Shock	N/A
		Headset	FSA No. 57B Orbit ZS, Caged Lower Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
<b>\</b>	$\checkmark$	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
<b>\</b>	<b>√</b>	Front Hub	Alloy, Double Seal Cartridge Bearings, 15 X 110mm Boost, Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
<b>\</b>	<b>√</b>	Rims	WTB STp i25 29" Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
	<b>√</b>	Tyres	Maxxis Tomahawk TR 60TPI, 3C with Maxx Terra, 29"x 2.30", Folding Front, Maxxis Crossmark II TR 60TPI, 29" x 2.25", Folding Rear
	$\checkmark$	Shift Levers	SRAM NX, 11 Speed
		Front Derailleur	N/A
	$\checkmark$	Rear Derailleur	SRAM NX, 11 Speed
	<b>\</b>	Cassette	SRAM PG-1030, 11-42, 11 Speed
	<b>√</b>	Chain	SRAM PC-1110, 11 Speed
$\checkmark$	<b>V</b>	Crankset	SRAM NX, X-SYNC Direct Mount 28T, 11 Speed
$\checkmark$	<b>V</b>	<b>Bottom Bracket</b>	SRAM Power Spline, 73mm
		Seatpost	Whyte 20mm Offset, 30.9mm x 400mm (350mm on Small), 2014 Alloy, 2 Bolt Clamp
	$\checkmark$	Seat	Whyte Custom, Triple Panel Design
<b>V</b>		Bar	Whyte Riser Bar 15mm Rise, 31.8mm, 740mm Wide
$\checkmark$		Stem	Whyte Custom, 45mm S & M, 60mm L & XL
<b>√</b>		Grips	Whyte Lock-on V Grip
$\checkmark$	<b>√</b>	Front Brakes	SRAM Level, 180mm Rotor
<b>√</b>	<b>√</b>	Rear Brakes	SRAM Level, 160mm Rotor (170mm on XL), Internal Routing
<b>√</b>	<b>√</b>	Brake Levers	SRAM Level
<u></u>		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	_		

Indicates an upgrade or improvement over the model below

Our Alloy 29er hardtail frame is further developed for 2018 with a dedicated SCR frame. Not needing inner chainring clearance means our engineers are able to further reduce the length of the chainstays for improved agility and a more dynamic ride.

This new frame bristles with UK design features such as the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

A full SRAM NX 1 by 11 is specced on the 629, along with a RockShox Recon RL fork to give this bike proper trail-slaying abilities.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.2Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	66.5°	75.5	609	305	810
	М	66.5°	76.5	628.3	305	820
	L	66.5°	77.5	647.6	305	846
ĺ	XL	66.5°	78.5	665.4	305	860
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	S	1146.5	425	30.9	110	406.4
ĺ	М	1166.5	425	30.9	115	444.5
ĺ	L	1186.5	425	30.9	120	495.7
Ì	XL	1206.5	425	30.9	135	533.4

#### **Carbon Performance Hardtail 29er - C29 Series**

SRP £2,699



	Colour	Matt Black with Lime/Grey
	Sizes Available	S,M,L
	Frame	Uni-directional Multi Monocoque with DOX Internal Cable Routing, Chainstay Post Mount Disc Brake and Full Carbon Dropouts, Inter-Grip Seat Clamp System
<b>√</b>	Fork	Fox Float Performance SC 32, 29", 100mm Travel with 2 Position Remote Adjust, GRIP Damper, Black Coating, Tapered Steerer and 110mm x 15mm Boost E-Thru Axle
	Rear Shock	N/A
	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Shimano XT QR, 32 Hole
<b>✓</b>	Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 110mm Boost Through Axle, 32 Hole
	Spokes	Black Stainless Steel
	Rims	RaceFace AR-27, 27mm wide, Tubeless ready
	Tyres	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection
	Shift Levers	Shimano XT I-Spec II, 11 Speed
	Front Derailleur	N/A
	Rear Derailleur	Shimano XT M8000, Shadow Plus, 11 Speed
	Cassette	Shimano XT M8000, 11-46, 11 Speed
	Chain	Shimeno HG600, 11 Speed
$\checkmark$	Crankset	RaceFace Ride, Direct Mount 34T, 11 Speed
	Bottom Bracket	RaceFace BSA, 73mm
	Seatpost	Whyte 20mm Offset, 30.9mm x 400mm (350mm on Small), 6061 Alloy, 2 Bolt Clamp, Adjuster
	Seat	Whyte Custom Dual Density, Triple Panel Design
	Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
	Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
LT	Grips	Whyte Lock-on, EVA Lightweight Foam
	Front Brakes	Shimano MT500, 180mm Rotor
	Rear Brakes	Shimano MT500, 160mm Rotor, Internal Routing
	Brake Levers	Shimano XT I-Spec II
	Pedals	N/A
<b>√</b>	Indicates an upgra	ade or improvement over last years model
V	Indicates an upgra	ade or improvement over the model below

The 29CS comes fitted with the Fox Step-Cast front fork. This fork has proven to be the benchmark in XC over the last season by exploiting the Boost front hub in a lightweight narrow pitch chassis.

This bike will not only get you round your favourite XC loop in record time, it will also give you the control and balance of the very best of our Whyte trail bikes.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
М	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
М	1127.9	437.5	30.9	110	444.5
Ĺ	1144.9	437.5	30.9	120	495.7

# **29C TEAM**

#### Carbon Performance Hardtail 29er - C29 Series

SRP £4,999



		Colour	Matt Black with Orange/Grey
		Sizes Available	S,M,L
		Frame	Uni-directional Multi Monocoque with DOX Internal Cable Routing, Chainstay Post Mount Disc Brake and Full Carbon Dropouts, Inter-Grip Seat Clamp System
	<b>✓</b>	Fork	Fox Float Factory SC 32, 29", 100mm Travel with 2 Position Remote Adjust, FIT4 Damper, Kashima Coating, Tapered Steerer and 110mm x 15mm Boost E-Thru Axle
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
	<b>√</b>	Rear Hub	Whyte XC-209-Carbon Team Wheelset, 32 StSt Spokes, Whyte Cartridge Bearing, XD Driver, Micro Engagement Freehub, 32 Hole
	<b>√</b>	Front Hub	Whyte XC-209-C Carbon Team Wheelset, 28 StSt Spokes, Whyte Boost 15mm x 110mm Through Axle, 28 Hole
		Spokes	Double Butted Black Stainless Steel
	<b>√</b>	Rims	Whyte XC-209 Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
		Tyres	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall Protection
	<b>√</b>	Shift Levers	SRAM XX1 Eagle, MMX Matchmaker, 12 Speed
		Front Derailleur	N/A
	<b>√</b>	Rear Derailleur	SRAM XX1 Eagle, 12 Speed
	<b>V</b>	Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
	<b>√</b>	Chain	SRAM PCXX1 Eagle, 12 Speed
	<b>√</b>	Crankset	SRAM XX1 Eagle, X-SYNC 2 Direct Mount 36T Chainring, 12 Speed
	<b>√</b>	Bottom Bracket	SRAM GXP Team, 73mm
	<b>√</b>	Seatpost	RaceFace NEXT, Matt UD Carbon, 30.9mm x 400mm, (350mm on Small), 2 Bolt Clamp, Adjuster
	<b>\</b>	Seat	Whyte Custom Road with Lightweight Foam, Triple Panel Design
	<b>√</b>	Bar	RaceFace NEXT, Matt UD Carbon, Flat Bar, 31.8mm, 720mm Wide
		Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
		Grips	Whyte Lock-on, EVA Lightweight Foam
	<b>√</b>	Front Brakes	SRAM Level Ultimate, 180mm CLX 2-Piece Rotor, StSt Hardware
	<b>√</b>	Rear Brakes	SRAM Level Ultimate, 160mm CLX 2-Piece Rotor, StSt Hardware, Internal Routing
	<b>√</b>	Brake Levers	SRAM Level Ultimate Carbon, MMX Matchmaker
		Pedals	N/A
<b>√</b>		Indicates an upgra	ade or improvement over last years model
		İ	

Indicates an upgrade or improvement over the model below

With the best of everything, including the all-new, Fox SC 32 fork with Boost and Kashima coating, Whyte in-house Carbon wheels and Raceface NEXT finishing kit, this is an "out of the box" ready race bike.

The 29-C Team comes with SRAM's XX1 Eagle 1 by 12 drive train. This massive spread of rear sprockets gives the range to increase the front chainring to a 34T, giving even more speed at the top end with no compromise on your climbing gear.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
М	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
М	1127.9	437.5	30.9	110	444.5
L	1144.9	437.5	30.9	120	495.7

# **FRISTON**

#### **Gravel/Adventure - GX Series**

SRP £1,699



	Calann	Mott Oceans with Plus/Clay		
	Colour	Matt Orange with Blue/Sky		
	Sizes Available	50,52,54,56,58		
	Frame	6061 Hydro Formed T6 Aluminium, SCR, Custom Drawn, Multi Butted, Chainstay Flat Mount 160 Disc Mount, DOX Cable Routing with Inter- Grip Seat Clamp System		
<b>✓</b>	Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, Tapered Alloy Steerer, Flat Mount Dropouts and 15mm Stealth Through Axle		
	Rear Shock	N/A		
	Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings		
<b>✓</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, XD Driver, 12mm X 142mm Through Axle, 32 Hole		
	Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Through Axle, 32 Hole		
	Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples		
	Rims	WTB Asym i23, 23mm TCS System, 32 Hole		
<b>√</b>	Tyres	Maxxis Rambler TR, 60tip, Silksheild, Folding Carbon Bead, 700 x 40c		
	Shift Levers	SRAM APEX 1, Full Hydraulic, 11 Speed		
	Front Derailleur	N/A		
	Rear Derailleur	SRAM APEX 1, Long Cage, 11 Speed		
	Cassette	SRAM XG-1150, 10-42, 11 Speed		
	Chain	SRAM PC-1110, 11 Speed		
	Crankset	SRAM APEX 1, X-SYNC 40T Chainring, 175mm Crank Length, 11 Speed		
	Bottom Bracket	SRAM GXP, 68mm		
	Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp		
	Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design		
$\overline{\mathbf{A}}$	Bar	Whyte Gravel, 31.8mm, 500mm Wide		
	Stem	Whyte 6 Degree, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm		
	Grips	Whyte Anti Slip, Cross Bar Tapes		
	Front Brakes	SRAM APEX 1 Hydraulic, 160mm Flat Mount, Internal Routing		
	Rear Brakes	SRAM APEX 1 Hydraulic, 160mm Flat Mount, Internal Routing		
	Brake Levers	SRAM APEX 1 Hydraulic		
	Pedals	None		
<b>✓</b>	Indicates an upgra	ade or improvement over last years model		
1	/ Indicates an upgra	ade or improvement over the model below		

The Friston takes everything we've learnt from MTBs and puts that knowledge into a great value Gravel/Adventure bike package. With hydraulic discs, ground-breaking geometry and SRAM's innovative Apex 1 groupset.

We have applied our unique Whyte frame geometry to the Friston, creating a supremely versatile all-terrain bike. It's equally at home riding your favourite bridle path, winter training or even commuting.

A straight bladed carbon fork with a tapered steerer tube, internal hose routing and 15mm through axle, give this bike great front end stiffness and steering precision.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	557	277	776
52cm	70	74	566	277	797
54cm	70	74	595	277	814
56cm	70	74	604	277	829
58cm	70	74	623	277	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1037	425	30.9	130	500
52cm	1047	425	30.9	145	520
54cm	1077	425	30.9	160	540
56cm	1087	425	30.9	175	560

## **GISBURN**

**Gravel/Adventure - GX Series** 

SRP £1,999



		T	
		Colour	Matt Lime with Eucalyptus/Olive
		Sizes Available	50,52,54,56,58
		Frame	6061 Hydro Formed T6 Aluminium, SCR, Custom Drawn, Multi Butted, Chainstay Flat Mount 160 Disc Mount, DOX Cable Routing with Inter- Grip Seat Clamp System
<b>√</b>		Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, Tapered Alloy Steerer, Flat Mount Dropouts and 15mm Stealth Through Axle
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated Road, 1 1/8" Upper Sealed Cartridge Bearing, 1.5 Lower Sealed Cartridge Bearing
		Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, XD Driver, 12mm X 142mm Through Axle, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples.
		Rims	WTB Asym i23, 23mm TCS System, 32 Hole
<b>√</b>		Tyres	Maxxis Rambler TR, 120TPI, Exo Protection, Folding Carbon Bead, 700 x 40c
	$\checkmark$	Shift Levers	SRAM Force 1, Carbon Hydraulic, 11 Speed
		Front Derailleur	N/A
	$\checkmark$	Rear Derailleur	SRAM Force 1, Long Cage, 11 Speed
	$\checkmark$	Cassette	SRAM PG-1150, 10-42, 11 Speed
		Chain	SRAM PC-1110, 11 Speed
	<b>√</b>	Crankset	SRAM Force 1, X-SYNC 38T Chainring, 175mm Crank Length, Carbon, 11 Speed
		Bottom Bracket	SRAM GXP XR, 68mm
$\checkmark$	<b>√</b>	Seatpost	KS Speed Up, 100mm Dropper Post with Nose Lever Control
	<b>√</b>	Seat	Whyte Custom Road, with Lightweight Foam, CrMo Rails, Triple Panel Design
$\checkmark$		Bar	Whyte Gravel, 31.8mm, 500mm Wide
$\checkmark$		Stem	Whyte 6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
		Grips	Whyte Anti Slip, Cross Bar Tapes
	<b>√</b>	Front Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
	<b>√</b>	Rear Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
	<b>√</b>	Brake Levers	SRAM Force 1, Carbon
		Pedals	None
<b>√</b>		Indicates an upgra	ade or improvement over last years model
		i	

Indicates an upgrade or improvement over the model below

A truly ground-breaking Gravel/Adventure bike with MTB-inspired geometry, tubeless ready wheels and tyres, hydraulic disc brakes and SRAM's innovative Force 1 groupset - and a dropper post so you can make the most out of the geometry on the descents.

Whyte geometry makes this bike exceptionally competent and controllable off-road. "1 by 11" technology offers simplicity and efficiency that cannot be rivalled. Full hydraulic disc brakes add stopping power and control.

Whyte's straight bladed carbon fork with its tapered steerer tube and 15mm through axle gives this bike great front end stiffness and steering precision. Combined with an ultra-wide 500mm wide bar which allows the rider to truly exploit the radical geometry.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	557	277	776
52cm	70	74	566	277	797
54cm	70	74	595	277	814
56cm	70	74	604	277	829
58cm	70	74	623	277	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1037	425	30.9	130	500
52cm	1047	425	30.9	145	520
54cm	1077	425	30.9	160	540
56cm	1087	425	30.9	175	560
58cm	1107	425	30.9	190	580

# **GLENCOE**

#### **RoadPLUS/Adventure**

SRP £1,299



	Colour		Matt Granite with Brown/Tan
	Sizes A	Available	50,52,54,56,58
	Frame		6061 Hydro Formed T6 Aluminium, SCR, Custom Drawn, Multi Butted, Chainstay Flat Mount 160 Disc Mount, DOX Cable Routing with Inter- Grip Seat Clamp System
	Fork		Straight Bladed Alloy Front Fork with Internal Hose Routing, Tapered Alloy Steerer, Flat Mount Dropouts and 12mm Stealth Through Axle
	Rear S	hock	N/A
	Headse	et	FSA No. 42 Integrated Road, 1 1/8" Upper Sealed Cartridge Bearing, 1.5 Lower Sealed Cartridge Bearing
	Rear H	ub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 142mm Through Axle, Centre-lock, 32 Hole
	Front I	Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 100mm Through Axle, Centre-lock, 32 Hole
	Spokes	5	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
	Rims		WTB Asym i23, 23mm, 650b, TCS System, 32 Hole
	Tyres		WTB Horizon, TCS, DNA Compound, Folding, 650b x 47c
	Shift L	evers	SRAM APEX 1, Mechanical, 11 Speed
	Front [	Derailleur	N/A
	Rear D	erailleur	SRAM APEX 1, Long Cage, 11 Speed
	Casset	te	SRAM PC-1130, 11-42, 11 Speed
	Chain		SRAM PC-1110, 11 Speed
	Cranks	et	Whyte Forged Cranks, Direct Mount 44T Narrow Wide Chainring, 11 Speed
	Botton	n Bracket	Shimano SM-BB52, BSA 73mm
	Seatpo	st	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
	Seat		Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
	Bar		Whyte Gravel, 31.8mm, 500mm Wide
	Stem		Whyte -6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
	Grips		Whyte Anti Slip, Cross Bar Tapes
	Front E	Brakes	TRP HyRd Hydraulic, 160mm Flat Mount, Linear Outer Cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Rear B	rakes	TRP HyRd, Flat Mount 160mm, Linear outer cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Brake I	Levers	SRAM APEX 1 Mechanical
	Pedals		None
<b>√</b>	Indicat	es an upgr	ade or improvement over last years model
	✓ Indicat	es an upgr	ade or improvement over the model below

The Glencoe combines our Gravel/Adventure frame with Road Plus tyres. These high air volume 650b tyres have the same rolling circumference as a 700c X 28c setup and give huge levels of comfort and security on even the roughest road surfaces.

"1 by 11" technology offers simplicity and efficiency that cannot be rivalled. TRP mechanical/hydraulic disc brakes add stopping power and control.

Whether you're an innercity, year round commuter or a C or D back-road rider, the Glencoe is perfect bike to give you control on unpredictable surfaces. The Glencoe is the best all round road bike we have ever made.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	557	270	776
52cm	70	74	566	270	797
54cm	70	74	595	270	814
56cm	70	74	604	270	829
58cm	70	74	623	270	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1037	425	30.9	130	500
52cm	1047	425	30.9	145	520
54cm	1077	425	30.9	160	540
56cm	1087	425	30.9	175	560
58cm	1107	425	30.9	190	580

### **DORSET**

#### **Sports Road/Commuter Disc - RD7 Series**

**SRP** £999



	Colour	Matt Granite Orange/Blue/Grey
	Sizes Available	52,54,56,58
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc Mount
	Fork	Whyte, Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Flat Mount Dropouts with Eyelets for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	Rear Hub	Alloy Centre-Lock Disc, Double Sealed Cartridge Bearing Hub, 32 Hole
	Front Hub	Alloy Centre-Lock Disc, Double Sealed Cartridge Bearing Hub, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
	Tyres	WTB Exposure 700 x 32c Race tyre, Distance Compound, Folding
	Shift Levers	Shimano Sora SL-R3000, 9 Speed
	Front Derailleur	Shimano Sora FD-R3000, 9 Speed
	Rear Derailleur	Shimano Sora RD-R3000 GS, 9 Speed
	Cassette	Shimano CS-HG-200-9, 11-32, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-R345, 50-34, 9 Speed
	Bottom Bracket	Shimano BB-ES300 Splined Hollow-Type
	Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, Road, 31.8mm, Compact "Wing" Bar
	Stem	Whyte -6 Degree 50cm 90mm, 52cm 100mm, 54cm&56cm 110mm, 58cm 120mm
	Grips	Whyte Anti Slip with 3M Reflective Logos on Tapes
	Front Brakes	TRP HyRd Hydraulic, 160mm Flat Mount, Linear Outer Cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Rear Brakes	TRP HyRd Hydraulic, 160mm Flat Mount, Linear Outer Cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Brake Levers	Shimano Sora ST-R3000
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
	✓ Indicates an upgr	ade or improvement over the model below

The Dorset features Shimano's 9-speed Sora groupset, with a wide-ratio cassette to make getting up the hills a breeze. On the descents, reliable TRP Flat Mount disc brakes will slow you down safely and easily.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide section Offset Rimmed RD-7 rims and TRP Hydro/Mechanical disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	72.5	74	540	271.5	781.5
54cm	73	73.5	555	271.5	798.5
56cm	73	73	570	271.5	814.5
58cm	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat
					Tube
52cm	998.4	425	27.2	145	520
52cm 54cm	998.4 1003.3	425 425	27.2 27.2	145 160	
					520

# DEVON COMPACT-FII Sports Road/Commuter Disc - RD7 Series SRP £999



	Colour	Matt Granite Magenta/Orange
	Sizes Available	47,49,51,53
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc Mount
	Fork	Whyte, Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Flat Mount Dropouts with Eyelets for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	Rear Hub	Alloy Centre-Lock Disc, Double Sealed Cartridge Bearing Hub, 32 Hole
	Front Hub	Alloy Centre-Lock Disc, Double Sealed Cartridge Bearing Hub, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
<b>V</b>	Tyres	WTB Exposure 700 x 32c Race tyre, Distance Compound, Folding
	Shift Levers	Shimano Sora SL-R3000, 9 Speed
	Front Derailleur	Shimano Sora FD-R3000, 9 Speed
	Rear Derailleur	Shimano Sora RD-R3000 GS, 9 Speed
<b>V</b>	Cassette	Shimano CS-HG-3000-9, 11-34, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	FSA Vero Adventure Pro 48-32, 9 Speed
	Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge Bearings
	Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, Road, 31.8mm, Compact "Wing" Bar
	Stem	Whyte -6 Degree 47cm&49cm 80mm, 51cm 90mm, 53cm 100mm
	Grips	Whyte Anti Slip with 3M Reflective Logos on Tapes
	Front Brakes	TRP HyRd Hydraulic, 160mm Flat Mount, Linear Outer Cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Rear Brakes	TRP HyRd Hydraulic, 160mm Flat Mount, Linear Outer Cables with Kevlar Reinforcement, 160mm Rotor, Internal Routing
	Brake Levers	Shimano Sora ST-R3000
	Pedals	Fibre Reinforced Composite Platform
<b>✓</b>	Indicates an upgr	ade or improvement over last years model
	✓ Indicates an upgr	ade or improvement over the model below

Compact geometry makes for a more comfortable femalefocused fit. The Devon's TRP HyRd disc brakes use an innovative hybrid cable/hydraulic system to provide powerful braking whatever the conditions.

A strong alloy 6061 frame, with mudguard and rack eyelets combined with wide section offset rimmed RD-7 wheels will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with Road geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47cm	71.5	75	507	269	721
49cm	72	74.5	515	271.5	742.5
51cm	72.5	74	525	271.5	776.5
53cm	73	73.5	535	271.5	793.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size 47cm	Wheelbase 984.8	Chain Stay 425	Seat Post 27.2	Head Tube	
		,			Tube
47cm	984.8	425	27.2	115	<b>Tube</b> 470

### **WESSEX ONE**

#### **Carbon Performance Road - RDC7 Series**

SRP £2,199



		Calann	Matt Lines with Europhystus (Olive
		Colour	Matt Lime with Eucalyptus/Olive
		Sizes Available	50,52,54,56,58
		Frame	Uni-directional Multi Monocoque, One-By Specific, with Flat Mount 160 Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm
		Fork	Straight Bladed Carbon Front Fork, Tapered Carbon Steerer with 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
		Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm x 142mm Through Axle, 28 Hole, XD Driver
		Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm x 100mm Through Axle, 28 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples.
		Rims	WTB Asym i23, 23mm TCS System, 28 Hole
		Tyres	WTB Exposure, 700 x 30c, TCS System, Distance Compound
		Shift Levers	SRAM APEX 1, Full Hydraulic, 11 Speed
		Front Derailleur	N/A
		Rear Derailleur	SRAM APEX 1, Long Cage, 11 Speed
		Cassette	SRAM PG-1150, 10-42, 11 Speed
		Chain	SRAM PC-1110, 11 Speed
		Crankset	SRAM APEX 1, X-SYNC 44T Chainring
		Bottom Bracket	SRAM GXP XR, BSA 68mm
		Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3d Forged 2014 Alloy, 2 Bolt Clamp
		Seat	Whyte Custom Road, with Lightweight Foam, CrMo Rails, Triple Panel Design
		Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
		Stem	Whyte -6 Deg/6 Deg, 90mm 50cm, 100mm 52cm, 110mm 54cm, 120mm 56/58cm
		Grips	Whyte Anti Slip with 3M Reflective Logos on Tapes
		Front Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
		Rear Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
		Brake Levers	SRAM APEX 1 Hydraulic
		Pedals	None
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

When we set about designing this bike, we wanted to create an even simpler version of the Wessex. A  $1\times11$  drive train gives 11 useable gears with no overlaps and utter simplicity.

WTB TCS system tyres and rims give all the advantages of tubeless tyres. The lower pressure creates both comfort and grip to give the security that creates the feeling of confidence in all weather and road conditions.

Hydraulic brakes give one finger control from either the hoods or the drops, this modulation allows for complete control in all situations and weather conditions.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	8.8Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72	74.5	525	271.5	764
52cm	72.5	74	540	271.5	781.5
54cm	73	73.5	555	271.5	798.5
56cm	73	73	570	271.5	814.5
58cm	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993	425	27.2	130	500
52cm	998.4	425	27.2	145	520
54cm	1003.3	425	27.2	160	540
56cm	1012.8	425	27.2	175	560
58cm	1027.8	425	27.2	190	580

### WESSEX

#### **Carbon Performance Road - RDC7 Series**

SRP £2,499



		Colour	Matt Zinc with Lime/Grey
		Sizes Available	50,52,54,56,58
		Frame	Uni-directional Multi Monocoque with Flat Mount 160 Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
		Fork	Straight Bladed Carbon Front Fork, Tapered Carbon Steerer with 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 142mm Through Axle, 28 Hole
	<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 100mm Through Axle, 28 Hole
	<b>√</b>	Spokes	DT Competition butted, Black Sandvik Stainless with Black Brass Nipples
	<b>√</b>	Rims	Easton AR-21, 21mm Wide Tubeless Ready, 28 Hole
	<b>√</b>	Tyres	Schwalbe G-ONE Speed, 700 x 30c, TL-Easy Tubeless System, MicroSkin Puncture Protection
	<b>✓</b>	Shift Levers	Shimano ST-R8020 Ultegra, 11 Speed
$\checkmark$	<b>√</b>	Front Derailleur	Shimano FD-580 105, 11 Speed
$\checkmark$	<b>√</b>	Rear Derailleur	Shimano RD-R8000 GS Ultegra, 11 Speed
	<b>/</b>	Cassette	Shimano CS-5800 105, 11-32, 11 Speed
	<b>✓</b>	Chain	Shimano HG-601, 11 Speed
$\checkmark$	<b>√</b>	Crankset	Shimano FC-R510, Double 50-34, 11 Speed, Octalink
	<b>√</b>	Bottom Bracket	Shimano SM-BB52, BSA 68mm
		Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3d Forged 2014 Alloy, 2 Bolt Clamp
		Seat	Whyte Custom Road, with Lightweight Foam, CrMo Rails, Triple Panel Design
		Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
<b>√</b>		Stem	Whyte -6 Deg/6 Deg, 90mm 50cm, 100mm 52cm, 110mm 54cm, 120mm 56/58cm
L		Grips	Whyte Anti Slip with 3M Reflective Logos on Tapes
<b>√</b>	<b>√</b>	Front Brakes	Shimano Ultegra BR-R8070 Hydraulic, Centre-lock 160mm Flat Mount, Internal Routing
<b>√</b>	<b>√</b>	Rear Brakes	Shimano Ultegra BR-R8070 Hydraulic, Centre-lock 160mm Flat Mount, Internal Routing
<b>√</b>	<b>√</b>	Brake Levers	Shimano Ultegra, ST-8020
		Pedals	None
<b>√</b>		Indicates an upgra	ade or improvement over last years model

Indicates an upgrade or improvement over the model below

The Wessex was conceived to be the ideal British road bike. Developed, specified for riding on all road surfaces, it uses the very latest in tubeless-ready, high air volume 30c Schwalbe tyres on 21mm wide Easton AR rims.

The road.cc Endurance Bike of the Year and recipient of a European Design and Innovation Award, the Wessex delivers previously unimaginable levels of grip, confidence and control, whatever the weather.

12mm through axles, tubeless tyres, disc brakes and the ability to fit full length mud guards makes the Wessex arguably the most versatile and capable carbon road bike we have ever made.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72	74.5	525	271.5	764
52cm	72.5	74	540	271.5	781.5
54cm	73	73.5	555	271.5	798.5
56cm	73	73	570	271.5	814.5
58cm	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993	425	27.2	130	500
52cm	998.4	425	27.2	145	520
54cm	1003.3	425	27.2	160	540
56cm	1012.8	425	27.2	175	560
58cm	1027.8	425	27.2	190	580

### **WESSEX SE**

#### **Carbon Performance Road - RDC7 Series**

SRP £6,750



		Colour	Sanded UD with Bronze/Grey
		Sizes Available	50,52,54,56,58
	<b>✓</b>	Frame	Uni-directional Multi Monocoque with core shell rubber. Flat Mount 160 Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
	<b>√</b>	Fork	Straight Bladed Carbon Front Fork, Tapered Carbon Steerer with 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	$\checkmark$	Rear Hub	Easton EC-90, 12mm x 142mm Stealth Through Axle
	<b>√</b>	Front Hub	Easton EC-90, 12mm x 100mm Stealth Through Axle
	<b>V</b>	Spokes	Easton Stainless Steel Bladed
	<b>√</b>	Rims	Easton EC-90 SL Disk, 19mm Wide, 38mm Deep Tubeless Ready Aero Rims, 20 Hole Front, 24 Hole Rear
	<b>√</b>	Tyres	Schwalbe Pro-ONE, 700 x 28c, TL-Easy Tubeless System, MicroSkin Puncture Protection
	$\checkmark$	Shift Levers	SRAM Red Full Hydraulic, eTap Wireless Shifting, 11 Speed
	<b>√</b>	Front Derailleur	SRAM Red, eTap Wireless Shifting with Yaw, 11 Speed
	<b>√</b>	Rear Derailleur	SRAM Red, eTap Wireless Shifting, 11 Speed
	<b>√</b>	Cassette	SRAM, XG 1190, 11-32, 11 Speed
	<b>√</b>	Chain	SRAM PC-RED22, 11 Speed
	<b>√</b>	Crankset	SRAM Red, Double 52-36, Carbon, 11 Speed
	<b>√</b>	<b>Bottom Bracket</b>	SRAM GXP TM, BSA 68mm
	<b>\</b>	Seatpost	FSA Metron, 20mm Offset, 27.2mm x 350mm, UD Carbon, 2 Bolt
	<b>√</b>	Seat	Fi'zi:k Arione R1, Carbon Braided Rails
	<b>√</b>	Bar	FSA Metron 5D Integrated Bar, UD Carbon, 52cm & 54cm 400mm, 56cm 420mm, 58cm 440mm
	<b>√</b>	Stem	FSA Metron 5D Integrated, 52cm & 54cm 100mm, 56cm & 58cm120mm
	<b>/</b>	Grips	Whyte Anti Slip with 3M layer
	<b>√</b>	Front Brakes	SRAM Red Hydraulic, 160mm Flat Mount, Internal Routing
	<b>√</b>	Rear Brakes	SRAM Red Hydraulic, 160mm Flat Mount, Internal Routing
	<b>√</b>	Brake Levers	SRAM Red Hydraulic
		Pedals	None
/		Indicates an upgr	ade or improvement over last years model
	<b>√</b>	Indicates an upgr	ade or improvement over the model below

The Wessex SE is designed to be The Ultimate British Road Bike, designed to take you further, faster and in more comfort than any road bike we have ever designed. The Wessex SE is, without doubt, the fastest bike that can take full length mudguards.

A stripped back finish means we have only lacquered the UD carbon finish to save weight. The lay-up utilises Core Shell Rubber - this nano-technology brings more comfort to both the fork and rear stays, resulting in less rider fatigue.

SRAM Red eTap wireless shifting gives the ultimate in weather proofing with no cables to seal from the environment. Full hydraulic brakes give one finger control and a FSA Metron aero finishing kit completes our best of breed package.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	7.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72	74.5	525	271.5	764
52cm	72.5	74	540	271.5	781.5
54cm	73	73.5	555	271.5	798.5
56cm	73	73	570	271.5	814.5
58cm	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993	425	27.2	130	500
52cm	998.4	425	27.2	145	520
54cm	1003.3	425	27.2	160	540
56cm	1012.8	425	27.2	175	560
58cm	1027.8	425	27.2	190	580

# WHITECHAPEL

#### Fast Urban/Commuter - R7 Series

SRP £599



	Colour	Matt Zinc with Lime/Grey
	Sizes Available	S,M,L,XL
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
	Fork	Whyte, Straight Bladed 6061 T6 Alloy with Forged Crown and Alloy Steerer Tube, Post Mount with Single Eyelets for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
	Tyres	Vittoria Zaffiro, 700 x 32c, Black, with Puncture Protection
$\checkmark$	Shift Levers	Shimano Altus SL-M2000, 9 Speed
	Front Derailleur	N/A
	Rear Derailleur	Shimano Altus RD-M2000, 9 Speed
	Cassette	Shimano CS-HG-200, 11-36, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Alloy, 42T Chainring with Alloy Chain Guard
	Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge Bearings, 68mm
	Seatpost	Whyte Alloy 6061, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
	Seat	Whyte Custom
	Bar	Whyte Alloy 6061, 31.8mm, 30mm Rise, 620mm Wide
	Stem	Whyte Alloy 6061, S 45mm, M 60mm, L 70mm, XL 80mm
	Grips	Whyte Custom with Extra-Thick Bar Plugs
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Rear Brakes	Tektro HD-M285, 160mm Rotor, Internal Routing
	Brake Levers	Tektro HD-M285
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
,	/ Indicates an upgr	ade or improvement over the model below

The Whitechapel is all about simplicity: a single chain ring and nine gears at the back will give years of reliable urban use.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	569.4	266.5	716.5
M	70	73.5	595.2	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1061.4	430	27.2	145	406.4
M	1078.4	430	27.2	165	444.5
L	1078.4 1094.3	430 430	27.2 27.2	165 185	444.5 495



### Fast Urban/Commuter - R7 Series

**SRP** £599



	Colour	Matt Blue with Orange/Sky
	Sizes Available	S,M,L
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
	Fork	Whyte, Straight Bladed 6061 T6 Alloy with Forged Crown and Alloy Steerer Tube, Post Mount with Single Eyelets for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
	Tyres	Vittoria Zaffiro, 700 x 32c, Black, with Puncture Protection
$\checkmark$	Shift Levers	Shimano Altus SL-M2000, 9 Speed
	Front Derailleur	N/A
	Rear Derailleur	Shimano Altus RD-M2000, 9 Speed
$\checkmark$	Cassette	Shimano CS-HG-200, 11-36 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Alloy, 39T chainring with Alloy Chain Guard
	Bottom Bracket	JIS Square Interface, BB-7420ST, Cartridge Bearings, 68mm
	Seatpost	Whyte Alloy 6061, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
	Seat	Whyte Custom, Compact Fit
	Bar	Whyte Alloy 6061, 31.8mm, 30mm Rise, 600mm Wide
	Stem	Whyte Alloy 6061, S 45mm, M 60mm, L 70mm
	Grips	Whyte Custom with Extra-Thick Bar Plugs
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Rear Brakes	Tektro HD-M285, 160mm Rotor, Internal Routing
	Brake Levers	Tektro HD-M285
	Pedals	Fibre Reinforced Composite Platform
<b>✓</b>	Indicates an upgr	ade or improvement over last years model
<b>✓</b>	Indicates an upgr	ade or improvement over the model below

32c tyres on 20mm wide rims give the Carnaby both speed and comfort from the toughest urban commute to a open road adventure.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	11Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
М	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
<b>Size</b> S	Wheelbase 1049.5	Chain Stay 420	Seat Post 27.2	Head Tube	
					Tube

## **SHOREDITCH**

### Fast Urban/Commuter - R7 Series

SRP £699



		Colour	Matt Orange with Black/Grey
		Sizes Available	S,M,L,XL
		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
	<b>√</b>	Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelet for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
		Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
		Front Hub	Alloy Disc, Cup & Cone, Double Seal, 28 Hole
		Spokes	2.0mm PG Spokes with Brass Nipples
		Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
		Tyres	Vittoria Zaffiro, 700 x 32c, Black, with Puncture Protection
$\checkmark$	<b>√</b>	Shift Levers	Shimano Deore, SL-M6000, 10 Speed
		Front Derailleur	N/A
$\overline{\ }$	<b>/</b>	Rear Derailleur	Shimano Deore, Shadow Plus, RD-M6000-SGS, 10 Speed
<b>/</b>	<b>V</b>	Cassette	Shimano CS-HG-500, 11-42, 10 Speed
$\checkmark$	<b>√</b>	Chain	Shimano CN-HG54, 10 Speed
	<b>/</b>	Crankset	Alloy Narrow Wide 44T Chainring with Guard, 10 Speed
		Bottom Bracket	JIS Square interface, BB-7420ST, Cartridge Bearings, 68mm
		Seatpost	Whyte Alloy 6061, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
		Seat	Whyte Custom
		Bar	Whyte Alloy 6061, 31.8mm, 30mm Rise, 620mm Wide
		Stem	Whyte Alloy 6061, S 45mm, M 60mm, L 70mm, XL 80mm
		Grips	Whyte Custom with Extra-Thick Bar Plugs
	<b>√</b>	Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
	<b>√</b>	Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
	<b>√</b>	Brake Levers	Tektro Auriga, HD-M290
		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgr	ade or improvement over last years model
	<b>√</b>	Indicates an upgr	ade or improvement over the model below

Featuring mountain bike clutch mech technology and the all-new Deore 11-42 wide range cassette the Shoreditch has the right gear for any ride.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. 1 by 10 MTB gearing promises years of reliable urban use and hydro discs guarantee consistent performance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	569.4	266.5	716.5
M	70	73.5	595.2	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1061.4	Chain Stay 430	Seat Post 27.2	Head Tube	
		,			Tube
S	1061.4	430	27.2	145	Tube 406.4



### Fast Urban/Commuter - R7 Series SRP £799



	Colour	Matt Granite with Grey/Magenta
	Sizes Available	S,M,L
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
<b>√</b>	Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelet for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
<b>√</b>	Tyres	Vittoria Zaffrio Pro, 700 x 28c, Black, with Puncture Protection, Folding
<b>√</b>	Shift Levers	Shimano Sora SL-R3000, 9 Speed
<b>√</b>	Front Derailleur	Shimano Sora FD-R3000, 9 Speed
<b>√</b>	Rear Derailleur	Shimano Sora RD-R3000, 9 Speed
	Cassette	Shimano CS-HG-200, 11-32, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
	Bottom Bracket	Shimano Octalink BB-ES300, 68mm
<b>√</b>	Seatpost	Whyte Alloy 6061, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
<b>√</b>	Seat	Whyte Custom Compact Fit, Triple Panel Design
	Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 600mm Wide
<b>√</b>	Stem	Whyte Alloy 6061, S 45mm, M 60mm, L 70mm
<b>√</b>	Grips	Whyte Custom Dual Density Lock-on
<b>√</b>	Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
<b>√</b>	Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
<b>1</b>	Brake Levers	Tektro Auriga, HD-M290
	Pedals	Fibre Reinforced Composite Platform
✓	Indicates an upgra	ade or improvement over last years model
<b>√</b>	Indicates an upgra	ade or improvement over the model below

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.4Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1049.5	Chain Stay 430	Seat Post 27.2	Head Tube	
		<u> </u>			Tube

# **PORTOBELLO**

### Fast Urban/Commuter - R7 Series

SRP £799



	Colour	Matt Granite Grey/Lime
	Sizes Available	S,M,L,XL
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
	Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelet for Mud Guards
	Rear Shock	N/A
	Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 28 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
V	Tyres	Vittoria Zaffrio Pro, 700 x 32c, Black, with Puncture Protection, Folding
	Shift Levers	Shimano Sora SL-R3000, 9 Speed
	Front Derailleur	Shimano Sora FD-R3000, 9 Speed
	Rear Derailleur	Shimano Sora RD-R3000, 9 Speed
	Cassette	Shimano CS-HG-200, 11-32 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
	Bottom Bracket	Shimano Octalink BB-ES300, 68mm
V	Seatpost	Whyte Alloy 6061, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
V	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
V	Stem	Whyte Alloy 6061, S 60mm, M 70mm, L 80mm, XL 90mm
V	Grips	Whyte Custom Dual Density Lock-on
	Front Brakes	Tektro Auriga, HD-M290, 160mm Rotor
	Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
	Brake Levers	Tektro Auriga, HD-M290
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
,	/ Indicates an upgr	ade or improvement over the model below

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

The Portobello features a carbon fork and 32c tyres to smooth out the road chatter. The fork has dropout eyelets to allow our custom mud guards to be fitted.

"A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required."

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	569.4	266.5	716.5
М	70	73.5	595.2	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1061.4	Chain Stay 430	Seat Post 27.2	Head Tube	
		<u> </u>			Tube
S	1061.4	430	27.2	145	Tube 406.4

## **CAMBRIDGE**

### Fast Urban/Commuter - R7 Series

**SRP** £899



		Colour	Matt Zinc with Grey/Blue
		Sizes Available	S,M,L,XL
		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
		Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelets for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
		Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
		Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
	<b>√</b>	Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
	<b>√</b>	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
	$\checkmark$	Tyres	Vittoria Zaffrio Pro, 700 x 32c, Black, with Puncture Protection, Folding
	$\checkmark$	Shift Levers	SRAM APEX 1, 11 Speed
		Front Derailleur	N/A
	$\checkmark$	Rear Derailleur	SRAM Apex 1, 11 Speed
	$\checkmark$	Cassette	SRAM PG-1130, 11-42, 11 Speed
	$\checkmark$	Chain	SRAM PC-1110, 11 Speed
	<b>V</b>	Crankset	Whyte Forged Cranks, Direct Mount 44T Narrow Wide Chainring
		<b>Bottom Bracket</b>	FSA Square Taper, 68mm
		Seatpost	Whyte Alloy 6061, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
		Seat	Whyte Custom, Triple Panel Design
	$\checkmark$	Bar	Whyte Alloy 6061, 31.8mm, 30mm Rise, 620mm Wide
		Stem	Whyte Alloy 6061, S 70mm, M 80mm, L&XL 90mm
		Grips	Whyte Custom Dual Density Lock-on
		Front Brakes	Tektro Auriga, 160mm Rotor
		Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
$\checkmark$		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

We were excited to be able to spec SRAM's Apex 1 road groupset on the Cambridge. With its 1 by 11 wide range 11-44T drivetrain, it will help you conquer even the hilliest of cities.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, with a shorter stem for excellent slow speed manoeuvrability.

32c tyres on 20mm wide rims give the Cambridge both speed and comfort from the toughest urban commute to a open road adventure.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	569.4	266.5	716.5
М	70	73.5	595.2	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1061.4	Chain Stay 430	Seat Post 27.2	Head Tube	
		<u> </u>			Tube
S	1061.4	430	27.2	145	Tube 406.4



#### Fast Urban/Commuter - R7 Series

SRP £1,099



		Colour	Matt Zinc with Orange/Magenta
		Sizes Available	S,M,L
		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
		Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelet for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
$\checkmark$	<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
$\checkmark$	<b>\</b>	Front Hub	Alloy, Double sealed Cartridge Bearings, 28 Hole
	<b>√</b>	Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
	<b>√</b>	Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
$\checkmark$	<b>\</b>	Tyres	WTB Exposure, 700 x 32c, 60tpi, Distance Compound, Folding
	$\checkmark$	Shift Levers	SRAM X5, 10 Speed
	<b>√</b>	Front Derailleur	SRAM Via Centro, 10 Speed
$\checkmark$	<b>\</b>	Rear Derailleur	SRAM Via GT, 10 Speed
	$\checkmark$	Cassette	SRAM PG-1030, 11-32, 10 Speed
	<b>√</b>	Chain	SRAM PC-1031, 10 Speed
$\checkmark$	$\checkmark$	Crankset	SRAM APEX, 48-34, 10 Speed, Compact
	<b>\</b>	Bottom Bracket	SRAM GXP Team, 68mm
		Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clemp
	<b>√</b>	Seat	Whyte Custom Compact Fit, Triple Panel Design
$\checkmark$		Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 600mm Wide
		Stem	Whyte Alloy 6061, S 60mm, M 70mm, L 80mm
		Grips	Whyte Custom Dual Density Lock-on
		Front Brakes	Tektro Auriga, 160mm Rotor
		Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

A lightweight aluminium frame employs compact geometry to make this bike a perfect fit for smaller riders, while a carbon fork does a great job of dampening out road buzz.

Based on our high performance mountain bike geometry, the Pimlico has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability.

The Pimlico takes advantage of SRAM's transmission, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	9.9Kg

Siz	:e	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S		69	74.5	547.9	266.5	732.5
M	I	69.5	73.5	573.6	266.5	735.5
L		70	73	599.8	266.5	767.5
Siz	'O	Wheelbase	Chain Stav	Seat Post	Head Tube	Seat
	.c	Wileelbase	Chain Stay	Seat Post	неай тире	Tube
S		1049.5	430	27.2	140	<b>Tube</b> 393.7
S			,			

# **STIRLING**

Fast Urban/Commuter - R7 Series

**SRP** £1,099



		Colour	Matt Granite with Grey/Orange
		Sizes Available	S,M,L,XL
		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
		Fork	Whyte, Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Post Mount with Eyelet for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
	<b>√</b>	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
$\sqrt{}$	<b>√</b>	Front Hub	Alloy, Double Sealed Cartridge Bearings, 28 Hole
		Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
		Rims	Whyte Disc Road 20mm Deep, 20mm Wide, Offset Sleeved Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
$\checkmark$	<b>\</b>	Tyres	WTB Exposure, 700 x 32c, 60tpi, Distance Compound, Folding
	<b>√</b>	Shift Levers	SRAM X5, 10 Speed
	$\checkmark$	Front Derailleur	SRAM Via Centro, 10 Speed
	$\checkmark$	Rear Derailleur	SRAM Via GT, 10 Speed
	$\checkmark$	Cassette	SRAM PG-1130, 11-32, 10 Speed
		Chain	SRAM PC-1130, 10 Speed
	$\checkmark$	Crankset	SRAM APEX, 50-34, 10 Speed, Compact
	<b>√</b>	Bottom Bracket	SRAM GXP XR, 68mm
		Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clemp
	$\checkmark$	Seat	Whyte Custom, Triple Panel Design
		Bar	Whyte Alloy 6061, 31.8mm, 30mm Rise, 620mm Wide
		Stem	Whyte Alloy 6061, S 70mm, M 80mm, L&XL 90mm
		Grips	Whyte Custom Dual Density Lock-on
		Front Brakes	Tektro Auriga, 160mm Rotor
		Rear Brakes	Tektro Auriga, HD-M290, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
$\checkmark$		Indicates an upgr	ade or improvement over last years model
	<b>✓</b>	Indicates an upgra	ade or improvement over the model below

The Stirling features a carbon fork and 32c tyres to smooth out the road chatter. 2x10 SRAM gearing combines MTB durability with road bike performance.

Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	10Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	569.4	266.5	716.5
M	70	73.5	595.2	266.5	748.5
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
<b>Size</b> S	Wheelbase 1061.4	Chain Stay 430	Seat Post 27.2	Head Tube	
		<u> </u>			Tube
S	1061.4	430	27.2	145	Tube 406.4

### **RIDGEWAY**

#### **All Terrain/Leisure - C7 Series**

SRP £599



	Colour	Matt Orange with Grey/Orange
	Sizes Available	S,M,L,XL
<b>√</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
	Fork	SR Suntour NEX HLO, Alloy Steerer, 63mm Travel, Hydro Lockout
	Rear Shock	N/A
	Headset	FSA No.10, Semi Integrated, Caged Bearings
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Rims	Whyte 700c, 32 Hole
<b>√</b>	Tyres	Schwalbe SILENTO K-Guard 700 x 35c
<b>/</b>	Shift Levers	Shimano Altus SL-M2000, 9 Speed
	Front Derailleur	Shimano Acera FD-T3000, 9 Speed
<b>/</b>	Rear Derailleur	Shimano Altus RD-M2000, 9 Speed
<b>V</b>	Cassette	Shimano CS-HG-200-9, 11-32, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-M371, 48-36-26, 9 Speed
	Bottom Bracket	Shimano BB-UN-100 Square Taper
	Seatpost	Whyte Alloy 6061. 12mm Offset, 30.9mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, High Rise 30mm, 31.8mm, 620mm Wide
	Stem	Whyte Alloy 6061, S 80mm, M&L 90mm
	Grips	Whyte Custom Dual Density Lock-on
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Rear Brakes	Tektro HD-M285, 160mm Rotor
	Brake Levers	Tektro HD-M285
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgr	ade or improvement over last years model
	✓ Indicates an upgr	ade or improvement over the model below

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0°	74	592	278	765
М	69.0°	73.5	617	278	774
L	69.0°	73	632	278	805
XL	69.0°	73	646.6	278	854
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1099	Chain Stay 435	Seat Post 30.9	Head Tube	
		<u> </u>			Tube
S	1099	435	30.9	115	<b>Tube</b> 457

# **RIDGEWAY WOMEN'S**

**All Terrain/Leisure - C7 Series** 

SRP £599



Sizes Available  Noise Alluminium, Multi Butted, Internal Cable Routin  Mount  Sizes Available  Noise Alluminium, Multi Butted, Internal Cable Routin  Mount  Sizes Available  Noise Alluminium, Multi Butted, Internal Cable Routin  Mount  Sizes Available  Noise Alluminium, Multi Butted, Internal Cable Routin  Noise Alluminium, Alluminium, Alluminium, Alluminium Sizes Alluminium  Sizes Available Alluminium  Sizes Available Allow Sizes Alluminium  Sizes Available A
with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount  Fork SR Suntour NEX HLO, Alloy Steerer, 63mm Travel, Hydro Lockout  Rear Shock N/A  Headset FSA No.10, Semi Integrated, Caged Bearings Rear Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole Front Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole Spokes 2.0mm PG Spokes with Brass Nipples  Rims Whyte 700c, 32 Hole  Tyres Schwalbe SILENTO K-Guard 700 x 35c Shiff Levers Shimano Altus SL-M2000, 9 Speed Front Derailleur Shimano Acera FD-T3000, 9 Speed  Rear Derailleur Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53 Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Rear Shock  N/A  Headset  FSA No.10, Semi Integrated, Caged Bearings  Rear Hub  Alloy Disc, Cup & Cone, Double Seal, 32 Hole  Front Hub  Alloy Disc, Cup & Cone, Double Seal, 32 Hole  Spokes  2.0mm PG Spokes with Brass Nipples  Rims  Whyte 700c, 32 Hole  ✓ Tyres  Schwalbe SILENTO K-Guard 700 x 35c  Shiff Levers  Shimano Altus SL-M2000, 9 Speed  Front Derailleur  Mear Derailleur  Shimano Acera FD-T3000, 9 Speed  Cassette  Shimano CS-HG-200-9, 11-32, 9 Speed  Chain  Shimano CN-HG53  Crankset  Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket  Shimano BB-UN-100 Square Taper  Seatpost  Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Headset FSA No.10, Semi Integrated, Caged Bearings  Rear Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole  Front Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole  Spokes 2.0mm PG Spokes with Brass Nipples  Rims Whyte 700c, 32 Hole  Tyres Schwalbe SILENTO K-Guard 700 x 35c  Shiff Levers Shimano Altus SL-M2000, 9 Speed  Front Derailleur Shimano Acera FD-T3000, 9 Speed  Rear Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Rear Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole Front Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole Spokes 2.0mm PG Spokes with Brass Nipples Rims Whyte 700c, 32 Hole  ✓ Tyres Schwalbe SILENTO K-Guard 700 x 35c  ✓ Shifft Levers Shimano Altus SL-M2000, 9 Speed Front Derailleur Shimano Acera FD-T3000, 9 Speed  ✓ Rear Derailleur Shimano Altus RD-M2000, 9 Speed  ✓ Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Front Hub Alloy Disc, Cup & Cone, Double Seal, 32 Hole Spokes 2.0mm PG Spokes with Brass Nipples Rims Whyte 700c, 32 Hole  ✓ Tyres Schwalbe SILENTO K-Guard 700 x 35c Shift Levers Shimano Altus SL-M2000, 9 Speed Front Derailleur Shimano Acera FD-T3000, 9 Speed  Front Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53 Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Spokes 2.0mm PG Spokes with Brass Nipples  Rims Whyte 700c, 32 Hole  ✓ Tyres Schwalbe SILENTO K-Guard 700 x 35c  ✓ Shift Levers Shimano Altus SL-M2000, 9 Speed  Front Derailleur Shimano Acera FD-T3000, 9 Speed  ✓ Rear Derailleur Shimano Altus RD-M2000, 9 Speed  ✓ Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Rims Whyte 700c, 32 Hole  ✓ Tyres Schwalbe SILENTO K-Guard 700 x 35c  ✓ Shift Levers Shimano Altus SL-M2000, 9 Speed  Front Derailleur Shimano Acera FD-T3000, 9 Speed  ✓ Rear Derailleur Shimano Altus RD-M2000, 9 Speed  ✓ Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Tyres Schwalbe SILENTO K-Guard 700 x 35c  Shift Levers Shimano Altus SL-M2000, 9 Speed  Front Derailleur Shimano Acera FD-T3000, 9 Speed  Rear Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Shift Levers Shimano Altus SL-M2000, 9 Speed Front Derailleur Shimano Acera FD-T3000, 9 Speed  Rear Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Front Derailleur Shimano Acera FD-T3000, 9 Speed  Rear Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Rear Derailleur Shimano Altus RD-M2000, 9 Speed  Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Cassette Shimano CS-HG-200-9, 11-32, 9 Speed  Chain Shimano CN-HG53  Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Chain   Shimano CN-HG53
Crankset Shimano FC-M371, 48-36-26, 9 Speed  Bottom Bracket Shimano BB-UN-100 Square Taper  Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Bottom Bracket Shimano BB-UN-100 Square Taper Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Seatpost Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
Seat Whyte Custom Women's Fit, Triple Panel Design
Bar Whyte Alloy 6061, High Rise 30mm, 31.8mm, 620mm Wide
Stem Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
Grips Whyte Custom Dual Density Lock-on
Front Brakes Tektro HD-M285, 160mm Rotor
Rear Brakes Tektro HD-M285, 160mm Rotor
Brake Levers Tektro HD-M285
Pedals Fibre Reinforced Composite Platform
✓ Indicates an upgrade or improvement over last years model
✓ Indicates an upgrade or improvement over the model below

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.6Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	68	74.5	570	278	718
	M	69	74	587	278	737
	L	69	73.5	612	278	756.9
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
J	S	1081.3	435	30.9	107	431.8
	M	1094	435	30.9	115	457

## **CALEDONIAN**

### All Terrain/Leisure - C7 Series

**SRP** £875



		Colour	Matt Zinc with Lime/Grey
		Sizes Available	S,M,L
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts and Integrated Kickstand Mount
	<b>\</b>	Fork	SR Suntour NCX-D LO, Alloy Steerer, 63mm travel, Hydro Lockout
		Rear Shock	N/A
		Headset	FSA No.10, Semi Integrated, Caged Bearings
		Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
		Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
		Spokes	2.0mm PG, Spokes with Brass Nipples
		Rims	Whyte 700c, 32 Hole
	<b>√</b>	Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture Protection
	<b>√</b>	Shift Levers	Shimano Deore SL-T6000, 10 Speed
	$\checkmark$	Front Derailleur	Shimano Deore FD-T6000, 10 Speed
$\checkmark$	<b>√</b>	Rear Derailleur	Shimano Deore LX RD-T670, 10 Speed
<b>V</b>	<b>\</b>	Cassette	Shimano Deore CS-HG500, 11-34, 10 Speed
	<b>√</b>	Chain	Shimano CN-HG54, 10 Speed
<b>V</b>	<b>V</b>	Crankset	Shimano FC6010, 48-36-26, 10 Speed
	$\checkmark$	<b>Bottom Bracket</b>	Shimano BB-ES300 Splined Hollow-Type
		Seatpost	Whyte Alloy 6061, 15mm Offset, 30.9mm, 2 Bolt Clamp
	$\checkmark$	Seat	Whyte Custom, Triple Panel Design
		Bar	Whyte Alloy 6061, High Rise 30mm, 31.8mm, 620mm Wide
		Stem	Whyte Alloy 6061, S 80mm, M&L 90mm
		Grips	Whyte Custom Ergo Dual Density Lock-on
		Front Brakes	Shimano BR-M447, 160mm Rotor
		Rear Brakes	Shimano BR-M447, 160mm Rotor
		Brake Levers	Shimano BL-M445
		Pedals	Fibre Reinforced Composite Platform
<b>√</b>		Indicates an upgr	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that are internally routed to keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.1Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0°	74	592	278	765
М	69.0°	73.5	617	278	774
L	69.0°	73	632	278	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099	435	30.9	115	457
М	1119	435	30.9	125	495
	1129	435	30.9	135	546

## **CALEDONIAN WOMEN'S**

All Terrain/Leisure - C7 Series

**SRP** £875



		Pedals	Fibre Reinforced Composite Platform		
		Brake Levers	Shimano BL-M445		
		Rear Brakes	Shimano BR-M447, 160mm Rotor		
		Front Brakes	Shimano BR-M447, 160mm Rotor		
		Grips	Whyte Custom Ergo Dual Density Lock-on		
		Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm		
	_	Bar	Whyte Alloy 6061, High Rise 30mm, 31.8mm, 620mm Wide		
	<b>√</b>	Seat	Whyte Custom Women's Fit, Triple Panel Design		
	_	Seatpost	Whyte Alloy 6061, 15mm Offset, 30.9mm, 2 Bolt Clamp		
	<b>\</b>	Bottom Bracket	Shimano BB-ES300 Splined Hollow-Type		
<b>/</b>	/	Crankset	Shimano FC6010, 48-36-26, 10 Speed		
	/	Chain	Shimano CN-HG54, 10 Speed		
<b>y</b>	<u></u>	Cassette	Shimano Deore CS-HG500, 11-34, 10 Speed		
<u></u>	<u></u>	Rear Derailleur	Shimano Deore LX RD-T670, 10 Speed		
<u>v</u>	<u>v</u>	Front Derailleur	Shimano Deore FD-T6000, 10 Speed		
	<b>√</b>	Shift Levers	Protection Shimano Deore SL-T6000, 10 Speed		
	/	Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture		
_		Rims	Whyte 700c, 32 Hole		
		Spokes	2.0mm PG, Spokes with Brass Nipples		
		Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole		
		Rear Hub	FSA No.10, Semi Integrated, Caged Bearings  Alloy Disc, Cup & Cone, Double Seal, 32 Hole		
		Rear Shock Headset	N/A		
	<b>√</b>	Fork	SR Suntour NCX-D LO, Alloy Steerer, 63mm Travel, Hydro Lockout		
<b>√</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts and Integrated Kickstand Mount		
		Sizes Available	S,M,L		
		Colour	Matt Granite with Grey/Orange		

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are more flexible and offer less steering control).

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.1Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	68	74.5	570	278	718
	М	69	74	587	278	737
	L	69	73.5	612	278	756.9
Ш						
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	Size S	Wheelbase 1081.3	Chain Stay 435	Seat Post 30.9	Head Tube	
						Tube

## **CLIFTON E-BIKE**

Fast Urban/Commuter STEPS e-Bike - eR7 Series

SRP £2,350



		Colour	Matt Granite with Bronze/Blue
		Sizes Available	M,L,XL
<b>✓</b>		Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
<b>√</b>		Fork	Whyte, Straight Bladed Alloy 6061, with Flat Mount and Single Eyelets, Internal Cable Route
		Rear Shock	N/A
		Headset	FSA No. 42 B CUP for 1 1/8" Upper and 1.5" Lower
$\overline{\ }$		Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
		Spokes	2.0mm, Black Stainless with Brass Nipples
<b>√</b>		Rims	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
$\checkmark$		Tyres	WTB Byway, TCS System, DNA Compound, Folding, 650 x 47c
$\checkmark$		Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
		Front Derailleur	N/A
$\checkmark$		Rear Derailleur	Shimano RD-M6000, Deore, 10-Speed, Shadow Plus
$\checkmark$		Cassette	Shimano CS-HG500, 11-34T, 10 Speed
		Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
		Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
		Bottom Bracket	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
		Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
		Seat	Whyte Custom, Triple Panel Design
		Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
		Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
$\checkmark$		Grips	Whyte Custom Dual Density Lock-on
$\checkmark$		Front Brakes	Tektro Auriga, 160mm Rotor, Flat Mount, Internal Routing
		Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
		Brake Levers	Tektro Auriga
		Pedals	Fibre Reinforced Composite Platform
$\checkmark$		Indicates an upgr	ade or improvement over last years model
	<b>√</b>	Indicates an upgr	ade or improvement over the model below

Using Shimano's STEPS e-Bike Drive Unit the Clifton is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

The Clifton comes fitted with 650b wheels and 47c RoadPlus, WTB Byway tyres, these offer great comfort, better grip and security on rough urban roads or light off road rides.

Integrated lighting, controlled from your STEPS head unit gives you fingertip control of your lights for year-round usage. These powerful lights make night riding easy but also give you the ability to use them as daytime running lights for extra visibility in traffic.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	18.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	70°	73.5	595.2	266.5	755.5
L	70°	73.5	608.8	266.5	785.5
XL	70°	73	628.5	266.5	812.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	1099	450	27.2	165	445.3
L	1113.7	450	27.2	185	495.3
XL	1128.7	450	27.2	205	533.4

## HIGHGATE E-BIKE WARREN

Fast Urban/Commuter STEPS e-Bike - eR7 Series

SRP £2,350



	Colour	Matt Granite with Bronze/Magenta
	Sizes Available	S.M.L
<b>√</b>	Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
<b>✓</b>	Fork	Whyte, Straight Bladed Alloy 6061, with Flat Mount and Single Eyelets, Internal Cable Route
	Rear Shock	N/A
	Headset	FSA No. 42 B CUP for 1 1/8" upper and 1.5" lower
	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
<b>/</b>	Front Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
	Spokes	2.0mm, Black Stainless with Brass Nipples
<b>√</b>	Rims	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
$\checkmark$	Tyres	WTB Byway, TCS System, DNA Compound, Folding, 650 x 47c
<b>√</b>	Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
	Front Derailleur	N/A
$\checkmark$	Rear Derailleur	Shimano RD-M6000, Deore, 10-Speed, Shadow Plus
$\checkmark$	Cassette	Shimano CS-HG500, 11-34T, 10 Speed
	Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
	Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
	Bottom Bracket	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
	Seatpost	Whyte Alloy 6061, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
	Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
<b>V</b>	Grips	Whyte Custom Dual Density Lock-on
$\checkmark$	Front Brakes	Tektro Auriga, 160mm Rotor, Flat Mount, Internal Routing
	Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
	Brake Levers	Tektro Auriga
	Pedals	Fibre Reinforced Composite Platform
✓	Indicates an upgr	rade or improvement over last years model
	✓ Indicates an upgr	rade or improvement over the model below

Using Shimano's STEPS e-Bike Drive Unit the Highgate is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling of this compact fit bike.

The Highgate comes fitted with 650b wheels and 47c Road Plus, WTB Byway tyres. These offer great comfort with better grip and security on rough urban roads or light off road rides.

Integrated lighting, controlled from your STEPS head unit gives you fingertip control of your lights for year-round usage. These powerful lights make night riding easy but also give you the ability to use them as daytime running lights for extra visibility in traffic.

Dropout Code	DROPWHRC0
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	18.6Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	69°	74.5	547.9	266.5	755.5
	М	69.5°	73.5	573.6	266.5	785.5
	L	70°	73	600	266.5	812.5
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
	S	1069.8	450	27.2	140	393.7
l	M	1081.8	450	27.2	160	431.8

# **CONISTON E-BIKE**

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP £2,299



	Colour	Matt Granite with Grey/Blue
	Sizes Available	S,M,L
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
	Fork	SR Suntour NCX-D LO, 63mm Travel, Tapered Steerer Tube, Coil Spring and Hydro Lockout
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
	Rims	WTB SX-17 700c, 32 Hole, with Eyelets
	Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture Protection
$\checkmark$	Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
	Front Derailleur	N/A
$\checkmark$	Rear Derailleur	Shimano RD-T670, 10 Speed
$\checkmark$	Cassette	Shimano CS-HG500-10, 11-34, 10 Speed
	Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
	Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
	<b>Bottom Bracket</b>	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
	Seatpost	Whyte Alloy 6061, 15mm Offset, 30.9mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
	Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
	Grips	Whyte Custom Ergo Dual Density Lock-on
	Front Brakes	Shimano M425, 160mm Rotor
	Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
	Brake Levers	Shimano M395
	Pedals	Fibre Reinforced Composite Platform
<b>✓</b>	Indicates an upgr	ade or improvement over last years model
	Indicates an upgra	ade or improvement over the model below

Using Shimano's STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance, plus Whyte's very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	20.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5°	74	593.8	278	757
М	70°	73.5	620.5	278	811
L	70°	73	640.9	278	815
					Seat
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Tube
Size S	Wheelbase 1115.5	Chain Stay 455	Seat Post 30.9	Head Tube	
					Tube

# **CONISTON WOMEN'S E-BIKE**

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP £2,299



	Colour	Matt Granite with Bronze/Magenta
	Sizes Available	S,M,L
<b>✓</b>	Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
	Fork	SR Suntour NCX-D LO, 63mm Travel, Tapered Steerer Tube, Coil Spring and Hydro Lockout
	Rear Shock	N/A
	Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
	Rims	WTB SX-17 700c, 32 Hole, with Eyelets
	Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture Protection
$\checkmark$	Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
	Front Derailleur	N/A
<b>√</b>	Rear Derailleur	Shimano SLX T670, 10 Speed
$\checkmark$	Cassette	Shimano CS-HG500-10, 11-34, 10 Speed
	Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
	Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
	<b>Bottom Bracket</b>	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
	Seatpost	Whyte Alloy 6061, 15mm Offset, 30.9mm, 2 Bolt Clamp
	Seat	Whyte Custom, Triple Panel Design
	Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
	Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
	Grips	Whyte Custom Ergo Dual Density Lock-on
	Front Brakes	Shimano M425, 160mm Rotor
	Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
	Brake Levers	Shimano M395
	Pedals	Fibre Reinforced Composite Platform
<b>√</b>	Indicates an upgra	ade or improvement over last years model
	✓ Indicates an upgr	ade or improvement over the model below

Using Shimano's STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance plus Whyte's very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	20.2Kg

	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	S	68	74.5	559.4	278	706
	M	69	74	587.3	278	738
	L	69	73.5	612.2	278	758
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
l	S	1101.6	455	30.9	107	406.4
ı						
	М	1114.3	455	30.9	115	444.5

# **STRAWBERRY HILL**

Lightweight Classic/Leisure

SRP £650



	Colour	Matt Granite with Grey/Gold
	Sizes Available	S,M,L
	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts and Integrated Kickstand Mount
	Fork	Whyte Alloy 6061, Curved Blade with Alloy Steerer
	Rear Shock	N/A
	Headset	FSA No.10, Semi Integrated, Caged Bearings
	Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
	Front Hub	Alloy Cup & Cone, Double Seal, 32 Hole
	Spokes	2.0mm, Silver Stainless with Brass Nipples
	Rims	Whyte Double Walled Alloy, 700c, 32 Hole
	Tyres	Maxxis Roamer, 700 x 42c High Air Volume, with Kevlar Puncture Guard
	Shift Levers	Shimano Altus SL-M2000, 9 Speed
<b>√</b>	Front Derailleur	Shimano Acera FD-T3000, 9 Speed
	Rear Derailleur	Shimano Acera RD-T3000, 9 Speed
	Cassette	Shimano CS-HG-201, 11-34, 9 Speed
	Chain	KMC, 9 Speed
	Crankset	Shimano FC-T3010, 48-36-26
	Bottom Bracket	Shimano BB-UN-100 Square Taper
	Seatpost	Whyte Alloy 6061, 20mm Offset, 30.9mm, 2 Bolt Clamp
	Seat	Whyte Custom Women's Fit, Triple Panel Design
	Bar	Whyte Swept Bar, 25.4mm, 600mm Wide, 45mm Sweep
	Stem	Whyte Custom, High Rise, 20 Deg
	Grips	Ergon, Single Density For Swept Bar
	Front Brakes	Tektro Forged V Brake
	Rear Brakes	Tektro Forged V Brake
	Brake Levers	Tektro V Brake Levers with Integrated Bell
	Pedals	Alloy Body with Non Slip Grip
<b>✓</b>	Indicates an upgr	ade or improvement over last years model
<b>✓</b>	Indicates an upgr	ade or improvement over the model below

Whyte's take on a stylish, comfortable, lifestyle bike. Combining the elegance of a vintage machine with a 27 speed drivetrain and a remarkably lightweight frame, we've made it even easier to get up the hills, or just to lift up the stairs when you get home.

Comfort was given top priority with the Strawberry Hill. The Whyte saddle is highly cushioned but also lightweight. The grips are specifically designed to fit your palm on a swept handle bar and even the brake levers have a Kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover, kick stand, and internal cable routing keep all the moving parts away from the rider.

Dropout Code	DROPWHLC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	537.3	288	663
M	69	74	563	288	686
L	69	73.5	586.8	288	677
					Seat
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Tube
Size S	Wheelbase 1066	Chain Stay 445	Seat Post 30.9	Head Tube	
					Tube

### T-130C R

#### T-130 Trail Suspension - 130mm

SRP £3,250



		Colour	Matt Petrol with Reef/Orange
		Sizes Available	M,L,XL
	<b>√</b>	Frame	Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System with Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
		Fork	RockShox Revelation RC, 27.5", 130mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Lite
		Rear Shock	RockShox Monarch Debonair, RT, Fast Black Coating, Adjustable Rebound and Compression
	<b>√</b>	Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
		Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
		Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
		Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
		Rims	WTB STp i29 29mm Wide, TCS System, 32 Hole
	<b>✓</b>	Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra), EXO Sidewall Protection Front, Maxxis Crossmark II TR 27.5 X 2.25" EXO Sidewall Protection, Rear
		Shift Levers	SRAM GX Eagle, Matchmaker Clamp, 12 Speed
		Front Derailleur	N/A
		Rear Derailleur	SRAM GX Eagle, 12 Speed
		Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
		Chain	SRAM GX Eagle, Silver, 12 Speed
		Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, Boost, 12 Speed
		<b>Bottom Bracket</b>	SRAM GXP XR, BSA, 73mm
		Seatpost	KS LEV Intrega, 150mm, 30.9mm
		Seat	Whyte Custom Dual Density, Triple Panel Design
		Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide (30mm Rise, 780mm on XL)
		Stem	Whyte Gravity Stem, 40mm M, 50mm L/XL
		Grips	Whyte Lock-on V Grip
	<b>√</b>	Front Brakes	SRAM Guide T, 4 Pots, 180mm Rotor
	<b>V</b>	Rear Brakes	SRAM Guide T, 4 Pots, 160mm Rotor (170mm on XL), Internal Routing
	<b>√</b>	Brake Levers	SRAM Guide T, Matchmaker
		Pedals	None
✓		Indicates an upgr	ade or improvement over last years model

Indicates an upgrade or improvement over the model below

The T-130C R features our "5/5 award winning" single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

SRAM's all-new Eagle GX 12 speed drive-train is used on the T-130C R. This evolutionary groupset give the rider a massive 500% gear range allowing Whyte to increase the chain ring size without sacrificing the lower gearing size.

The all new Rockshox Revelation RC is a ground up design based on the brand new Pike fork. This Trail fork brings new levels of lightweight stiffness and balance to the T-130C R.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	67	73.5	611.1	331	766
L	67	73.3	631	331	776
XL	67	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6

### Youth 26er Trail Hardtail - 400 Series - 100mm

**SRP** £599



		Colour	Matt Granite with Grey/Silver
		Sizes Available	13"
<b>✓</b>		Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip Seat Clamp System
		Fork	Suntour, XCR, 100mm Travel, 32mm, HYDRO Lock-out, Air Spring, Adjustable Rebound, Post Mount
		Rear Shock	N/A
		Headset	FSA No.10, Semi Integrated, Caged Bearings
		Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
		Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
		Spokes	2.0mm, Black Stainless with Brass Nipples
		Rims	Whyte Trail-403, 28 Hole
		Tyres	WTB Trail Boss, 26" X 2.25" Front, WTB Nano, 26" X 2.1" Rear
$\checkmark$		Shift Levers	Shimano Altus SL-M310, 9 Speed Trigger Shifter
		Front Derailleur	N/A
$\checkmark$		Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
$\checkmark$		Cassette	Sunrace 9 Speed, ED Black 11-40T
$\checkmark$		Chain	KMC, 9 Speed
		Crankset	28T Narrow/Wide Chainring, 165mm Crank Length
		<b>Bottom Bracket</b>	JIS Square Interface, BB-7420ST, Cartridge Bearings
		Seatpost	Whyte 20mm Offset, 30.9mm x 300mm, 6061 Alloy, 2 Bolt Clamp
		Seat	Whyte Custom
		Bar	Whyte Riser Bar 30mm Rise DB, 31.8mm, 640mm Wide
$\checkmark$		Stem	Whyte Custom, 45mm S, M, 60mm L & XL
L		Grips	Whyte Lock-on V Grip
		Front Brakes	Promax Solve, 160mm Rotor
		Rear Brakes	Promax Solve, 160mm Rotor, Internal Routing
		Brake Levers	Promax Solve, Short Reach
		Pedals	Fibre Reinforced Composite Platform
$\checkmark$		Indicates an upgra	ade or improvement over last years model
	<b>√</b>	Indicates an upgra	ade or improvement over the model below

We've broken the mould with our kids bikes. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

For 2018 Whyte has specced a trigger shifter, which will help with the transition to an adult bike.

The 403 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.4Kg

ı						
	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
	13"	68.5	74	540.1	297.5	706.5
1	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
1	13"	1022.9	400	30.9	100	331

## **WESSEX Di2**

Carbon Performance Road - RDC7 Series

SRP £3,799



		Colour	Forest Green with Reef/Sky
		Sizes Available	50,52,54,56,58
		Frame	Uni-directional Multi Monocoque with Flat Mount 160 Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
		Fork	Straight Bladed Carbon Front Fork, Tapered Carbon Steerer with 12mm x 100mm Steelth Through Axle, Concealed Eyelets for Mud Guards
		Rear Shock	N/A
		Headset	FSA No. 42 Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	1	Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 142mm Through Axle, 24 Hole
	1	Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, Centre-lock, 12mm x 100mm Through Axle, 24 Hole
		Spokes	DT Competition butted, Black Sandvik Stainless with Black Brass Nipples
	/	Rims	Whyte Carbon, 21mm wide Tubeless Ready, 24 Hole
	/	Tyres	Schwalbe Pro One, 700 x 28c, TL-Easy Tubeless System, MicroSkin Puncture Protection
	/	Shift Levers	Shimano ST-R8070 Ultegra Di2, 11 Speed
	/	Front Derailleur	Shimano FD-R8050 Ultegra Di2, 11 Speed
	/	Rear Derailleur	Shimano RD-R8050 GS Ultegra Di2 GS, 11 Speed
	/	Cassette	Shimano CS-R8000 Ultegra, 11-34, 11 Speed
		Chain	Shimano HG-601, 11 Speed
- 1	/	Crankset	Shimano FC-R8000 Ultegra, Double 50-34, 11 Speed, Hollowtech
	/	<b>Bottom Bracket</b>	Shirnano SM-BBR60, BSA 68mm
		Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs Carbon UD, 2 Bolt Clamp
	1	Seat	Whyte Custom Road, with Lightweight Foam, CrMo Rails, Triple Panel Design
	1	Bar	Whyte Road, 31.8mm, Compact Carbon UD "Wing" Bar
		Stem	Whyte -6 Deg/6 Deg, 90mm 50cm, 90mm 52cm, 100mm 54cm, 120mm 56/58cm
	/	Grips	Whyte Anti Slip with 3M Reflective
		Front Brakes	Shimano Ultegra BR-R8070 Hydraulic, Centre-lock 160mm Flat Mount, Internal Routing
		Rear Brakes	Shimano Ultagra BR-R8070 Hydraulic, Centre-lock 160mm Flat Mount, Internal Routing
		Brake Levers	Shimano, ST-8070 Ultegra Di2
		Pedals	None
			ade or improvement over last years model

Ultegra Di2 takes all year-round riding to a new level. With Tubeless tyres mounted on our own Whyte carbon rims and the all new Ultegra disk brakes consistent control in all weather is guaranteed.

Shimano's new Di2 Ultegra gives the rider more control over shifting, Whyte have fitted a bar mounted junction box/display, so the rider can see battery life and adjust shifting settings with ease.

The ability to fit full length mud guards makes the Wessex arguably the most versatile and capable carbon road bike we have ever made.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	??15Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72	74.5	525	271.5	764
52cm	72.5	74	540	271.5	781.5
54cm	73	73.5	555	271.5	798,5
56cm	73	73	570	271.5	B14.5
58cm	73	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993	425	27.2	130	500
52cm	998.4	425	27.2	145	520
54cm	1003.3	425	27.2	160	540
56cm	1012,8	425	27.2	175	560
58cm	1027.8	425	27.2	190	580

# **RIDGEWAY WOMEN'S**

All Terrain/Leisure - C7 Series

**SRP** £599



<b>√</b>	Indicates an upgra	ade or improvement over the model below
✓	Indicates an upgra	ade or improvement over last years model
	Pedals	Fibre Reinforced Composite Platform
	Brake Levers	Tektro HD-M285
	Rear Brakes	Tektro HD-M285, 160mm Rotor
	Front Brakes	Tektro HD-M285, 160mm Rotor
	Grips	Whyte Custom Dual Density Lock-on
	Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
	Bar	Whyte Alloy 6061, High Rise 30mm, 31.8mm, 620mm Wide
	Seat	Whyte Custom Women's Fit, Triple Panel Design
	Seatpost	Whyte Alloy 6061, 12mm Offset, 30.9mm, 2 Bolt Clamp
	Bottom Bracket	Shimano BB-UN-100 Square Taper
	Crankset	Shimano FC-M371, 48-36-26, 9 Speed
	Chain	Shimano CN-HG53
<b>√</b>	Cassette	Shimano CS-HG-200-9, 11-32, 9 Speed
<b>√</b>	Rear Derailleur	Shimano Altus RD-M2000, 9 Speed
-	Front Derailleur	Shimano Acera FD-T3000, 9 Speed
<u></u>	Shift Levers	Shimano Altus SL-M2000, 9 Speed
<b>√</b>	Tyres	Schwalbe SILENTO K-Guard 700 x 35c
	Rims	Whyte 700c, 32 Hole
	Spokes	2.0mm PG Spokes with Brass Nipples
	Front Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Rear Hub	Alloy Disc, Cup & Cone, Double Seal, 32 Hole
	Headset	FSA No.10, Semi Integrated, Caged Bearings
	Rear Shock	N/A
<b>√</b>	Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount  SR Suntour NEX HLO, Alloy Steerer, 63mm Travel, Hydro Lockout
	Sizes Available	S,M,L
	Colour	Matt Petrol with Silver

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	13.6Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat
					Tube
S	1081.3	435	30.9	107	431.8
S M	1081.3 1094	435 435	30.9 30.9	107 115	