

G-170 S

G-170 Gravity Enduro Suspension - 170mm

SRP £2,399



Colour	Matt Blue with Orange/Denim/Sky
Sizes Available	S,M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Yari RC, 27.5", 170mm Travel, Fast Black Coating, Tapered Steerer, 110mm X 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe R, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing, 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STp i29 Rims with TCS System, Pinned Joint, Tubeless Ready
Tyres	WTB Convict TCS System Light High Grip 27.5 X 2.5" Folding Front, WTB Riddler TCS System Light Fast Rolling 27.5" X 2.4" Folding Rear
Shift Levers	SRAM GX, MMX Clamp, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed Alloy
Cassette	SRAM NX-1130, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM Descendant 6K GXP, X-SYNC 2, Direct Mount 30T Chainring, 11 Speed
Bottom Bracket	SRAM GXP XR, BSA 73mm
Seatpost	Whyte drop.it, 30.9mm, 125mm on S, 150mm Travel on M & L, 170mm XL, Paddle Remote
Seat	Whyte Custom Dual Density, Triple Panel Design
Bar	Whyte Custom Alloy 6061, 35mm Bar Bore, 15mm Rise, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide R, 4 Pots, 200mm Rotor (180mm on the S)
Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX Matchmaker
Pedals	None

The all new G-170 frame takes everything we learnt from the G-160 and improves it. From the oversize hardware on our main pivot complete with Enduro bearings, to the new Flat Mount dropout, the G-170 is literally built to handle anything you throw at it.

The S is loaded with the very latest developments in Enduro/Trail bikes. WTB i29mm rims combined with TCS front and rear specific tyres help to give neutral handling without too much drag.

The G-170 has extra width built into the rear chainstays to allow the rider to fully exploit the future developments in wide high volume tyres but maintain mud clearance.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm
Weight	15Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	75.83	582.9	333.5	839.5
M	65	75.5	602.7	333.5	843.5
L	65	75.19	627.5	333.5	848.5
XL	65	74.9	652.3	333.5	848.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1195.6	430	30.9	110	406.4
M	1215.6	430	30.9	120	431.8
L	1240.6	430	30.9	130	457.2
XL	1265.6	430	30.9	135	482.6