





	Colour	Matt Zinc with Grey / Lime		
	Sizes Available	S,M,L,XL		
	Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts		
$\checkmark$	Fork	Fox Float Performance SC 34, Step Cast, 29", 120mm Travel, 44mm Offset, GRIP 3-Pos Damper, Tapered Steerer, Black Coating, 110mm x 15mm Boost, E-Thru Axle		
✓	Rear Shock	Fox Float DPS, Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol LV		
	Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings		
	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole		
	Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole		
	Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples		
	Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole		
✓	Tyres	Maxxis Forekaster TR 29" x 2.35" 120TPI 3C MaxxSpeed Compound, EXO Sidewall Protection, Front, Ardent Race TR 29" x 2.35" 60TPI Dual Compound, EXO Sidewall Protection, Rear		
	Shift Levers	SRAM NX Eagle, Matchmaker, 12 Speed		
	Front Derailleur	N/A		
	Rear Derailleur	SRAM NX Eagle, 12 Speed		
	Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed		
	Chain	SRAM Eagle, 12 Speed		
$\checkmark$	Crankset	SRAM Style 6K Eagle, X-SYNC 2, Direct Mount 34T, Boost, 175mm, 12 Speed		
	Bottom Bracket	SRAM DUB, BSA, 73mm		
	Seatpost	KS RAGEi, Dropper Post, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Southpaw-Alloy Remote Lever		
	Seat	Whyte Custom Dual Density, Triple Panel Design		
	Bar	Whyte 6061 Alloy, 15mm Low Rise, 31.8mm, 780mm Wide		
	Stem	Whyte Gravity Stem, 40mm Extension		
	Grips	Whyte Lock-on V Grip		
	Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor		
	Rear Brakes	SRAM Guide T, 4 Pot, 180mm Rotor, Internal Routing		
	Brake Levers	SRAM Guide T, Matchmaker		
	Pedals	None		
✓	Indicates an upgrade or improvement over previous version			
$\checkmark$	Indicates an upgrade or improvement over the model below			

The S-120 is perfect for the rider that wants speed, but still wants to feel the trail beneath them, it's more of a rally car than a monster truck. Incredibly confident with a voracious appetite for speed, it's an exceptionally versatile all-round MTB using our latest 120mm 29er Trail platform.

Superb suspension and technical trail handling redefine what you can expect from a 120mm bike, whether you're powering up the climbs, shredding the trail or charging the descents.

The S-120 geometry was designed around a short 44mm offset fork and the exceptional Fox 34 Step Cast platform is the perfect choice for benchmark performance.

Dropout Code	DROPWHQ4SD2		
Shock Stroke and Sag Setting	50mm, Sag 12mm (25%) to 15mm (30%)		
Reducer Bush Widths	25mm x 8mm, no hardware at the rear		
Eye to Eye Length	210mm		

Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
65.6	75	592	340	796
65.6	75	583	340	802
65.6	75	640	340	808
65.6	75	669	340	815
Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
1168	430	30.9	112	406.4
1198	430	30.9	125	431.8
1227	430	30.9	140	457.2
1256	430	30.9	150	482.6
	65.6 65.6 65.6 65.6 <b>Wheelbase</b> 1168 1198 1227	65.6 75   65.6 75   65.6 75   65.6 75   65.6 75   65.6 75   65.6 75   65.6 75   1168 430   1198 430   1227 430	65.6 75 592   65.6 75 583   65.6 75 640   65.6 75 669   Wheelbase Chain Stay Seat Post   1168 430 30.9   1198 430 30.9   1227 430 30.9	65.6 75 592 340   65.6 75 583 340   65.6 75 640 340   65.6 75 640 340   65.6 75 669 340   40 75 669 340   1168 430 30.9 112   1198 430 30.9 125   1227 430 30.9 140

## **S-120 C / Trail Suspension - 120mm** SRP £3,099 Product Code - WS120CR(size)V2

## ADDITIONAL SPECIFICATION & REPLACEMENT PARTS

Top Tube	High Modulus Uni-Directional Carbon
Down Tube	High Modulus Uni-Directional Carbon
Rear Stays	6061 Alloy Double Butted
Paint Code	WAMTU004
Freehub Part Code	WHYFHUB01
Rear Hub Bearings	6903
Front Hub Bearings	6902
Suspension Bearings	WB0025 X 10
Headset Bearings	HS003 (FSA No42)
Headset Code	
Bottom Bracket	BSA SRAM DUB, 73mm
ISG Chainguide Compatibility	
ICR Grommets	1 x WHYICR18-3, 2 x WHYICR18-1
Brake Mount Adaptor	WHYFM180
Spoke Lengths	294 × 292mm (front) 294 × 292mm (rear)
Max Chain Ring Size	
Chain Length for the stock chainring	118
Tubeless Status	Tubeless Ready Rims
Max Tyre Size	29 X 2.6 Front / 29 X 2.5 Rear
Max Tyre Size with Mudguards	N/A
Mudguard Code	N/A
Rack Compatible	N/A
Kickstand Compatible	N/A
Chain Guide Code	WAMCG1
Rear Thru-Axle Length	M12 X 1.5, 180mm Long
Downtube Protector	N/A
Chainstay Protector	WHYPROD7
Seat Post Seal	WHYPOSTSEAL 3/4/5
Kitbox Contents	