

Color	Granite Black Matt with Aqua
Sizes Available	S, M, L, XL
Weight	8.2kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Press Fit BB Shell
Fork	Straight Bladed Full Carbon Front Fork and Steerer
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Hope EVO, with Stainless Steel bearings, 32 Hole
Front Hub	Hope EVO, with Stainless Steel bearings. 28 Hole
Spokes	DT Competition, 15g/14g Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM SL700, 10 Speed
Front Derailleur	SRAM APEX
Rear Derailleur	SRAM Rival 10 Speed
Cassette	SRAM PG-1050, 11-32, 10 Speed
Chain	SRAM PC-1050
Crankset	FSA Gossamer, 50-34, 10 Speed, Compact
Bottom Bracket	SRAM Press Fit
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	SR Viper, with Scuff Guards, Snake Skin Cover
Bar	Whyte Ultra Narrow, 31.8mm, Flat Bar, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	GP1 Ergon Grip, Dual Density
Front Brakes	Hope X-2 Race, Matchmaker Clamps
Rear Brakes	Hope X-2 Race, Matchmaker Clamps
Brake Levers	Hope X-2 Race
Pedals	None

Built on the same fantastic frame as last year, the 2012 Montpellier gets a more affordable spec, the Hope brakes and hubs are still there and it is still packaged as the ultimate "stealth" bike

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed maneuverability

The Montpellier weighs in at a fraction over 18 $\!\!\!$ - unbeatably svelte for a rugged Urban-proof commuter bike



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Rear Stays 6061 Hydro Formed

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5°	74°	572	272	717
М	70°	73.5°	597	272	743
L	70°	73°	611	272	779
XL	70°	73°	625	272	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	120	406
М	1069	420	27.2	140	444
L	1079	420	27.2	160	495
XL	1094	420	27.2	180	533

TYPICAL USAGE: URBAN/COMMUTE SRP £999



Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed maneuverability

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride, especially when combined with a top quality carbon fibre front fork



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5°	74°	572	272	717
М	70°	73.5°	597	272	743
L	70°	73°	611	272	779
XL	70°	73°	625	272	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	120	406
М	1069	420	27.2	140	444
L	1079	420	27.2	160	495
XL	1094	420	27.2	180	533

Color	Granite Black Mat with Orange Decals
Sizes Available	S, M, L, XL
Weight	9.1kg
Frame	$6061\ \text{Hydro}$ Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Double Eyelets and Low Rider Bosses
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Competition, 15g/14g Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM SL700, 10 Speed
Front Derailleur	SRAM APEX, 10 Speed
Rear Derailleur	SRAM Rival, 10 Speed
Cassette	SRAM PG-1050, 11-32, 10 Speed
Chain	SRAM PC-1030, 10 Speed
Crankset	SRAM APEX, 50-34, 10 Speed, Compact
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	SR Viper, with Scuff Guards, Snake Skin Cover
Bar	Whyte Ultra Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Avid Elixir 1, 160mm Rotor
Rear Brakes	Avid Elixir 1, 160mm Rotor
Brake Levers	Avid Elixir 1
Pedals	Full Alloy with Toe Clip

CAMBRIDGE TYPICAL USAGE: URBAN/COMMUTE SRP £899



Color	White Matt with Aqua Decals
Sizes Available	S, M, L, XL
Weight	10kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Double Eyelets and Low Rider Bosses
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM APEX, 10 Speed
Rear Derailleur	SRAM APEX, 10 Speed
Cassette	SRAM APEX PG-1050, 11-32, 10 Speed
Chain	SRAM PC-1030, 10 Speed
Crankset	FSA Omega, 50-34, 10 Speed, Compact
Bottom Bracket	FSA MegaExo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design, Snake Skin Cover
Bar	Whyte Ultra Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density. Lock-on
Front Brakes	Hayes Dyno Comp, 160mm Rotor
Rear Brakes	Hayes Dyno Comp, 160mm Rotor
Brake Levers	Hayes Dyno Comp
Pedals	Composite with Alloy Cage and Toe Clip

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed maneuverability

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride, especially when combined with a top quality carbon fibre front fork



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5°	74°	572	272	717
M	70°	73.5°	597	272	743
L	70°	73°	611	272	779
XL	70°	73°	625	272	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	120	406
М	1069	420	27.2	140	444
L	1079	420	27.2	160	495
XL	1094	420	27.2	180	533

PORTOBELLO TYPICAL USAGE: URBAN/COMMUTE SRP £699



Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed maneuverability

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride, especially when combined with a top quality carbon fibre front fork



Top Tube

6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



61	Hydro	Formed	

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5°	74°	572	272	717
М	70°	73.5°	597	272	743
L	70°	73°	611	272	779
XL	70°	73°	625	272	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052	420	27.2	120	406
М	1069	420	27.2	140	444
L	1079	420	27.2	160	495
XL	1094	420	27.2	180	533

Color	Granite Black Matt with Apple Green
Sizes Available	S, M, L, XL
Weight	10.4kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 Alloy T6 Front Fork, with Double Eyelets and Low Rider Bosses
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano SL-R440, 9 Speed
Front Derailleur	Shimano R440, 9 Speed
Rear Derailleur	Shimano Sora, 9 Speed
Cassette	SRAM PG-950, 11-28 9 Speed
Chain	Shimano HG-53
Crankset	FSA Tempo 50-34, 9 Speed, Compact
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design, Snake Skin Cover
Bar	Whyte Ultra Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density, Lock-on
Front Brakes	Pro Max Hornet, Light weight 160mm Rotor
Rear Brakes	Pro Max Hornet, Light weight 160mm Rotor
Brake Levers	Pro Max Hornet
Pedals	Composite with Alloy Cage and Toe Clip





Color	Satin Granite with Orange
Sizes Available	S, M, L
Weight	11.8kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NRX-S LO Lite, 63mm travel, Hydro Lock-out and Internal Rebound Control, Alloy Upper and Mag Lower legs
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	SRAM 506 Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	SRAM 506 Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g/14g Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole with Eyelets
Tire	WTB All Terrain Comp 700 x 35c, Folding with Flat Gaurd and Reflective Sidewall and Flat Guard
Shift Levers	Shimano Deore, 9 Speed
Front Derailleur	Shimano Deore, 9 Speed
Rear Derailleur	Shimano XT Shadow, 9 Speed
Cassette	Shimano Deore, 11-32, 9 Speed
Chain	Shimano HG-53
Crankset	Shimano M660 SLX, Hollow Tech II, 48-36-26, 9 Speed
Bottom Bracket	Hollow Tech II
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Daul Density Comfort Lock-on
Front Brakes	Avid Elixir 1, 160mm Rotor
Rear Brakes	Avid Elixir 1, 160mm Rotor
Brake Levers	Avid Elixir 1
Pedals	VP Full Alloy with Toe Clip

When we set out to create a range of bikes that would handle allterrain use we started with the geometry of the frame. 11 years of off-road experience told us that these bikes first and foremost need to handle sweetly, whether riding along a canal tow path, heading down a woodland trail, or beating the traffic on the way through town

A custom rear drop out allows us to fit the hydraulic disc brake caliper inside the rear triangle leaving you plenty of room to fit a rack and mudguards if desired

Full Shimano 9 speed SLX and XT mountain bike components make the Coniston a class act



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69°	74°	592	288	784
М	69°	73.5°	617	288	815
L	69°	73°	632	288	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
М	1121	435	30.9	125	495
L	1131	435	30.9	135	546

C7 ALL TERRAIN CALEDDNIAN



Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifting working smoother for longer

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear stays which really improve the comfort and performance, whatever the terrain

Full Shimano 9 speed Deore and SLX with Octolink BB and MTB durability $% \left({{\rm Deore}} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \left({{\rm Deore} \right) = {\rm Deore} \left({{\rm Deore} \left({$



6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69°	74°	592	288	784
М	69°	73.5°	617	288	815
L	69°	73°	632	288	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
М	1121	435	30.9	125	495
L	1131	435	30.9	135	546

Color	Gloss White with Pacific Blue
Sizes Available	S, M, L
Weight	12.6kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NRX-E LO Lite, 63mm travel, Hydro Lockout and Internal Rebound Control
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tire	WTB All Terrain Comp 700 x 35c, with Flat Guard
Shift Levers	Shimano Alivio, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano SLX Shadow, 9 Speed
Cassette	Shimano Deore HG-50, 11-32, 9 Speed
Chain	Shimano HG-53
Crankset	Shimano Deore M431, 48-36-26, Octalink
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Daul Density Comfort Lock-on
Front Brakes	Hayes Dyno Comp, 160mm Rotor
Rear Brakes	Hayes Dyno Comp, 160mm Rotor
Brake Levers	Hayes Dyno Comp
Pedals	VP Composite with Alloy Cage and Toe Clip





Color	Gloss Jet Black with Silver
Sizes Available	S, M, L
Weight	12.9kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NVX HLO Lite, 63mm travel, Hydro Lockout
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Silver Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tire	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Alivio, 9 Speed
Cassette	Shimano Alivio HG-30, 11-32, 9 Speed
Chain	Shimano HG-53
Crankset	Shimano M430 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Daul Density Comfort Lock-on
Front Brakes	Tektro Draco, 160mm Rotor
Rear Brakes	Tektro Draco, 160mm Rotor
Brake Levers	Tektro Draco
Pedals	VP Composite with Toe Clip

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifting working smoother for longer

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear stays which really improve the comfort and performance, whatever the terrain

Full Shimano 9 Speed group to give years of unrivaled performance and puncture proof tyres for extra reliability and piece of mind



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69°	74°	592	288	784
М	69°	73.5°	617	288	815
L	69°	73°	632	288	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101	435	30.9	115	457
М	1121	435	30.9	125	495
L	1131	435	30.9	135	546



SRP £799



All the same key design features as the men's version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexy and offer less steering control)

Full Shimano 9 speed Deore with Octolink BB and MTB durability



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68°	74.5°	560	288	728
М	69°	74°	587	288	747
L	69°	73.5°	612	288	767
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1073	435	30.9	107	432
М	1085	435	30.9	115	457
L	1105	435	30.9	125	495

	1
Color	Gloss White with Silver
Sizes Available	S, M, L
Weight	12.6kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NRX-E LO Lite, 63mm travel, Hydro Lockout and Internal Rebound Control
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tire	WTB All Terrain Comp 700 x 35c, Folding with Flat Guard
Shift Levers	Shimano Alivio, 9 Speed
Front Derailleur	Shimano Deore, 9 Speed
Rear Derailleur	Shimano Deore Shadow, 9 Speed
Cassette	Shimano Deore HG-50, 11-32, 9 Speed
Chain	Shimano HG-53
Crankset	Shimano Deore M431, 48-36-26, Octalink
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Womens Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Daul Density Comfort Lock-on
Front Brakes	Hayes Dyno Comp, 160mm Rotor
Rear Brakes	Hayes Dyno Comp, 160mm Rotor
Brake Levers	Hayes Dyno Comp
Pedals	VP Composite with Alloy Cage and Toe Clip





Color	Gloss Jet Black with Aqua
Sizes Available	S, M, L
Weight	12.9kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NVX HLO Lite, 63mm travel, Hydro Lockout
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Silver Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tire	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Alivio, 9 Speed
Cassette	Shimano Alivio HG-30, 11-32, 9 Speed
Chain	Shimano HG-53
Crankset	Shimano M430 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Womens Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Daul Density Comfort Lock-on
Front Brakes	Tektro Draco, 160mm Rotor
Rear Brakes	Tektro Draco, 160mm Rotor
Brake Levers	Tektro Draco
Pedals	VP Composite with Toe Clip

All the same key design features as the men's version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexy and offer less steering control)

Full Shimano 9 Speed group to give years of unrivaled performance and puncture proof tyres for extra reliability and piece of mind



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68°	74.5°	560	288	728
М	69°	74°	587	288	747
L	69°	73.5°	612	288	767
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1073	435	30.9	107	432
М	1085	435	30.9	115	457
L	1105	435	30.9	125	495



Color	White Matt with Black and Aqua Decals
Sizes Available	18.5", 20.5"
Weight	TBC
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube and Adjustable Modular Dropouts
Fork	Fox 32 F29 RL Evolution Series, 100mm Travel, Rebound and Lock-out
Rear Shock	N/A
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Whyte XC-202 Wheelset, 32 StSt flat spokes, 6 Bolt hub, double sealed catridge bearing
Front Hub	Whyte XC-202 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed catridge bearing
Spokes	Stainless Steel Spokes
Rims	Whyte XC-202 29er
Tire	WTB Bronson 29" X 2.2", DNA Compound, 60 TPI, Folding
Shift Levers	Shimano SL-M660 SLX, 10 Speed
Front Derailleur	Shimano FD-M786 XT, 10 Speed
Rear Derailleur	Shimano RD-M780 XT, 10 Speed
Cassette	Shimano CS-HG81 11-36, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano FC-M785 38-26 Compact Double, 10 Speed
Bottom Bracket	Hollowtech II
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 2014 Alloy, flat, 700mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L
Grips	Whyte Custom Lock-on
Front Brakes	Shimano BR-M666 SLX, 180mm Rotor
Rear Brakes	Shimano BR-M666 SLX, 160mm Rotor
Brake Levers	Shimano BL-M666 SLX
Pedals	VP Full Alloy with Toe Clip

A wholly unique 29er, built around our agile Whyte Frame Geometry and featuring Shimano's brand new XT 3 x 10 groupset, light weight wheelset and a Fox F100 RL Evolution fork for a benchmark XC package

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth

Mud clearance and all weather features have long been associated with our designs and when Whyte set out to design a 29er there was no exception. We have fitted our unique adjustable dropouts, so you can run the chainstays short in the summer and when the weather turns bad, give yourself a whole load more mud clearance by moving the rear wheel backwards



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Rear Stays 6061 Triple Butted Hydro Formed

_						
	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
Γ	18.5"	69°	73°	627	305	808
Γ	20.5"	69°	73°	636	305	847
Γ	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Γ	18.5"	1133	425	30.9	110	470
	20.5"	1142	425	30.9	120	521

TYPICAL USAGE: CROSS COUNTRY SRP £1,499



Brand new Shimano XT 2 by 10, a Fox F100 RL Evolution fork and a light weight Whyte X-C 202 wheelset combine to give a benchmark X-C package, that's also "Trail Ready" with its Whyte Frame Geometry

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth

The same high quality frameset features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel



6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	581	314	773
М	68.5°	73.5°	596	314	797
L	68.5°	73°	615	314	824
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1092	425	30.9	115	406
М	1107	425	30.9	125	444
L	1122	425	30.9	135	495

Color	White Matt with Black and Aqua Decals
Sizes Available	S, M, L
Weight	11kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	Fox F100 RL Evolution Series, 100mm Travel, Rebound and Lock-out
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Whyte XC-202 Wheelset, 28 StSt flat spokes, 6 Bolt hub with double sealed catridge bearings
Front Hub	Whyte XC-202 Wheelset, 24 StSt flat spokes, 6 Bolt hub, double sealed catridge bearing
Spokes	Stainless Steel Spokes
Rims	Whyte XC-202
Tire	Continental Race King Fold 26" x 2.2"
Shift Levers	Shimano SL-M660 SLX, 10 Speed
Front Derailleur	Shimano FD-M786 XT, 10 Speed
Rear Derailleur	Shimano RD-M780, 10 Speed
Cassette	Shimano CS-HG81, 11-36, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano FC-M785 38-26 Compact Double, 10 Speed
Bottom Bracket	Hollowtech II
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L
Grips	Whyte Custom Lock-on
Front Brakes	Shimano BR-M666 SLX, 160mm Rotor
Rear Brakes	Shimano BR-M666 SLX, 160mm Rotor
Brake Levers	Shimano BL-M666
Pedals	VP Full Alloy with Toe Clip





Color	White Matt with Apple Green and Black Decals
Sizes Available	S, M, L
Weight	11.2kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	RockShox Recon Gold RL, 100mm Travel, Solo Air, Adjustable Compression
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed 28 Hole
Front Hub	Whyte Alloy Double Sealed 28 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-202 Rims, 28 Hole
Tire	Continental RACE King Fold 26" x 2.2", Folding
Shift Levers	Shimano Deore SL-M951, 10 Speed
Front Derailleur	Shimano Deore FD-M590, 10 Speed
Rear Derailleur	Shimano SLX RD-M663, 10 Speed
Cassette	Shimano CS-HG63-10, 12-36, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Shimano FC-M522, 42-32-24, Octolink, 10 Speed
Bottom Bracket	Shimano Octolink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Low Rise 20mm, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 3, 160mm Rotor
Rear Brakes	Avid Elixir 3, 160mm Rotor
Brake Levers	Avid Elixir 3
Pedals	VP Full Alloy with Toe Clip

The same high quality frameset features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel

Our trail-honed geometry is both fast and reassuring, encouraging you to push your limits on the descents as well as the climbs

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	581	314	773
М	68.5°	73.5°	596	314	797
L	68.5°	73°	615	314	824
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1092	425	30.9	115	406
М	1107	425	30.9	125	444
L	1122	425	30.9	135	495

TYPICAL USAGE: CROSS COUNTRY SRP £899



The same high quality frameset features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel

Our trail-honed geometry is both fast and reassuring, encouraging you to push your limits on the descents as well as the climbs

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth



Top Tube

6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	581	314	773
М	68.5°	73.5°	596	314	797
L	68.5°	73°	615	314	824
XL	68.5°	73°	626	314	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1092	425	30.9	115	406
М	1107	425	30.9	125	444
L	1122	425	30.9	135	495
XL	1134	425	30.9	145	533

Color	White Matt with Orange and Black Decals
Sizes Available	S, M, L, XL
Weight	11.9kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	RockShox XC-30 TK, 100mm Travel, Adjustable Rebound, Turn Key Lockout
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 1.8mm, Black Stainless with Brass Nipples
Rims	Whyte XC-22, 32 Hole
Tire	X King 26" x 2.2", Folding
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7, 10 Speed
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	SRAM FC800, 44-32-22 with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Low Rise 20mm, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 1, 160mm Rotor
Rear Brakes	Avid Elixir 1, 160mm Rotor
Brake Levers	Avid Elixir 1
Pedals	VP Composite with Alloy Cage and Toe Clip



Color	Jet Black Matt with Red and White Decals
Sizes Available	S, M, L, XL
Weight	12.1kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	RockShox XC 28, 100mm Travel, Adjustable Rebound, Turn Key Lockout
Rear Shock	N/A
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-20, 32 Hole
Tire	Continental Race King Wire 26" x 2.2"
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow, 9 Speed
Cassette	Shimano HG-20, 11-34, 9 Speed
Chain	KMC X9, 9 Speed
Crankset	Shimano M391, 44-32-22, 9 Speed
Bottom Bracket	Shimano BB-ES25 Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Low Rise 20mm, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Draco, 160mm rotor
Rear Brakes	Tektro Draco, 160mm rotor
Brake Levers	Tektro Draco
Pedals	VP Composite with Alloy Cage and Toe Clip

The same high quality frameset features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth

Shimano 9 speed drive train, Rockshox X-C 28 with Lock-out and Tektro Draco Hydraulic Disk Brakes, coupled to the X-8 triple butted Alloy 6061 frame make for an amazing package



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Rear Stays 6061 Hydro Formed

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	581	314	773
М	68.5°	73.5°	596	314	797
L	68.5°	73°	615	314	824
XL	68.5°	73°	626	314	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1092	425	30.9	115	406
М	1107	425	30.9	125	444
L	1122	425	30.9	135	495
XL	1134	425	30.9	145	533



Color	Brushed Raw Ti
Sizes Available	S, M, L
Weight	10.8kg
Frame	3AL2.5V Aerospace Grade Titanium Alloy, Custom Cold-drawn, Tapered Headtube
Fork	Fox F120RL FIT Cartridge Performance Series, 120mm Travel, OR15 Dropouts, Tapered Steerer Tube
Rear Shock	N/A
Headset	FSA Orbit ITA 1, 1.5" Lower, 1 1.8" Upper Bearing and Alloy Cups, Taper Steerer
Rear Hub	Easton XCT-70 Wheelset, UST Tubeless Rims, 15mm
Front Hub	Easton XCT-70 Wheelset, UST Tubeless Rims, 9mm
Spokes	Easton XCT-70
Rims	Easton XCT-70, UST Tubeless Rims
Tire	Maxxis Aspen 26" x 2.25" DKFW AR
Shift Levers	Shimano XTR SL-M980, 10 Speed
Front Derailleur	Shimano XT FD-M7710, 10 Speed
Rear Derailleur	Shimano XTR RD-M985, 10 Speed, Shadow Plus
Cassette	Shimano XT SC-M771, 11-36, 10 Speed
Chain	Shimano CN-HG94, 10 Speed
Crankset	FSA Afterburner Crankset PressFit30, 42-32-24, 10 Speed
Bottom Bracket	FSA Press Fit BB
Seatpost	Thomson 16 Degree Lay-Back, 30.9mm x 410mm
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Easton Haven Carbon XC Low Rise 711mm Wide, 31.8mm OD
Stem	Thomson Elite X-4, 31.8mm, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Lock-on
Front Brakes	Hope RACE X2, with Hope Tech Levers, 183mm Rotor
Rear Brakes	Hope RACE X2, with Hope Tech Levers, 160mm Rotor
Brake Levers	Hope RACE Levers
Pedals	None

The ultimate Ti hardtail features Whyte Frame Geometry, acknowledged by our customers and independent reviewers as the best numbers in the business. Cold worked 3/2.5 for light weight, with the unique compliant, responsive ride that can only come from top quality Titanium

High performance trail bike components including XT/XTR shifting and FSA PressFit 30 Afterburner Crank, with Hope X2 brakes. Ultimate trail bike finishing kit, including FSA Afterburner stem and seatpost, Easton Haven Carbon XC handlebar and Fizik Gobi XM saddle

Fox F120 RL Fit Performance suspension fork – with 120mm of travel and 15mm QR through axle. Unique contemporary frame, featuring superbly shaped rear stays, Whyte adjustable dropouts and PressFit 30 BB and for 2012 the frame features a Tapered headtube for increased front end stiffness



Top Tube 3AL2.5V Aerospace Grade Titanium Alloy, Custom Cold-drawn



Down Tube 3AL2.5V Aerospace Grade Titanium Alloy, Custom Cold-drawn



Rear Stays 3AL2.5V Aerospace Grade Titanium Alloy, Custom Cold-drawn

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.2° - 67.7°	72.2° - 72.7°	565	323	778
м	67.2° - 67.7°	72.2° - 72.7°	584	323	802
L	67.2° - 67.7°	72.2° - 72.7°	609	323	823
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1067 - 1084	425	30.9	100	406
М	1086 - 1103	425	30.9	120	436
L	1112 - 1129	425	30.9	130	482

19 ALLOY TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £1,999



Light enough to race - tough enough for trails. This is our most versatile hardtail - from the Quantocks to the Alps, the 19 Alloy can do it all

The Alloy 19 frame features a tapered headtube for increased front end stiffness and a Press Fit 30 BB for outstanding power transfer and improved reliability

The unique 19 dropouts allow for geometry adjustment and easy conversion to a single speed. Our choice of Trail bike finishing kit includes Hope brakes, Easton Haven bar, and FSA Afterburner stem and seat post and Easton XCT-70 UST compatible wheels



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.2° - 67.7°	72.2° - 72.7°	567	323	759
М	67.2° - 67.7°	72.2° - 72.7°	586	323	789
L	67.2° - 67.7°	72.2° - 72.7°	611	323	819
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1065 - 1083	425	30.9	115	406
М	1085 - 1102	425	30.9	125	455
L	1111 - 1128	425	30.9	145	491

Color	Granite Matt and Gloss Nickel Decals
Sizes Available	S, M, L
Weight	11.3kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, with Press Fit BB Shell, Tapered Headtube and Adjustable Modular Dropouts
Fork	Fox F120 RL Evolution Series, 120mm Travel, QR15 Dropouts and Tapered Steerer Tube
Rear Shock	N/A
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Easton XCT-70 Wheelset, UST Tubeless Rims, 15mm
Front Hub	Easton XCT-70 Wheelset, UST Tubeless Rims, 9mm
Spokes	Easton XCT-70
Rims	Easton XCT-70, UST Tubeless Rims
Tire	Maxxis Aspen 26" x 2.25" DK60 AR
Shift Levers	SRAM X-9, 10 Speed
Front Derailleur	SRAM X-9, 10 Speed
Rear Derailleur	SRAM X-0 Medium Cage, 10 Speed
Cassette	SRAM PG-1070, 12-36, 10 Speed
Chain	SRAM PC-1050, 10 Speed
Crankset	FSA Afterburner PressFit, 39-27, 10 Speed, Compact Double
Bottom Bracket	FSA Press Fit-30
Seatpost	FSA Afterburner 30.9 X 410mm, 2014 Alloy
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Easton Haven Alloy, Low Rise, 31.8mm, 711mm Wide
Stem	FSA Afterburner, 80mm S and M, 90mm L
Grips	Whyte Custom Lock-on
Front Brakes	Hope X2, with Tech Carbon Levers, 180mm Rotor
Rear Brakes	Hope X2, with Tech Carbon Levers, 160mm Rotor
Brake Levers	Hope Tech Levers
Pedals	None

19 STEEL TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £1,699



Color	Chalk Matt with Orange Decals
Sizes Available	S, M, L
Weight	11.1kg
Frame	Reynolds 631 Air Hardening Steel, Custom Drawn and Multi Butted, Tapered Headtube
Fork	Fox 32 F120 RL Evolution Series, 120mm Travel, Tapered Steerer, QR15
Rear Shock	N/A
Headset	FSA Orbit ITA 1, 1.5" Lower, 1 1.8" Upper Bearing Cup
Rear Hub	Hope EVO, 32 Hole with Shimano XT QR
Front Hub	Alloy, Sealed Bearings with Shimano QR
Spokes	DT Competition Butted 15g/14g, Black Stainless with Brass Nipples
Rims	Mavic XM 319, 32 Hole
Tire	Maxxis Aspen 26" x 2.25", DK60 AR Folding Bead
Shift Levers	Shimano Deore SL-M591, 10 Speed
Front Derailleur	Shimano Deore FD-M590
Rear Derailleur	Shimano SLX RD-663
Cassette	Shimano CS-HG62, 11-36
Chain	Shimano CN-HG54
Crankset	Shimano SLX RD-66010, 42-32-24T, Hollow Tech II
Bottom Bracket	Hollow Tech II
Seatpost	Whyte 20mm Offset, 27.2mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L and XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 5, 180mm Rotor
Rear Brakes	Avid Elixir 5, 160mm Rotor
Brake Levers	Avid Elixir 5
Pedals	None

Using geometry and tubing profiles developed from the 19 Ti and constructed from the finest British made Reynolds 631 tubing, the 19 Steel frame stirs the emotions while delivering an addictive, trailtaming ride

Whyte's unique adjustable dropouts allow for easy conversion to and from a single speed setup

The 2012 19 Steel frame features a tapered headtube for increased front end stiffness



Top Tube

Reynolds 631 Air Hardening Steel, Custom Drawn and Multi Butted



Down Tube



Reynolds 631 Air Hardening Steel, Custom Drawn and Multi Butted



Rear Stays Reynolds 631 Air Hardening Steel, Custom Drawn and Multi Butted

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.2° - 67.7°	72.2° - 72.7°	565	323	776
М	67.2° - 67.7°	72.2° - 72.7°	584	323	796
L	67.2° - 67.7°	72.2° - 72.7°	609	323	823
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
0120	VVIICEIDASE	Gliain Stay	00001000	ricau rube	Jear Inne
S	1066 - 1083	425	30.9	100	406
	1066 -				

905 TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £1,675



Using the same trial geometry developed for the 19, the 905 offers no-compromise performance and sublime handling

The frame is constructed from the highest quality 6061 Aluminium Alloy, extruded and manipulated to our exact specification. The rear seat stays are a work of art internally and contribute in a big way to the 905's outstanding ride characteristics

In a recent review What Mountain Bike Magazine said "it's sharp yet smooth.... a superb blend of race speed and technical confidence", giving it an Editor's Choice and a Gold Award



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.5°	72.5°	565	323	774
М	67.5°	72.5°	585	323	800
L	67.5°	72.5°	610	323	826
XL	67.5°	72.5°	629	323	853
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082	425	30.9	122	406
М	1102	425	30.9	132	455
L	1129	425	30.9	152	491
XL	1154	425	30.9	160	533

Color	White Matt with Gloss Black and Nickel Decals
Sizes Available	S, M, L, XL
Weight	11kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, with Press Fit BB Shell and Tapered Headtube
Fork	RockShox Reba RL, Maxle Light, 120mm Travel, Motion Control Damping with Turn Key Lockout, Tapered Steerer
Rear Shock	N/A
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Hope EVO Disc, 32 Hole with Shimano XT QR
Front Hub	Alloy, Double Sealed Bearing Hub 15mm, 32 Hole
Spokes	DT Competition Butted 15g/14gmm, Black Stainless with Brass Nipples
Rims	Mavic XM 319, 32 Hole
Tire	Maxxis Aspen 26" x 2.25", DK60 AR Folding Bead
Shift Levers	SRAM X-7, 10 Speed
Front Derailleur	SRAM X-7, 10 Speed
Rear Derailleur	SRAM X-9, 10 Speed
Cassette	SRAM PG-1050, 12-36, 10 Speed
Chain	SRAM PC-1050
Crankset	SRAM X9 Press Fit-30, 26-39, 10 Speed, Compact Double
Bottom Bracket	SRAM Press Fit-30
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L and XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 5, 180mm Rotor
Rear Brakes	Avid Elixir 5, 160mm Rotor
Brake Levers	Avid Elixir 5
Pedals	None

901 TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £1,149



Color	Granite Black Matt with Gloss Lime Green
Sizes Available	S, M, L, XL
Weight	11.4kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube
Fork	RockShox Recon TK, Maxle Light 120mm Travel, Solo Air, Adjustable Compression, Tapered Steerer
Rear Shock	N/A
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub 15mm Through Axle, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Mavic XM 119 Disc Noir, 32 Hole
Tire	Continental Mountain King Fold 26" x 2.2"
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-9 Long Cage, 10 Speed, Custom Colour
Cassette	SRAM PG-1030, 12-36, 10 Speed
Chain	SRAM PC-1030, 10 Speed
Crankset	SRAM FC S1000, GXP, 39-26, 10 Speed, Double Compact
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L and XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 3, 180mm Rotor
Rear Brakes	Avid Elixir 3, 160mm Rotor
Brake Levers	Avid Elixir 3
Pedals	None

Using the same trail geometry developed for the 19, the 901 offers no-compromise performance and sublime handling

The frame is constructed from 6061 Aluminum Alloy, extruded and manipulated to our exact specification. For 2012 the 901 gains a Tapered Headtube

The rear seat stays are precisely shaped and sculpted to help give the 901 excellent ride characteristics $% \left(1-\frac{1}{2}\right) =0$



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Rear Stays 6061 Hydro Formed

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.5°	72.5°	565	323	774
М	67.5°	72.5°	585	323	800
L	67.5°	72.5°	610	323	826
XL	67.5°	72.5°	629	323	853
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082	425	30.9	122	406
М	1102	425	30.9	132	455
L	1129	425	30.9	152	491
XL	1154	425	30.9	160	533

20-C WORKS XX TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £4,999



Color	UD Matt Carbon and Apple Green
Sizes Available	S, M, L
Weight	8.8kg
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts
Fork	Fox F100 Ti FIT, Terralogic, Tapered Steerer, Kashima Coating, Custom Decals
Rear Shock	N/A
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Easton EC-90, Full Carbon Tubeless Compatible Wheelset
Front Hub	Easton EC-90, Full Carbon Tubeless Compatible Wheelset
Spokes	Easton Double Butted
Rims	Easton EC-90, Full Carbon Tubeless Compatible
Tire	Maxxis Aspen 26" x 2.1", DKFW AR 465g
Shift Levers	SRAM XX, 10 Speed
Front Derailleur	SRAM XX, 10 Speed
Rear Derailleur	SRAM XX, 10 Speed
Cassette	SRAM XX, 11-32T, 10 Speed
Chain	SRAM PC-1030, 10 Speed
Crankset	FSA K-Force, BB-30, 39-27, 10 Speed, Compact Double
Bottom Bracket	FSA PressFit 30
Seatpost	FSA K-Force SBO, 27.2mm X 350mm
Seat	Fi'zi:k Tundra II, Ti Rails
Bar	FSA K-Force Light, Flat Nano Carbon, 31.8mm OD, 600mm Wide
Stem	FSA K-Force Carbon, -6 degree, 90mm S/M, 100mm L
Grips	Whyte Race, Foam Lock-on
Front Brakes	SRAM XX, 160mm Rotor
Rear Brakes	SRAM XX, 160mm Rotor
Brake Levers	SRAM XX Carbon Levers
Pedals	None

The Works spec is the spec of choice for our Pro Rider, Billy Whenman. Quite simply, the finest performance finishing parts available, on our state of the art frame

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections

The 2 by 10 FSA K-force and SRAM XX specs gives close ratio compact gearing, to maximize the time you're on the power



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	585	300	755
М	68.5°	73.5°	604	300	775
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1094	425	30.9	115	406
М	1114	425	30.9	125	444

ZD-C TEAM TYPICAL USAGE: CROSS COUNTRY/RACE SRP £3,699



The 20-C Team bike is specced using the FSA SLK Carbon PressFit 30 crankset combined with XTR brakes, XTR drive train, and the fantastic Easton EA-90 full UST compatible wheels

This all-new chassis delivers exceptional torsional stiffness for surgically precise tracking and unflinching power delivery

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections



Top Tube High Modulus Uni-Directional Carbon



Down Tube

High Modulus Uni-Directional Carbon



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	585	300	755
М	68.5°	73.5°	604	300	775
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1094	425	30.9	115	406
М	1114	425	30.9	125	444

Color	UD Matt Carbon with White and Red Decals			
Sizes Available	S, M, L			
Weight	9kg			
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts $% \left(\mathcal{A}_{1}^{\prime}\right) =\left(\mathcal{A}_{1}^{\prime}\right) \left(\mathcal{A}_{1}^{\prime}$			
Fork	Fox 32 F100 RL FIT Catridge, Performance Series, Remote Lock-out, Tapered Steerer, Custom Decals			
Rear Shock	N/A			
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings			
Rear Hub	Easton EA-90, UST Tubeless Compatible Wheelset			
Front Hub	Easton EA-90, UST Tubeless Compatible Wheelset			
Spokes	Easton EA-90			
Rims	Easton EA-90, UST Tubeless Compatible			
Tire	Maxxis Aspen 26" x 2.1", DK60 AR Folding Bead			
Shift Levers	Shimano XTR SL-M980, 10 Speed, Ispec			
Front Derailleur Shimano XTR FD-M985, 10 Speed				
Rear Derailleur	Shimano XTR RD-M980, 10 Speed, Shadow Plus			
Cassette	Shimano XTR CS-M980, 11-34, 10 Speed			
Chain	FSA Team Issue, 10 Speed			
Crankset	FSA SLK Carbon 39-27, 10 Speed, Compact Double			
Bottom Bracket	FSA PressFit 30			
Seatpost	FSA SLK 27.2mm X 350mm			
Seat	Fi'zi:k Tundra II, Mag Rails			
Bar	FSA SLK Carbon Riser, 31.8mm, 660mm Wide			
Stem	FSA SLK, 80mm S, 90mm M, 100mm L			
Grips	Whyte Race, Foam Lock-on			
Front Brakes	Shimano XTR BL-M985, 160mm Rotor			
Rear Brakes	Shimano XTR BL-M985, 160mm Rotor			
Brake Levers	Shimano XTR BL-M985			
Pedals	None			





Color	UD Matt Carbon and White and Orange Decals
Sizes Available	S, M, L
Weight	9.5kg
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts
Fork	RockShox SID RLT, 100mm Travel, Remote Poploc
Rear Shock	N/A
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Easton XCT-70 Custom Wheelset, 6 Bolt, UST Tubeless Compatible
Front Hub	Easton XCT-70 Custom Wheelset, 6 Bolt, UST Tubeless Compatible
Spokes	Easton XCT-70
Rims	Easton XCT-70 Custom, UST Tubeless Compatible
Tire	Continental Race King 26" x 2.2"
Shift Levers	SRAM X-0, 10 Speed with Discreate Matchmaker Clamp
Front Derailleur	SRAM X-0, 10 Speed
Rear Derailleur	SRAM X-0 Medium Cage, 10 Speed
Cassette	SRAM PG-1070, 11-32, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA SLK, BB30, 39-27, 10 Speed, Compact Double
Bottom Bracket	FSA PressFit30
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp
Seat	Fi'zi:k Tundra II, Mag Rails
Bar	FSA SLK Carbon Riser, 31.8mm, 660mm Wide
Stem	Whyte Custom, 70mm S/M and 80mm L
Grips	Whyte Race, Foam Lock-on
Front Brakes	Avid Elixir 7, Matchmaker, 160mm Rotor
Rear Brakes	Avid Elixir 7, Matchmaker, 160mm Rotor
Brake Levers	Avid Elixin 7
Pedals	None
	· · · · · · · · · · · · · · · · · · ·

This all-new chassis delivers exceptional torsional stiffness for surgically precise tracking and unflinching power delivery

FSA SLK parts, with X-0 and Easton custom XCT-70 UST compatible wheels deliver a race winning package $% \left({{{\rm{SL}}} \right) = {{\rm{SL}}} \right)$

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



_						
	Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
ſ	S	68.5°	73.5°	585	300	755
ſ	М	68.5°	73.5°	604	300	775
	Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
ſ	S	1094	425	30.9	115	406
ſ	М	1114	425	30.9	125	444

ZD-C TYPICAL USAGE: CROSS COUNTRY/RACE SRP £1,999



This all-new chassis delivers exceptional torsional stiffness for surgically precise tracking and unflinching power delivery

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections

Whyte X-C 202 wheelset is a light and hand build in one of the best wheel building factories in the world



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5°	73.5°	585	300	755
М	68.5°	73.5°	604	300	775
Size Wheelbase		Chain Stay	Seat Post	Head Tube	Seat Tube
S	1094	425	30.9	115	406
М	1114	425	30.9	125	444

Color	UD Matt Carbon with White and Apple Green Decals	
Sizes Available	S, M, L	
Weight	10.2kg	
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts	
Fork	Rockshox Reba RL, 100mm Travel, Tapered Steerer, Poploc Remote Lockout	
Rear Shock	N/A	
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings	
Rear Hub	Whyte XC-202 Wheelset, 28 StSt spokes, 6 Bolt hub with double sealed catridge bearings	
Front Hub	Whyte XC-202 Wheelset, 24 StSt spokes, 6 Bolt hub, double sealed catridge bearing	
Spokes	Stainless Steel Spokes	
Rims	Whyte X-C 202	
Tire	Continental Race King 26" x 2.2"	
Shift Levers	SRAM X-9, 10 Speed, Custom Green	
Front Derailleur	SRAM X-7, 10 Speed	
Rear Derailleur	SRAM X-9 Carbon Medium Cage, 10 Speed, Custom Green	
Cassette	SRAM PG-1050, 11-32, 10 Speed	
Chain	FSA Team Issue, 10 Speed	
Crankset	FSA Comet PressFit30, 39-27, 10 Speed, Compact Double	
Bottom Bracket	FSA PressFit 30	
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp	
Seat	Whyte Custom, triple panel design	
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide	
Stem	Whyte Custom, 70mm S/M and 80mm L	
Grips	Whyte Race, Foam Lock-on	
Front Brakes	Avid Elixir 3, Matchmaker, 160mm Rotor	
Rear Brakes	Avid Elixir 3, Matchmaker, 160mm Rotor	
Brake Levers	Avid Elixir 3	
Pedals	N/A	

29ER CS TYPICAL USAGE: CROSS COUNTRY/RACE SRP £2,599



Color	UD Matt Carbon and White and Orange Decals
Sizes Available	18.5", 20.5"
Weight	TBC
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts
Fork	RockShox SID RLT, 100mm Travel, 15mm Maxle Lite, Remote Poploc
Rear Shock	N/A
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Easton XCT-70 Wheelset, 6 Bolt, UST Tubeless Compatible
Front Hub	Easton XCT-70 Wheelset, 6 Bolt, 15mm, UST Tubeless Compatible
Spokes	Easton XCT-70
Rims	Easton XCT-70, UST Tubeless Compatible
Tire	Continental Race King 29" x 2.2"
Shift Levers	SRAM X-0, 10 Speed with Discreate Matchmaker Clamp
Front Derailleur	SRAM X-0, 10 Speed
Rear Derailleur	SRAM X-O Carbon Medium Cage, 10 Speed
Cassette	SRAM PG-1050, 11-36, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA SLK PressFit30, 39-27, 10 Speed, Compact Double
Bottom Bracket	FSA PressFit 30
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp
Seat	Fi'zi:k Tundra II, Mag Rails
Bar	FSA SLK Carbon Riser, 31.8mm, 660mm Wide
Stem	Whyte Custom, -6 Degree, 70mm 18.5" and 80mm 20.5"
Grips	Whyte Race, Foam Lock-on
Front Brakes	Avid Elixir 7, Matchmaker, 180mm Rotor
Rear Brakes	Avid Elixir 7, Matchmaker, 160mm Rotor
Brake Levers	Avid Elixir 7
Pedals	N/A

We have taken all our experience in award winning hardtail designs and applied the same winning formula to our 29er's to deliver balance and control

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections

With a Tapered steerer tube and 15mm Maxle Lite front wheel interface and the excellent Easton XCT-70 UST compatible wheelset this bike will not only get you round your favorite XC loop in a record breaking time, it will also give you the control and balance of the very best of our Whyte trail bikes



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



Rear Stays High Modulus Uni-Directional Carbon

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
18.5"	69°	73°	627	305	818
20.5"	69°	73°	620	305	847
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
18.5"	1130	438	30.9	110	470
20.5"	1142	438	30.9	120	521

ZGER C TYPICAL USAGE: CROSS COUNTRY/RACE SRP £1,999



We have taken all our experience in award winning hardtail designs and applied the same winning formula to our 29er's to deliver balance and control

Our Unique Whyte Frame Geometry is more surefooted than a typical light-weight X-C Race bike, inspiring confidence on more technical sections

Whyte X-C 202 wheelset is a light and hand build, in one of the best wheel building factories in the World



Top Tube High Modulus Uni-Directional Carbon



Down Tube

High Modulus Uni-Directional Carbon



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
18.5"	69°	73°	627	305	818
20.5"	69°	73°	620	305	847
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
18.5"	1130	438	30.9	110	470
20.5"	1142	438	30.9	120	521

Color	UD Matt Carbon with White and Apple Green Decals			
Sizes Available	18.5", 20.5"			
Weight	TBC			
Frame	Uni-directional Multi Monoque, with Post Mount chainsty mounted disk brake and full carbon dropouts $% \left({{\left[{{{\rm{D}}_{\rm{T}}} \right]}_{\rm{T}}} \right)$			
Fork	Rockshox Reba RL, 100mm Travel, Tapered Steerer, Poploc Remote Lockout			
Rear Shock	N/A			
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings			
Rear Hub	Whyte XC-202 Wheelset, 32 StSt spokes, 6 Bolt hub with double sealed catridge bearings			
Front Hub	Whyte XC-202 Wheelset, 32 StSt spokes, 6 Bolt hub, double sealed catridge bearing			
Spokes	Stainless Steel Spokes			
Rims	Whyte X-C 202			
Tire	Continental Race King 29" x 2.2"			
Shift Levers	SRAM X-9, 10 Speed, Custom Green			
Front Derailleur	SRAM X-7, 10 Speed			
Rear Derailleur	SRAM X-9 Carbon Long Cage, 10 Speed, Custom Green			
Cassette	SRAM PG-1050, 11-36, 10 Speed			
Chain	FSA Team Issue, 10 Speed			
Crankset	SRAM S1000 PressFit30, 44-33-22, 10 Speed, Triple			
Bottom Bracket	SRAM PressFit 30			
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp			
Seat	Whyte Custom, triple panel design			
Bar	Whyte Custom 2014 Alloy, Flat, 700mm Wide			
Stem	Whyte Custom, -6 Degree, 70mm 18.5" and 80mm 20.5"			
Grips	Whyte Race, Foam Lock-on			
Front Brakes	Avid Elixir 3, Matchmaker, 180mm Rotor			
Rear Brakes	Avid Elixir 3, Matchmaker, 160mm Rotor			
Brake Levers	Avid Elixir 3			
Pedals	N/A			





Color	Jet Black Matt / Gloss with Apple Green Decals
Sizes Available	S, M, L
Weight	10.9kg
Frame	Uni-directional Monocoque Front Triangle, Single Monocoque Rear Swingarm, Modular Dropouts
Fork	Fox 32 Float 150 RCL FIT, Kashima Coating, Factory Series, QR15 with Tapered Steereer Tube, Adjustable Rebound and High and Low Speed Compression Adjustment
Rear Shock	Fox Float RP23 with XV 2 Sleeve and Kashima Coating, Rebound Adjustment and Adjustable DOHC ProPedal. Whyte Designs Cartridge Bearing Shock Bushings
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Easton Haven Carbon 12mm X 142 Shimano E-Thru
Front Hub	Easton Haven Carbon QR15
Spokes	Easton Double Butted
Rims	Easton Haven Carbon, Tubeless Compatible Wheelset
Tire	Maxxis Ardent 26 x 2.25" 120 TPI with Kevlar Bead Front, Maxxis Crossmark 2.1" 120 TPI Rear
Shift Levers	Shimano XTR M980 Ispec, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XTR RD-M985 Shadow Plus
Cassette	Shimano XTR, CS-M980 11-36T, 10 Speed
Chain	Shimano CN-M980, 10 Speed
Crankset	E-13 XCX Single Crank, PF30, 34T Chainring with E-13 ISCG 5 Chainguide
Bottom Bracket	Press Fit-30
Seatpost	Rock Shox REVERB Remotely Adjustable, 30.9mm x 420mm
Seat	Fi'zi:k Gobi II Shiny Black and Black
Bar	Easton Haven Carbon Low Rise, 31.8mm OD, 711mm Wide
Stem	Easton Haven, 31.8mm Bar Clamp, 70mm S, 70mm M, 85mm L
Grips	Whyte Lock-on
Front Brakes	Avid Elixir XX World Cup, 180mm Rotor
Rear Brakes	Avid Elixir XX World Cup, 160mm Rotor, Direct Mount
Brake Levers	Avid Elixir XX World Cup Matchmaker
Pedals	None

1 by 10 is the new trail bench mark. Featuring an 11-36 10-speed rear cassette and a single chain ring with a light weight chain device, this bike has all the trail taming attributes needed to slay a local DH trail or the steepest of trail center runs - then pop up the block and spin you back up to the top

Whyte has worked with Fox to give the 146 X a fantastic Kashima coated rear RP23 rear shock which exploits the all-new XV2 sleeve to give this bike a "bottomless" feel. At the front end there is Taper steerer tubed Kashima Float 150 "Factory" spec fork with FIT damper. Combine this with a stripped off, raw carbon finish and we have a do-anything trail bike that only weighs 24lbs (medium size) without pedals

We use monocoque technology as it allows us to integrate key parts of the frame in one structure, rather than building separate parts and joining them together later. This has real performance benefits. It's the lightest way to produce a frame that is both stiff and strong



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



Rear Stays High Modulus Uni-Directional Carbon

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66°	73.5°	576	338	795
М	66°	73.5°	599	338	803
L	66°	73.5°	624	338	810
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136	440	30.9	115	406
М	1159	440	30.9	120	445
L	1185	440	30.9	125	483

K





We use monocoque technology as it allows us to integrate key parts of the frame in one structure, rather than building separate parts and joining them together later. This has real performance benefits. It's the lightest way to produce a frame that is both stiff and strong

A full carbon tapered headtube gives us fantastic stiffness which delivers very accurate tracking and steering performance in both low and high speed use. 146mm of rear suspension travel. Complete bike weighs only 25.5lbs (medium size) without pedals

SRAM PF30 bottom bracket improves durability in UK conditions and integrated ISCG05 tabs allow you to easily change your setup to a single chainring with a chain device



Top Tube

High Modulus Uni-Directional Carbon



Down Tube

High Modulus Uni-Directional Carbon



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66°	73.5°	576	338	795
М	66°	73.5°	599	338	803
L	66°	73.5°	624	338	810
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136	440	30.9	115	406
М	1159	440	30.9	120	445
L	1185	440	30.9	125	483

Color	Jet Black / White / Nickel
Sizes Available	S, M, L
Weight	11.8kg
Frame	Uni-directional Monocoque Front Triangle, Single Monocoque Rear Swingarm, Modular Dropouts
Fork	Fox 32 Float 150 RCL FIT Factory Series, QR15 with Tapered Steereer Tube, Adjustable Rebound and High and Low Speed Compression Adjustment
Rear Shock	Fox Float RP23 with XV 2 Sleeve, Rebound Adjustment and Adjustable DOHC ProPedal. Whyte Designs Cartridge Bearing Shock Bushings
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Easton EA-90 12mm X 142 Shimano E-Thru
Front Hub	Easton EA-90 QR15
Spokes	Easton EA-90
Rims	Easton EA-90, UST Tubeless
Tire	Maxxis Ardent 26 x 2.25" 120 TPI with Kevlar Bead Front, Maxxis Crossmark 2.1" 120 TPI Rear
Shift Levers	SRAM XX, 10 Speed
Front Derailleur	SRAM XX, 10 Speed
Rear Derailleur	SRAM XX Long Cage, 10 Speed
Cassette	SRAM XX, 11-36T, 10 Speed
Chain	SRAM, 10 Speed
Crankset	SRAM XX Press Fit-30, 26-39, 10 Speed, Compact Double
Bottom Bracket	Press Fit-30
Seatpost	Rock Shox REVERB Remotely Adjustable, 30.9mm x 420mm
Seat	Fi'zi:k Gobi Chalk White and Black
Bar	Easton Haven Carbon Low Rise, 31.8mm OD, 711mm Wide
Stem	Easton Haven, 31.8mm Bar Clamp, 70mm S, 70mm M, 85mm L
Grips	Whyte Lock-on
Front Brakes	Avid Elixir 9, 180mm Rotor
Rear Brakes	Avid Elixir 9, 160mm Rotor, Direct Mount
Brake Levers	Avid Elixir 9 Matchmaker
Pedals	None



Color	Jet Black / White / Nickel			
Sizes Available	S, M, L			
Weight	11.8kg			
Frame	Uni-directional Monocoque Front Triangle, Single Monocoque Rear Swingarm, Modular Dropouts			
Fork	Fox 32 Float 150 RL FIT Performance Series, QR15 Tapered Steerer Tube, Adjustable Rebound and Compression Adjustment			
Rear Shock	Fox Float RP2 with XV 2 Sleeve, Rebound Adjustment and Adjustable DOHC ProPedal. Whyte Designs Cartridge Bearing Shock Bushings			
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5° Lower, 1 1.8° Upper Bearings			
Rear Hub	Easton XCT-70 12mm X 142 Shimano E-Thru			
Front Hub	Easton XCT-70 QR15			
Spokes	Easton XCT-70			
Rims	Easton XCT-70, UST Tubeless Rims			
Tire	Maxxis Ardent 26 x 2.25" 120 TPI with Kevlar Bead Front, Maxxis Crossmark 2.1" 120 TPI Rear			
Shift Levers	SRAM X-9, 10 Speed			
Front Derailleur	SRAM X-9, 10 Speed			
Rear Derailleur	SRAM X-0 Long Cage, 10 Speed			
Cassette	SRAM PG-1050, 12-36, 10 Speed			
Chain	SRAM, 10 Speed			
Crankset	SRAM X-9 Press Fit-30, 26-39, 10 Speed, Compact Double			
Bottom Bracket	Press Fit-30			
Seatpost	Whyte Alloy 2014, 30.9mm x 410mm, 2 Bolt Clamp			
Seat	Fi:zik Gobi XM			
Bar	Easton Haven Alloy Low Rise, 31.8mm, 711mm Wide			
Stem	Whyte, 31.8mm Bar Clamp,S & M 70mm, L 80mm			
Grips	Whyte Lock-on			
Front Brakes	Avid Elixir 7, 180mm Rotor			
Rear Brakes	Avid Elixir 7, 160mm Rotor			
Brake Levers	Avid Elixir 7 Matchmaker			
Pedals	None			
· · · · · · · · · · · · · · · · · · ·				

The 146 S is built around exactly the same ground-breaking full carbon monocoque chassis and swingarm as the Works and X models

Whyte designed suspension systems are engineered to perform smoothly for years to come. To back that up, we provide a lifetime warranty on all the suspension pivot bearings $% \left({{{\rm{s}}_{\rm{s}}}} \right) = {{\rm{s}}_{\rm{s}}} \right)$

The frame has integrated gravity dropper seatpost hose runs for easy upgrading without the need for unsightly cable ties. 146mm of rear suspension travel. Complete bike weighs only 26 lbs(medium size) without pedals



Top Tube High Modulus Uni-Directional Carbon



Down Tube High Modulus Uni-Directional Carbon



Rear Stays High Modulus Uni-Directional Carbon

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66°	73.5°	576	338	795
М	66°	73.5°	599	338	803
L	66°	73.5°	624	338	810
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136	440	30.9	115	406
М	1159	440	30.9	120	445
L	1185	440	30.9	125	483



Confidence inspiring handling is guaranteed with Whyte's Trail Geometry. Custom drawn M6 Magnesium enriched Aluminium main frame is light and strong. Updated design is 1.5lbs lighter than 2011 model

Tapered headtube gives excellent front end stiffness which delivers accurate tracking and steering performance

Full carbon single monocoque swingarm is light, strong and very stiff for exceptional power transfer and rear end stability. The replaceable dropouts come standard with the latest post-mount brake and 12 x 142 Maxle setup, but are interchangeable to future-proof the swingarm



Top Tube

High Modulus Uni-Directional Carbon



Down Tube

High Modulus Uni-Directional Carbon

and the second	- Inco
1	
10 C	and the second

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68°	72.3°	582	342	757
М	68°	73°	602	337	777
L	68°	73.3°	614	335	800
XL	68°	74.3°	628	327	827
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1093	425	30.9	115	419
М	1119	425	30.9	125	445
L	1135	425	30.9	135	483
XL	1158	425	30.9	145	521

Color	White Gloss and Apple Green			
Sizes Available	S, M, L, XL			
Weight	12.2kg			
Frame	Alloy M6 Magnesium Enriched, Front Triangle with Tapered Head Tube, Single Monocoque Rear Swingarm with Modular Dropouts			
Fork	RockShox Reba RL, Maxle Light, 120mm Travel, Motion Control Damping with Turn Key Lockout			
Rear Shock	Rock Shox Monarch TL with large air volume can, with Rebound Adjustment and compression floodgate			
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings			
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole, 12mm x 142mm Maxle			
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole, 15mm Maxle			
Spokes	WTB Double Butted 15g/16g, Black Stainless			
Rims	WTB TCS Cross Contry Disc, 19mm, 32 Hole			
Tire	WTB Wolverine 26" x 2.1" with Kevlar Bead UST Tubeless System			
Shift Levers	SRAM X-7, 10 Speed, Custom Colour			
Front Derailleur	SRAM X-7, 10 Speed, Custom Colour			
Rear Derailleur	SRAM X-9 Long Cage, 10 Speed, Custom Colour			
Cassette	SRAM PG-1030, 12-36, 10 Speed			
Chain	SRAM, 10 Speed			
Crankset	SRAM S1000, 26-39, 10 Speed, Compact Double			
Bottom Bracket	SRAM GXP			
Seatpost	Whyte Alloy 2014, 30.9mm x 410mm, 2 Bolt Clamp			
Seat	Whyte Custom, Triple Panel Design			
Bar	Whyte Custom 2014 Alloy, Low Rise, 710mm Wide			
Stem	Whyte, 31.8mm Bar Clamp, XS & S 70mm, M 80mm, L & XL 90mm			
Grips	Whyte Lock-on			
Front Brakes	Avid Elixir 3, 180mm Rotor			
Rear Brakes	Avid Elixir 3, 160mm Rotor			
Brake Levers	Avid Elixir 3 Matchmaker			
Pedals	None			



Color	Granite / White Gloss with Red Decals
Sizes Available	53cm, 55cm, 57cm, 59cm
Weight	10kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Disk mount
Fork	Straight Bladed Full Carbon Front Fork with Tapered Alloy Steerer, with Post Mount Dropouts
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 28 Hole
Spokes	DT Competition 14g/15g Double Butted Black StSt
Rims	Alex CXD-26 Cross Rim, Disk Specific, 28/32 Hole
Tire	Maxxis Raze CX Tyre, 700 x 33c, Black
Shift Levers	SRAM Apex 10 Speed
Front Derailleur	SRAM Apex, 10 Speed
Rear Derailleur	SRAM Rival, 10 Speed
Cassette	SRAM PG-1050, 11-28, 10 Speed
Chain	SRAM PC-1031
Crankset	FSA Gossamer Pro Cross PF-386, 36-46, 10 Speed, Compact Double
Bottom Bracket	FSA PF-386
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Gossamer Ergo, 460mm Wide
Stem	Whyte -6 Deg, 70mm 51, 80mm 53, 90mm 55 & 57
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	AVID BB-7 Mech, 160mm Rotor
Rear Brakes	AVID BB-7 Mech, 160mm Rotor
Brake Levers	SRAM Apex
Pedals	None

SAXON CROSS

SRP £1,299

TYPICAL USAGE: ALL TERRAIN

New for 2012 Whyte have applied the Whyte Frame Geometry to the all purpose CX category. The Saxon Cross gives you Whyte's most versatile bike, whether commuting, riding your favorite bridle path or winter training this bike will do it all. Or alternatively go try a CX race this winter, this bike can do it all!

SRAM Apex and Rival combine to give a great power delivery, Avid provide the stopping power with BB-7's and Whyte have designed a truly great all-round frame

A straight bladed carbon fork with a tapered steerer tube give this bike great front end stiffness and steering precision



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	69.3°	74.5°	538	290	795
53cm	69.3°	74°	558	290	810
55cm	69.3°	73.5°	585	290	824
57cm	69.3°	73°	600	290	840
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	1036	425	27.2	130	510
53cm	1057	430	27.2	145	530
55cm	1075	430	27.2	160	550
57cm	1106	435	27.2	175	570

CHARING CROSS TYPICAL USAGE: COMMUTE/ALL TERRAIN SRP £999



A strong Alloy 6061 frame, with mudguard and rack eyelets combined with deep section R-7 wheels and disk brakes will give years of low cost cycling

New for 2012 Whyte have applied the Whyte Frame Geometry to the all purpose CX category, designed for commuting longer distances, through your favorite park or down the local Sustrans path, this versatile bike will soak up whatever you throw at it

Shimano Tiagra 10 speed drive train with compact gearing will give a great spread of gear ratios whether commuting fully loaded or winter training



6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	69.3°	74.5°	543	290	795
53cm	69.3°	74°	567	290	810
55cm	69.3°	73.5°	591	290	824
57cm	69.3°	73°	610	290	840
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	1041	425	27.2	130	510
53cm	1066	430	27.2	145	530
55cm	1086	430	27.2	160	550
57cm	1106	435	27.2	175	570

Color	Granite Black Matt with White and Orange Decals
Sizes Available	53cm, 55cm, 57cm, 59cm
Weight	9.8kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Disk mount
Fork	Straight Bladed Carbon Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Black, with Puncture Protection, Folding
Shift Levers	Shimano ST-4600 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4600 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4600 Tiagra, 10 Speed
Cassette	Shimano CS-4600 11-30, 10 Speed
Chain	Shimano CN-4601 Tiagra, 10 Speed
Crankset	FSA Gossamer Cross 36-46, 10 Speed, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Cross, 31.8mm, Compact Style Drop Bar, 440mm Wide
Stem	Whyte 6 Deg, 70mm 51, 80mm 53, 90mm 55 & 57
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	AVID BB-5 Mech, 160mm Rotor
Rear Brakes	AVID BB-5 Mech, 160mm Rotor
Brake Levers	Shimano ST-4600
Pedals	Full Alloy with Toe Clip

KINGS CROSS

TYPICAL USAGE: COMMUTE/ALL TERRAIN SRP £799



Color	Granite Matt with White and Aqua Decals
Sizes Available	53cm, 55cm, 57cm, 59cm
Weight	10.3kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Disk mount
Fork	Straight Bladed Alloy Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Rear Shock	N/A
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front
Tire	Maxxis Detonator, 700 x 28c, Grey, with Puncture Protection
Shift Levers	Shimano ST-3400 SORA, 9 Speed
Front Derailleur	Shimano FD-3400 SORA, 9 Speed
Rear Derailleur	Shimano RD-3400 SORA, 9 Speed
Cassette	SRAM PG-950, 11-28, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	FSA Vero Cross, 36-46, 9 Speed, Compact Double
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Cross, 31.8mm, Compact Style Drop Bar, 440mm Wide
Stem	Whyte 6 Deg, 70mm 51, 80mm 53, 90mm 55 & 57
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	Tektro Lyra Mech, 160mm Rotor
Rear Brakes	Tektro Lyra Mech, 160mm Rotor
Brake Levers	Shimano ST-3400 SORA
Pedals	Composite with Alloy Cage and Toe Clip

New for 2012 Whyte have applied the Whyte Frame Geometry to the all purpose CX category, designed for commuting longer distances, through your favorite park or down the local Sustrans path, this versatile bike will soak up whatever you throw at it

A strong Alloy 6061 frame, with mudguard and rack eyelets combined with deep section R-7 wheels and disk brakes will give years of low cost cycling

Shimano 9 speed drive train with compact gearing will give a great spread of gear ratios whether commuting fully loaded or winter training



Top Tube 6061 Triple Butted Hydro Formed



Down Tube 6061 Triple Butted Hydro Formed



Rear Stays 6061 Hydro Formed

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51cm	69.3°	74.5°	543	290	795
53cm	69.3°	74°	567	290	810
55cm	69.3°	73.5°	591	290	824
57cm	69.3°	73°	610	290	840
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51cm	1041	425	27.2	130	510
53cm	1066	430	27.2	145	530
55cm	1086	430	27.2	160	550
57cm	1106	435	27.2	175	570

) | | | |