

### E N Ē B S G 0 R D E Ρ R F M Ν C





2014 UK DEALER BOOK





Color	Matt Granite/Aqua
Sizes Available	52cm, 54cm, 56cm, 58cm
Weight	9.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted and Post Mount Disk mount
Fork	Straight Bladed Full Carbon Front Fork with Tapered Alloy Steerer, with Post Mount Dropouts
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Spokes	WTB PG 15g, Black Sandvik Stainless with Black Brass Nipples
Rims	WTB Custom Frequency Team i19 TCS, Tubeless Ready, Disk Specific, 32 Hole
Tyre	WTB Cross Wolf, TCS CX Tyre, DNA Compound, 700 x 33c, Black
Shift Levers	SRAM Apex 10 Speed
Front Derailleur	SRAM Apex, 10 Speed
Rear Derailleur	SRAM Rival, Mid Cage, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031
Crankset	FSA Gossamer Pro Cross PF-386, 36-46, 10 Speed, Compact Double
Bottom Bracket	FSA PF-386
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Omega Compact, 460mm Wide
Stem	Whyte -6 Deg, 70mm 51, 80mm 53, 90mm 55 & 57
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	TRP HyRd, 160mm Rotor
Rear Brakes	TRP HyRd, 160mm Rotor
Brake Levers	SRAM Apex with In-Line Bar Top Levers

We have applied our unique Whyte frame geometry to the Saxon Cross, creating Whyte's most versatile all-terrain bike. It's equally at home riding your favourite bridle path, winter training or even commuting. Alternatively, try a CX race this winter - this bike can do it all!

SRAM Apex and Rival combine to give a great power delivery and TRP's new HyRd brakes provide the stopping power to give you unrivalled control on any terrain.

A straight bladed carbon fork with a tapered steerer tube gives this bike great front end stiffness and steering precision.

Dropout Code	DROPWHX
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	70.0	74.0	560mm	279mm	799mm
54cm	70.0	73.5	575mm	279mm	813mm
56cm	70.0	73.0	589mm	279mm	829mm
58cm	69.3	73.0	598mm	279mm	844mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52cm	1050mm	430mm	27.2mm	145mm	520mm
54cm	1060mm	430mm	27.2mm	160mm	540mm
56cm	1075mm	435mm	27.2mm	175mm	560mm
58cm	1085mm	435mm	27.2mm	190mm	580mm



# SAXON CROSS TEAM

SRP £2,499.00



The Saxon Cross Team is Whyte's off the shelf CX race bike. Whether round the local park or on the 3 Peaks this bike is all you need. Trail oriented geometry makes this bike exceptionally competent and controllable off-road.

SRAM's Force 11 speed group combined with the new RED22 levers give you the world's first fully hydraulic disc road brakes.

Easton's straight bladed EC-90 XD carbon fork with its tapered steerer tube gives this bike great front end stiffness and steering precision.

Dropout Code

DROPWHX

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52cm	70.0	74.0	560mm	279mm	799mm
54cm	70.0	73.5	575mm	279mm	813mm
56cm	70.0	73.0	589mm	279mm	829mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52cm	1050mm	430mm	27.2mm	145mm	520mm
54cm	1060mm	430mm	27.2mm	160mm	540mm
56cm	1075mm	435mm	27.2mm	175mm	560mm

Color	Matt Granite/Aqua
Sizes Available	52cm, 54cm, 56cm
Weight	8.65Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted and Post Mount Disk mount
Fork	Easton EC-90 Straight Bladed Full Carbon Front Fork with Tapered Carbon Steerer, with Post Mount Dropouts
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Easton EA90XD, UST Wheelset
Front Hub	Easton EA90XD, UST Wheelset
Spokes	Easton Stainless Steel
Rims	Easton EA90XD, UST Rims
Tyre	Maxxis Raze CX Tyre, 700 x 33c, Black
Shift Levers	SRAM RED22 11 Speed, Hydraulic Levers
Front Derailleur	SRAM Force, 11 Speed
Rear Derailleur	SRAM Force, Mid Cage, 11 Speed
Cassette	SRAM PG-1170, 11-32, 11 Speed
Chain	SRAM PC-1190
Crankset	FSA Team Issue Cross PF-386, 36-46, 11 Speed, Compact Double
Bottom Bracket	FSA PF-386
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Gossamer Wing Compact, 440mm Wide
Stem	Whyte -6 Deg, 70mm 51, 80mm 53, 90mm 55 & 57
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM RED22, 160mm Rotor
Rear Brakes	SRAM RED22. 160mm Rotor
Brake Levers	SRAM RED22

**CROSS RACE: SAXON CROSS TEAM** 

### SUSSEX TYPICAL USAGE: COMMUTER/ANYROAD SRP £799.00



(	
Color	Matt Zinc/Aqua
Sizes Available	50cm, 52cm, 54cm, 56cm, 58cm
Weight	10.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Alloy Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Headset	FSA Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Sealed Ball Retainer
Rear Hub	Whyte Alloy, Double Sealed Bearings, 32 Hole
Front Hub	Whyte Alloy, Double Sealed Bearings, 28 Hole
Spokes	WTB PG 15g, Black Sandvik Stainless with Black Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection
Shift Levers	Shimano ST-3500 SORA, 9 Speed
Front Derailleur	Shimano FD-3500 SORA, 9 Speed
Rear Derailleur	Shimano RD-3500 SORA, 9 Speed
Cassette	SRAM PG-950, 11-32, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	FSA Vero, 34-50, 9 Speed, Compact Double
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar, 440mm Wide
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 57cm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500 SORA
Pedals	Composite with Alloy Cage and Toe Clip

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte road disc range offers Cyclo Cross durability with pure road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets combined with deep section R-7 wheels and disk brakes will give years of reliable all-season performance.

Shimano Sora 9 speed drive train with compact gearing gives a great spread of gear ratios whether commuting fully loaded or winter training.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72.0	74.5	525mm	279mm	771mm
52cm	72.5	74.0	540mm	279mm	789mm
54cm	73.0	73.5	555mm	279mm	806mm
56cm	73.0	73.0	570mm	279mm	822mm
58cm	73.0	73.0	585mm	279mm	838mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	993mm	425mm	27.2mm	130mm	500mm
52cm	998mm	425mm	27.2mm	145mm	520mm
54cm	1003mm	425mm	27.2mm	160mm	540mm
56cm	1013mm	425mm	27.2mm	175mm	560mm
58cm	1028mm	425mm	27.2mm	190mm	580mm

DESIG

Н

U Z



A strong alloy 6061 frame, with mudguard and rack eyelets combined with deep section R-7 wheels and disc brakes will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte road disc range offers Cyclo Cross durability with pure road geometry.

Shimano Tiagra 10 speed drive train with 34-50 compact gearing gives a great spread of gear ratios, whether commuting fully loaded or winter training.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72.0	74.5	525mm	279mm	771mm
52cm	72.5	74.0	540mm	279mm	789mm
54cm	73.0	73.5	555mm	279mm	806mm
56cm	73.0	73.0	570mm	279mm	822mm
58cm	73.0	73.0	585mm	279mm	838mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size 50cm	Wheelbase 993mm	Chain Stay 425mm	Seat Post 27.2mm	Head Tube 130mm	Seat Tube 500mm
50cm	993mm	425mm	27.2mm	130mm	500mm
50cm 52cm	993mm 998mm	425mm 425mm	27.2mm 27.2mm	130mm 145mm	500mm 520mm

Color	Matt Zinc/Apple
Sizes Available	50cm, 52cm, 54cm, 56cm, 58cm
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Carbon Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Sandvik Stainless with Black Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	Shimano ST-4600 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4600 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4600 Tiagra, 10 Speed
Cassette	Shimano CS-4600 Tiagra 11-30, 10 Speed
Chain	Shimano CN-4601 Tiagra, 10 Speed
Crankset	FSA Omega 34-50, 10 Speed, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar, 440mm Wide
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 57cm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-4600
Pedals	Full Alloy with Toe Clip



AXX A

Color	Matt Granite/Burnt Grange
Sizes Available	50cm, 52cm, 54cm, 56cm, 58cm
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Carbon Front Fork, with Eyelets, Post Mount disk mount, Tapered Steerer
Headset	FSA Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Sandvik Stainless with Black Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Black/Grey, with Puncture Protection, Folding
Shift Levers	Shimano ST-5700 105, 10 Speed
Front Derailleur	Shimano FD-4600 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-5700 105, 10 Speed
Cassette	Shimano CS-4600 Tiagra 11-30, 10 Speed
Chain	Shimano CN-4601 Tiagra, 10 Speed
Crankset	FSA Gossamer 34-50, 10 Speed, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar, 440mm Wide
Stem	Whyte -6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 57cm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	TRP HyRd, 160mm Rotor
Rear Brakes	TRP HyRd, 160mm Rotor
Brake Levers	Shimano ST-5700
Pedals	Full Alloy with Toe Clip

Matt Granite/Burnt Orange

Color

A strong alloy 6061 frame, with mudguard and rack eyelets combined with deep section R-7 wheels and disc brakes will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte road disk range offers Cyclo Cross durability with pure road geometry.

Shimano 105 drive train with 34-50 compact gearing gives a great spread of gear ratios, whether commuting fully loaded or winter training, while TRP's HyRd hydraulic brakes give you all-weather control.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	72.0	74.5	525mm	279mm	771mm
52cm	72.5	74.0	540mm	279mm	789mm
54cm	73.0	73.5	555mm	279mm	806mm
56cm	73.0	73.0	570mm	279mm	822mm
58cm	73.0	73.0	585mm	279mm	838mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size 50cm	Wheelbase 993mm	Chain Stay 425mm	Seat Post 27.2mm	Head Tube 130mm	Seat Tube 500mm
50cm	993mm	425mm	27.2mm	130mm	500mm
50cm 52cm	993mm 998mm	425mm 425mm	27.2mm 27.2mm	130mm 145mm	500mm 520mm

# VICTORIA WOMEN'S

SRP £699.00



Based on our high performance mountain bike geometry, the Victoria has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability and slightly shorter and lower top tube to fit a woman's physique better.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.5	549mm	272mm	708mm
м	69.5	73.5	574mm	272mm	738mm
L	70.0	73.0	600mm	272mm	763mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040mm	420mm	27.2mm	115mm	394mm
м	1052mm	420mm	27.2mm	135mm	432mm

DESIG

≻ m

PERFORMANC



# PIMLICO WOMEN'S

SRP £849.00



Based on our high performance mountain bike geometry, the Pimlico has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability and slightly shorter and lower top tube to fit a woman's physique better.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

The Pimlico takes advantage of SRAM's Via Centro groupset, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.5	549mm	272mm	708mm
М	69.5	73.5	574mm	272mm	738mm
L	70.0	73.0	600mm	272mm	763mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040mm	420mm	27.2mm	115mm	394mm
5	104011111	42011111	27.2000	115mm	394mm
M	1040mm 1052mm	420mm	27.2mm 27.2mm	135mm	432mm
-					

Color	Matt Plum/Grey
Sizes Available	S, M, L
Weight	9.9Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Single Eyelets
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Folding Black/Grey, with Puncture Protection
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design with Snake Skin Cover
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm XS & S, 80mm M
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Draco 2, Light weight 160mm Rotor
Rear Brakes	Tektro Draco 2, Light weight 160mm Rotor
Brake Levers	Tektro Draco 2
Pedals	Composite with Alloy Cage and Toe Clip



Color	Matt Granite/Apple
Sizes Available	S, M, L, XL, XXL
Weight	10.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork, with Single Eyelets
Headset	FSA Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Tyre	Maxxis Detonator, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Sora SL-3500, 9 Speed
Front Derailleur	Shimano Sora FD-3500, 9 Speed
Rear Derailleur	Shimano Sora RD-3500, 9 Speed
Cassette	SRAM PG-950, 11-32 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	FSA Tempo 50-34, 9 Speed, Compact
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design, Snake Skin Cover
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro HDC300, Light weight 160mm Rotor
Rear Brakes	Tektro HDC300, Light weight 160mm Rotor
Brake Levers	Tektro HDC300

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride.

Dropout Code DROPWHRC
-----------------------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	570mm	272mm	723mm
м	70.0	73.5	595mm	272mm	743mm
L	70.0	73.0	614mm	272mm	779mm
XL	70.0	73.0	628mm	272mm	805mm
XXL	70.0	72.5	643mm	272mm	829mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1052mm	420mm	27.2mm	120mm	406mm
м	1069mm	420mm	27.2mm	140mm	445mm
L	1084mm	420mm	27.2mm	160mm	495mm
XL	1099mm	420mm	27.2mm	180mm	533mm

DESIG

Ъ

PERFORMANC



Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

The Cambridge takes advantage of SRAM's Via Centro groupset, specifically designed for urban riding, with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	570mm	272mm	723mm
М	70.0	73.5	595mm	272mm	743mm
L	70.0	73.0	614mm	272mm	779mm
XL	70.0	73.0	628mm	272mm	805mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1052mm	Chain Stay 420mm	Seat Post 27.2mm	Head Tube 120mm	Seat Tube 406mm
		,			
S	1052mm	420mm	27.2mm	120mm	406mm

Color	Matt Zinc/Aqua
Sizes Available	S, M, L, XL
Weight	10Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Single Eyelets
Headset	Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB PG 15g, Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Туге	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design, Dark Brown Snake Skin Cover
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Draco 2, 160mm Rotor
Rear Brakes	Tektro Draco 2, 160mm Rotor
Brake Levers	Tektro Draco 2
Pedals	Composite with Alloy Cage and Toe Clip

CAMBRIDGE

R



Color	Matt Granite/Burnt Orange		
Sizes Available	S, M, L, XL, XXL		
Weight	9.7Kg		
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts		
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Single Eyelets		
Headset	FSA No23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter		
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole		
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole		
Spokes	DT Champion, 1.8mm Black Stainless with Brass Nipples		
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals		
Tyre	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection		
Shift Levers	SRAM Via GT, 10 Speed		
Front Derailleur	SRAM Via Centro, 10 Speed		
Rear Derailleur	SRAM Via GT, 10 Speed		
Cassette	SRAM PG-1030, 11-32, 10 Speed		
Chain	SRAM PC-1031, 10 Speed		
Crankset	SRAM Via GT, 48-32 Urban Compact, 10 Speed		
Bottom Bracket	SRAM GXP		
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp		
Seat	Whyte Custom, Triple Panel Design, Black Snake Skin Cover		
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide		
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL		
Grips	GP1 Ergon, Dual Density		
Front Brakes	Avid DB-1, 160mm Rotor		
Rear Brakes	Avid DB-1, 160mm Rotor		
Brake Levers	Avid DB-1		
Pedals	Full Alloy with Toe Clip		
	J		

Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake calliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

The Stirling takes advantage of SRAM's Via GT groupset, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG28

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	570mm	272mm	723mm
м	70.0	73.5	595mm	272mm	743mm
L	70.0	73.0	614mm	272mm	779mm
XL	70.0	73.0	628mm	272mm	805mm
XXL	70.0	72.5	643mm	272mm	829mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1052mm	Chain Stay 420mm	Seat Post 27.2mm	Head Tube 120mm	Seat Tube 406mm
S	1052mm	420mm	27.2mm	120mm	406mm
S M	1052mm 1069mm	420mm 420mm	27.2mm 27.2mm	120mm 140mm	406mm 445mm

DESIG

Ъ

PERFORMANC





SRP £1,499.00



The Montpellier uses a full carbon RC-7 frame and fork. We have incorporated our "Oversize/Undersize" approach from our carbon hardtails to give great power delivery away from the lights, but with class leading comfort.

Based on our high performance mountain bike geometry, the Montpellier bridges the gap between out-right road speed and MTB control, with its long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

The Montpellier takes advantage of SRAM's Via GT groupset, specifically designed for Urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code
--------------

DROPWH20

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
М	70.0	73.5	597mm	272mm	744mm
L	70.0	73.0	616mm	272mm	776mm
XL	70.0	73.0	623mm	272mm	804mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	1069mm	420mm	27.2mm	140mm	445mm
L	1084mm	420mm	27.2mm	160mm	495mm
XL	1099mm	420mm	27.2mm	180mm	533mm

Color	Matt UD Black/Gloss Black
Sizes Available	M, L, XL
Weight	9.1Kg
Frame	Full Carbon Monocoque with tapered headtube and internal cable routing
Fork	Straight Bladed Carbon Front Fork with Alloy Tapered Steerer and single eyelet
Headset	FSA Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion, 1.8mm Black Stainless with Brass Nipples
Rims	Alex Black Dragon 24, Deep Section, Disk Specific Road, 32 Hole Rear and 28 Front, Reflective 3M decals
Туге	Maxxis Detonator, 700 x 28c, Grey, Folding with Puncture Protection
Shift Levers	SRAM Via GT, Matchmaker, 10 Speed
Front Derailleur	SRAM Via GT 10 Speed
Rear Derailleur	SRAM Via GT 10 Speed
Cassette	SRAM PG-1050, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via GT, 48-32 Urban Compact, 10 Speed
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, Flat Bar, 580mm Wide
Stem	Whyte, 80mm M, 90mm L & XL
Grips	GP1 Ergon Grip, Dual Density
Front Brakes	SRAM Via GT, 160mm Rotor
Rear Brakes	SRAM Via GT, 160mm Rotor
Brake Levers	SRAM Via GT, Matchmaker
Pedals	None

**R7 FAST URBAN ROAD: MONTPELLIER** 



Color	Matt Granite/Silver			
Sizes Available	S, M, L, XL			
Weight	13.75Kg			
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts			
Fork SR Suntour NEX HLO, 63mm travel, Hydro Locko				
Headset FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearing				
Rear Hub	Alloy, Double Sealed Bearing, 32 Hole			
Front Hub	Alloy, Double Sealed Bearing, 32 Hole			
Spokes	WTB 15g, Silver Stainless with Brass Nipples			
Rims	WTB SX-17 700c, 32 Hole, with eyelets			
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard			
Shift Levers	Shimano Acera, 9 Speed			
Front Derailleur	Shimano Altus, 9 Speed			
Rear Derailleur	Shimano Alivio, 9 Speed			
Cassette	Shimano HG-20, 11-32, 9 Speed			
Chain	Shimano HG-53, 9 Speed			
Crankset	Shimano M391 Acera, 48-36-26			
Bottom Bracket Square Taper				
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp			
Seat	Whyte Custom, triple panel design			
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide			
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L			
Grips	Whyte Custom Ergo Dual Density Lock-on's			
Front Brakes	Tektro HDC 300, 160mm Rotor			
Rear Brakes	Tektro HDC 300, 160mm Rotor			
Brake Levers	Tektro HDC 300			
Pedals	VP Composite with Toe Clip			

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifting working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Full Shimano 9 speed group to give years of unrivalled performance and puncture resistant tyres for extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG35

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	589mm	288mm	784mm
М	69.0	73.5	614mm	288mm	815mm
L	69.0	73.0	629mm	288mm	842mm
XL	69.0	73.0	644mm	288mm	864mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101mm	435mm	30.9mm	115mm	457mm
М	1121mm	435mm	30.9mm	125mm	495mm
L	1131mm	435mm	30.9mm	135mm	546mm
XL	1146mm	435mm	30.9mm	145mm	585mm

DESIG

Ъ

PERFORMANC





SRP £799.00



Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifting working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Full Shimano 9 speed with SLX Shadow rear derailleur and Octalink BB interface for MTB levels of durability.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG35

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	589mm	288mm	784mm
М	69.0	73.5	614mm	288mm	815mm
L	69.0	73.0	629mm	288mm	842mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1101mm	435mm	30.9mm	115mm	457mm
М	1121mm	435mm	30.9mm	125mm	495mm

Color	Matt Zinc/Aqua
Sizes Available	S, M, L
Weight	13,5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Bearings, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c, with Flat Guard
Shift Levers	Shimano Alivio, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano SLX Shadow
Cassette	Shimano Alivio HG-30, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano Acera M391, 48-36-26, Octalink
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M446, 160mm Rotor
Rear Brakes	Shimano M446, 160mm Rotor
Brake Levers	Shimano M445
Pedals	VP Composite with Alloy Cage and Toe Clip



[	
Color	Matt Granite/Apple
Sizes Available	S, M, L
Weight	13Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-E LO Lite, 63mm travel, Air Spring, Hydro Lock-out, Alloy Upper legs with Alloy Steerer
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Spokes	DT Champion 15g Black Stainless with Black Brass Nipples
Rims	WTB SX-17 700c, 32 Hole with Eyelets
Tyre	WTB All Terrain Comp 700 x 35c, Folding with Flat Guard and Reflective Sidewalls
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano XT, 10 Speed
Cassette	Shimano CS-HG62, 11-34, 10 Speed
Chain	Shimano HG-54. 10 Speed
Crankset	Shimano T551, Hollow Tech II, 48-36-26, 10 Speed
Bottom Bracket	Shimano, Hollow Tech II
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano 446, 160mm Rotor
Rear Brakes	Shimano 446, 160mm Rotor
Brake Levers	Shimano 445
Pedals	VP Full Alloy with Toe Clip

When we set out to create a range of bikes that would handle all-terrain use we started with the geometry of the frame. 13 years of off-road experience told us that these bikes first and foremost needed to handle sweetly, whether riding along a canal tow path, heading down a woodland trail, or beating the traffic on the way through town.

A custom rear drop out allows us to fit the hydraulic disc brake calliper inside the rear triangle leaving you plenty of room to fit a rack and mudguards if desired.

Full Shimano 10 speed using the Deore/XT Trekking groupset for unbeatable performance and reliability.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG35

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	589mm	288mm	784mm
М	69.0	73.5	614mm	288mm	815mm
L	69.0	73.0	629mm	288mm	842mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size	Wheelbase 1101mm	Chain Stay 435mm	Seat Post 30.9mm	Head Tube 115mm	Seat Tube 457mm

DESIG

Ъ

PERFORMANCE





Color	Matt Granite/Silver
Sizes Available	S, M, L
Weight	13.75Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel with Hydro Lockout
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing, 32 Hole
Front Hub	Alloy, Double Sealed Bearing, 32 Hole
Spokes	WTB 15g, Silver Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Туге	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Alivio, 9 Speed
Cassette	Shimano CS-HG-20, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro HDC 300, 160mm Rotor
Rear Brakes	Tektro HDC 300, 160mm Rotor
Brake Levers	Tektro HDC 300
Pedals	VP Composite with Toe Clip

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control).

Full Shimano 9 speed group to give years of unrivalled performance and puncture resistant tyres for extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG35

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	557mm	288mm	728mm
М	69.0	74.0	584mm	288mm	747mm
L	69.0	73.5	609mm	288mm	767mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1073mm	435mm	30.9mm	107mm	432mm
М	1085mm	435mm	30.9mm	115mm	457mm
L	1105mm	435mm	30.9mm	125mm	495mm

DESIG

⊢В

PERFORMANCE



# CALEDONIAN LADIES

SRP £799.00



All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases standover height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control).

Full Shimano 9 speed Deore with Octalink BB interface for MTB durability.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG35

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	557mm	288mm	728mm
М	69.0	74.0	584mm	288mm	747mm
L	69.0	73.5	609mm	288mm	767mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size	Wheelbase 1073mm	Chain Stay 435mm	Seat Post 30.9mm	Head Tube 107mm	Seat Tube 432mm
S	1073mm	435mm	30.9mm	107mm	432mm

Color	Matt Bone/ Silver
Sizes Available	S, M, L
Weight	13.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy steerer tube
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing, 32 Hole
Front Hub	Alloy, Double Sealed Bearing, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c, Folding with Flat Guard
Shift Levers	Shimano Alivio, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore Shadow
Cassette	Shimano CS-HG-30, 11-32, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano Acera M391, 48-36-26, Octalink
Bottom Bracket	Shimano ES-25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design With Snake Skin effect
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro HCD330 WDS, 160mm Rotor
Rear Brakes	Tektro HCD330 WDS, 160mm Rotor
Brake Levers	Tektro HCD330 WDS
Pedals	VP Composite with Alloy Cage and Toe Clip

C7 CROSS TERRAIN WOMEN'S: CALEDONIAN LADIES

# STRAWBERRY HILL LADIES



Color	Granite/Plum
Sizes Available	S, M, L
Weight	12.6Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Whyte Alloy, curved blade with Alloy Steerer
Headset	FSA Semi Integrated, 1 1/8" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Bearing, 32 Hole
Front Hub	Alloy, Double Sealed Bearing, 32 Hole
Spokes	WTB 15g, Silver Stainless with Brass Nipples
Rims	Whyte Double Walled Alloy, 700c, 32 Hole
Tyre	Maxxis Roamer, 700 x 42c High Air Volume, with Kevlar Puncture Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-30, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Selle Royal, Milo Women's fit Saddle
Bar	Whyte Swept Bar, 25.4mm, 600mm Wide, 45mm Sweep
Stem	Whyte Custom, High Rise
Grips	GP1 Ergon, Swept Bar specific
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro V Brake Levers with Integrated Bell
Pedals	VP Alloy Body with Non Slip Grip

The Strawberry Hill is Whyte's take on a lifestyle bike. Stylish is clearly the aim but we also wanted to add a technical solution, so that this bike could handle hills and headwinds without drama. A 30-speed Shimano drive train concealed behind a full chain guard gives you performance and elegance.

Comfort was given top priority, with the Strawberry Hill, the Selle Royal Milo saddle is very comfortable but also lightweight. The grips from Ergo are designed to fit your palm on a swept handle bar bike and even the brake levers have a kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover and internal cable routing keep all the moving parts away from the rider.

	1
Dropout Code	DROPWH14

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	537mm	283mm	685mm
М	69.0	74.0	563mm	283mm	681mm
L	69.0	73.5	587mm	283mm	672mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1056mm	435mm	30.9mm	130mm	432mm
М	1070mm	435mm	30.9mm	160mm	457mm

# X-401 26er KIDS

TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £899.00



[	· · · · · · · · · · · · · · · · · · ·
Color	Matt White/Aqua
Sizes Available	13"
Weight	11.4Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	SR Raidon, 100mm Travel, Alloy Stanchions, Alloy Steerer, Adjustable Rebound, Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 28 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-20, 28 Hole
Tyre	Continental X-King Folding 26" x 2.2"
Shift Levers	SRAM X0 GripShift, 10 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-7, Type 2, 10 Speed
Cassette	SRAM 1030, 11-36, 10 Speed
Chain	SRAM PC3031, 10 Speed
Crankset	SRAM Firex GXP, T33 Single With Chain Guard, 170mm Crank, 10 Speed
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Kids
Bar	Whyte Flat Kids Bar, 31.8mm, 580mm Wide
Stem	Whyte Custom, 70mm -6 Deg
Grips	SRAM Lock-On's
Front Brakes	Tektro HDC 330, 160mm rotor
Rear Brakes	Tektro HDC 330, 160mm rotor
Brake Levers	Tektro HDC 330 WDS, Adjustable Reach
Pedals	VP Composite Kids
	·

The 401 is the first Kid's bike we've made. Driven by our passion for high-speed bikes we decided to ditch the usual route of making a 24" wheel bike and instead we have created a 26er with a 13" frame. So now your son or daughter can keep up with you on your Whyte 29er.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

SRAM's X0 10-speed Grip Shift combined with a 1 by 10 drivetrain gives a totally up-to-date set up. SRAM's Type 2 rear mech keeps the chain under control and a chainguard keeps little fingers safe.

Dropout Code	DROPWH8
--------------	---------

NZ

BY DESIG

U Z

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13″	68.5	74.0	563mm	305mm	714mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1076mm	425mm	30.9mm	100mm	331mm

# 802 650B/27.5 WOMEN'S

SRP £699.00



Color	Matt White/Aqua	
Sizes Available	XS, S, M	
Weight	13,3Kg	
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted	
Fork	SR XCR, 100mm Travel, Alloy Steerer, Adjustable Rebound, Hydro Lockout	
Headset	FSA No. 10 Caged Bearings	
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole	
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole	
Spokes	WTB 15g, Black Stainless with Brass Nipples	
Rims	Whyte XC-20, 32 Hole	
Tyre	Maxxis IKON Wire 27.5" x 2.2"	
Shift Levers	Shimano Acera, 9 Speed	
Front Derailleur	Shimano Altus, 9 Speed	
Rear Derailleur	Shimano Deore RD-M592 Shadow	
Cassette	Shimano HG-20, 11-34, 9 Speed	
Chain	KMC X9, 9 Speed	
Crankset	Shimano M391, 44-32-22, Silver, 9 Speed with 170mm Cranks, Octalink	
Bottom Bracket	Shimano BB-ES25 Octalink	
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp	
Seat	Whyte Custom Women's fit	
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide	
Stem	Whyte Custom, 70mm S, 70mm M, 90mm L & XL	
Grips	Whyte Custom Lock-on	
Front Brakes	Tektro HDC 300, 160mm rotor	
Rear Brakes	Tektro HDC 300, 160mm rotor	
Brake Levers	Tektro HDC 300	
Pedals	VP Composite with Alloy Cage and Toe Clip	

The 802 geometry is designed with a slightly shorter top tube and a little more standover height to offer a better fit for women. For 2014 there is a brand new 650b/27.5" high quality frameset which features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Shimano 9 speed drive train, with shorter 170mm cranks and women's anatomic saddle complete the package.

Dropout Code	DROPWH8
--------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74.0	571mm	304mm	776mm
S	68.5	73.5	586mm	304mm	784mm
М	68.5	73.5	600mm	304mm	804mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089mm	435mm	30.9mm	107mm	381mm
S	1099mm	435mm	30.9mm	115mm	406mm

BY DESIG

U Z

## 806 650B/27.5 WOMEN'S TYPICAL USAGE: CROSS COUNTRY

CAL USAGE: CROSS COUNTRY SRP £999.00



The 806 geometry is designed with a slightly shorter top tube and a little more standover height to offer a better fit for women. For 2014 there is a brand new high quality 650b/27.5" frameset which features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Shimano 10 speed drive train, with shorter 170mm cranks and women's anatomic saddle complete the package. This bike is also tubeless ready so need to worry about punctures.

Dropout Code	DROPWH

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74.0	571mm	304mm	776mm
S	68.5	73.5	586mm	304mm	784mm
М	68.5	73.5	600mm	304mm	804mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089mm	435mm	30.9mm	107mm	381mm
S	1099mm	435mm	30.9mm	115mm	406mm
М	1114mm	435mm	30.9mm	125mm	445mm

Color	Matt White/Plum
Sizes Available	XS, S, M
Weight	12.7Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted
Fork	RockShox XC 30, 100mm Travel, Adjustable Rebound, Turn Key Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Double Sealed, 32 Hole
Front Hub	Alloy, Double Sealed, 28 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	WTB STi19 650b Rims with TCS System, Tubeless Ready, 28 Hole Front, 32 Hole Rear
Tyre	WTB BeeLine TCS Folding 650b x 2.2"
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano SLX RD-M670 Shadow
Cassette	Shimano HG-62, 11-36, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	Shimano M522 Hollow Tech, 42-32-22, Silver, 10 Speed with 170mm Cranks
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's fit
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 90mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro HDC 330, 160mm rotor
Rear Brakes	Tektro HDC 330, 160mm rotor
Brake Levers	Tektro HDC 330 WDS
Pedals	VP Composite with Alloy Cage and Toe Clip

**PERFORMANCE XC HT WOMEN'S 650B: 806 650B/27.5** 



Color	Matt Granite/Agua	
Sizes Available	S, M, L, XL	
Weight	14Kg	
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts	
Fork	SR XCR, 100mm Travel, Alloy Steerer, Adjustable Rebound, Hydro Lockout	
Headset	FSA No. 10 Caged Bearings	
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole	
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole	
Spokes	WTB 15g, Black Stainless with Brass Nipples	
Rims	Whyte XC-20, 32 Hole	
Tyre	Maxxis IKON Wire 27.5" x 2.2"	
Shift Levers	Shimano Acera, 9 Speed	
Front Derailleur	Shimano Altus, 9 Speed	
Rear Derailleur	Shimano Deore RD-M592 Shadow	
Cassette	Shimano HG-20, 11-34, 9 Speed	
Chain	KMC X9, 9 Speed	
Crankset	Shimano M391, 44-32-22, 9 Speed, Octalink	
Bottom Bracket	Shimano BB-ES25 Octalink	
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp	
Seat	Whyte Custom	
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide	
Stem	Whyte Custom, 70mm S, 70mm M, 90mm L & XL	
Grips	Whyte Custom Lock-on	
Front Brakes	Tektro HDC 300, 160mm rotor	
Rear Brakes	Tektro HDC 300, 160mm rotor	

For 2014 the 801 gets our all new 650b/27.5" frameset which features on all our XC performance hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code DROPWH8
----------------------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594mm	304mm	779mm
м	68.5	73.5	608mm	304mm	797mm
L	68.5	73.0	628mm	304mm	822mm
XL	68.5	73.0	639mm	304mm	851mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107mm	435mm	30.9mm	115mm	406mm
м	1123mm	435mm	30.9mm	125mm	445mm
L	1137mm	435mm	30.9mm	135mm	483mm
XL	1149mm	435mm	30.9mm	145mm	533mm

DESIG

Ъ

U Z





For 2014 there is a brand new high quality 650B/27.5" frameset which features on all the X-8 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

Our trail-honed geometry is both fast and reassuring, encouraging you to push your limits on the descents as well as the climbs.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

_	
Dropout (	Code

AXXI

DROPWH8

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	594mm	304mm	779mm
М	68.5	73.5	608mm	304mm	797mm
L	68.5	73.0	628mm	304mm	822mm
XL	68.5	73.0	639mm	304mm	851mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Size S	Wheelbase 1107mm	Chain Stay 435mm	Seat Post 30.9mm	Head Tube 115mm	Seat Tube 406mm
S	1107mm	435mm	30.9mm	115mm	406mm

Color	Matt White/Apple
Sizes Available	S, M, L, XL
Weight	12.5Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts
Fork	RockShox XC-30 Gold, 100mm Travel, Adjustable Rebound, Tapered Alloy Steerer, Turn Key Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole, Green Anodize
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole, Green Anodize
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-22, sleeve joint rim, 32 Hole
Туге	Maxxis IKON, Wire 27.5" x 2.2"
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7, Long Cage, 10 Speed
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM FC800, 44-32-22 with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 90mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 1, 160mm Rotor
Rear Brakes	Avid Elixir 1, 160mm Rotor
Brake Levers	Avid Elixir 1
Pedals	VP Composite with Alloy Cage and Toe Clip

### **529** TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £799.00



Color	Matt Cranite/Purnt Orange
	Matt Granite/Burnt Orange
Sizes Available	S, M, L
Weight	13.7Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts
Fork	RockShox XC-28, 100mm Travel, Adjustable Rebound, Turn Key Lockout
Headset	FSA No. 10 Caged Bearings
Rear Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-29, sleeve joint rims, 32 Hole
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-30, 11-34, 9 Speed
Chain	KMC X9, 9 Speed
Crankset	Shimano M391, 44-32-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES25 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Tektro HDC330, 160mm rotor
Rear Brakes	Tektro HDC330, 160mm rotor
Brake Levers	Tektro HDC330
Pedals	VP Composite with Alloy Cage and Toe Clip

The same high quality frameset features on all the X-29 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring something very special to the 29er movement.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWH8
--------------	---------

DESIC

Ъ

U Z

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.0	600mm	305mm	805mm
М	68.5	73.0	615mm	305mm	820mm
L	68.5	73.0	629mm	305mm	832mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113mm	440mm	30.9mm	110mm	432mm
м	1128mm	440mm	30.9mm	115mm	470mm

629 TYPICAL USAGE: CROSS COUNTRY/TRAIL SRP £999.00



The same high quality frameset features on all the X-29 bikes. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring some thing very special to the 29er movement.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWH8

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.0	600mm	305mm	805mm
М	68.5	73.0	615mm	305mm	820mm
L	68.5	73.0	629mm	305mm	832mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113mm	440mm	30.9mm	110mm	432mm
М	1128mm	440mm	30.9mm	115mm	470mm
L	1143mm	440mm	30.9mm	120mm	521mm

Color	Matt White/Aqua
Sizes Available	S, M, L
Weight	12.4Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts
Fork	RockShox XC-30 TK 29, 100mm Travel, Alloy Tapered Steerer and Lock out and rebound
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Whyte Alloy Double Sealed 32 Hole Rear, 28 Hole Front
Front Hub	Whyte Alloy Cartridge Bearing hub with 28mm Flange 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte XC-229 sleeve joint Rims, 32 Hole Rear, 28 Hole Front
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7, Type 2, Medium Cage, 10 Speed
Cassette	SRAM PG-1030, 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM S1000 GXP, 38-24 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 1, 170mm Rotor
Rear Brakes	Avid Elixir 1, 160mm Rotor
Brake Levers	Avid Elixir 1
Pedals	VP Full Alloy with Toe Clip

PERFORMANCE BY

### 729 **TYPICAL USAGE: CROSS COUNTRY/TRAIL** SRP £1,499.00

Color

Weight

Frame

Fork

Headset

Rear Hub

Front Hub

Spokes

Rims

Tyre

Shift Levers

Cassette

Crankset

Seatpost

Seat

Bar

Stem

Grips

Front Brakes Rear Brakes

Brake Levers

Chain

Front Derailleur

Rear Derailleur

**Bottom Bracket** 

Sizes Available



Matt Granite/Apple         S, M, L         12Kg         6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Dropouts         RockShox Reba RL 100mm Travel, Alloy Tapered Steerer, 15mm Maxle, Rebound and Compression adjust         FSA No. 10 upper and 1.5" lower external cup with Cartridge Bearings         Whyte XC-209 Wheelset, 32 StSt flat spokes, 6 Bolt hub with double sealed cartridge bearings         Whyte XC-209 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed cartridge bearing         Black Stainless Steel Spokes         Whyte XC-209, welded joint         Maxxis IKON, 120TPI, 29" X 2.2" Folding         SRAM X-9 Matchmaker, 10 Speed, Custom Green         SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green         SRAM X-7, 10 Speed         SRAM PC 1031, 10 Speed         SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed         SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed         Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp         Whyte Custom dual density, triple panel design         Whyte Custom Lock-on         Avid Elixir 5 Matchmaker, 170mm Rotor         Avid Elixir 5 Matchmaker, 160mm Rotor	
12Kg6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount DropoutsRockShox Reba RL 100mm Travel, Alloy Tapered Steerer, 15mm Maxle, Rebound and Compression adjustFSA No. 10 upper and 1.5" lower external cup with Cartridge BearingsWhyte XC-209 Wheelset, 32 StSt flat spokes, 6 Bolt hub with double sealed cartridge bearingsWhyte XC-209 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed cartridge bearingBlack Stainless Steel SpokesWhyte XC-209, welded jointMaxxis IKON, 120TPI, 29" X 2.2" FoldingSRAM X-9 Matchmaker, 10 Speed, Custom GreenSRAM X-7, 10 SpeedSRAM X-7, 10 SpeedSRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 SpeedSRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 SpeedSRAM GXPWhyte Custom dual density, triple panel designWhyte Flat 29er 2014 Bar, 31.8mm, 700mm WideWhyte Custom Lock-onAvid Elixir 5 Matchmaker, 170mm Rotor	Matt Granite/Apple
O61Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount DropoutsRockShox Reba RL 100mm Travel, Alloy Tapered Steerer, 15mm Maxle, Rebound and Compression adjustFSA No. 10 upper and 1.5" lower external cup with Cartridge BearingsWhyte XC-209 Wheelset, 32 StSt flat spokes, 6 Bolt hub 	S, M, L
Butted with Post Mount Dropouts         RockShox Reba RL 100mm Travel, Alloy Tapered Steerer, 15mm Maxle, Rebound and Compression adjust         FSA No. 10 upper and 1.5" lower external cup with Cartridge Bearings         Whyte XC-209 Wheelset, 32 St5t flat spokes, 6 Bolt hub with double sealed cartridge bearings         Whyte XC-209 Wheelset, 28 St5t flat spokes, 6 Bolt hub, double sealed cartridge bearing         Black Stainless Steel Spokes         Whyte XC-209, welded joint         Maxxis IKON, 120TPI, 29" X 2.2" Folding         SRAM X-9 Matchmaker, 10 Speed, Custom Green         SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green         SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green         SRAM Y-9 Type 2, Medium Cage, 10 Speed Custom Green         SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed         SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed         SRAM GXP         Whyte Custom dual density, triple panel design         Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide         Whyte Custom Lock-on         Avid Elixir 5 Matchmaker, 170mm Rotor	12Kg
15mm Maxle, Rebound and Compression adjustFSA No. 10 upper and 1.5" lower external cup with Cartridge BearingsWhyte XC-209 Wheelset, 32 StSt flat spokes, 6 Bolt hub with double sealed cartridge bearingsWhyte XC-209 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed cartridge bearingBlack Stainless Steel SpokesWhyte XC-209, welded jointMaxxis IKON, 120TPI, 29" X 2.2" FoldingSRAM X-9 Matchmaker, 10 Speed, Custom GreenSRAM X-9 Type 2, Medium Cage, 10 Speed Custom GreenSRAM X-9 Type 2, Medium Cage, 10 Speed Custom GreenSRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 SpeedSRAM GXPWhyte Custom dual density, triple panel designWhyte Flat 29er 2014 Bar, 31.8mm, 700mm WideWhyte Custom Lock-onAvid Elixir 5 Matchmaker, 170mm Rotor	
Cartridge Bearings Whyte XC-209 Wheelset, 32 StSt flat spokes, 6 Bolt hub with double sealed cartridge bearings Whyte XC-209 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed cartridge bearing Black Stainless Steel Spokes Whyte XC-209, welded joint Maxxis IKON, 120TPI, 29" X 2.2" Folding SRAM X-9 Matchmaker, 10 Speed, Custom Green SRAM X-7, 10 Speed SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM Y-7, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	
<ul> <li>with double sealed cartridge bearings</li> <li>Whyte XC-209 Wheelset, 28 StSt flat spokes, 6 Bolt hub, double sealed cartridge bearing</li> <li>Black Stainless Steel Spokes</li> <li>Whyte XC-209, welded joint</li> <li>Maxxis IKON, 120TPI, 29" X 2.2" Folding</li> <li>SRAM X-9 Matchmaker, 10 Speed, Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green</li> <li>SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed</li> <li>SRAM GXP</li> <li>Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp</li> <li>Whyte Custom dual density, triple panel design</li> <li>Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide</li> <li>Whyte Custom Lock-on</li> <li>Avid Elixir 5 Matchmaker, 170mm Rotor</li> </ul>	
double sealed cartridge bearing Black Stainless Steel Spokes Whyte XC-209, welded joint Maxxis IKON, 120TPI, 29" X 2.2" Folding SRAM X-9 Matchmaker, 10 Speed, Custom Green SRAM X-7, 10 Speed SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	
Whyte XC-209, welded jointMaxxis IKON, 120TPI, 29" X 2.2" FoldingSRAM X-9 Matchmaker, 10 Speed, Custom GreenSRAM X-7, 10 SpeedSRAM Y-7, 10 SpeedSRAM PG-1050, 11-36, 10 SpeedSRAM PC 1031, 10 SpeedSRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 SpeedSRAM GXPWhyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt ClampWhyte Flat 29er 2014 Bar, 31.8mm, 700mm WideWhyte Custom Lock-onAvid Elixir 5 Matchmaker, 170mm Rotor	
Maxxis IKON, 120TPI, 29" X 2.2" Folding SRAM X-9 Matchmaker, 10 Speed, Custom Green SRAM X-7, 10 Speed SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	Black Stainless Steel Spokes
SRAM X-9 Matchmaker, 10 Speed, Custom Green SRAM X-7, 10 Speed SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	Whyte XC-209, welded joint
SRAM X-7, 10 Speed SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	Maxxis IKON, 120TPI, 29" X 2.2" Folding
SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM X-9 Matchmaker, 10 Speed, Custom Green
SRAM PG-1050, 11-36, 10 Speed SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM X-7, 10 Speed
SRAM PC 1031, 10 Speed SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM X-9 Type 2, Medium Cage, 10 Speed Custom Green
SRAM S1400 GXP, 38-24 29er Ratio, Compact Double, 10 Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM PG-1050, 11-36, 10 Speed
Speed SRAM GXP Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM PC 1031, 10 Speed
Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	
Clamp Whyte Custom dual density, triple panel design Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	SRAM GXP
Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	
Whyte Custom, -6 Degree, 70mm S and M and 80mm Large Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	Whyte Custom dual density, triple panel design
Whyte Custom Lock-on Avid Elixir 5 Matchmaker, 170mm Rotor	Whyte Flat 29er 2014 Bar, 31.8mm, 700mm Wide
Avid Elixir 5 Matchmaker, 170mm Rotor	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
,	Whyte Custom Lock-on
Avid Elixir 5 Matchmaker, 160mm Rotor	Avid Elixir 5 Matchmaker, 170mm Rotor
	Avid Elixir 5 Matchmaker, 160mm Rotor
Avid Elixir 5 Matchmaker	Avid Elixir 5 Matchmaker

e same high quality frameset features on all the X-29 bikes. e custom tubing is drawn to our specification and then ofiled, butted and shaped to give what we consider to be the rfect ride feel.

e X-29 geometry is based on the ground breaking 29-C frame. e unique Whyte combination of XC speed, trail bike handling d all-day comfort bring some thing very special to the 29er ovement.

ese frames bristle with UK design features, such as extra ud clearance for all-weather usability, forward facing seat ot to keep rear wheel spray out of the frame, continuous ters for improved cable life and crud-catcher mounts on the wntube to keep the grit out of your teeth.

Dropout Code	DROPWH8
--------------	---------

0 0 Ш ۵ ≻ 'n

U Z

Σ Ľ ٥ БR

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.0	600mm	305mm	805mm
М	68.5	73.0	615mm	305mm	820mm
L	68.5	73.0	629mm	305mm	832mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1113mm	440mm	30.9mm	110mm	432mm
М	1128mm	440mm	30.9mm	115mm	470mm
L	1143mm	440mm	30.9mm	120mm	521mm





Color	Matt UD Carbon/Aqua
Sizes Available	S, M, L
Weight	10.7Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	RockShox Reba RL, 100mm Travel, Tapered Steerer, Crown Activated Lockout
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, with CNC Machined pockets, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Oversize 28mm hub flanges, CNC Machined pockets, 32 Hole
Spokes	WTB 15g, Black Stainless with Brass Nipples
Rims	Whyte X-C 229-S, Sleeve Joint
Tyre	Maxxis IKON, 60TPI Folding Bead, 29" x 2.2"
Shift Levers	SRAM X-9 Matchmaker, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed, High Direct Mount
Rear Derailleur	SRAM X-9 Type 2 medium Cage, 10 Speed, White/Black
Cassette	SRAM PG-1030, 11-36, 10 Speed
Chain	SRAM 1031 with Power Link, 10 Speed
Crankset	SRAM S1000 PressFit30, 38/24, 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM PressFit 30
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 6061 Alloy, Flat, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Avid Elixir 3, Matchmaker, 170mm Rotor
Rear Brakes	Avid Elixir 3, Matchmaker, 160mm Rotor

We have taken all our experience in award winning hardtail designs and applied the same unique formula to our 29ers to deliver perfect balance and control.

Our unique Whyte frame geometry is more surefooted than a typical light-weight XC race bike, inspiring confidence on more technical sections.

Lightweight wheels are essential to 29er performance. Whyte's XC-229-S rims combined with CNC machined hubs give a real performance benefit. The front hub features oversize 28mm flanges to increase the front end stiffness.

Dropout Code	DROPWH20
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612mm	304mm	789mm
М	69.3	72.8	627mm	304mm	809mm
L	69.3	72.8	641mm	304mm	844mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117mm	438mm	30.9mm	100mm	432mm
М	1128mm	438mm	30.9mm	110mm	470mm

DESIG

Ъ

PERFORMANC

### 29-CS TYPICAL USAGE: CROSS COUNTRY/RACE SRP £2,999.00



We have taken all our experience in award winning hardtail designs and applied the same unique formula to our 29ers to deliver perfect balance and control.

Our unique Whyte frame geometry is more surefooted than a typical light-weight XC race bike, inspiring confidence on more technical sections.

With a tapered steerer tube, 15mm Maxle Lite front wheel interface and the excellent Whyte XC-209-C Carbon wheelset, this bike will not only get you round your favourite XC loop in a record breaking time, it will also give you the control and balance of the very best of our Whyte trail bikes.

	Dropout Code
--	--------------

DROPWH20

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612mm	304mm	789mm
М	69.3	72.8	627mm	304mm	809mm
L	69.3	72.8	641mm	304mm	844mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117mm	438mm	30.9mm	100mm	432mm
м	1128mm	438mm	30.9mm	110mm	470mm
L	1145mm	438mm	30.9mm	120mm	521mm

Color	Matt UD Carbon/Apple
Sizes Available	S, M, L
Weight	10.45Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	RockShox Sid RL, 100mm Travel, 15mm Maxle Lite, Matchmaker PushLock Remote lockout
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-C Carbon Wheelset, 32 StSt spokes, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-C Carbon Wheelset, 28 StSt spokes, 6 Bolt hub with double sealed cartridge bearings
Spokes	Stainless Steel
Rims	Whyte X-C-209-C Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Туге	Maxxis IKON, 120TPI Folding Bead, 29" x 2.2"
Shift Levers	Shimano SLX I Spec, 10 Speed
Front Derailleur	Shimano SLX, 10 Speed, High Direct Mount
Rear Derailleur	Shimano XT M786, Shadow Plus, 10 Speed
Cassette	Shimano SLX CS-HG81, 11-36, 10 Speed
Chain	Shimano, HG54, 10 Speed
Crankset	FSA SL-K UD Carbon, PressFit30, 38-24 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	FSA PressFit 30
Seatpost	Whyte Custom 2014 Alloy, 30.9mm x 400mm, 2 bolt clamp
Seat	Whyte Custom dual density, triple panel design
Bar	FSA SL-K UD Carbon, Flat Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano SLX, 180mm Rotor
Rear Brakes	Shimano SLX, 160mm Rotor
Brake Levers	Shimano SLX I Spec





Color	Matt UD Carbon/Burnt Orange
Sizes Available	S, M, L
Weight	9.9Kg
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Fox Float 32 Factory, 100mm Travel with CTD Adjust, FIT, Tapered steerer and 15QR
Headset	FSA Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-C Team Wheelset, 28 Straight Pull StSt spokes, Alloy Freehub, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-C Team Wheelset, 28 Straight Pull StSt spokes, 6 Bolt hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, DT Swiss Prolock Alloy Nipples
Rims	Whyte X-C-209-C Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON, 120TPI Folding Bead, 29" x 2.2"
Shift Levers	Shimano XT I Spec, 10 Speed
Front Derailleur	Shimano XT, 10 Speed, High Direct Mount
Rear Derailleur	Shimano XTR M985, Shadow Plus, 10 Speed
Cassette	Shimano XT CS-M771, 11-36, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA SL-K UD Carbon, PressFit30, 38-24 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	FSA PressFit 30
Seatpost	FSA SL-K, UD Carbon, 30.9mm x 400mm
Seat	Fi'zi:k Tundra II, Mag Rails
Bar	FSA SL-K UD Carbon Flat Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor
Brake Levers	Shimano XT I-Spec

We have taken all our experience in award winning hardtail designs and applied the same unique formula to our 29ers to deliver perfect balance and control.

Our unique Whyte frame geometry is more surefooted than a typical light-weight XC race bike, inspiring confidence on more technical sections.

Whyte's brand new Team unidirectional high modulus carbon wheels are stiff, light, tubeless ready and have wide 23mm rims making the 29-C Team even faster off the line and out of corners.

Dropout Code	DROPWH20
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612mm	304mm	789mm
М	69.3	72.8	627mm	304mm	809mm
L	69.3	72.8	641mm	304mm	844mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117mm	438mm	30.9mm	100mm	432mm
М	1128mm	438mm	30.9mm	110mm	470mm
L	1145mm	438mm	30.9mm	120mm	521mm

Dealance In The Like

DESIG

Ъ

PERFORMANC

### M-109 TYPICAL USAGE: CROSS COUNTRY/MARATHON SRP £1,999.00



Color	Matt Granite FT, Matt White RT/Apple
Sizes Available	S, M, L, XL
Weight	13.2Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with E-Thru dropouts
Fork	Fox Float 32 Evolution 29", 100mm Travel, Tapered steerer and 15QR
Rear Shock	Float Performance with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lower and $11.8''$ Upper Bearing
Rear Hub	Whyte XC-209 Wheelset, 32 StSt flat spokes, 12mm E Tru, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209 Wheelset, 28 StSt flat spokes, QR15, 6 Bolt hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes
Rims	Whyte XC-209, welded joint
Tyre	Maxxis IKON, 120TPI, 29" X 2.2" Folding
Shift Levers	Shimano Deore I-Spec, 10 Speed
Front Derailleur	Shimano Deore, High Direct Mount, 10 Speed
Rear Derailleur	Shimano SLX, Shadow Plus, 10 Speed
Cassette	Shimano HG62-10 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano SLX, Hollow Tech II, 40-30-22, 10 Speed 29er specific Ratios
Bottom Bracket	Shimano Hollow Tech II
Seatpost	Whyte Alloy 2014, 30.9mm x 410mm Zero Offset, 2 Bolt Clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 6061 Alloy, Flat, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M, 90mm L
Grips	Whyte Lock-on
Front Brakes	Shimano BR596, 180mm XT Rotor
Rear Brakes	Shimano BR596, 160mm Rotor
Brake Levers	Shimano BR596, I-Spec

Conceived as the ideal Marathon/Endurance ride, our "Award Winning" 100mm travel M-109 bikes are designed for long, high-speed days in the saddle. Our Quad 4 suspension layout creates room for a larger 29" wheel and is built around lifetime bearings for smooth operation today and forever - guaranteed.

Whyte's 29er XC geometry keeps the back of the bike as short as possible, uniquely combining 26" agility with 29er momentum for speed and control.

The M-109 combines Whyte's XC-209 custom wheelset and Maxxis, high air volume lkon tyres for an exceptional lightweight wheel package - essential for a nimble feel on any 29er.

Dropout Code			DROPWHQ4SH			
Shock Str	oke and Sag	Setting	50mm, Sag 1	.3-15mm		
Reducer B	ush Widths	;	22mm X 8mi	m, 35.5mm X	8mm	
Eye to Eye	e Length		190mm			
Recomme	nded Mudg	uards	N/A			
Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over	
S	69.5	74.2	579mm	335mm	795mm	
М	69.5	74.0	599mm	335mm	797mm	
L	69.5	73.8	614mm	335mm	801mm	
XL	69.5	73.7	629mm	335mm	805mm	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube	
S	675mm	431mm	30.9mm	105mm	432mm	
М	695mm	431mm	30.9mm	105mm	445mm	
L	710mm	431mm	30.9mm	115mm	483mm	
XL	725mm	431mm	30.9mm	120mm	521mm	

Dealance In The Like

DESIG

Ъ

U Z

M-109 S TYPICAL USAGE: CROSS COUNTRY/MARATHON SRP £2,999.00



Conceived as the ideal Marathon/Endurance ride, our award winning 100mm travel M-109 bikes are designed for long, high-speed days in the saddle. No faster way to get from A to B XC under your own power.

Lifetime warranty bearings are used throughout the design, giving this bike exceptional durability, in the harshest UK conditions.

Whyte's own design XC-209C Carbon Wheelset guarantees excellent acceleration and manoeuvrability. For 2014 the rims are upgraded to 23mm wide tubeless ready.

Dropout Code			DROPWHQ4SH			
Shock Str	oke and Sa	gSetting	50mm, Sag	13-15mm		
Reducer Bush Widths		22mm X 8m	m, 35.5mm X	(8mm		
Eye to Eye Length			190mm			
Recomme	nded Mudg	uards	N/A			
Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over	
S	69.5	74.2	579mm	335mm	795mm	
М	69.5	74.0	599mm	335mm	797mm	
L	69.5	73.8	614mm	335mm	801mm	
XL	69.5	73.7	629mm	335mm	805mm	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube	
S	675mm	431mm	30.9mm	105mm	432mm	
М	695mm	431mm	30.9mm	105mm	445mm	
L	710mm	431mm	30.9mm	115mm	483mm	
XL	725mm	431mm	30.9mm	120mm	521mm	

Color	Matt Granite FT, Matt White RT/Aqua
Sizes Available	S, M, L, XL
Weight	12.45Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with E-Thru dropouts
Fork	Fox Float 32 Performance 29" with CTD FIT, 100mm Travel, Tapered steerer and $15 \ensuremath{QR}$
Rear Shock	Float Performance with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lower and Cartridge Bearing 1 1.8" Upper Bearing
Rear Hub	Whyte XC-209-C Carbon Wheelset, 32 StSt spokes, 12mm E Thru, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-C Carbon Wheelset, 28 StSt spokes, QR 15, 6 Bolt hub with double sealed cartridge bearings
Spokes	Triple Butted Stainless Steel
Rims	Whyte X-C-209-C Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON, 120TPI, 29" X 2.2" Folding
Shift Levers	Shimano XT I-Spec, 10 Speed
Front Derailleur	Shimano XT, High Direct Mount, 10 Speed
Rear Derailleur	Shimano XT, Shadow Plus, 10 Speed
Cassette	Shimano HG81-10 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano XT, Hollow Tech II, 40-30-22, 10 Speed 29er specific Ratios
Bottom Bracket	Shimano Hollow Tech II
Seatpost	Whyte Alloy 2014, 30.9mm x 410mm, Zero Offset, 2 Bolt Clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 2014 Alloy, Flat, 730mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT BR785, 180mm Rotor
Rear Brakes	Shimano XT BR785, 160mm Rotor
Brake Levers	Shimano XT BR785 I-Spec

M-109 XC MARATHON SUSPENSION 29ER: M-109 S

### M-109 C TEAM TYPICAL USAGE: CROSS COUNTRY/MARATHON SRP £3,999.00

SIXXVW



Color	Matt UD Carbon FT, Matt Granite RT/Aqua
Sizes Available	M, L
Weight	11.2Kg
Frame	High-Modulus UD Carbon Front Triangle with Tapered Head Tube and alloy rear Triangle with E-Thru dropouts
Fork	Fox Float 32 Factory 29" with CTD Adjust, FIT, 100mm Travel, Tapered steerer and 15QR
Rear Shock	Float Factory with Boost Valve, Rebound Adjustment and CTD Adjust
Headset	FSA Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Whyte XC-209-C Team Carbon Wheelset, 28 Straight Pull StSt spokes, 12mm E Thru, Alloy Freehub, 6 Bolt hub with double sealed cartridge bearings
Front Hub	Whyte XC-209-C Team Wheelset, 28 Straight Pull StSt flat spokes, QR15, 6 Bolt hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, DT Swiss Prolock Alloy Nipples
Rims	Whyte X-C-209-C Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON, 120TPI, 29" X 2.2" Folding
Shift Levers	Shimano XTR I-Spec, 10 Speed
Front Derailleur	Shimano XTR, High Direct Mount, 10 Speed
Rear Derailleur	Shimano XTR, Shadow Plus, 10 Speed
Cassette	Shimano HG771-10 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano XT, Hollow Tech II, 40-30-22, 10 Speed 29er specific Ratios
Bottom Bracket	Shimano Hollow Tech II
Seatpost	FSA SL-K, 30.9mm x 410mm, Zero Offset, 2 Bolt Clamp
Seat	Fi'zi:k Custom Tundra II
Bar	FSA SL-K Flat Bar 700mm Wide
Stem	Whyte Custom, -6 Degree, 80mm M, 90mm L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XTR, 180mm Ice Tech Rotor with metal pads and Cooling Fin's
Rear Brakes	Shimano XTR, 160mm Ice Tech Rotor with metal pads and Cooling Fin's
Brake Levers	Shimano XTR I-Spec

The M-109-C Team is the ultimate Marathon/Endurance ride in our 100mm travel line. Designed for long, high-speed days in the saddle. Our Quad 4 suspension delivers efficiency and reliability, built around lifetime pivot bearings for smooth operation today and forever - guaranteed.

The new carbon front triangle reduces weight, as does the all-new XC-209-C Team wheelset. These next generation carbon wheels from Whyte use wide, low-profile 23mm tubeless-ready carbon rims.

Shimano XTR parts combined with an XT 29er ratio chainset and Fox Racing's Factory suspension gives you the benchmark spec for a Marathon bike.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	50mm, Sag 13-15mm
Reducer Bush Widths	22mm X 8mm, 35.5mm X 8mm
Eye to Eye Length	190mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
м	69.5	74.0	599mm	335mm	797mm
L	69.5	73.8	614mm	335mm	801mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
М	695mm	431mm	30.9mm	105mm	445mm
L	710mm	431mm	30.9mm	115mm	483mm

Dealance In The Like

DESIG

Ъ

U Z





Color	Matt Zinc/Lime
Sizes Available	S, M, L, XL
Weight	12.2Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube
Fork	RockShox Sektor Gold 27.5" Lock-out, Maxle Light 130mm Travel, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Headset	FSA Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Double Sealed, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub 15mm Through Axle, 32 Hole
Spokes	WTB 15 gauge Black Sandvik Stainless with Brass Nipples
Rims	Whyte Trail 21 Disc rim, 32 Hole
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Bead, Maxxis Crossmark, 27.5" X 2.1" 60TPI Folding Bead Rear
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM X-5, 10 Speed
Rear Derailleur	SRAM X-7 Type 2 Medium Cage, 10 Speed, Custom Green
Cassette	SRAM PG-1030, 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM FC S1000, GXP, 38-24, 10 Speed, Double Compact
Bottom Bracket	SRAM GXP
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, Low Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 60mm M, 70mm L, 80mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Avid Elixir 3, 180mm Rotor
Rear Brakes	Avid Elixir 3, 160mm Rotor
Brake Levers	Avid Elixir 3

The 901 gets an all new 650b/27.5" frameset in 2014 but the wheel size is not the only change; the new 900 series geometry takes Whyte's latest thinking on trail geometry and implants it into the DNA of this bike.

The frame is constructed from 6061 aluminium alloy, extruded and manipulated to our exact specification. The 901 gains a fraction more travel and stiffness with the 130mm Sektor Gold fork.

The cockpit parts combine with the geometry to give maximum control, a 750mm wide bar and Whyte's new short, wide mouthed, Gravity stem add huge stiffness and precision.

Dropout Code	DROPWH14
--------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73.0	599mm	305mm	777mm
м	66.5	73.0	618mm	305mm	805mm
L	66.5	73.0	635mm	305mm	832mm
XL	66.5	73.0	654mm	305mm	861mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1119mm	425mm	30.9mm	110mm	406mm
м	1139mm	425mm	30.9mm	120mm	455mm
L	1169mm	425mm	30.9mm	140mm	491mm
XL	1189mm	430mm	30.9mm	150mm	533mm

DESIG

Ъ

PERFORMANCE





**TRAIL HT 650B: 905** 

A LI HL NI DUBU

The 905 gets an all new 650b/27.5" frameset in 2014 but the wheel size is not the only change; the new 900 series geometry takes Whyte's latest thinking on trail geometry and implants it into the DNA of this bike.

The frame is constructed from the highest quality 6061 aluminium alloy, extruded and manipulated to our exact specification.

The cockpit parts combine with the geometry to give maximum control, a 750mm wide bar and Whyte's new short, wide mouthed, Gravity stem add huge stiffness and precision.

Dropout Code DROPWH14
-----------------------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73.0	599mm	305mm	777mm
М	66.5	73.0	618mm	305mm	805mm
L	66.5	73.0	635mm	305mm	832mm
XL	66.5	73.0	654mm	305mm	861mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1119mm	425mm	30.9mm	110mm	406mm
М	1139mm	425mm	30.9mm	120mm	455mm
L	1169mm	425mm	30.9mm	140mm	491mm
XL	1189mm	430mm	30.9mm	150mm	533mm

Color	Matt Zinc/Aqua
Sizes Available	S, M, L, XL
Weight	12Kg
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube
Fork	RockShox Revelation RL, 27.5" Lock-out, Maxle Light 130mm Travel, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Headset	FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Hope EVO Disc, 32 Hole, 135mm, Shimano XT QR
Front Hub	Alloy, Double Sealed Bearing Hub 15mm, 32 Hole
Spokes	DT Champion 1.8mm Black Stainless with Brass Nipples
Rims	Whyte Trail 22 Disc Rims, 32 Hole
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Bead, Maxxis Crossmark, 27.5" X 2.1" 60TPI Folding Bead Rear
Shift Levers	Shimano Deore, 10 Speed, I-Spec
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano SLX, Shadow Plus, 10 Speed
Cassette	Shimano HG-81 SLX, 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Race Face Ride, 38-24, 10 Speed, Compact Double
Bottom Bracket	Race Face
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 2014 Alloy, Low Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 60mm M, 70mm L, 80mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Shimano BR-615, 180mm Rotor
Rear Brakes	Shimano BR-615, 160mm Rotor
Brake Levers	Shimano BL-615, Matchmaker





Color     Matt Zinc/Grey       Sizes Available     S, M, L       Weight     11.8Kg       Frame     6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube and Whyte's adjustable dropout system       Fork     Fox 32 Performance, CTD FIT, 27.5" 130mm Travel, Tapered Steerer and 15QR       Headset     FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings       Rear Hub     Hope EVO Disc, 11 Speed, 32 Hole, 135mm, Shimano XT QR       Front Hub     Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
Weight       11.8Kg         Frame       6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube and Whyte's adjustable dropout system         Fork       Fox 32 Performance, CTD FIT, 27.5" 130mm Travel, Tapered Steerer and 15QR         Headset       FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings         Rear Hub       Hope EVO Disc, 11 Speed, 32 Hole, 135mm, Shimano XT QR         Front Hub       Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
Frame       6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube and Whyte's adjustable dropout system         Fork       Fox 32 Performance, CTD FIT, 27.5" 130mm Travel, Tapered Steerer and 15QR         Headset       FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings         Rear Hub       Hope EVO Disc, 11 Speed, 32 Hole, 135mm, Shimano XT QR         Front Hub       Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
Tapered Steerer and 15QR         Headset       FSA Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1         1.8" Upper Bearings         Rear Hub       Hope EVO Disc, 11 Speed, 32 Hole, 135mm, Shimano XT         QR         Front Hub       Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
1.8" Upper Bearings         Rear Hub       Hope EVO Disc, 11 Speed, 32 Hole, 135mm, Shimano XT QR         Front Hub       Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
QR Front Hub Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole
32 Hole
Spokes WTB 15 gauge Black Sandvik Stainless with Brass Nipples
Rims WTB STi 19 TCS 650b Tubeless ready rims, 32 Hole
Tyre WTB Wolverine 650b x 2.25", 60TPI Dual Compound, Folding Bead Front, WTB Beeline TCS 27.5" x 2.25", 60TPI Dual Compound, Folding Bead, Rear
Shift Levers SRAM X01, 11 Speed
Front Derailleur N/A
Rear Derailleur SRAM X01, Type 2 medium cage, 11 Speed
Cassette SRAM XG-1195, 10-42, 11 Speed
Chain SRAM PCXX1, 11 Speed
Crankset SRAM X01, GXP, 32T, 11 Speed with Chain Guard
Bottom Bracket SRAM GXP
Seatpost Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat Fi'zi:k Gobi XM, Mag Rails
Bar Whyte Custom 2014 Alloy, Low Rise, 750mm Wide
Stem Whyte Gravity Stem, 60mm S, 60mm M, 70mm L
Grips Whyte Custom Lock-on
Front Brakes Shimano XT, 180mm Rotor
Rear Brakes Shimano XT, 160mm Rotor
Brake Levers Shimano

The 909 uses an all new 650b/27.5" frameset but the wheel size is not the only change, the new 900 series geometry takes Whyte's latest thinking on trail geometry and implants it into the DNA of this bike.

The 909 has SRAM's latest version of their revolutionary 1 by 11 drivetrain. This new X01 group has all the features of the XX1 group but uses alloy crank arms. Benchmark Shimano XT brakes, provide the anchors.

Mud clearance and all weather features have long been associated with our designs and when Whyte set out to design this 650b/27.5" frame there was no exception. We have fitted our unique adjustable dropouts, so you can run the chainstays short in the summer and longer in the winter for more mud clearance or singlespeed if that's your thing.

Dropout Code	DROPW19 Drive Side, DROPW19N Disk Side, DROPW19S Singlespeed
--------------	---

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.2 - 66.8	72.7 - 73.3	599mm	305mm	785mm + / - 3
М	66.2 - 66.8	72.7 - 73.3	618mm	305mm	801mm + / - 3
L	66.2 - 66.8	72.7 - 73.3	635mm	305mm	830mm + / - 3
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1109- 1129mm	415-435mm	30.9mm	110mm	406mm
М	1129- 1149mm	415-435mm	30.9mm	120mm	455mm
L	1149- 1169mm	415-435mm	30.9mm	140mm	491mm

DESIC

≻ ⊡

U Z



Color	Matt Zinc/Lime
Sizes Available	S, M, L
Weight	13.3Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts
Fork	RockShox Reba 29", RL, 120mm Travel, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch, RL, with Adjustable Rebound and Compression
Headset	FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lower and 1 1.8" Upper Bearing
Rear Hub	Alloy, Double Sealed Bearing Hub 12mm X 142mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Bearing Hub 15mm Through Axle, 32 Hole
Spokes	WTB Double Butted, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	Whyte Trail 22 Disc Rims, 32 Hole
Tyre	Maxxis Ardent, 29" X 2.25" Folding Front, Maxxis IKON, 29" X 2.2" Folding Rear
Shift Levers	SRAM X-7, 10 Speed
Front Derailleur	SRAM X-7, High Direct Mount, 10 Speed
Rear Derailleur	SRAM X-7, Type 2, 10 Speed, Custom Green
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM S1000 GXP, 36-22 29er Trail Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP
Seatpost	Whyte Alloy 2014, 30.9mm x 410mm, 2 Bolt Clamp
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom 6061 Alloy, 20mm Rise, 750mm Wide
Stem	Whyte Trail Stem, 60mm S, 70mm M, 80mm L
Grips	Whyte Lock-on
Front Brakes	Avid Elixir 3, 180mm Rotor
Rear Brakes	Avid Elixir 3, 160mm Rotor
Brake Levers	Avid Elixir 3

Our Quad 4 suspension layout allows us to apply our contemporary 29er Trail hardtail geometry to the 120mm suspension Trail bike category. Short chainstays give this bike the agility of a 650b/27.5" wheel bike but with the inertia and terrain flattening advantages of a larger 29er wheel.

Lifetime warranty bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Speed and flow is the name of the game with the T129 range. Keep off the brakes as long as you dare, tip the bike in as hard as you can and try and work out how you have tamed your favourite single track so fast.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm X 8mm, 35.5mm X 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.3	576mm	343mm	805mm
М	68.0	74.0	596mm	343mm	808mm
L	68.0	73.8	610mm	343mm	813mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1125mm	431mm	30.9mm	100mm	432mm
М	1145mm	431mm	30.9mm	100mm	445mm
L	1160mm	431mm	30.9mm	110mm	483mm

DESIG

Σ

PERFORMANCE



Our Quad 4 suspension layout allows us to apply our contemporary 29er Trail hardtail geometry to the 120mm suspension Trail bike category. Short chainstays gives this bike the agility of a 650b/27.5" wheel bike but with the inertia and terrain flattening advantages of a larger 29er wheel.

Reverb Stealth seat post, WTB TCS tubeless-ready tyres and rims and Whyte's all new cockpit finishing with ultra-wide 750mm bars and gravity short stem are just a few of the standout spec on the T-129 S.

Speed and flow is the name of the game with the T129 range. Keep off the brakes as long as you dare, tip the bike in as hard as you can and try and work out how you have tamed your favourite single track so fast.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm X 8mm, 35.5mm X 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.3	576mm	343mm	805mm
М	68.0	74.0	596mm	343mm	808mm
L	68.0	73.8	610mm	343mm	813mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1125mm	431mm	30.9mm	100mm	432mm
М	1145mm	431mm	30.9mm	100mm	445mm
L	1160mm	431mm	30.9mm	110mm	483mm

Color     Matt Zinc/Aqua       Sizes Available     S, M, L       Weight     13.4Kg       Frame     6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts       Fork     RockShox Reba 29", RL, 120mm Travel, Tapered steerer	
Weight         13.4Kg           Frame         6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts	
Frame         6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts	
Tube and alloy rear Triangle with 142 dropouts	
Fork RockShox Reba 29", RL, 120mm Travel, Tapered steerer	
and 15mm Maxle	
Rear Shock RockShox Monarch, RT3, Adjustable Rebound and Compression	
Headset FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lowe and 1 1.8" Upper Bearing	r
Rear Hub         Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32 Hole	
Front Hub Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole	
Spokes WTB Double Butted, Black Sandvik Stainless Steel Spoke Brass Nipples	s,
Rims WTB STi19 29" Rims with TCS System, Tubeless Ready	
Tyre WTB Bronson, 29" X 2.2" TCS Race DNA Folding Bead, WTB Nano, 29" X 2.2" TCS Race DNA Folding Bead Rear	
Shift Levers SRAM X-9 Matchmaker, 10 Speed	
Front Derailleur SRAM X-7, High Direct Mount, 10 Speed	
Rear Derailleur SRAM X-9, Type 2, 10 Speed	
Cassette SRAM PG-1050 11-36, 10 Speed	
Chain SRAM PC-1031, 10 Speed	
Crankset SRAM S1400 GXP, 36-22 29er Trail Ratio, Compact Doul 10 Speed	le,
Bottom Bracket SRAM GXP	
Seatpost RockShox Reverb Stealth, Matchmaker, 30.9 X 380mm	
Seat Whyte Custom dual density, triple panel design	
Bar Whyte Custom 2014 Alloy, 15mm Rise, 750mm Wide	
Stem Whyte Trail Stem, 60mm S, 70mm M, 80mm L	
Grips Whyte Lock-on	
Front Brakes Avid Elixir 5, 180mm Rotor	
Rear Brakes Avid Elixir 5, 160mm Rotor	
Brake Levers Avid Elixir 5 Matchmaker	



DESIG

Ъ

PERFORMANC

Color	Matt Zinc/Aqua
Sizes Available	S, M, L
Weight	13.2Kg
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts
Fork	Fox Float 32 Performance 29" with CTD FIT, 120mm Travel, Tapered steerer and 15QR
Rear Shock Float Performance with Boost Valve, Rebound Adjustm and CTD Adjust	
Headset FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Low and 1 1.8" Upper Bearing	
Rear Hub	Hope EVO Disc, 10 Speed, 32 Hole, 12 X 142mm
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm Through Axle, 32 Hole
Spokes	WTB Double Butted, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB STi19 29" Rims with TCS System, Tubeless Ready
Tyre	WTB Bronson, 29" X 2.2" TCS Race DNA Folding Bead, WTB Nano, 29" X 2.2" TCS Race DNA Folding Bead Rear
Shift Levers	Shimano XT, I-Spec, 10 Speed
Front Derailleur	Shimano SLX, High Direct Mount, 10 Speed
Rear Derailleur	Shimano XT Shadow Plus, 10 Speed, Black
Cassette	Shimano HG81 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Shimano XT, 38-24 29er Ratio, Compact Double, 10 Speed, Black
Bottom Bracket	Shimano Hollow Tech II
Seatpost	RockShox Reverb Stealth, 30.9 X 380mm
Seat	Fi'zi:k Gobi XM, Mag Rails
Bar	Whyte Custom 2014 Alloy, 15mm Rise, 750mm Wide
Stem	Whyte Gravity Stem, 60mm S, 70mm M, 80mm L
Grips	Whyte Lock-on
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor
Brake Levers	Shimano XT I-Spec

The Works is a new addition to the award winning T-129 line. A benchmark spec of Hope/Shimano XT and Fox suspension gives you year-round durability for whatever the UK weather throws at you.

Lifetime warranty bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Speed and flow is the name of the game with the T129 range. Keep off the brakes as long as you dare, tip the bike in as hard as you can and try and work out how you have tamed your favourite single track so fast.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	63mm, Sag 19mm
Reducer Bush Widths	22mm X 8mm, 35.5mm X 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.3	576mm	343mm	805mm
М	68.0	74.0	596mm	343mm	808mm
L	68.0	73.8	610mm	343mm	813mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1125mm	431mm	30.9mm	100mm	432mm
М	1145mm	431mm	30.9mm	100mm	445mm
L	1160mm	431mm	30.9mm	110mm	483mm

### **G-150** TYPICAL USAGE: GRAVITY ENDURO/TRAIL SRP £2,499.00



Color	Matt Zinc/Burnt Orange	
Sizes Available	S, M, L	
Weight	13.7Kg	
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts	
Fork	RockShox Pike 27.5", RC, 150mm Travel, Tapered steerer and 15mm Maxle	
Rear Shock	RockShox Monarch, RT3, Adjustable Rebound and Compression	
Headset	FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lower and Cartridge Bearing 1 1.8" Upper Bearing	
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub 12mm X 142mm Through Axle, 32 Hole	
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm, 32 Hole	
Spokes	WTB Double Butted, Black Sandvik Stainless Steel Spokes	
Rims	WTB STi23 650b Rims with TCS System, Tubeless Ready	
Tyre	WTB Wolverine TCS Race, 650b X 2.2" Folding Front, WTB Wolverine TCS Race with Inner Peace Sidewall Protection, 27.5" X 2.2"	
Shift Levers	SRAM X-9, Matchmaker, 10 Speed	
Front Derailleur	SRAM X-7, High Direct Mount, 10 Speed	
Rear Derailleur	SRAM X-9, Type 2, 10 Speed	
Cassette	SRAM PG-1050 11-36, 10 Speed	
Chain	SRAM PC-1031, 10 Speed	
Crankset	SRAM S1400 GXP, 36-22 Gravity Ratio Compact Double, 10 Speed	
Bottom Bracket	SRAM GXP	
Seatpost	RockShox Reverb Stealth, MatchMaker, 30.9 X 355mm	
Seat	Whyte Custom dual density, triple panel design	
Bar	Whyte Custom 2014 Alloy, 15mm Rise, 750mm Wide	
Stem	Whyte Gravity Stem, 50mm S, 50mm M, 60mm L	
Grips	Whyte Lock-on	
Front Brakes	Avid Elixir 7 Trail, 4 Pots, 180mm Rotor	
Rear Brakes	Avid Elixir 7 Trail, 4 Pots, 180mm Rotor	
Brake Levers	Avid Elixir 7 Trail, Matchmaker	

The G-150 is new for 2014, 150mm travel and 650b/27.5" wheels make this platform perfect for Gravity Enduro racing or just bombing around your local hardcore trails.

Lifetime warranty bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

23mm wide TCS Tubeless ready rims and tyres, combined with the new RS Pike fork make this bike ready for anything you want to throw at it. The rear Wolverine tyre is specced with Inner Peace side wall protection for that extra security through rocky sections.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm X 8mm/35.5mm X 8mm
Eye to Eye Length	216mm

Si	ze	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
9	5	67.0	74.2	599mm	343mm	815mm
N	N	67.0	74.0	613mm	343mm	816mm
1	L	67.0	73.8	633mm	343mm	820mm
Si	ze	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
9	5	1154mm	425mm	30.9mm	95mm	432mm
N	N	1169mm	425mm	30.9mm	110mm	445mm

DESIC

Ъ

U Z



The G-150 is new for 2014, 150mm travel and 650b/27.5" wheels make this platform perfect for Gravity Enduro racing or just bombing around your local hardcore trails.

Lifetime warranty bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

The G-150 Works has SRAM's latest version of their revolutionary 1 by 11 drivetrain. This new X01 group has all the features of the XX1 group but uses alloy crank arms. The G-150 is all about suspension and the Works is fitted with the best, FOX Factory spec with Kashima coating.

Dropout Code	DROPWHQ4SH
Shock Stroke and Sag Setting	63mm, Sag 16-19mm
Reducer Bush Widths	22mm X 8mm, 35.5mm X 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0	74.2	599mm	343mm	815mm
М	67.0	74.0	613mm	343mm	816mm
L	67.0	73.8	633mm	343mm	820mm
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1154mm	425mm	30.9mm	95mm	432mm
М	1169mm	425mm	30.9mm	110mm	445mm
L	1189mm	425mm	30.9mm	120mm	483mm

Color	Matt Zinc/Aqua	
Sizes Available	S, M, L	
Weight	12.9Kg	
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and alloy rear Triangle with 142 dropouts	
Fork	Fox Float 34 Factory Kashima, 27.5" with CTD Adjust, FIT, 150mm Travel, Tapered steerer and 15QR	
Rear Shock	Float Float X, Kashima with CTD Adjust and Rebound Adjustment	
Headset	FSA Orbit ZS, 1.5" Cartridge Sealed Lower Bearing Lower and Cartridge Bearing 11.8" Upper Bearing	
Rear Hub	SRAM Rail, 23mm wide 27.5", Full UST Wheelset	
Front Hub	SRAM Rail, 23mm wide 27.5", Full UST Wheelset	
Spokes	SRAM Rail, 23mm wide 27.5", Full UST Wheelset	
Rims	SRAM Rail, 23mm wide 27.5", Full UST Wheelset	
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Bead, Maxxis Crossmark, 27.5" X 2.1" 60TPI Folding Bead Rear	
Shift Levers	SRAM X01, Matchmaker, 11 Speed	
Front Derailleur	N/A	
Rear Derailleur	SRAM X01, Type 2, 11 Speed	
Cassette	SRAM XG1195 10-42, 11 Speed	
Chain	SRAM PCXX1, 11 Speed	
Crankset	SRAM X01 32T, 11 Speed with Chain Guard	
Bottom Bracket	SRAM GXP	
Seatpost	RockShox Reverb Stealth Matchmaker, 30.9 X 380mm	
Seat	Fi'zi:k Gobi XM, Matt/Gloss	
Bar	Easton Havoc 35mm Oversize, 800mm wide	
Stem	Easton Havoc, 35mm Oversize, 50mm long	
Grips	Whyte Lock-on	
Front Brakes	Avid X0 Trail 4 Pots, 180mm Rotor	
Rear Brakes	Avid X0 Trail 4 Pots, 180mm Rotor	
Brake Levers	Avid X0 Trail Matchmaker	

# G-150 GRAVITY ENDURO 650B: G-150 WORKS