



WHYTE
PERFORMANCE BY DESIGN



DESIGNED IN THE U.K.

whyte.bike

29-CS

TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £2,299



Colour	Matt Black with Aqua/ Grey
Sizes Available	S,M,L
Frame	Uni-directional Multi Monocoque with DOX internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts, Inter-Grip integrated seat clamp system
Fork	RockShox Reba RL 29", 100mm Travel, Tapered steerer and 15QR, 32mm Stanchions
Rear Shock	N/A
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, Shimano XT GR
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 15mm
Spokes	Black Stainless Steel
Rims	Easton ARC-24, 24mm UST Rims, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	Shimano XT I Spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, Shadow Plus, 11 Speed
Cassette	Shimano XT M8000, 11-42, 11 Speed
Chain	Shimano, HG600, 11 Speed
Crankset	FSA Comet, Mega EXO, 32t 29er, Speed
Bottom Bracket	FSA Mega EXO, BSA
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	Shimano XT, 180mm Rotor
Rear Brakes	Shimano XT, 160mm Rotor
Brake Levers	Shimano XT I Spec II
Pedals	N/A

The 29CS wheelset comes with Easton 24mm welded rims laced to Whyte's double sealed cartridge bearing hubs with DT Swiss spokes making for a light-weight and durable wheelset.

This bike will not only get you round your favourite XC loop in record time, it will also give you the control and balance of the very best of our Whyte trail bikes.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
M	1127.9	437.5	30.9	110	444.5
L	1144.9	437.5	30.9	120	495.7

29-C TEAM

TYPICAL USAGE: CROSS COUNTRY/RACE

SRP £4,799



Colour	Matt Granite with Orange/Aqua
Sizes Available	S, M, L
Frame	Uni-directional Multi Monocoque with DOX internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts, Inter-Grip integrated seat clamp system
Fork	RockShox RS1 29", 100mm Travel, Fast Black coating, Full Carbon uppers and Tapered steerer, 15mm Maxle Lite
Rear Shock	N/A
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte XC-209-Carbon Team Wheelset, 32 StSt spokes, SRAM X-0 32 Hole, XD Driver for 11 Speed
Front Hub	Whyte XC-209-C Carbon Team Wheelset, 28 StSt spokes, SRAM X-0 28 Hole
Spokes	Double Butted Black Stainless Steel
Rims	Whyte X-C-209-Carbon Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready
Tyre	Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM XX1 MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1, 11Speed
Cassette	SRAM XX1 XG1199 10-42, 11 Speed
Chain	SRAM PCXX1, 11 Speed
Crankset	SRAM XX1, XSYNC direct mount 32T chainring, 11 Speed
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	Easton EC-70 Matt UD Carbon, 30.9mm x 400mm, 2 bolt clamp
Seat	Prologo Custom X-Zero, Ti Rail
Bar	Easton EC-70 Matt UD Carbon, Flat Bar, 31.8mm, 720mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S, 80mm M & L
Grips	Whyte Lock-on, EVA Light-weight Foam
Front Brakes	SRAM Guide RSC, 170mm Rotor, StSt hardware
Rear Brakes	SRAM Guide RSC, 160mm Rotor, StSt hardware
Brake Levers	SRAM Guide RSC, MMX Matchmaker
Pedals	N/A

Picture your dream cross-country race bike: it looks just like the 29-C Team, right? With the best of everything, including the Rockshox RS1 inverted fork with it's huge mud clearance. This is the bike dreams are made of.

Our unique Whyte frame geometry is more surefooted than a typical light-weight XC race bike, inspiring confidence on more technical sections.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

Dropout Code	DROPWH20
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.3	72.8	612.2	304	789
M	69.3	72.8	627	304	809
L	69.3	72.8	640.8	304	844
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1117.3	437.5	30.9	100	406
M	1127.9	437.5	30.9	110	444.5
L	1144.9	437.5	30.9	120	495.7

405

TYPICAL USAGE: TRAIL

SRP £999



Colour	Matt Orange with Grey/Denim
Sizes Available	13
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Get A Grip seat clamp system
Fork	SR Epixon, 100mm Travel, Alloy Stanchions, Alloy Steerer, Adjustable Rebound, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, 4 Cartridge Sealed Bearing, 28 Hole, XD Driver
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-405, 28 Hole
Tyre	WTB Bronson Race, 26" X 2.1", 60TPI Folding Front, WTB Riddler, 26" X 1.95", Rear
Shift Levers	SRAM GX Gripshift, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM GX 1150, 10-42, 11 Speed
Chain	SRAM PC1130, 11 Speed
Crankset	SRAM X1-1000 GXP, XSYNC direct mount 30T chainring, 11 Speed Alloy, 165mm Crank Arms
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Custom 6061 Alloy, Low Rise, 680mm Wide
Stem	Whyte Gravity, 40mm
Grips	SRAM Lock-On's
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor
Brake Levers	Tektro Auriga WS, Adjustable Reach
Pedals	Fibre reinforced Composite Platform

We've broken the mould with the 405. By putting 26" wheels on a kids MTB we've given a boost in performance similar to an adult switching to a 650b/27.5" Trail Hardtail. More confidence, more control and easier riding.

With the all new SRAM GX 1 by 11 spec and Gripshift Shifter, small hands can easily exploit the huge range of gears but we haven't stopped there, we have spec'd a XSYNC Direct Mount chainring so multiple chainrings are available to tune this bike to the local terrain.

The 405 also comes with Whyte's own Get-a-Grip seat post clamping system, this easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWH9
---------------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13	68.5	74.0	563.3	305.0	714
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13	1076	425	30.9	100.0	331.0

529

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £799



Colour	Matt Granite with Orange/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat clamp system
Fork	RockShox XC-30, 100mm Travel, Adjustable Rebound, TK Lockout
Rear Shock	N/A
Headset	FSA No. 10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-20 29" sleeve joint Offset rims, 32 Hole
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Acera M3000, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M4000, 40-30-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 180mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

This great value 29er has exceptional geometry, a lightweight frame and a range of UK-proof features, giving the rider the confidence to ride further, faster, more often.

The same high quality frameset features on all the X-29 bikes.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring something very special to the 29er movement.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.0	611.1	305	800
M	68.5	73.0	625.6	305	810
L	68.5	73.0	645.2	305	836
XL	68.5	73.0	664.5	305	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1123	440.0	30.9	110	406.4
M	1138	440.0	30.9	115	444.5
L	1158	440.0	30.9	120	495.7
XL	1178	440.0	30.9	135	533.4

603 APPLE OPTION

TYPICAL USAGE: CROSS COUNTRY

SRP £525



Colour	Matt Apple with Grey/Teal
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Cable routing, Post Mount Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano Altus, 8 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-41, 11-34, 8 Speed
Chain	KMC HG-40, 8 Speed
Crankset	Shimano M361, 42-32-22, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S & M, 80mm L & 90mm XL
Grips	Whyte Custom
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

The X-6 series is our entry point 650b/27.5" MTB range. Based on the popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWH6
---------------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	593.5	303.5	778.5
M	68.5	73.5	608.1	303.5	796.5
L	68.5	73.0	627.9	303.5	821.5
XL	68.5	73.0	638.8	303.5	850.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107.1	435	30.9	115	406
M	1122.6	435	30.9	125	444
L	1137.4	435	30.9	135	482.6
XL	1149.1	435	30.9	145	533

603 ZINC OPTION

TYPICAL USAGE: CROSS COUNTRY

SRP £525



Colour	Matt Zinc with Black/Apple
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Cable routing, Post Mount Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano Altus, 8 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-41, 11-34, 8 Speed
Chain	KMC HG-40, 8 Speed
Crankset	Shimano M361, 42-32-22, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S & M, 80mm L & 90mm XL
Grips	Whyte Custom
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

You'll find it hard to believe the 603 is Whyte's entry level mountain bike: with carefully chosen, branded parts and a well designed frame it has all the hallmarks of Whyte's award winning DNA.

The X-6 series is our entry point 650b/27.5" MTB range. Based on the popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPHW6
---------------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	593.5	303.5	778.5
M	68.5	73.5	608.1	303.5	796.5
L	68.5	73.0	627.9	303.5	821.5
XL	68.5	73.0	638.8	303.5	850.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107.1	435	30.9	115	406
M	1122.6	435	30.9	125	444
L	1137.4	435	30.9	135	482.6
XL	1149.1	435	30.9	145	533

604 COMPACT-FIT

TYPICAL USAGE: CROSS COUNTRY

SRP £525



Colour	Matt Aqua with Grey/Teal
Sizes Available	XS,S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Cable routing, Post Mount Dropouts
Fork	SR XCM, 100mm Travel, Fixed Rebound Damping, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano Altus, 8 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-41, 11-34, 8 Speed
Chain	KMC HG-40, 8 Speed
Crankset	Shimano M361, 42-32-22, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm XS & S, 80mm M
Grips	Whyte Custom
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga WS
Pedals	Fibre reinforced composite platform

Our Compact MTBs feature shorter geometry and components to better fit a smaller rider. The 604 may be our entry level model, but with carefully chosen parts and an exceptional frame it remains distinctly Whyte.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

The X-6 series is our entry point 650b/27.5" MTB range. Based on the popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

Dropout Code	DROPWH6
---------------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74.0	570.6	303.5	775.5
S	68.5	73.5	585.5	303.5	783.5
M	68.5	73.5	599.6	303.5	803.5
L	68.5	73.5	613.7	303.5	829

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089.1	435	30.9	107	381
S	1099.1	435	30.9	115	406
M	1114.1	435	30.9	125	444
L	1129.1	435	30.9	135	482.6

605

TYPICAL USAGE: CROSS COUNTRY

SRP £625



Colour	Matt Orange with Denim/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Internal Routing, Post Mount Dropouts
Fork	SR XCR, 100mm Travel, Alloy Steerer, Adjustable Rebound, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-19, 32 Hole
Tyre	WTB Nano Wire 27.5" x 2.1"
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Acera M-3000, 9 Speed
Rear Derailleur	Shimano Alivio RD-M4000 Shadow, 9 Speed
Cassette	Shimano HG-200-9, 11-34, 9 Speed
Chain	KMC HG-53, 9 Speed
Crankset	Shimano M3000, 40-30-22, 9 Speed
Bottom Bracket	Shimano BB-UN26 Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Riser Bar 30mm rise DB, 31.8mm, 680mm Wide
Stem	Whyte Custom, 70mm S, 80mm M & L, 90mm XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

The X-6 series is our entry point 650b/27.5" MTB range. Based on the popular X8 frameset it features Whyte's award winning geometry as found on all our XC hardtails. The custom tubing is drawn to our specification and then profiled, butted and shaped to give what we consider to be the perfect ride feel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

For 2016 the 605 features Shimano's new M3000 Acera groupset with a new 40-30-22 ratio chainset.

Dropout Code	DROPWH6
---------------------	---------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	593.5	303.5	778.5
M	68.5	73.5	608.1	303.5	796.5
L	68.5	73.0	627.9	303.5	821.5
XL	68.5	73.0	638.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107.1	435	30.9	115	406
M	1122.6	435	30.9	125	444
L	1137.4	435	30.9	135	482.6
XL	1149.1	435	30.9	145	533

629

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £999

"I loved it... it's a bike handling dream – built with the British climate in mind.
bikemagic.com



Colour	Matt Zinc with Lime/Black
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat clamp system
Fork	RockShox Recon Silver TK 29", Solo Air, 100mm Travel, Alloy Tapered Steerer and Lock out and rebound
Rear Shock	N/A
Headset	FSA No. 10 upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-229 29" sleeve joint Offset Rims, 32 Hole Rear, 28 Hole Front
Tyre	Maxxis IKON 60TPI, 29"x 2.2", Folding
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM GX, 10 Speed
Rear Derailleur	SRAM GX, Type 2, Medium Cage, 10 Speed
Cassette	SRAM PG-1020, 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM S1000 GXP, 36-22 29er Ratio, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Flat 29er 6061 Bar, 31.8mm, 700mm Wide
Stem	Whyte Custom, -6 Degree, 70mm S and M and 80mm Large
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Gemini, 180mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced composite platform

Featuring a 2x10 SRAM GX drivetrain and a lightweight Rockshox fork, the 629 is equally at home lining up at the start of a cross-country race as it is spending long days exploring the hills.

The X-29 geometry is based on the ground breaking 29-C frame. The unique Whyte combination of XC speed, trail bike handling and all-day comfort bring something very special to the 29er movement.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, continuous outers for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.0	611.1	305	800
M	68.5	73.0	625.6	305	810
L	68.5	73.0	645.2	305	836
XL	68.5	73.0	664.5	305	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1123	440.0	30.9	110	406.4
M	1138	440.0	30.9	115	444.5
L	1158	440.0	30.9	120	495.7
XL	1178	440.0	30.9	135	533.4

801

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £750



Colour	Matt Granite with Lime/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat clamp system
Fork	RockShox 30 Silver, 100mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout
Rear Shock	N/A
Headset	FSA No. 10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-20, sleeve joint, Offset rims, 32 Hole
Tyre	Maxxis IKON Wire 27.5" x 2.2"
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Acera M3000, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M4000, 40-30-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

Our range of aluminium hardtails offer a fine balance of fun and speed, and the 801 is the perfect entry point with 27 Shimano gears and RockShox 30 Silver fork with Solo Air.

Offset rims give equal spoke tension to reduce the asymmetric load on the wheel.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	593.5	303.5	778.5
M	68.5	73.5	608.1	303.5	796.5
L	68.5	73.0	627.9	303.5	821.5
XL	68.5	73.0	638.8	303.5	850.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107.1	435	30.9	115	406
M	1122.6	435	30.9	125	444
L	1137.4	435	30.9	135	482.6
XL	1149.1	435	30.9	145	533

802

COMPACT-FIT

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £750

“Super efficient, lightweight, insatiably rapid short travel race or rave machine”

What Mountain Bike - GroupTest Winner



“the Whyte had us grinning from ear to ear and enthused every ride.” mbr - Best in Test and Hardtail of the Year



Colour	Magenta with Black/Aqua
Sizes Available	XS,S,M
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat clamp system
Fork	RockShox 30 Silver, 100mm Travel, Solo Air, Adjustable Rebound, Alloy Steerer, Turn Key Lockout.
Rear Shock	N/A
Headset	FSA No. 10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte XC-20, sleeve joint, Offset rims, 32 Hole
Tyre	Maxxis IKON Wire 27.5" x 2.2"
Shift Levers	Shimano Acera M3000, 9 Speed
Front Derailleur	Shimano Acera M3000, 9 Speed
Rear Derailleur	Shimano Deore RD-M592 Shadow
Cassette	Shimano HG-200, 11-34, 9 Speed
Chain	Shimano HG-53, 9 Speed
Crankset	Shimano M4000, 40-30-22, 9 Speed, Octalink
Bottom Bracket	Shimano BB-ES300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, 60mm XS, 60mm S, 70mm M
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced composite platform

The 802 is available in the XS size, and all sizes sport more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach suiting riders with shorter proportions.

The Multi Award winning 802 offers a great package of Trail Geometry combined with XC parts from Shimano, RockShox and Whyte's in house design team.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing for improved cable life and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74.0	570.6	303.5	775.5
S	68.5	73.5	585.5	303.5	783.5
M	68.5	73.5	599.6	303.5	803.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089.1	435	30.9	107	381
S	1099.1	435	30.9	115	406
M	1114.1	435	30.9	125	444

805

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £999



Colour	Apple with Grey/White
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat post system
Fork	RockShox Recon Silver, 100mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer with 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 10 Semi Integrated, 1 1/8" upper and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole, 15mm X 100mm Through Axle
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i19 27.5" Rims with TCS System, Tubeless Ready, 32 Hole
Tyre	Maxxis IKON TR Tubeless Ready, Folding 60TPI EXO 27.5" x 2.2"
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM GX, 10 Speed
Rear Derailleur	SRAM GX, Medium Cage, Type 2, 10 Speed
Cassette	SRAM PG-1020 11-36, 10 Speed
Chain	SRAM PC 1031, 10 Speed
Crankset	SRAM FC800, 22/36 compact double with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, 70mm S, 70mm M, 80mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor, Internal Routing
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced composite platform

Internal cable routing keeps cables clean and clear of grime whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine.

WTB TCS Asym rims with Maxxis TR IKON tyres combine to make a Tubeless Ready package.

These frames bristle with UK design features, such as extra mud clearance for all-weather usability, forward facing seat slot to keep rear wheel spray out of the frame, internal routing and crud-catcher mounts on the downtube to keep the grit out of your teeth.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.5	73.5	593.5	303.5	778.5
M	68.5	73.5	608.1	303.5	796.5
L	68.5	73.0	627.9	303.5	821.5
XL	68.5	73.0	638.8	303.5	850.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107.1	435	30.9	115	406
M	1122.6	435	30.9	125	444
L	1137.4	435	30.9	135	482.6
XL	1149.1	435	30.9	145	533

806

COMPACT-FIT

TYPICAL USAGE: CROSS COUNTRY/TRAIL

SRP £999



Colour	Matt Granite with Grey/Aqua
Sizes Available	XS,S,M
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, internal Brake and Cable routing with Chainstay Post Mount Dropouts, Get A Grip seat clamp system
Fork	RockShox Recon Silver, 100mm Travel, Solo Air, Adjustable Rebound, Tapered Alloy Steerer, Turn Key Lockout
Rear Shock	N/A
Headset	FSA No. 10 Semi Integrated, upper 1 1/8" and 1.5" lower external cup Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i19 27.5" Rims with TCS System, Tubeless Ready, 32 Hole
Tyre	WTB BeeLine TCS Light Fast Rolling, 27.5" x 2.2" Folding Bead
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano Deore RD-M610 Shadow
Cassette	Shimano HG-50, 11-36, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano M523 Hollow Tech, 40-30-22, Silver, 10 Speed with 170mm Cranks
Bottom Bracket	Shimano BB-ES300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's fit
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 700mm Wide
Stem	Whyte Custom, 60mm XS, 60mm S, 70mm M
Grips	Whyte Custom Lock-on
Front Brakes	Tektro Auriga, 160mm rotor
Rear Brakes	Tektro Auriga, 160mm rotor, Internal Routing
Brake Levers	Tektro Auriga WS
Pedals	Fibre reinforced composite platform

With compact geometry and shorter 170mm cranks as standard, the 806 allows shorter riders to get all the benefits of the intermediate 650b wheel size.

The RockShox Recon 30 Solo Air front fork allows easy set up for a wide range of rider size.

The 806 is also tubeless ready - so no need to worry about punctures.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	68.5	74.0	570.6	303.5	775.5
S	68.5	73.5	585.5	303.5	783.5
M	68.5	73.5	599.6	303.5	803.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1089.1	435	30.9	107	381
S	1099.1	435	30.9	115	406
M	1114.1	435	30.9	125	444

901

TYPICAL USAGE: TRAIL

SRP £1,199

“an inspiring, near-faultless bike.”
What Cycle?



“a massive smile every time you ride.”
mbr. Grouptest Winner



Colour	Matt Zinc with Lime/Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Get A Grip seat clamp system, Internal Stealth Reverb routing
Fork	RockShox Sektor Gold 27.5" Lock-out, Maxle Light 130mm Travel, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Trail 21 Offset Disc rim, 32 Hole
Tyre	Maxxis Ardent, 27.5" X 2.25" 60TPI Folding Front, Maxxis Ardent Race, 27.5" X 2.2" 60TPI Folding Rear
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM GX 36T, 10 Speed
Rear Derailleur	SRAM GX Type 2, Medium Cage, 10 Speed
Cassette	SRAM PG-1020, 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM FC S1000, GXP, 22/36, 10 Speed, Double Compact
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM DB3, 180mm Rotor
Rear Brakes	SRAM DB 3, 160mm Rotor
Brake Levers	SRAM DB 3
Pedals	None

With the 901, it's all about the geometry - it will make you feel more confident in all situations than any hardtail you've ever ridden. For 2016 we have evolved the geometry around a 760mm wide bar and short stems.

The award winning 901 features the "Get A Grip" seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Awarding a magnificent 10/10 MBR describes the 901 as "everything a great trail hardtail should be".

Dropout Code	DROPWH14
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73.0	618.7	305.0	778
M	66.5	73.0	637.5	305.0	794
L	66.5	73.0	655.1	305.0	816
XL	66.5	73.0	674	305.0	833
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

905

TYPICAL USAGE: TRAIL

SRP £1,599

“The perfect Trail Hardtail.”
mbr magazine



“The best Trail Hardtail bar none.”
Dirt 100 2015



Colour	Matt orange with black/denim
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip integrated seat clamp system with Internal Cable routing for Dropper Post
Fork	RockShox Revelation RL, 27.5" Lock-out, Maxle Light 130mm Travel, Fast Black coating, Solo Air, Adjustable Compression and Rebound, Tapered Steerer
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1/8" Upper Bearings
Rear Hub	Alloy, Double Sealed, Cartridge Bearing, 32 Hole
Front Hub	Alloy, Double Sealed, Cartridge Bearing Hub, 15mm X 100mm, 32 Hole
Spokes	DT Champion 2.0mm Black Stainless with Brass Nipples
Rims	WTB Asym i23 TCS 27.5" Tubeless ready rims, 32 Hole
Tyre	WTB Trail Boss, 27.5" X 2.25" TCS, 60TPI Folding
Shift Levers	Shimano Deore, 10 Speed, I-Spec
Front Derailleur	Shimano Deore M-618, 10 Speed
Rear Derailleur	Shimano SLX, Shadow Plus, 10 Speed
Cassette	Shimano HG-81 SLX, 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	Race Face Ride, 22/36, 10 Speed, Compact Double
Bottom Bracket	Race Face
Seatpost	KS CRUXi Dropper Post with KG remote, 30.9mm X 425mm, 100mm travel
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	Shimano BR-615, 180mm Rotor
Rear Brakes	Shimano BR-615, 160mm Rotor
Brake Levers	Shimano BL-615, I-Spec
Pedals	None

The award winning 905 is back and better than ever for 2016, the geometry has been evolved to fit shorter stems and a KS Dropper Post comes as standard as does WTB TCS tubeless tyres and Offset rims.

The 905 gains the “Intergrip” seat post clamp system first introduced on the 2015 suspension bikes, this neat solution gives the 905 a clean look and fantastic weather proofing.

The 905 was included in the 2015 Dirt 100 with the quote “the best trail hardtail bar none”. We are sure the 2016 version is even better!

Dropout Code	DROPWH14
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73.0	618.7	305.0	767
M	66.5	73.0	637.5	305.0	795
L	66.5	73.0	655.1	305.0	822
XL	66.5	73.0	673.9	305.0	851
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

909

TYPICAL USAGE: TRAIL

SRP £1,999



Colour	Matt granite with grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn and Multi Butted, Tapered Headtube, Intergrip integrated seat clamp system with Internal Cable routing for Dropper Post
Fork	Fox Float Performance 34, 27.5", 130mm Travel with FIT4 Damper, Tapered steerer and 15mm x 100mm Thru Axle
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, Sealed Cartridge Bearings, 1.5" Lower, 1 1.8" Upper Bearings
Rear Hub	Hope EVO II with StSt Bearings, Boost 12mm X 148mm, 11 Speed Shimano Freehub.
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 15mm X 100mm Thru Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB Asym i23 TCS 27.5" Tubeless ready rims, 32 Hole
Tyre	Maxxis Ardent TR 27.5" x 2.25", 60TPI Dual Compound, Folding Front, Maxxis Ardent Race TR 27.5" x 2.2", 60TPI Dual Compound with EXO protection, Folding Rear
Shift Levers	Shimano XT M8000 I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus
Cassette	Shimano XT M8000, 11-42, 11 Speed
Chain	Shimano HG-600, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount 32T chainring, 11 Speed, Alloy with 30mm alloy axle
Bottom Bracket	RaceFace BSA 30mm, 73mm
Seatpost	KS CRUXi Dropper Post with Southpaw-P remote, 30.9mm X 425mm, 100mm travel
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Custom Alloy, Low Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Custom Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor
Rear Brakes	Shimano XT M8000, 160mm Rotor
Brake Levers	Shimano XT M8000, I-Spec II
Pedals	None

Our top-end trail hardtail is dripping with lust-worthy components such as Shimano's brand New XT M8000 1 by 11 groupset and brakes, RaceFace's Turbine Clinch direct mount chainset system with a 30mm alloy axle and screw in BSA BB cups.

For 2016 the 909 gets full-on Enduro/Trail attitude with the all new Fox 34 fork with its FIT4 damper up front which gives amazing steering precision and poise when combined with Whyte's trail geometry.

Mud clearance and all weather features have long been associated with our designs and when Whyte set out to design this frame there was no exception. This year we have added the "Intergrip" integrated seat clamp system first seen on the 2015 suspension bikes. This neat solution gives the 909 a clean look and fantastic weather proofing.

Dropout Code	DROPWH14
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	73.0	618.7	305.0	767
M	66.5	73.0	637.5	305.0	795
L	66.5	73.0	655.1	305.0	822
XL	66.5	73.0	673.9	305.0	851
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1138.8	425	30.9	110	406.2
M	1168.8	425	30.9	120	431
L	1178.8	425	30.9	140	457.2
XL	1203.8	430	30.9	150	482.6

CALEDONIAN WOMEN'S

TYPICAL USAGE: ALL TERRAIN

SRP £799

“Very practical and easy to ride. Genuinely nippy, responsive and fun on pretty much any surface.” 9/10

Women's Cycling Magazine



Colour	Matt Granite with Aqua/Lime
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX T670, 10 Speed
Cassette	Shimano Deore, CS-HG-62, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano T521, 48-36-26, Octalink, Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	Fibre reinforced Composite Platform

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are more flexible and offer less steering control).

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	556.6	288.0	728
M	69.0	74	584.4	288.0	747
L	69.0	73.5	609.2	288.0	766.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457.0
L	1105.4	435	30.9	125	495.0

CALEDONIAN

TYPICAL USAGE: ALL TERRAIN

SRP £799



Colour	Matt Zinc with Grey/Aqua
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	Shimano Deore, 10 Speed
Rear Derailleur	Shimano LX T670, 10 Speed
Cassette	Shimano Deore, CS-HG-62, 11-34, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Shimano T521, 48-36-26, Octalink, Hollow Tech, 10 Speed
Bottom Bracket	Shimano ES-300 Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 80mm S, 90mm M & L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	Fibre reinforced Composite Platform

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74	589.4	288.0	784
M	69.0	73.5	614.2	288.0	815
L	69.0	73.0	629.2	288.0	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546

CAMBRIDGE

TYPICAL USAGE: URBAN/COMMUTER

SRP £850



Colour	Matt Zinc with Grey/Aqua
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced Composite Platform

We were excited to be able to spec SRAM's Via Centro urban groupset on the Cambridge. With a 2x10 drivetrain, it will help you conquer even the hilliest of cities.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. Via Centro group has a slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	567.9	271.5	721.5
M	70.0	73.5	595.7	271.5	753.5
L	70.0	73.0	613	271.5	785.5
XL	70.0	73.0	626.9	271.5	816.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

CARNABY COMPACT-FIT

TYPICAL USAGE: URBAN/COMMUTER

SRP £550



Colour	Matt Aqua with Black/Grey
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork with Forged crown, Post mount with Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Vittoria Zaffiro, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Acera RD-M3000, 9 Speed
Cassette	Shimano HG-200-9, 11-34 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Lasco 39T, with Alloy Chain Guard
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S & M, 70mm L
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor
Brake Levers	Tektro Auriga WS
Pedals	Fibre reinforced Composite Platform

The Carnaby is all about simplicity, with the addition of female-specific components such as Whyte's women's specific saddle. Nine gears operated by one shifter will give years of urban use while disc brakes guarantee consistent stopping performance whatever the weather.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	271.5	737.5
M	69.5	73.5	572.1	271.5	740.5
L	70	73	598.3	271.5	772.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

CONISTON WOMEN'S e-BIKE

TYPICAL USAGE: ALL TERRAIN

SRP £1,999



Colour	Matt Granite with Magenta/Aqua
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	SR Suntour NCX-D LO, 63mm travel, Alloy Tapered Steerer tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano SLX M675, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano SLX M675, 10 Speed
Cassette	Shimano Deore HG-62, 11-34, 10 Speed
Chain	Shimano STEP's E6090, e-Bike Specific, 10 Speed
Crankset	Shimano STEP's E-6000, 44T With Double Sided Chain Gaurd, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6000 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	Fibre reinforced Composite Platform

Using Shimano's new STEP's e-Bike mid-ship Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance and Whyte's very own take on All Terrain geometry, this bike is ready to explore!

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	557	288.0	716
M	69	74	584	288.0	748
L	69	73.5	590	288.0	768
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1093	445	30.9	107	406.4
M	1106	445	30.9	115	444.5
L	1126	445	30.9	125	495.3

CONISTON e-BIKE

TYPICAL USAGE: ALL TERRAIN

SRP £1,999



Colour	Matt Granite with Grey/Apple
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	SR Suntour NCX-D LO, 63mm travel, Alloy Tapered Steerer tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano SLX M675, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano SLX M675, 10 Speed
Cassette	Shimano Deore HG-62, 11-34, 10 Speed
Chain	Shimano STEP's E6090, e-Bike Specific, 10 Speed
Crankset	Shimano STEP's E-6000, 44T With Double Sided Chain Guard, 10 Speed
Bottom Bracket	STEP's Drive Unit E-6000 with Speed Sensor and Magnet
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano M447, 160mm Rotor
Rear Brakes	Shimano M447, 160mm Rotor
Brake Levers	Shimano M445
Pedals	Fibre reinforced Composite Platform

Using Shimano's new STEP's e-Bike mid-ship Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance and Whyte's very own take on All Terrain geometry, this bike is ready to explore!

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74	591	288.0	767
M	70	73.5	617.6	288.0	821
L	70	73	637.8	288.0	825
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1107	445	30.9	115	406.4
M	1123.3	445	30.9	125	444.5
L	1138.3	445	30.9	135	495.3

CORNWALL

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £1,850

“Matching versatility with light weight,
Whyte’s carbon all-rounder is county class”
Bikes Etc



Colour	Matt Black with Grey
Sizes Available	51,54,57,60
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 32 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxshield Puncture Protection, Folding
Shift Levers	Shimano 105 ST-505, Full Hydraulic brake lever, 11 Speed
Front Derailleur	Shimano 105, 11 Speed
Rear Derailleur	Shimano 105, 32T Max Capacity, 11 Speed
Cassette	Shimano 105, 11-32, 11 Speed
Chain	Shimano HG600, 11 Speed
Crankset	FSA Gossamer Pro EVO-386 DB 34-50, 11 Speed, Compact Double
Bottom Bracket	FSA EVO-8681
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg, 100mm 51, 110mm 54 & 57, 120mm 60
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Shimano BR-785 Hydraulic, 160mm Rotor
Rear Brakes	Shimano BR-785 Hydraulic, 160mm Rotor
Brake Levers	Shimano ST-505 Hydraulic
Pedals	None

An upgrade over the Suffolk to a full-carbon fibre frame and Shimano 105 hydraulic disc brakes makes the Cornwall something of a dream machine. The perfect British road bike? We think so!

Hydraulic discs deliver modulation and control in all weather conditions. However there is more to the Cornwall than just brakes. The ability to fit full length mud guards combined with strong wheels make it the perfect all weather workhorse, with the added comfort and performance only carbon can give.

A carbon bladed fork, 27.2mm seat post and skinny seat stays combine to give a beautifully smooth ride.

Dropout Code	DROPWHRD
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51	71.5	72.5	543	279	758
54	72	72.5	553	279	788
57	72	72	568	282	817
60	72	72	593	281	843
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51	1005	430	27.2	120	510
54	1011	430	27.2	155	540
57	1022	430	27.2	180	570
60	1047	430	27.2	210	600

DEVON

COMPACT-FIT

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £999



Colour	Matt Zinc with Magenta/Aqua
Sizes Available	47,49,51,53
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, with Maxshield Puncture Protection, Folding, Black/Grey
Shift Levers	Shimano ST-4700 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4700 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4600 Tiagra, 10 Speed
Cassette	Shimano HG-500 11-32, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA Omega 34-50, 10 Speed, 172.5mm Crank Length, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 80mm 47cm, 90mm 49cm/51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-4700 Tiagra with In Line Brake Levers
Pedals	Fibre reinforced Composite with Toe Clip

The Devon's TRP HyRd disc brakes use an innovative hybrid cable/hydraulic system to provide powerful braking whatever the conditions. Compact geometry makes for a more comfortable female-specific fit.

A strong alloy 6061 frame, with mudguard and rack eyelets combined with deep section offset rimmed RD-7 wheels will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte Road Disc range offers Cyclo Cross durability with Road geometry.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47	71.5	75	507	269.0	721
49	72	74.5	515	271.5	742.5
51	72.5	74	525	271.5	776.5
53	73	73.5	535	271.5	793.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47	984.8	425	27.2	115	470
49	985	425	27.2	130	490
51	985.4	425	27.2	145	510
53	985.4	425	27.2	160	530

DORSET

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £999

“a thoroughly sorted all-weather, all-surface machine”
Cycling Plus Magazine



“Classy commuter built for bad weather”

BikeRadar score ★★★★★ 4.5/5



Colour	Matt Granite with Apple/Aqua
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxshield Puncture Protection, Folding
Shift Levers	Shimano ST-4700 Tiagra, 10 Speed
Front Derailleur	Shimano FD-4700 Tiagra, 10 Speed
Rear Derailleur	Shimano RD-4700 Tiagra
Cassette	Shimano CS-4700 Sora 11-32, 10 Speed
Chain	FSA Team Issue, 10 Speed
Crankset	FSA Omega 34-50, 10 Speed, Compact Double
Bottom Bracket	FSA Mega Exo
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3d Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-4700 Tiagra
Pedals	Fibre reinforced Composite Platform

The Dorset benefits from Shimano's all new 10-speed Tiagra groupset, with a wide-ratio cassette to make getting up the hills a breeze. On the descents, reliable TRP disc brakes will slow you down.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section Offset Rimmed RD-7 wheels and TRP Hydro/Mechanical disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73	570	271.5	814.5
58	73.0	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

FAIRFIELD WOMEN'S

TYPICAL USAGE: ALL TERRAIN

SRP £499



Colour	Matt Granite with Magenta/Aqua
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, concealed rear brake post
Fork	6061 Alloy, curved blade with Alloy Steerer and Eyelets
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyre	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano FD-M191, 8 Speed
Rear Derailleur	Shimano Acrea RD-T3000,
Cassette	Shimano CS-HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

The Fairfield is where Whyte's ideas of 29" wheel MTB design dove-tails with classic European-style trekking bikes. With a lightweight, comfortable chassis and a full Shimano drivetrain, it will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHLC
Recommended Mudguards	WHYMG50

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.5	546.7	288.0	712
M	69.0	74	563	288.0	735
L	69.0	73.5	586.9	288.0	761
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	431.8
M	1079.8	445	30.9	160	457.0
L	1099.9	445	30.9	180	495.0

FAIRFIELD

TYPICAL USAGE: ALL TERRAIN

SRP £499



Colour	Matt Granite with Grey/Orange
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, concealed rear brake post
Fork	6061 Alloy, curved blade with Alloy Steerer and Eyelets
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	WTB DX-17 700c, 32 Hole
Tyre	Maxxis Roamer 700 x 42c with Kevlar Puncture Protection
Shift Levers	Shimano Altus, 8 Speed
Front Derailleur	Shimano FD-M191, 8 Speed
Rear Derailleur	Shimano Acera RD-T3000,
Cassette	Shimano CS-HG-31, 11-32, 8 Speed
Chain	Shimano HG-40, 8 Speed
Crankset	Shimano M311, 48-38-28, 8 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro Ergo Style brake lever with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

The Fairfield is where Whyte's ideas of 29" wheel MTB design dove-tails with classic European-style trekking bikes. With a lightweight, comfortable chassis, and a full Shimano drivetrain, it will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame. Our bikes are also mud guard ready for all year use.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHLC
Recommended Mudguards	WHYMG50

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	563	288.0	773
M	69.0	73.5	586.9	288.0	798
L	69.0	73.5	605.2	288.0	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1079.8	445	30.9	160	457
M	1099.9	445	30.9	180	495
L	1119.8	445	30.9	200	546

G-160 RS

TYPICAL USAGE: GRAVITY ENDURO/TRAIL

SRP £2,799



Colour	Matt Granite/Aqua & Lime
Sizes Available	S, M, L
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Dropouts
Fork	RockShox Pike RC, 27.5", 160mm Travel, Fast Black coating, tapered steerer and Boost 110mm X 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub Boost 12mm X 148mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub Boost Hub 15mm x 110mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes
Rims	WTB Asym i29 Rims with TCS System, Sleeve Joint, Tubeless Ready
Tyre	WTB Vigilante AM TCS Light Fast Rolling 27.5 X 2.3" Folding Front, WTB Riddler TCS light Fast Rolling 27.5" X 2.4" Folding Rear
Shift Levers	SRAM X-1, MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-1, 11 Speed Alloy
Cassette	SRAM XG-1175 10-42, 11 Speed
Chain	SRAM PC1, 11 Speed
Crankset	SRAM X1-1000 GXP, XSYNC Direct Mount 32T chainring, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	RockShox Reverb 125 Stealth, MMX MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 780mm Wide
Stem	Whyte Gravity Stem, 40mm
Grips	Whyte Lock-on
Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX Matchmaker
Pedals	None

The G-160 RS features the very latest Whyte thinking on geometry. With a super short stem and wide bar the rider can exploit every ounce of performance from the bike

The RS is loaded with the very latest developments in Trail/Enduro bikes, WTB Asym i29mm rims combined with TCS front and rear specific tyres help to give neutral handling without too much drag. SRAM improves both stiffness and gear tuning with their direct mount XSYNC system chain rings, allowing the rider to change ratios easily to suit their terrain

This bike is ready for anything you want to throw at it from hard-core trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	342.5	807.5
M	66.0+0/-1	74.5	636.6	342.5	815.5
L	66.0+0/-1	74.3	655.9	342.5	822.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2

G-160 WORKS

TYPICAL USAGE: GRAVITY ENDURO/TRAIL

SRP £3,999

“Extremely capable and riotous fun to ride.”

G-150 Works Enduro Mountainbike Magazine **ENDURO**
MOUNTAINBIKE MAGAZINE

“An absolute blast to unleash on your local trails.”

G-150 Works What Mountain Bike Magazine



Colour	Matt Burnt Orange/Black and Denim
Sizes Available	S, M, L
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Dropouts
Fork	RockShox Pike, RCT3, 27.5", 160mm Travel, Fast Black coating, tapered steerer and Boost 110mm X 15mm Maxle
Rear Shock	RockShox Monarch Plus Debonair, RC3, Fast Black coating, Adjustable Rebound and Compression
Headset	Hope, Stainless Steel Cartridge Sealed Upper and Lower Bearings
Rear Hub	SRAM Rail 40, Boost 12 x 148mm
Front Hub	SRAM Rail 40, Boost 15 x 110mm
Spokes	SRAM Rail 40, StSt Butted
Rims	SRAM Rail 40, 23mm wide 27.5", Full UST Rims
Tyre	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Daul TLR, Folding Bead, EXO Sidewall protection
Shift Levers	SRAM XO, MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1, 11 Speed, Carbon
Cassette	SRAM XG1195 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM XO1 Carbon Cranks, XSYNC direct mount 32T Chaining, 11 Speed
Bottom Bracket	Hope Staninless Steel 73mm BSA
Seatpost	RockShox Reverb Stealth 125mm, MMX Matchmaker, 30.9 X 380mm
Seat	Whyte Custom, Triple Panel Design
Bar	RaceFace SIXC Carbon 35mm Oversize, 800mm wide, 20mm rise
Stem	Easton Haven 35mm Oversize, 32mm long
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide RSC MMX Matchmaker
Pedals	None

This is the bike our Gravity Enduro Team race on, and as such, it's got the best of everything, from SRAM, Easton, Hope, RaceFace, Maxxis, and of course, Whyte.

This bike is ready for anything you want to throw at it, from hard-core trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

The 2016 frame geometry progresses even further as our Race Team experience is backfed into our development programme.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	342.5	807.5
M	66.0+0/-1	74.5	636.6	342.5	815.5
L	66.0+0/-1	74.3	655.9	342.5	822.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2

MALVERN WOMEN'S

TYPICAL USAGE: ALL TERRAIN

SRP £699



Colour	Matt Granite with Lime/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO Lite, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Shimano FH-RM-33, 32 Hole with Centre-Lock
Front Hub	Shimano HB-RM-33, 32 Hole with Centre-Lock
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore Shadow, 9 Speed
Cassette	Shimano HG-300-9, 11-32, 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Shimano FC-T4010 Alivio, 48-36-26, Octalink, 9 Speed
Bottom Bracket	Shimano ES-300, Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano BR-M355, 160mm Rotor, Centre-Lock
Rear Brakes	Shimano BR-M355, 160mm Rotor, Centre-Lock
Brake Levers	Shimano BR-M355
Pedals	Fibre reinforced Composite Platform

To save yet more weight, the Malvern's suspension fork comes with an alloy steerer tube. Combined with a lightweight, comfortable chassis and full Shimano drivetrain, the Malvern Ladies will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	556.6	288.0	728
M	69.0	74	584.4	288.0	747
L	69.0	73.5	609.2	288.0	766.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457.0
L	1105.4	435	30.9	125	495.0

MALVERN

TYPICAL USAGE: ALL TERRAIN

SRP £699



Colour	Matte Granite with Grey
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NCX-D LO, 63mm travel, Coil Spring, Hydro Lockout and Alloy Steerer tube
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Shimano FH-RM-33, 32 Hole with Centre-Lock
Front Hub	Shimano HB-RM-33, 32 Hole with Centre-Lock
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	Vittoria Randonneur Trail 700 x 35c, with Double Shielding puncture protection
Shift Levers	Shimano Acera, 9 Speed
Front Derailleur	Shimano Acera, 9 Speed
Rear Derailleur	Shimano Deore Shadow, 9 Speed
Cassette	Shimano HG-300-9, 11-32, 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Shimano FC-T4010 Alivio, 48-36-26, Octalink, 9 Speed
Bottom Bracket	Shimano ES-300, Octalink
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 80mm S, 90mm M & L, 100mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Shimano BR-M355, 160mm Rotor, Centre-Lock
Rear Brakes	Shimano BR-M355, 160mm Rotor, Centre-Lock
Brake Levers	Shimano BL-M355
Pedals	Fibre reinforced Composite Platform

To save yet more weight, the Malvern's suspension fork comes with an alloy steerer tube, which is significantly lighter than steel. Combined with a lightweight, comfortable chassis and full Shimano drivetrain, the Malvern will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74	589.4	288.0	784
M	69.0	73.5	614.2	288.0	815
L	69.0	73.0	629.2	288.0	842
XL	69.0	73.0	644	288.0	864
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546
XL	1146	435	30.9	145	585

MONTPELLIER

TYPICAL USAGE: URBAN/COMMUTER

SRP £1,499



Colour	Matt Granite with Metallic Brass
Sizes Available	M,L,XL
Frame	Full Carbon Monocoque with tapered headtube and internal cable routing and Full Carbon Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Tapered Steerer
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole with XD Driver
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM S700, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Rival 1, Long Cage, 11 Speed
Cassette	SRAM PG-1150, 10-42, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM S350, XSYNC direct mount 44T chainring, 175mm Crank Length
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, Riser Bar 30mm, 580mm Wide
Stem	Whyte, 80mm M, 90mm L & XL
Grips	GP1 Ergon Grip, Dual Density
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor
Brake Levers	Tektro Gemini
Pedals	None

Whyte's latest carbon technology comes to the urban market, combined with SRAM's Rival 1 by 11 groupset it creates one of the lightest and most progressive Urban bikes available today.

We have incorporated our "Oversize/Undersize" approach from our carbon hardtails to give great power delivery away from the lights, but with class leading comfort.

Based on our high performance mountain bike geometry, the Montpellier bridges the gap between out-right road speed and MTB control, with its long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

Dropout Code	DROPWHRD
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70.0	73.5	597	271.5	744
L	70.0	73.0	616.1	271.5	776
XL	70.0	73.0	623.3	271.5	804.1
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1069.1	420	27.2	140	444.5
L	1084	420	27.2	160	495.0
XL	1099.1	420	27.2	180	533.0

PIMLICO COMPACT-FIT

TYPICAL USAGE: URBAN/COMMUTER

SRP £850



Colour	Matt Zinc with Black/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM Via Centro, 10 Speed
Front Derailleur	SRAM Via Centro, 10 Speed
Rear Derailleur	SRAM Via Centro, 10 Speed
Cassette	SRAM PG-1030, 11-32, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM Via Centro, 48-32, 10 Speed, Compact
Bottom Bracket	SRAM Power Spline, 68mm Shell
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm XS & S, 80mm M
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor
Brake Levers	Tektro Auriga WS
Pedals	Fibre reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike a perfect fit for female riders, while a carbon fork does a great job of damping out road buzz.

Based on our high performance mountain bike geometry, the Pimlico has a long wheelbase and relaxed head angle for high speed stability, a shorter stem for excellent slow speed manoeuvrability and slightly shorter and lower top tube to fit a woman's physique better.

The Pimlico takes advantage of SRAM's Via Centro groupset, specifically designed for urban riding with optimised ratios and slightly wider Q factor for a little more heel clearance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	271.5	737.5
M	69.5	73.5	572.1	271.5	740.5
L	70	73	598.3	271.5	772.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

PORTOBELLO

TYPICAL USAGE: URBAN/COMMUTER

SRP £750



Colour	Matt Granite with Grey/Green
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Vittoria Zaffiro Pro, 700 x 28c, Black, with Puncture Protection, Folding
Shift Levers	Shimano Sora SL-3500, 9 Speed
Front Derailleur	Shimano Sora FD-3500, 9 Speed
Rear Derailleur	Shimano Sora RD-3500, 9 Speed
Cassette	Shimano HG-200, 11-32 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
Bottom Bracket	Shimano, Octalink BB-ES300
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 20mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	Whyte Custom Dual Density Lock-on's
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite Platform

Our lightweight aluminium frame uses MTB-inspired geometry to increase confidence on rough city streets while a carbon fork does a great job of damping out road buzz.

The Portobello features a carbon fork to smooth out the road chatter. Dropout eyelets allow our custom mudguards to be fitted.

Our shaped, butted and uniquely profiled rear stays give all our Fast Urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	567.9	271.5	721.5
M	70.0	73.5	595.7	271.5	753.5
L	70.0	73.0	613	271.5	785.5
XL	70.0	73.0	626.9	271.5	816.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

RIDGEWAY WOMEN'S

TYPICAL USAGE: ALL TERRAIN

SRP £599



Colour	Matt Granite with Aqua/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel with Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Acera, 9 Speed
Cassette	Shimano HG-200-9, 11-32, 9 Speed
Chain	KMC CN-HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 bolt clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 70mm S, 80mm M, 90mm L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro T29D, 160mm Rotor
Rear Brakes	Tektro T29D, 160mm Rotor
Brake Levers	Tektro T29D
Pedals	Fibre reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	556.6	288.0	728
M	69.0	74	584.4	288.0	747
L	69.0	73.5	609.2	288.0	766.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1082.9	435	30.9	107	431.8
M	1095.4	435	30.9	115	457.0
L	1105.4	435	30.9	125	495.0

RIDGEWAY

TYPICAL USAGE: ALL TERRAIN

SRP £599



Colour	Matt Granite with Grey/Apple
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	SR Suntour NEX HLO, 63mm travel, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with eyelets
Tyre	WTB All Terrain Comp 700 x 35c with Flat Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Acera T3000, 9 Speed
Cassette	Shimano HG-200-9, 11-32, 9 Speed
Chain	KMC CN-HG-53, 9 Speed
Crankset	Shimano M371, 48-36-26, 9 Speed
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom, triple panel design
Bar	Whyte High Rise 30mm, 31.8mm, 620mm Wide
Stem	Whyte Custom, 80mm S, 90mm M & L
Grips	Whyte Custom Ergo Dual Density Lock-on's
Front Brakes	Tektro T290, 160mm Rotor
Rear Brakes	Tektro T290, 160mm Rotor
Brake Levers	Tektro T290
Pedals	Fibre reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the RidgeWay is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG46

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74	589.4	288.0	784
M	69.0	73.5	614.2	288.0	815
L	69.0	73.0	629.2	288.0	842
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1100.6	435	30.9	115	457
M	1120.5	435	30.9	125	495
L	1130.6	435	30.9	135	546

SAXON CROSS TEAM

TYPICAL USAGE: CYCLOCROSS/ALL TERRAIN

SRP £1,999

“Nimble, intuitive, fun to ride.”
bikeradar

BikeRadar score ★★★★★ 4/5



Colour	Matt Granite with Orange/Aqua
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, Chainstay Post Mount Disk mount with Inter-Grip integrated seat clamp system
Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, tapered alloy steerer, Flat Mount dropouts and 15mm Through Axle
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole with XD Driver
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 15mm Axle
Spokes	DT Champion 2.0mm with Brass Nipples
Rims	Easton ARC-24, 24mm UST Rims
Tyre	Maxxis Mud Wrestler TR, 700 x 33c, 60TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection
Shift Levers	SRAM Force 1, 11 Speed Carbon Hydraulic Levers
Front Derailleur	N/A
Rear Derailleur	SRAM Force 1, Mid Cage, 11 Speed
Cassette	SRAM PG-1170, 11-32, 11 Speed
Chain	SRAM PCX1
Crankset	SRAM Force 1, XSYNC direct mount 3BT chaining, 170mm Crank Length, Carbon
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 2014 Alloy, 1pcs 3D forged
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Gossamer Compact, 440mm Wide
Stem	Whyte -6 Deg, 80mm 54, 90mm 56
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM Force 1, 160mm Rotor
Rear Brakes	SRAM Force 1, 160mm Rotor
Brake Levers	SRAM Force 1, Carbon
Pedals	None

A truly ground-breaking cross bike with MTB-inspired geometry, tubeless ready wheels and tyres, hydraulic disc brakes and SRAM's innovative Force 1 groupset, this bike is ready for anything from a CX Race to an all-day adventure

Whyte geometry makes this bike exceptionally competent and controllable off-road. "1 by 11" technology offers simplicity and efficiency that cannot be rivalled. Full hydraulic disc brakes add stopping power and control.

Whyte's straight bladed carbon fork with its tapered steerer tube and 15mm through axle gives this bike great front end stiffness and steering precision.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	70.0	74	560.2	283.0	793
54	70.0	73.5	574.5	283.0	808
56	70.0	73.0	589.2	283.0	823
58	70.0	73.0	598.3	283.0	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	1034.7	415	30.9	145	520
54	1044.7	415	30.9	160	540
56	1054.7	415	30.9	175	560
58	1064.7	415	30.9	190	580

SAXON CROSS

TYPICAL USAGE: CYCLOCROSS/ALL TERRAIN

SRP £1,499



Colour	Matt Granite with Orange/Aqua
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted, Chainstay Post Mount Disk mount with Inter-Grip integrated seat clamp system
Fork	Straight Bladed Carbon Front Fork with Internal Hose Routing, tapered alloy steerer, Flat Mount dropouts and 15mm Through Axle
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/8" upper Sealed Cartridge Bearing, 1.5 lower Sealed Cartridge Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 15mm
Spokes	WTB 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	WTB Custom Asym i19 TCS, Tubeless Ready, I-Beam technology, Disk Specific, 32 Hole
Tyre	WTB Cross Boss, TCS CX Tyre, DNA Compound, 700 x 35c, Black
Shift Levers	SRAM Rival 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Rival 1, Long Cage, 11 Speed
Cassette	Shimano XT M8000 11-42, 11 Speed
Chain	Shimano HG-600, 11 Speed
Crankset	SRAM Rival 1, XSYNC direct mount 38T chainring, 175mm Crank Length
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	FSA Omega Compact
Stem	Whyte -6 Deg, 70mm 52mm, 80mm 54, 90mm 56mm & 58mm
Grips	Whyte Anti Slip, Cross Bar Tapes
Front Brakes	SRAM Rival 1 Hydraulic, 160mm Rotor
Rear Brakes	SRAM Rival 1 Hydraulic, 160mm Rotor
Brake Levers	SRAM Rival 1 Hydraulic
Pedals	None

The Saxon Cross takes everything we've learnt from MTBs and puts that knowledge into a great value cyclocross package. With hydraulic discs, ground-breaking geometry and SRAM's innovative Force 1 groupset, this bike is ready for anything from a CX Race to an all-day adventure.

We have applied our unique Whyte frame geometry to the Saxon Cross, creating Whyte's most versatile all-terrain bike. It's equally at home riding your favourite bridle path, winter training or even commuting. Alternatively, try a CX race this winter - this bike can do it all!

A straight bladed carbon fork with a tapered steerer tube, internal hose routing and 15mm through axle, give this bike great front end stiffness and steering precision.

Dropout Code	DROPWHRC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	70.0	74	560.2	283.0	793
54	70.0	73.5	574.5	283.0	808
56	70.0	73.0	589.2	283.0	823
58	70.0	73.0	598.3	283.0	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	1034.7	415	30.9	145	520
54	1044.7	415	30.9	160	540
56	1054.7	415	30.9	175	560
58	1064.7	415	30.9	190	580

SHOREDITCH

TYPICAL USAGE: URBAN/COMMUTER

SRP £650



Colour	Matt Granite with Grey/Orange
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork, with Post Mount and Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Vittoria Zaffiro Pro, 700 x 28c, Black, with Puncture Protection, Folding
Shift Levers	Shimano Deore, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore Shadow Plus, 10 Speed
Cassette	Shimano HG-50-10, 11-36 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Lasco 42T Alloy Chain ring and Guard, 10 Speed
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pc 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S, 70mm M, 80mm L, 90mm XL
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite Platform

The Shoreditch employs mountain biking clutch mech technology to ensure the chain stays put no matter how rough the route becomes. Elsewhere, the upgrade to a carbon fork saves weight and smooth's out road chatter.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. 1 by 10 MTB gearing promises years of reliable urban use and hydro discs guarantee consistent performance in all conditions.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	567.9	271.5	721.5
M	70.0	73.5	595.7	271.5	753.5
L	70.0	73.0	613	271.5	785.5
XL	70.0	73.0	626.9	271.5	816.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

SOMERSET COMPACT-FIT

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £799



Colour	Matt Granite with Lime/Aqua
Sizes Available	47,49,51,53
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Alloy Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Gaards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Caged Double Sealed
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 28 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Maxshield with Puncture Protection. Aqua/Black, folding
Shift Levers	Shimano ST-3500 SORA, 9 Speed
Front Derailleur	Shimano FD-3500 SORA, 9 Speed
Rear Derailleur	Shimano RD-3500 SORA, 9 Speed
Cassette	Shimano HG-300, 11-32, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	Shimano R345-L, 34-50, Octalink, 9 Speed, Compact Double
Bottom Bracket	Shimano BB-ES300, Octalink
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 6061Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 80mm 47cm, 90mm 49cm/51cm, 100mm 53cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500 SORA with In Line brake levers
Pedals	Fibre reinforced Composite with Toe Clip

The Somerset's compact geometry makes for a more comfortable female-specific fit. Combined with lightweight aluminium tubing and an 18spd Shimano drivetrain you have a bike that loves the hills.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section RD-7 wheels and disc brakes that will give years of reliable all-season performance.

Ergonomic Wing handlebar, combined with tuned bar width and stem length make for a comfortable fit. In-line brake levers give more control in traffic.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47	71.5	75	507	269.0	721
49	72	74.5	515	271.5	742.5
51	72.5	74	525	271.5	776.5
53	73	73.5	535	271.5	793.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47	984.8	425	27.2	115	470
49	985	425	27.2	130	490
51	985.4	425	27.2	145	510
53	985.4	425	27.2	160	530

STIRLING

TYPICAL USAGE: URBAN/COMMUTER

SRP £999

“High quality kit on a mountain bike-style frame creates a great urban bike” **BikeRadar score** ★★★★★ 4.5/5

Cycling Plus Magazine Groupstest Winner ★★★★★



Colour	Matt Granite with Grey/Orange
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed Carbon Front Fork with Alloy Steerer Tube, Full Carbon Dropout and eyelet for Mud Guards
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	DT Champion, 2.0mm Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	SRAM S700, 11 Speed
Front Derailleur	SRAM Rival 22, 11 Speed
Rear Derailleur	SRAM Rival 22, 11 Speed
Cassette	SRAM PG-1130, 11-32, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM Rival 22, 50-34 Compact, 11 Speed
Bottom Bracket	SRAM GXP XR
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 3D Forged 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 70mm S, 80mm M, 90mm L & XL
Grips	GP1 Ergon, Dual Density
Front Brakes	Tektro Gemini, 160mm Rotor
Rear Brakes	Tektro Gemini, 160mm Rotor
Brake Levers	Tektro Gemini
Pedals	Fibre reinforced Composite Platform

The Stirling is our top of the range aluminium urban bike, boasting Tektro's powerful Gemini disc brakes and SRAM's superb Rival 22 flat bar drivetrain.

Based on our high performance mountain bike geometry, the Stirling has a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	567.9	271.5	721.5
M	70.0	73.5	595.7	271.5	753.5
L	70.0	73.0	613	271.5	785.5
XL	70.0	73.0	626.9	271.5	816.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533

STOWE RIVAL

TYPICAL USAGE:ROAD

SRP £1,999



Colour	Matt UD/Aqua
Sizes Available	51cm, 54cm, 57cm
Frame	Uni-directional Multi Monocoque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Full Carbon Front Fork with Tapered Alloy Steerer and Post Mount full carbon Dropouts
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 28 Hole
Front Hub	Whyte Alloy Double Sealed with Cartridge Bearings, 24 Hole
Spokes	DT Champion 2.0mm, Black Sandvik Stainless with Brass Nipples
Rims	Whyte Road Disk 28mm Offset Deep Section, 28 Hole Rear and 24 Front
Tyre	Maxxis Relix, 700 x 25c, 170tpi, with Silkshield Puncture Protection, Folding
Shift Levers	SRAM Rival, Full Hydraulic, 11 Speed
Front Derailleur	SRAM Rival, Yaw function with Chain Stopper, 11 Speed
Rear Derailleur	SRAM Force, 32T Max Capacity, WiFi Function, 11 Speed
Cassette	SRAM PG-1130, 11-28, 11 Speed
Chain	SRAM PC-1130
Crankset	SRAM Rival 50-34 compact, Yaw function, 11 Speed
Bottom Bracket	GXP
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 2014 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar, 400mm 51, 420mm 54, 440mm 57 & 60
Stem	Whyte -6 Deg (flipflop design), 90mm 51, 100mm 54, 110mm 57 & 60
Grips	Whyte Anti Slip with 3M Reflective logos
Front Brakes	SRAM Rival Hydraulic, 160mm Rotor
Rear Brakes	SRAM Rival Hydraulic, 160mm Rotor
Brake Levers	SRAM Rival Hydraulic
Pedals	None

Our new road platform has more aggressive geometry than the RD-7 for better aerodynamics and more speed. An 11-speed SRAM Rival groupset with hydraulic disc brakes helps seal the deal.

SRAM's new group includes a Yaw shifting crankset and WiFi rear derailleur to give the very latest in modern road bike shifting.

Up front we have a carbon bladed fork with internal hose management. A 27.2mm seat post and skinny seat stays offer added compliance for comfort.

Dropout Code	DROPWHRD
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51	72.5	73.5	540	272	750
54	73	73.5	549	272	784
57	73	73	566	274	808
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51	999	430	27.2	120	510
54	1005	430	27.2	155	540
57	1016	430	27.2	180	570

STOWE ULTEGRA

TYPICAL USAGE: ROAD

SRP £3,199



Colour	Matt UD/Aqua
Sizes Available	51cm, 54cm, 57cm
Frame	Uni-directional Multi Mono-coque with internal cable routing, Post Mount chainstay mounted disk brake and full carbon dropouts
Fork	Straight Bladed Full Carbon Front Fork with internal hose routing, Tapered Carbon Steerer, with Post Mount full carbon Dropouts
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Whyte Road Disk Carbon Wheelset, 28 Straight Pull StSt spokes, Alloy Freehub, Center-Lock hub with double sealed cartridge bearings
Front Hub	Whyte Road Disk Carbon Wheelset, 24 Straight Pull StSt spokes, Center-Lock hub with double sealed cartridge bearings
Spokes	Black Stainless Steel Spokes, DT Swiss Prolock Alloy Nipples
Rims	Whyte Road Disk Carbon, 24mm Deep, 28 Hole Rear and 24 Front
Tyre	Maxxis Relix, 700 x 25c, 170tpi, with Silkshield Puncture Protection, Folding
Shift Levers	Shimano 685, Full Hydraulic, 11 Speed
Front Derailleur	Shimano Ultegra with Chain Stopper, 11 Speed
Rear Derailleur	Shimano Ultegra, Max capacity 32T, 11 Speed
Cassette	SRAM PG-1130, 11-28, 11 Speed
Chain	FSA Team Issue, 11 Speed
Crankset	FSA SL-K, UD Carbon, EVO-386 36-52, Compact Double, 11 Speed
Bottom Bracket	EVO 386
Seatpost	FSA SL-K, UD Carbon, 27.5mm X 350mm Lg, 20mm offset.
Seat	Fi'zi:k Aliante Delta, Maganese Rail
Bar	FSA SL-K Compact, UD Carbon, 400/420/440mm
Stem	Whyte -6 Deg (flipflop design), 90mm 51, 100mm 54, 110mm 57 & 60
Grips	Whyte Anti Slip with 3M Reflective logos
Front Brakes	Shimano 785, Full Hydraulic, 160mm Rotor
Rear Brakes	Shimano 785, Full Hydraulic, 140mm Rotor
Brake Levers	Shimano 685, Full Hydraulic
Pedals	None

The Stowe Ultegra is the road bike we've all dreamt of: hydraulic brakes, a lightweight and efficient carbon frame, carbon wheels and an 11-speed drivetrain make this a bona-fide dream machine.

Shimano full hydraulic brakes are the standout spec on this bike giving all year round modulation and control in all weather conditions. However there is more to the Stowe Ultegra than just brakes, a full Shimano Ultegra groupset combined with the clever FSA Gossamer Pro EVO-386 crankset that allows a 30mm alloy axle to fit a BSA external BB shell.

Up front we have a full carbon bladed fork with internal hose management. A 27.2mm seat post and skinny seat stays combine with Whyte's own carbon rimmed low profile wheels to give a beautifully smooth and efficient ride.

Dropout Code	DROPWHRD
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
51	72.5	73.5	540	272	750
54	73	73.5	549	272	784
57	73	73	566	274	808
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
51	999	430	27.2	120	510
54	1005	430	27.2	155	540
57	1016	430	27.2	180	570

STRAWBERRY HILL

“A perfect balance between practicality and style. A sleek, everyday bike with monster capabilities”

Ride On Magazine Australia

92%

Function	38/40
Quality	38/40
Price	7/10
Appearance	9/10

SRP £599



Colour	Matt Granite with Blood Red/Grey
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Whyte Alloy, curved blade with Alloy Steerer
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Silver Stainless with Brass Nipples
Rims	Whyte Double Walled Alloy, 700c, 32 Hole
Tyre	Maxxis Roamer, 700 x 42c High Air Volume, with Kevlar Puncture Guard
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	Shimano Altus, 9 Speed
Rear Derailleur	Shimano Acera RD-T3000, 9 Speed
Cassette	Shimano HG-30, 11-34, 9 Speed
Chain	KMC HG-53, 9 Speed
Crankset	Shimano M391 Acera, 48-36-26
Bottom Bracket	Square Taper
Seatpost	Whyte 20mm Offset, 30.9mm x 350mm, 6061 Alloy, With 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, triple panel design
Bar	Whyte Swept Bar, 25.4mm, 600mm Wide, 45mm Sweep
Stem	Whyte Custom, High Rise, 20 Deg
Grips	GP1 Ergon, Swept Bar specific
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro V Brake Levers with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

Whyte's take on a stylish, comfortable, lifestyle bike. Combining the elegance of a vintage machine with a 30 speed drivetrain and a remarkably lightweight frame, we've made it even easier to get up the hills, or just to lift up the stairs when you get home.

Comfort was given top priority with the Strawberry Hill. The Whyte saddle is highly cushioned but also lightweight. The grips are specifically designed to fit your palm on a swept handle bar bike and even the brake levers have a Kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover and internal cable routing keep all the moving parts away from the rider.

Dropout Code	DROPWHLC
---------------------	----------

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	537.3	288.0	663
M	69.0	74	563	288.0	686
L	69.0	73.5	586.8	288.0	677
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	431.8
M	1079.8	445	30.9	160	457.0
L	1099.8	445	30.9	180	495.0

SUFFOLK

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £1,199



Colour	Matt Granite with Orange/Aqua
Sizes Available	52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount Chainstay Disk mount
Fork	Straight Bladed Carbon Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower and 1 1/8" upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, 32 Hole, 11 Speed
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Black/Grey, with Maxxshield Puncture Protection, Folding
Shift Levers	Shimano 105 ST-5800, 11 Speed
Front Derailleur	Shimano 105 FD-5800, 11 Speed
Rear Derailleur	Shimano 105 RD-5800, 11 Speed
Cassette	Shimano 105 CS-5800 11-32, 11 Speed
Chain	Shimano CN-600, 11 Speed
Crankset	FSA Gossamer Pro EVO-386 DB 34-50, 11 Speed, Compact Double
Bottom Bracket	FSA EVO-8681
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	TRP HyRd, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano 105 ST-5800
Pedals	Fibre reinforced Composite Platform

The Suffolk benefits from Shimano's 11-speed 105 groupset, together with a wide-ratio cassette to make getting up the hills a breeze. On the descents, powerful TRP disc brakes will slow you down.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section R-7 wheels and disc brakes will give years of reliable all-season performance.

Best in Test in the Cycling Plus "Bikes For All Seasons" group test. The Suffolk was described as a "Fantastic all-round road bike with superb hydraulic brakes"

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73	570	271.5	814.5
58	73.0	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

SUSSEX

TYPICAL USAGE: COMMUTER/ANYROAD

SRP £799



Colour	Matt Zinc with Black/Lime
Sizes Available	50,52,54,56,58
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Post Mount, Chainstay Disk mount
Fork	Straight Bladed Alloy Front Fork, Tapered Alloy Steerer with Internal Hose Routing and Post Mount Dropouts and with eyelets for Mud Guards
Rear Shock	N/A
Headset	FSA No. 42 Integrated Road, 1 1/2" lower Sealed Cartridge Bearing and 1 1/8" upper Sealed Ball Retainer
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless with Black Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, with Maxshield Puncture Protection, Black/Grey
Shift Levers	Shimano ST-3500 SORA, 9 Speed
Front Derailleur	Shimano FD-3500 SORA, 9 Speed
Rear Derailleur	Shimano RD-3500 SORA, 9 Speed
Cassette	Shimano HG-300, 11-32, 9 Speed
Chain	Shimano HG53, 9 Speed
Crankset	Shimano R345-L, 34-50, Octalink, 9 Speed, Compact Double
Bottom Bracket	Shimano BB-ES300, Octalink
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Road, 31.8mm, Compact "Wing" Bar
Stem	Whyte -6 Deg/6 Deg, 100mm 52cm, 110mm 54cm/56cm, 120mm 58cm
Grips	Whyte Anti Slip with 3M Reflective logos on tapes
Front Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Rear Brakes	Pro Max CX Mechanicals, Linear outer cables with Kevlar Reinforcement, 160mm Rotor
Brake Levers	Shimano ST-3500 SORA
Pedals	Fibre reinforced Composite with Toe Clip

Our lightweight aluminium frame offers large tyre clearances, great geometry and reliable disc braking, making it a perfect companion for big rides out in the hills.

Whether you're commuting longer distances, winter training or entering summer sportifs, the Whyte road disc range offers Cyclo Cross levels of durability with pure road speed.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with deep section offset rimmed RD-7 wheels and disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72.0	74.5	525	271.5	763.5
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73	570	271.5	814.5
58	73.0	73	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	992.9	425	27.2	130	500
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

T-129 RS

TYPICAL USAGE: TRAIL

SRP £2,750

“surefooted, very capable and a hell of a lot more fun than a 120mm 29er really should be. We love it”



“Technically tenacious, superbly balanced, exploratory entertainer with easy 29er speed.”

T-129 - highest scoring 29er in 2015 Awards



Colour	Matt Zinc with Grey/ Orange
Sizes Available	M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm Dropouts, Shimano Direct Mount hanger
Fork	Fox Float Performance 34, 29", 120mm Travel with FIT4 Damper, Tapered steerer and 15mm x 100mm Thru Axle
Rear Shock	Fox Float DPS Performance, Rebound Adjustment and 3pos Adjust Evol
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Hope EVO II with StSt Bearings, Boost 12mm X 148 mm, 11 Speed Shimano Freehub, 148mm
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub Hub 15mm X 100mm, 32 Hole
Spokes	DT Swiss Champion 2.0mm with Brass Nipples
Rims	WTB Asym i23 29" Rims with TCS System, Tubeless Ready, 32 Hole
Tyre	Maxxis Ardent TR 27.5 X 2.25" EXO Sidewall protection, Folding Front, Maxxis Ardent Race TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000, 11-42, 11 Speed
Chain	Shimano XT HG-600, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount 32T chainring, 11 Speed, Alloy with 30mm alloy axle
Bottom Bracket	RaceFace BSA 73mm
Seatpost	RockShox Reverb 125 Stealth, MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 50mm
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor, Internal Routing
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-spec II
Pedals	

The Works SCR features our single ring specific frame with mega stiff symmetrical chainstays, a full width main pivot for extended bearing life and maximised suspension performance.

The Geometry of the T-129 RS is further improved over the 2015 award winning Works SCR bike. These angles are the very latest in progressive trail geometry from Whyte.

The T-129 RS features a wish list parts pick, from Fox, Shimano, RaceFace, Hope and WTB.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	74	613.4	335	805
L	67.0 +0/-1	73.8	633.1	335	810
XL	67.0 +0/-1	73.6	652.8	335	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1176.1	430.9	30.9	100	431.8
L	1196.1	430.9	30.9	110	457.2
XL	1216.1	430.9	30.9	120	482.6

T-129S

TYPICAL USAGE: TRAIL/XC

SRP £2,199



Colour	Matt Apple with Grey/Denim
Sizes Available	S,M,L,XL
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube, Intergrated seat clamp system and alloy rear Triangle with Maxle 148 dropouts
Fork	RockShox Revelation RL 29", RL, 120mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle Lite
Rear Shock	RockShox Monarch Debonair, RT, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub Boost 12mm X 148mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 100mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB Asym i23 29" Rims with TCS System, Tubeless Ready, 32 Hole
Tyre	WTB Trail Boss, TCS Light Fast Rolling, 29" X 2.25", Folding Front, WTB Nineline, TCS Light Fast Rolling, 29" X 2.0", Folding Rear
Shift Levers	SRAM GX MMX Matchmaker, 10 Speed
Front Derailleur	SRAM GX, High Direct Mount, 10 Speed
Rear Derailleur	SRAM GX, Type 2, 10 speed
Cassette	SRAM PG-1030 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM GX S1000 GXP, 22/36, Compact Double, 10 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	RockShox Reverb 125mm Stealth, MMX Matchmaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S, 50mm M/L/XL
Grips	Whyte Lock-on
Front Brakes	SRAMDB5, 180mm Rotor, Internal Routing
Rear Brakes	SRAM DB5, 160mm Rotor, Internal Routing
Brake Levers	SRAM DB5 MMX Matchmaker
Pedals	None

The entry point to the T-129 range features a Rockshox Reverb Stealth seatpost and Whyte's integrated "Intergrip" seat post system. This neat solution gives the T-129S a clean look and fantastic weather proofing.

The Geometry of the T-129S is further improved over the 2015 award winning Works SCR bike and these angles are the very latest in progressive trail geometry from Whyte.

Our Quad 4 suspension layout allows us to apply our contemporary 29er geometry to the 120mm suspension Trail bike category. Short chainstays give this bike the agility of a 27.5" wheel bike but with the inertia and terrain flattening advantages of a larger 29er wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	74.2	593.4	335	800
M	67.0 +0/-1	74	613.4	335	805
L	67.0 +0/-1	73.8	633.1	335	810
XL	67.0 +0/-1	73.6	652.8	335	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1156.1	430.9	30.9	100	406.4
M	1176.1	430.9	30.9	100	431.8
L	1196.1	430.9	30.9	110	457.2
XL	1216.1	430.9	30.9	120	482.6

T-130C RS

TYPICAL USAGE: TRAIL

SRP 3499



Colour	Orange with Grey/Denim
Sizes Available	M, L, XL
Frame	Uni-directional Multi Monocoque Front Triangle with internal cable routing, Tapered Head Tube and Intergrip integrated seat clamp system with alloy symmetrical SCR rear Triangle, 148mm Dropouts
Fork	RockShox Pike RC, 27.5", 130mm Travel, Fast Black coating, tapered steerer and Boost 110mm X 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	SRAM Roam 40, Boost 12 x 148mm
Front Hub	SRAM Roam 40, Boost 15 x 110mm
Spokes	SRAM Roam 40, St:St Butted
Rims	SRAM Roam 40, 21mm wide 27.5", Full UST welded Rims
Tyre	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Ardent Race TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM X-1, Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X-0, 11 Speed Carbon
Cassette	SRAM XG-1180 10-42, 11 Speed
Chain	SRAM PCX1, 11 Speed
Crankset	SRAM X1-1000 GXP, XSYNC direct mount 32T chainring, 11 Speed Alloy
Bottom Bracket	SRAM GXP Team 73mm
Seatpost	RockShox Reverb 125 Stealth, MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S, 50mm M/L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor, Internal Routing
Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, Matchmaker
Pedals	None

The T-130 C RS features our new single ring specific Carbon frame, a full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

The T130 C is designed to be a full suspension version of our award winning 900 series hardtails. 130mm travel front and rear and a long and low geometry will give you full trail control.

SRAM Roam 40 Boost Wheels feature wide, offset welded UST Tubeless rims and are combined with Maxxis TR tyres to give exceptional levels of control. Boost 148mm rear and 110mm front hubs have 10mm wide flange spacing creating a stiffer wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	73.5	611.1	331.0	766
L	67.0 +0/-1	73.3	631	331.0	776
XL	67.0 +0/-1	73.2	650.7	331.0	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420.0	30.9	115	431.8
L	1176.5	420.0	30.9	120	457.2
XL	1196.5	420.0	30.9	130	482.6

T-130C WORKS

TYPICAL USAGE:TRAIL

SRP 4499



Colour	Matt Orange with Black/Denim
Sizes Available	M, L, XL
Frame	Uni-directional Multi Monocoque Front Triangle with internal cable routing, Tapered Head Tube and Intergrip seat clamp with alloy symmetrical SCR rear Triangle, 148mm Dropouts, Shimano Direct Mount hanger
Fork	Fox Float Factory 34, 27.5", 130mm Travel with FIT4 Damper, Tapered steerer, Kashima Coating and 15mm x 100mm Thru Axle
Rear Shock	Fox Float DPS Factory, Kashima, Rebound Adjustment and 3pos Adjust Evol
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte Cartridge sealed bearing, 28H, Boost 12mm X 148mm with Micro Engagement 6 Pawl Shimano Free Hub
Front Hub	Whyte Cartridge sealed Bearing, 28H, 15mm x 100mm
Spokes	DT Comp RACE 2.0mm with 14mm Brass Nipples
Rims	Whyte 30mm Carbon Hookless, 28H, Tubeless Ready, 3M Rim strip with Tubeless valve included
Tyre	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Ardent Race TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000 11-42, 11 Speed
Chain	Shimano HG-600, 11 Speed
Crankset	RaceFace Next Carbon Clinch, direct mount 32T chainring, 11 Speed, Alloy with 30mm alloy axle
Bottom Bracket	RaceFace BSA
Seatpost	RockShox Reverb 125 Stealth, MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	RaceFace SIXC Carbon, 760mm wide, 20mm rise
Stem	Whyte Gravity Stem, 40mm S, 50mm M/L/XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor, Internal Routing
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-Spec II
Pedals	None

The T-130 C Works features our new single ring specific Carbon frame, a full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

The T130 is designed to be a full suspension version of our award winning 900 series hardtails. 130mm travel front and rear and a long and low geometry will give you full trail control.

A wish list spec combines Shimano's new XT M8000 Shifting with the multi award winning RaceFace Next Carbon Crank, Shimano XT brakes with Whyte all new 30mm wide Carbon Hookless/Tubeless wheels set and to keep it all under control Whyte geometry combines with a Whyte short stem and a RaceFace SIXC carbon bar.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	73.5	611.1	331.0	766
L	67.0 +0/-1	73.3	631	331.0	776
XL	67.0 +0/-1	73.2	650.7	331.0	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420.0	30.9	115	431.8
L	1176.5	420.0	30.9	120	457.2
XL	1196.5	420.0	30.9	130	482.6

T-130 RS

TYPICAL USAGE: TRAIL

SRP £2,750

“agile, forgiving, playful - and fun”
Australian Mountainbike Magazine

AUSTRALIAN MOUNTAIN BIKE
AMB

“the best Whyte full-sus to date.”
MBR Magazine



Colour	Matt Granite with Lime/Magenta
Sizes Available	S, M, L, XL
Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm dropouts, Shimano Direct Mount hanger
Fork	RockShox Pike RC, 27.5", 130mm Travel, Fast Black coating, tapered steerer and Boost 110mm X 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	SRAM Roam 30, Boost 12 x 148mm
Front Hub	SRAM Roam 30, Boost 15 x 110mm
Spokes	SRAM Roam 30, StSt Butted
Rims	SRAM Roam 30, 21mm wide 27.5", Full UST Rims
Tyre	WTB Trail Boss, 27.5" X 2.25" TCS, 60TPI Folding
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000 11-42, 11 Speed
Chain	Shimano XT HG600, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount 32T chainring, 11 Speed, Alloy with 30mm alloy axle
Bottom Bracket	RaceFace BSA
Seatpost	RockShox Reverb 125 Stealth, MatchMaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S, 50mm M/L/XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor, Internal Routing
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-spec II
Pedals	None

The T-130 RS features our SCR single ring specific frame with mega stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

The T130 is designed to be a full suspension version of our award winning 900 series hardtails. 130mm travel front and rear and a long and low geometry will give you full trail control.

SRAM Roam 30 Boost Wheels feature wide, offset UST Tubeless rims and are combined with WTB TCS tyres to give exceptional levels of control. Boost 148mm rear and 110mm front hubs have 10mm wide flange spacing creating a stiffer wheel.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	73.7	591.4	331.0	763
M	67.0 +0/-1	73.5	611.1	331.0	766
L	67.0 +0/-1	73.3	631	331.0	776
XL	67.0 +0/-1	73.2	650.7	331.0	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136.5	420.0	30.9	107	406.4
M	1156.5	420.0	30.9	115	431.8
L	1176.5	420.0	30.9	120	457.2
XL	1196.5	420.0	30.9	130	482.6

T-130S

TYPICAL USAGE: TRAIL

SRP £2,299



Colour	Matt Orange with Black/Denim
Sizes Available	S,M,L,XL
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCR rear Triangle, 148mm dropouts
Fork	RockShox Revelation 27.5", RL, 130mm Travel, Fast Black coating, Tapered steerer and 15mm Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Boost 12mm X 148mm Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 100mm, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB Asym i23 27.5" Rims with TCS System, Tubeless Ready
Tyre	WTB Trail Boss, TCS Light Fast Rolling 27.5" X 2.25", Folding
Shift Levers	SRAM GX MMX Matchmaker, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM PG-1175 10-42, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM GX S1000 GXP, 30T, 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	RockShox Reverb 125mm Stealth, MMX Matchmaker, 30.9 X 380mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S/M, 50mm L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM DB5, 180mm Rotor, Internal Routing
Rear Brakes	SRAM DB5, 160mm Rotor, Internal Routing
Brake Levers	SRAM DB5 MMX Matchmaker
Pedals	None

For 2016 the trickle-down technology reaches true affordability. Using Whyte's SCR frame, SRAM's new 1 by 11 GX group and the Stealth Reverb the T-130S is the new UK Trail Bike benchmark.

The geometry of the T-130 has been adjusted to accommodate a shorter stem for 2016 giving the bike some of the most progressive geometry in this category and very similar to the award winning 900 series trail hardtails.

A low slung shock gives the T130 plenty of stand-over height and suspension kinematics that make the bike really "pump" through your favourite singletrack.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	73.7	591.4	331.0	763
M	67.0 +0/-1	73.5	611.1	331.0	766
L	67.0 +0/-1	73.3	631	331.0	776
XL	67.0 +0/-1	73.2	650.7	331.0	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136.5	420.0	30.9	107	406.4
M	1156.5	420.0	30.9	115	431.8
L	1176.5	420.0	30.9	120	457.2
XL	1196.5	420.0	30.9	130	482.6

T-130 SX

TYPICAL USAGE: TRAIL

SRP £1,899



Colour	Magenta with Black/Aqua
Sizes Available	XS,S,M,L
Frame	6061 T6 Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy rear Triangle with 12mm E-Thru 142 dropouts, Shimano Direct Mount hanger
Fork	SR Suntour Aion LO-R 27.5" CTS, 130mm Travel, Tapered steerer and 15GR
Rear Shock	Fox Float DPS Performance, Rebound Adjustment and 3pos Evol
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Alloy, Double Sealed Cartridge Bearing Hub, Boost 12mm X 142mm Through Axle, 32
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
Rims	WTB Asym i23 27.5" TCS System, Tubeless Ready, 32 Hole
Tyre	WTB Trail Boss, TCS Light Fast Rolling 27.5" X 2.25", Folding Front, WTB Beeline, TCS Light Fast Rolling 27.5" X 2.2", Folding Rear
Shift Levers	Shimano SLX, I-Spec, 10 Speed, Black
Front Derailleur	Shimano Deore M-618, High Direct Mount, 10 Speed, Black
Rear Derailleur	Shimano XT M-786, Shadow Plus, 10 Speed, Direct Mount
Cassette	Shimano HG81 11-36, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	RaceFace Ride, 22/36, 10 Speed, Compact Double
Bottom Bracket	Race Face BSA 24mm
Seatpost	KS LEV-Integra, Dropper Post with KG remote, 30.9 X 342mm, 100mm travel
Seat	Whyte Custom, dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm XS/S, 50mm M/L
Grips	Whyte Lock-on
Front Brakes	TRP Slate T4, Four Pot, I-spec, 180mm Rotor, Internal Routing
Rear Brakes	TRP Slate T4, Four Pot, I-spec, 160mm Rotor, Internal Routing
Brake Levers	TRP Slate, I-Spec
Pedals	None

Our entry level 130mm travel 650b bike is available all the way down to an extra small size, so the broadest possible spread of riders can benefit from this great platform.

WTB Asym i23 TCS rims and TCS tyres give a Tubeless ready wheelset which when combined with the SR Aion fork and the all new Fox Float DPS double chamber rear shock gives the SX the ability to tame your favourite trails.

Internal routing keeps cables and hoses out of harms way and with our new rubberised frame grommets it's totally water tight.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67.0 +0/-1	74	571.7	331	761
S	67.0 +0/-1	73.7	591.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1116.5	420	30.9	100	368.3
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2

VICTORIA COMPACT-FIT

TYPICAL USAGE: URBAN/COMMUTER

SRP £699



Colour	Matt Granite with Grey/Aqua
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork with Forged crown, Post mount with Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep, Offset Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Maxxis Rouler, 700 x 28c, Folding Black/Aqua, with Puncture Protection
Shift Levers	Shimano Sora SL-3500, 9 Speed
Front Derailleur	Shimano Sora FD-R3500, 9 Speed
Rear Derailleur	Shimano Sora RD-3500, 9 Speed
Cassette	Shimano HG-200, 11-32 9 Speed
Chain	Shimano HG-53, 9 Sped
Crankset	Shimano FC-R345-L, Double 50-34, 9 Speed, Octalink
Bottom Bracket	Shimano, Octalink BB-ES300
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom Women's Fit, Triple Panel Design
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S, 70mm M, 80mm L
Grips	Whyte double Density, Lock-on
Front Brakes	Tektro Auriga 160mm Rotor
Rear Brakes	Tektro Auriga 160mm Rotor
Brake Levers	Tektro Auriga WS
Pedals	Fibre reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x9spd Shimano drivetrain.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	546.5	271.5	737.5
M	69.5	73.5	572.1	271.5	740.5
L	70	73	598.3	271.5	772.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1040.2	420	27.2	140	393.7
M	1052.2	420	27.2	160	431.8
L	1069.2	420	27.2	180	469.9

WHITECHAPEL

TYPICAL USAGE: URBAN/COMMUTER

SRP £550



Colour	Matt Zinc with Grey/Lime
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Custom Drawn, Multi Butted with Custom Whyte Dropouts
Fork	Straight Bladed 6061 T6 Alloy Front Fork with Forged crown, Post mount with Single Eyelets
Rear Shock	N/A
Headset	FSA No. 23 Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Disk Road 32mm Deep Section Rim, 32 Hole Rear and 28 Front, 3M Reflective Decals
Tyre	Vittoria Zaffiro, 700 x 28c, Black, with Puncture Protection
Shift Levers	Shimano Altus, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Acera RD-M3000, 9 Speed
Cassette	Shimano HG-200-9, 11-34 9 Speed
Chain	KMC CN-HG53, 9 Speed
Crankset	Lasco 42T, with Alloy Chain Guard
Bottom Bracket	FSA Square Taper
Seatpost	Whyte 20mm Offset, 27.2mm x 350mm, 1pcs 3D Forged 6061 Alloy, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte Narrow, 31.8mm, 30mm Rise, 580mm Wide
Stem	Whyte, 60mm S, 70mm M, 80mm L, 90mm XL
Grips	Whyte Custom with extra-thick bar plugs
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor
Brake Levers	Tektro Auriga
Pedals	Fibre reinforced Composite Platform

The Whitechapel is all about simplicity: a single chain ring and nine gears at the back will give years of urban use, and by placing the disc brake caliper inside the rear triangle, adding mudguards or a rack couldn't be easier.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Recommended Mudguards	WHYMG38

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.5	74.0	567.9	271.5	721.5
M	70.0	73.5	595.7	271.5	753.5
L	70.0	73.0	613	271.5	785.5
XL	70.0	73.0	626.9	271.5	816.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1047.8	420	27.2	145	406.4
M	1079.2	420	27.2	165	444.5
L	1094.1	420	27.2	185	495
XL	1109.3	420	27.2	205	533