

# G-170 S

G-170 Gravity Enduro Suspension - 170mm

SRP - £2,399

Product Code - WG170S(size)V1



Colour	Matt Midnight with Dark Red/Pewter/Grey
Sizes Available	S,M,L,XL
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Yari RC 27.5", 180mm Travel, 37mm Offset, DebonAir, Charger Dampers, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe R, DebonAir, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Convict TCS System 27.5" X 2.5" Light/High Grip, Front, WTB Trail Boss G2 TCS System 27.5" X 2.4" Light/Fast Rolling, Rear
Shift Levers	SRAM NX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 30T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it Post, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, 200mm Rotor
Rear Brakes	SRAM Guide T, 4 Pot, 200mm Rotor, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

The G-170 S scored a perfect 10/10 with MBR in 2018. The new model features a shorter 37mm offset and a 180mm travel fork to make this bike even more capable and ready to take on anything you throw at it.

The S is loaded with the very latest developments in Enduro/Trail bikes. WTB ST i29mm 2.0 rims combined with TCS front and rear specific tyres help to give neutral handling without too much drag.

The G-170 S has extra width built into the rear chainstays allowing the rider to fully exploit future developments in wide high volume tyres up to 27.5 x 2.8" and maintain mud clearance.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	75	583	337.5	840
M	64.5	75	603	337.5	844
L	64.5	75	628	337.5	869
XL	64.5	75	652	337.5	875

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1200	435	30.9	110	406.4
M	1221	435	30.9	120	431.8
L	1245	435	30.9	130	457.2
XL	1271	435	30.9	135	482.6

# G-170C RS 29ER

G-170 Gravity Enduro Suspension - 170mm

SRP - £3,750

Product Code - WG170CRS(size)V1



Colour	Matt Granite with Silver/Grey
Sizes Available	S,M,L
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	RockShox Lyrik RC 29", 160mm Travel, 42mm Offset, DebonAir, Charger 2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Super Deluxe RCT, DebonAir, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, Micro Engagement 6 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	RaceFace AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF WT, TR, 29" x 2.5" 60TPI, EXD Sidewall Protection, 3C Maxx Terra, Dual Compound, Folding Bead, Front, Maxxis Aggressor WT, TR, 29" x 2.5" 120TPI, Double Down Casing with Butyl Inserts, Dual Compound, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 7K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, S 125mm Travel, M/L 150mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Code R, 4 Pot with Sintered metal pads, 200mm Rotor
Rear Brakes	SRAM Code R, 4 Pot with Sintered metal pads, 200mm Rotor, Internal Routing
Brake Levers	SRAM Code R, MMX
Pedals	None

The RS uses the same highly developed frame as the Works bike, as used by our International EWS race team. This year we've gone big - the 29er wheels make this the fastest Gravity bike we've ever created.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its open front triangle design it is possible to fit various options of rear shock including coil shocks and still carry a full size water bottle.

The G-170C RS 29er has extra width built into the rear chainstays allowing the rider to fully exploit future developments in wide high volume tyres up to up to 29 x 2.5" and maintain mud clearance.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.3	75	585	349.0	840
M	64.3	75	604	349.0	844
L	64.3	75	629	349.0	869
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1205	435	30.9	110	406.4
M	1225	435	30.9	120	431.8
L	1250	435	30.9	130	457.2

# G-170C WORKS

G-170 Gravity Enduro Suspension - 170mm

SRP - £5,250

Product Code - WG170CW(size)V1



Colour	Matt Petrol with Lime/Mist/Grey
Sizes Available	S,M,L
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	RockShox Lyrik RC2 27.5", 180mm Travel, 37mm Offset, DebonAir, Charger 2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Super Deluxe, DebonAir, RCT, Fast Black Coating, Adjustable Rebound, 2 position low speed compression adjustment
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples
Rims	Whyte 30mm Carbon Hookless, Offset, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included, 28 Hole
Tyres	Maxxis Minion DHF WT, TR, 27.5" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Dual Compound, Front, Maxxis Aggressor WT, TR, 27.5" x 2.5" 120TPI, Double Down Casing with Butyl Inserts, Dual Compound, Rear
Shift Levers	SRAM XO1 Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XO1 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant Carbon Eagle, X-SYNC 2, Direct Mount 34T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	RockShox Reverb Stealth, 30.9mm, S 125mm Travel, M/L 150mm Travel, X1 Remote
Seat	Whyte Custom, Team, Lightweight Foam, CrMo Rails, Triple Panel
Bar	RaceFace NEXT R Carbon, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	RaceFace Turbine, 35mm Bar Bore, 32mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Code RSC, 4 Pot with Sintered metal pads, 200mm Rotor
Rear Brakes	SRAM Code RSC, 4 Pot with Sintered metal pads, 200mm Rotor, Internal Routing
Brake Levers	SRAM Code RSC, MMX
Pedals	None

This bike will not only be raced by our Gravity Enduro team - it was actually designed in conjunction with them. Their input to the geometry, combined with the new carbon front triangle and oversize hardware, adds up to a very stiff and capable chassis.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its open front triangle design it is possible to fit various options of rear shock including coil shocks and still carry a full size water bottle.

The G-170C Works has extra width built into the rear chainstays allowing the rider to fully exploit future developments in wide high volume tyres up to 27.5 x 2.8" and maintain mud clearance.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	75	583	337.5	840
M	64.5	75	603	337.5	844
L	64.5	75	628	337.5	869

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1200	435	30.9	110	406.4
M	1221	435	30.9	120	431.8
L	1245	435	30.9	130	457.2

# G-170C WORKS 29ER

G-170 Gravity Enduro Suspension - 170mm

SRP - £5,250

Product Code - WG170CWT(size)V1



Colour	Matt Petrol with Lime/Mist/Grey
Sizes Available	S,M,L
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	RockShox Lyrik RC2 29", 160mm Travel, 42mm Offset, DebonAir, Charger 2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Stealth
Rear Shock	RockShox Super Deluxe, Coil, RCT, Fast Black Coating, Adjustable Rebound, 2 position low speed compression adjustment
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples
Rims	Whyte 30mm Carbon Hookless, Offset, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included, 28 Hole
Tyres	Maxxis Minion DHF WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Dual Compound, Folding Bead, Front, Maxxis Aggressor WT, TR, 29" x 2.5" 120TPI, Double Down Casing with Butyl Inserts, Dual Compound, Rear
Shift Levers	SRAM XO1 Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XO1 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, Black, 12 Speed
Crankset	SRAM XO1 Carbon Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	RockShox Reverb Stealth, 30.9mm, S 125mm Travel, M/L 150mm Travel, X1 Remote
Seat	Whyte Custom, Team, Lightweight Foam, CrMo Rails, Triple Panel
Bar	RaceFace NEXT R Carbon, 10mm Rise, 35mm Bar Bore, 800mm Wide
Stem	RaceFace Turbine, 35mm Bar Bore, 32mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Code RSC, 4 Pot with Sintered metal pads, 200mm Rotor
Rear Brakes	SRAM Code RSC, 4 Pot with Sintered metal pads, 200mm Rotor, Internal Routing
Brake Levers	SRAM Code RSC, MMX
Pedals	None

When the Whyte Gravity Enduro team are not racing the 27.5" bike it's because they are riding the 29er version. The G-170 was always designed with both wheel sizes in mind - this modularity gives us the ability to offer both wheel sizes to suit your style.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. With its open front triangle design it is possible to fit various options of rear shock including coil shocks and still carry a full size water bottle.

The G-170C Works 29er has extra width built into the rear chainstays allowing the rider to fully exploit future developments in wide high volume tyres up to up to 29 x 2.5" and maintain mud clearance.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.3	75	585	349.0	840
M	64.3	75	604	349.0	844
L	64.3	75	629	349.0	869

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1205	435	30.9	110	406.4
M	1225	435	30.9	120	431.8
L	1250	435	30.9	130	457.2



# S-150 S

S-150 Trail/Enduro Suspension - 150mm

SRP - £2,699

Product Code - WS150S(size)V1



Colour	Matt Petrol with Reef/Orange/Sky
Sizes Available	S,M,L,XL
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Revelation RC 29", 150mm Travel, 42mm Offset, DebonAir, Charger Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	RockShox Deluxe R, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 29" x 2.3" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 29" x 2.4" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM GX Eagle MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM PG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, S 125mm Travel, M/L 150mm Travel, XL 175mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide (XL 30mm Rise)
Stem	Whyte Gravity Stem, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, S/M 180mm, L/XL 200mm Rotor
Rear Brakes	SRAM Guide T, 4 Pot, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

Latest generation Whyte geometry, 150mm of travel and 29er wheels make this trail bike fast and controllable in every situation. A wide main pivot with oversize hardware is a perfect way to get the power down.

The S-150 was built around the SRAM Eagle concept. With its huge 500% gear range Eagle GX helps you make the most of the S 150 S - both in the speed it climbs and the ability to get pedal strokes in, as well as a big top gear for the descents.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. Our wheel kits switch into your bike in the time it takes to go back to your car and change the Eagle cassette.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	602	341.5	836.5
M	65.6	75	623	341.5	837.5
L	65.6	75	640	341.5	862.5
XL	65.6	75	659	341.5	868.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1190	435	30.9	100	406.4
M	1211	435	30.9	110	431.8
L	1228	435	30.9	120	457.2
XL	1248	435	30.9	130	482.6

# S-150C RS

S-150 Trail/Enduro Suspension - 150mm

SRP - £3,499

Product Code - WS150CRS(size)V1



Colour	Matt Granite with Lime/Olive/Grey
Sizes Available	M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	RockShox Pike RC 29", 150mm Travel, 42mm Offset, DebonAir, Charger 2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, Micro Engagement 6 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon WT, TR 29" x 2.3" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 7K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, M/L 150mm Travel, XL 175mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide (XL 30mm Rise)
Stem	Whyte Gravity Stem, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide R, 4 Pot, M 180mm, L/XL 200mm Rotor
Rear Brakes	SRAM Guide R, 4 Pot, 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX
Pedals	None

With its sculpted carbon front triangle the RS certainly looks the part - add Whyte OTO geometry, Eagle GX, the fantastic Rockshox Pike and Deluxe suspension and you'll understand why this multi-award winning model sets the pace.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. Our wheel kits switch into your bike in the time it takes to go back to your car and change the Eagle cassette.

Maxxis 3C compound is peerless in the level of front end grip it provides. The 29mm wide rims create a stable bead platform for these tyres so you can push them right to the limit.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65.6	75	623	341.5	837.5
L	65.6	75	640	341.5	862.5
XL	65.6	75	659	341.5	868.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1211	435	30.9	110	431.8
L	1228	435	30.9	120	457.2
XL	1248	435	30.9	130	482.6

# S-150C WORKS

S-150 Trail/Enduro Suspension - 150mm

SRP - £4,999

Product Code - WS150CW(size)V1



Colour	Matt Lime with Eucalyptus/Olive/Grey
Sizes Available	M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	RockShox Pike RCT3 29", 150mm Travel, 42mm Offset, DebonAir, Charger 2 Damper with 3-Pos Compression Adjust, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe RT3, DebonAir, Fast Black Coating, Adjustable Rebound and 3 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples
Rims	Whyte 30mm Carbon Hookless, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included, 28 Hole
Tyres	Maxxis High Roller II WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Aggressor WT, TR, 29" x 2.5" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM XD1 Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant Carbon Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	RockShox Reverb Stealth, 30.9mm, M/L 150mm Travel, XL 170mm Travel, X1 Remote
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	RaceFace NEXT R Carbon, 10mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide RSC, 4 Pot, M 180mm, L/XL 200mm Rotor
Rear Brakes	SRAM Guide RSC, 4 Pot, 180mm Rotor
Brake Levers	SRAM Guide RSC, MMX
Pedals	None

Our Whyte Enduro team have a secret weapon - the S-150 Works is their bike of choice for the more all-round events. And it's a winner too, with Martyn Brookes' victory at the Master's National Championships in his very first race on this outstanding all-round bike.

There is a wish list spec on the Works, but stand-outs must include the 30mm hookless Whyte carbon rims hand-laced onto Hope Pro4 hubs, the XX1 Reverb with under-the-bar paddle lever and the RockShox suspension.

S stands for Switch - the ability to fit 650b wheels with 2.8" tyres and still have UK levels mud clearance. Our wheel kits switch into your bike in the time it takes to go back to your car and change the Eagle cassette.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65.6	75	623	341.5	837.5
L	65.6	75	640	341.5	862.5
XL	65.6	75	659	341.5	868.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1211	435	30.9	110	431.8
L	1228	435	30.9	120	457.2
XL	1248	435	30.9	130	482.6

# T-130 SR

T-130 Trail Suspension - 130mm

SRP - £2,299

Product Code - WT130SR(size)V1



Colour	Matt Petrol with Reef/Orange/Sky
Sizes Available	XS,S,M,L,XL
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	Fox Performance 34 27.5", 140mm Travel, 37mm Offset, GRIP 3-Pos Damper, Black Coating, Tapered Steerer, 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox Float DPS, Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol LV
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	Shimano SLX M7000, I-Spec B, 11 Speed, Black
Front Derailleur	N/A
Rear Derailleur	Shimano SLX RD-M7000-SGS, Shadow Plus, Direct Mount, 11 Speed
Cassette	Sunrace CSMS8, 11-46, 11 Speed
Chain	Shimano HG601, 11 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow Wide Chaining, 170mm, Boost, 11 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte drop.it Post, 30.9mm, XS 100mm Travel, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, M/L/XL 780mm Wide (L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	TRP Slate, 4 Pot, 180mm Rotor
Rear Brakes	TRP Slate, 4 Pot, XS/S 160mm, M/L/XL 180mm Rotor, Internal Routing
Brake Levers	TRP Slate, I-Spec II
Pedals	None

The new T-130 takes the playful, do-it-all attitude of its award-winning predecessor and massively updates it with more capable suspension, latest generation Whyte OTO geometry and sleeker packaging.

The T-130 geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities for the new chassis, the more neutral handling and the 2.6" tyres.

The SR is our most affordable spec, combining Fox Performance suspension with a Shimano based 11 speed drive-train - the result is a massively capable spec for an affordable price.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	65.6	75	554	330.0	788
S	65.6	75	583	330.0	796
M	65.6	75	612	330.0	802
L	65.6	75	640	330.0	808
XL	65.6	75	669	330.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1134	430	30.9	100	368.3
S	1163	430	30.9	112	406.4
M	1193	430	30.9	125	431.8
L	1222	430	30.9	140	457.2
XL	1251	430	30.9	150	482.6



# T-130 S

T-130 Trail Suspension - 130mm

SRP - £2,650

Product Code - WT130S(size)V1



Colour	Matt Midnight with Pewter/Dark Red
Sizes Available	XS,S,M,L,XL
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Revelation RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM PG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, XS 100mm Travel, S 125mm Travel, M/L/XL 150mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, M/L/XL 780mm Wide (L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide T, 4 Pot, XS/S 160mm, M/L/XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

The new T-130 takes the playful, do-it-all attitude of its award-winning predecessor and massively updates it with more capable suspension, latest generation Whyte OTO geometry and sleeker packaging.

The T-130 geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities for the new chassis, the more neutral handling and the 2.6" tyres.

The Eagle GX groupset is fitted to the T-130 giving it all the benefits of their massive 500% gear range and allowing Whyte to increase the chain ring size without sacrificing the lower gearing size.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	65.6	75	554	330.0	788
S	65.6	75	583	330.0	796
M	65.6	75	612	330.0	802
L	65.6	75	640	330.0	808
XL	65.6	75	669	330.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1134	430	30.9	100	368.3
S	1163	430	30.9	112	406.4
M	1193	430	30.9	125	431.8
L	1222	430	30.9	140	457.2
XL	1251	430	30.9	150	482.6

# T-130C R

T-130 Trail Suspension - 130mm

SRP - £3,050

Product Code - WT130CR(size)V1



Colour	Matt Petrol with Lime/Mist/Grey
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Revelation RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM NX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM NX-1230 Eagle, 11-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, M/L/XL 780mm Wide (L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide T, 4 Pot, S 160mm Rotor, M/L/XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

The new T-130 takes the playful, do-it-all attitude of its award-winning predecessor and massively updates it with more capable suspension, latest generation Whyte OTO geometry and sleeker packaging.

The T-130 geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities for the new chassis, the more neutral handling and the 2.6" tyres.

With a brand new carbon frame, the T-130 C R brings our best and latest frame to you at an affordable price. We have used the new NX Eagle drive-train combined with RockShox's excellent Revelation Fork with Debonair and Charger damper.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	583	330.0	796
M	65.6	75	612	330.0	802
L	65.6	75	640	330.0	808
XL	65.6	75	669	330.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1163	430	30.9	112	406.4
M	1193	430	30.9	125	431.8
L	1222	430	30.9	140	457.2
XL	1251	430	30.9	150	482.6

# T-130C RS

T-130 Trail Suspension - 130mm

SRP - £3,499

Product Code - WT130CRS(size)V1



Colour	Matt Lime with Eucalyptus/Olive/Grey
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Pike RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger 2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, Micro Engagement 6 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	RaceFace AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 7K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS LEV-Integra, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Southpaw-Alloy Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, M/L/XL 780mm Wide (L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide RS, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide RS, 4 Pot, S 160mm Rotor, M/L/XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, MMX
Pedals	None

The new T-130 takes the playful, do-it-all attitude of its award-winning predecessor and massively updates it with more capable suspension, latest generation Whyte OTO geometry and sleeker packaging.

The T-130 geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates, allows us to make the most of the 140mm travel fork, fully exploiting the capabilities for the new chassis, the more neutral handling and the 2.6" tyres.

SRAM's Eagle GX 12 speed drive-train is used on the T-130 C RS. This 500% range 10-50 cassette allows the chainring to be increased to 32t, giving both top and bottom range improvement.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	583	330.0	796
M	65.6	75	612	330.0	802
L	65.6	75	640	330.0	808
XL	65.6	75	669	330.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1163	430	30.9	112	406.4
M	1193	430	30.9	125	431.8
L	1222	430	30.9	140	457.2
XL	1251	430	30.9	150	482.6

# T-130C WORKS

T-130 Trail Suspension - 130mm

SRP - £5,250

Product Code - WT130CW(size)V1



Colour	Matt Granite with Silver/Grey
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube and Intergrip Seat Clamp System, ISCG 5 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	RockShox Pike RCT3 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger 2 Damper with 3-Pos Compression Adjust, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe RT3, DebonAir, Fast Black Coating, Adjustable Rebound and 3 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples
Rims	Whyte 30mm Carbon Hookless, Tubeless Ready, 3M Rim Strip with Tubeless Valves Included, 28 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM XX1 Gold Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1 Eagle Gold, 12 Speed
Cassette	SRAM XG-1299 Eagle Gold, 10-50, 12 Speed
Chain	SRAM XX1 Gold Eagle, 12 Speed
Crankset	SRAM XX1 Eagle Gold Carbon, X-SYNC 2, Direct Mount 34T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	RockShox Reverb Stealth, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, X1 Remote
Seat	Whyte Custom, Team, Lightweight Foam, CrMo Rails, Triple Panel Design
Bar	RaceFace NEXT R Carbon, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide RSC, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide RSC, 4 Pot, M/L/XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide RSC, MMX
Pedals	None

The new T-130 takes the playful, do-it-all attitude of its award-winning predecessor and massively updates it with more capable suspension, latest generation Whyte OTO geometry and sleeker packaging.

The T-130 geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates, allows us to make the most of the 140mm travel fork, fully exploiting the capabilities for the new chassis, the more neutral handling and the 2.6" tyres.

The Works bike gets a wish-list spec on our best and latest Whyte frame, creating what is for us, the ultimate trail bike.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	583	330.0	796
M	65.6	75	612	330.0	802
L	65.6	75	640	330.0	808
XL	65.6	75	669	330.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1163	430	30.9	112	406.4
M	1193	430	30.9	125	431.8
L	1222	430	30.9	140	457.2
XL	1251	430	30.9	150	482.6



# S-120C R

S-120 XC/Trail Suspension - 120mm

Guide UK SRP - £3,100

Product Code - WS120CR(size)V1



<b>Colour</b>	Matt Zinc with Grey/Lime/Black
<b>Sizes Available</b>	S,M,L,XL
<b>Frame</b>	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
<b>Fork</b>	RockShox Revelation RC 29", 120mm Travel, 42mm Offset, DebonAir, Charger Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
<b>Rear Shock</b>	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
<b>Headset</b>	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
<b>Spokes</b>	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
<b>Rims</b>	WTB ST i29 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
<b>Tyres</b>	Maxxis Forecaster TR 29" x 2.35" 60TPI Dual Compound, EXO Sidewall Protection, Front, Maxxis Crossmark II TR 29" x 2.25" 60TPI Dual Compound, EXO Sidewall Protection, Rear
<b>Shift Levers</b>	SRAM NX Eagle, Matchmaker, 12 Speed
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	SRAM NX Eagle, 12 Speed
<b>Cassette</b>	SRAM PG-1230 Eagle, 11-50, 12 Speed
<b>Chain</b>	SRAM Eagle, 12 Speed
<b>Crankset</b>	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, Boost, 12 Speed
<b>Bottom Bracket</b>	SRAM DUB, BSA, 73mm
<b>Seatpost</b>	Bike Yoke Devine, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Trigger Remote with MMX attachment
<b>Seat</b>	Whyte Custom Dual Density
<b>Bar</b>	Whyte 6061 Alloy, 15mm Low Rise, 31.8mm, 780mm Wide
<b>Stem</b>	Whyte Gravity Stem, 40mm Extension
<b>Grips</b>	Whyte Lock-on V Grip
<b>Front Brakes</b>	SRAM Guide T, 4 Pot, 180mm Rotor
<b>Rear Brakes</b>	SRAM Guide T, 4 Pot, 180mm Rotor, Internal Routing
<b>Brake Levers</b>	SRAM Guide T, Matchmaker
<b>Pedals</b>	None

Our brand-new S-120 frame takes everything we learnt from developing the multi-award-winning S-150 suspension system and applies it to this immensely capable new 120mm platform.

The S-120 is a perfect replacement for the iconic T129, which gave Whyte its 1st Bike Of The Year award. Designed to be an all-round XC/Trail bike from epic marathons to a flat out blast down your local single track, this bike will allow you to do it all.

"Stretches what you can expect from a short-travel bike"  
"Superb tech handling and easy velocity"  
MBUK Whyte S-120 Review December 2018

<b>Dropout Code</b>	DROPWHQ4SR
<b>Shock Stroke and Sag Setting</b>	50mm, Sag 12mm (25%) to 15mm (30%)
<b>Reducer Bush Widths</b>	25mm x 8mm, no hardware at the rear
<b>Eye to Eye Length</b>	210mm
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	592	340.0	796
M	65.6	75	583	340.0	802
L	65.6	75	640	340.0	808
XL	65.6	75	669	340.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	430	30.9	112	406.4
M	1198	430	30.9	125	431.8
L	1227	430	30.9	140	457.2
XL	1256	430	30.9	150	482.6

# S-120C RS

S-120 XC/Trail Suspension - 120mm

SRP - £3,499

Product Code - WS120CRS(size)V1



Colour	Matt Midnight with Dark Red/Bronze/Grey
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	Fox Float Performance SC 34, Step Cast, 29", 120mm Travel, 44mm Offset, GRIP 3-Pos Damper, Tapered Steerer, Black Coating, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float DPS, Performance, Black Coating, Rebound Adjustment and 3pos Adjust Evol LV
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, Micro Engagement 6 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	RaceFace AR-27, Offset, 27mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster TR 29" x 2.3" 60TPI Dual Compound, EXO Sidewall Protection, Front, Maxxis Crossmark II TR 29" x 2.25" 60TPI Dual Compound, EXO Sidewall Protection, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Stylo 7K Eagle, X-SYNC 2, Direct Mount 34T, DUB, 175mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Bike Yoke Revive, 30.9mm, S 125mm Travel, M/L/XL 160mm Travel, Trigger Remote with MMX attachment
Seat	Whyte Custom Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Low Rise, 31.8mm, 780mm Wide
Stem	Whyte Gravity Stem, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide RS, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide RS, 4 Pot, S/M/L 160mm, XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, MMX
Pedals	None

Our brand-new S-120 frame takes everything we learnt from developing the multi-award-winning S-150 suspension system and applies it to this immensely capable new 120mm platform.

The S-120 is a perfect replacement for the iconic T129, which gave Whyte its 1st Bike Of The Year award. Designed to be an all-round XC/Trail bike from epic marathons to a flat out blast down your local single track, this bike will allow you to do it all.

The S-120 geometry was design to have a short 44mm offset fork and this combined with the all new Fox 34 SC, gives amazing handling. This fork was designed to be the ultimate Trail 120mm 29er fork.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	50mm, Sag 12mm (25%) to 15mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	592	340.0	796
M	65.6	75	583	340.0	802
L	65.6	75	640	340.0	808
XL	65.6	75	669	340.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	430	30.9	112	406.4
M	1198	430	30.9	125	431.8
L	1227	430	30.9	140	457.2
XL	1256	430	30.9	150	482.6

# S-120C WORKS

S-120 XC/Trail Suspension - 120mm

SRP - £5,250

Product Code - WS120CW(size)V1



Colour	Matt Petrol with Orange/Reef/Grey
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle and 148mm Boost Dropouts
Fork	Fox Float Factory SC 34, Step Cast, 29", 120mm Travel, 44mm Offset, 3pos Lever w/ Open Mode Adj, Tapered Steerer, Kashima Coating, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float DPS, Factory, Kashima Coating, Rebound Adjustment and 3pos Lever w/ Open Mode Adj, Evol LV
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Shimano MT900, centre lock, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Shimano MT900, centre lock, 15mm x 110mm Boost Through Axle, 28 Hole
Spokes	DT Swiss Competition Butted 2.0-1.8-2.0mm, Black Stainless, Brass Nipples
Rims	Whyte 26mm Carbon Hookless, Offset, Tubeless Ready, 3M Rim Strip with Tubeless Valves included, 28 Hole
Tyres	Maxxis Forekaster TR 29" x 2.3" 60TPI Dual Compound, EXO Sidewall Protection, Front, Maxxis Crossmark II TR 29" x 2.25" 60TPI Dual Compound, EXO Sidewall Protection, Rear
Shift Levers	Shimano XTR M9100, I-Spec EV, 12 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XTR M9100, Shadow Plus, 12 Speed
Cassette	Shimano XTR M9100, 10-51, 12 Speed
Chain	Shimano XTR CN-M9100, 12 Speed
Crankset	RaceFace NEXT R Carbon, Direct Mount 34T, 175mm, Boost, 12 Speed
Bottom Bracket	RaceFace BSA, 73mm, 30mm diameter
Seatpost	Bike Yoke Revive, 30.9mm, S 125mm Travel, M/L/XL 160mm Travel, XTR MT800 I-Spec EV Remote
Seat	Whyte Custom Team, with Lightweight Foam, CrMo Rails, Triple Panel Design
Bar	RaceFace NEXT R Carbon, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Gravity Stem, 35mm Bar Bore, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Shimano XTR BR-9120, 4 Pot with metal pads and cooling fins, 180mm Rotor
Rear Brakes	Shimano XTR BR-9120, 4 Pot with metal pads and cooling fins, S/M/L 160mm, XL 180mm Rotor, Internal Routing
Brake Levers	Shimano XTR, I-Spec EV
Pedals	None

Our brand-new S-120 frame takes everything we learnt from developing the multi-award-winning S-150 suspension system and applies it to this immensely capable new 120mm platform.

The S-120 is a perfect replacement for the iconic T129, which gave Whyte its 1st Bike Of The Year award. Designed to be an all-round XC/Trail bike from epic marathons to a flat our blast down your local single track, this bike will allow you to do it all.

The S-120 geometry was design to have a short 44mm offset fork and this combined with the all new Fox 34 SC gives amazing handling. This fork was designed to be the ultimate Trail 120mm 29er fork.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	50mm, Sag 12mm (25%) to 15mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.6	75	592	340.0	796
M	65.6	75	583	340.0	802
L	65.6	75	640	340.0	808
XL	65.6	75	669	340.0	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	430	30.9	112	406.4
M	1198	430	30.9	125	431.8
L	1227	430	30.9	140	457.2
XL	1256	430	30.9	150	482.6

# T-120

Kid's / Youth Trail Bikes

SRP £1,650

Product Code - WT120V1



<b>Colour</b>	Matt Petrol with Lime / Mist
<b>Sizes Available</b>	13"
<b>Frame</b>	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
<b>Fork</b>	SR Raidon, 120mm Travel, Black Alloy Stanchions, Alloy Tapered Steerer, Hydro Lockout, Air Spring, Adjustable Rebound, 100mm x 15mm axle
<b>Rear Shock</b>	RockShox Deluxe RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
<b>Headset</b>	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 28 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearing, 15mm X 100mm Boost Through Axle, 28 Hole
<b>Spokes</b>	2.0mm, Black Stainless with Brass Nipples
<b>Rims</b>	WTB STp i25, 25mm Wide, TCS 2.0 System, 28 Hole
<b>Tyres</b>	WTB Trail Boss , Light/Fast TCS System 26" X 2.25", 60TPI
<b>Shift Levers</b>	Shimano Deore SL-M6000, 10 Speed
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
<b>Cassette</b>	Sunrace CSMS3, ED Black, 11-46, 10 Speed
<b>Chain</b>	Shimano HG-54, 10 Speed
<b>Crankset</b>	Whyte, Forged 2pcs Cranks, Direct Mount 28T Narrow Wide Chainring, 165mm, 10 Speed
<b>Bottom Bracket</b>	BSA, Cartridge Bearings, 73mm
<b>Seatpost</b>	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Custom
<b>Bar</b>	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 640mm Wide
<b>Stem</b>	Whyte Alloy, 35mm Extension
<b>Grips</b>	Whyte Lock-on V Grip
<b>Front Brakes</b>	Tektro Orion, 4 Pot, 180mm Rotor
<b>Rear Brakes</b>	Tektro Orion, 4 Pot, 180mm Rotor
<b>Brake Levers</b>	Tektro Orion
<b>Pedals</b>	Fibre Reinforced Composite Platform

The T-120 uses a frame that is derived from out T-130 platform but instead of using 650b wheels we have fitted 26" wheels to this 13" frame for a better balance.

Recommended size range is 124cm - 150cm.

The T-120 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

<b>Dropout Code</b>	DROPWHQ4SR
<b>Mudguard Code</b>	N/A
<b>Shock Stroke and Sag Setting</b>	55mm, Sag 14mm (25%) to 17mm (30%)
<b>Reducer Bush Widths</b>	25mm x 8mm, 35.5mm x 8mm
<b>Eye to Eye Length</b>	210mm
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	67	80	484	315	744
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1074	421	30.9	100	331



901

Trail/Enduro Hardtail - 900 Series - 130mm

SRP - £1,399

Product Code - W901(size)V1



Colour	Matt Petrol with Lime/Mist
Sizes Available	XS,S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Intergrip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Sektor RL 27.5", 130mm Travel, 37mm Offset, DebonAir, Fast Black Coating, Adjustable Compression and Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM NX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX, 11 Speed
Cassette	SRAM PG-1130, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM NX, X-SYNC Direct Mount 30T, 170mm, Boost 11 Speed
Bottom Bracket	SRAM GXP, 73mm
Seatpost	Whyte drop.it Post, 30.9mm, XS 100mm Travel, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS/S 760mm Wide, M/L/XL 780mm Wide (L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	TRP Slate, 4 Pot, 180mm Rotor, XL 200mm
Rear Brakes	TRP Slate, 4 Pot, XS/S 160mm, M/L 180mm, XL 200mm Rotor, Internal Routing
Brake Levers	TRP Slate
Pedals	None

With the 901 it's all about the geometry - it will make you feel more confident in all situations than any hardtail you've ever ridden. The latest 901 comes fitted with exactly the same frame as the 10/10 award winning 905 frame.

A frame size adjusted Whyte Drop.it post comes as standard and 4 Pot brakes give the rider the very latest in Trail control.

The 901 rides on 2.8" Maxxis high volume TR 3C compound tyres which combine with the WTB ST TCS 2.0 i35 rims to create more comfort, more control and more fun.

Dropout Code	DROPWH17-2
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64.5	74.5	584	297.5	764
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1143	430	30.9	105	381
S	1161	430	30.9	120	406.2
M	1190	430	30.9	130	431
L	1224	430	30.9	140	457.2
XL	1260	430	30.9	150	482.6

905

Trail/Enduro Hardtail - 900 Series - 130mm

SRP - £1,650

Product Code - W905(size)V1



Colour	Matt Blue with Orange/Denim/Sky
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Intergrip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Revelation RC 27.5", 130mm Travel, 37mm Offset, DebonAir, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM NX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant K6 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it Post, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide ( L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor, XL 200mm
Rear Brakes	SRAM Guide T, 4 Pot, S 160mm, M/L 180mm, XL 200mm Rotor, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

The 905 defines the modern Trail Hardtail. A stripped back SCR frame and new RockShox Revelation forks (with Charger damper and short 37mm offset) combine with 2.8" tyres to make this 905 the best yet.

The 905 brings ideas directly from our Whyte Enduro team, from the thicker V-Grips to the use of 170mm cranks, which bring the rider 5mm closer to the ground without compromising pedal clearance.

WTB STp i35 35mm wide TCS rims combined with Maxxis 2.8" high volume TR 3C compounds, create more comfort, more grip and more fun.

Dropout Code	DROPHW17-2
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1161	430	30.9	120	406.2
M	1190	430	30.9	130	431
L	1224	430	30.9	140	457.2
XL	1260	430	30.9	150	482.6

909

Trail/Enduro Hardtail - 900 Series - 130mm

SRP - £2,100

Product Code - W909(size)V1



Colour	Matt Granite with Grey/Silver
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Intergrip Seat Clamp System with Internal BBX Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	Fox Float Performance 34, 27.5", 130mm Travel, 37mm Offset, GRIP 3-Pos Damper, Tapered Steerer, Black Coating, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Sealed Stainless Steel Cartridge Bearings, 12mm x 148mm Boost Through Axle, 28 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM GX Eagle, X-SYNC 2, Direct Mount 34T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	SDG Tellis Dropper Post, 30.9mm, S 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide ( L/XL 30mm Rise)
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide R, 4 Pot, 180mm Rotor, XL 200mm
Rear Brakes	SRAM Guide R, 4 Pot, S 160mm, M/L 180mm, XL 200mm Rotor, Internal Routing
Brake Levers	SRAM Guide R, MMX
Pedals	None

Our top-end Trail Hardtail is dripping with lust-worthy components such as SRAM's revolutionary Eagle GX groupset, Fox suspension and a Hope Pro 4 rear hub.

WTB ST i35 35mm wide TCS 2.0 rims combined with Maxxis 2.8" high volume TR 3C compounds, create more comfort, more grip and more fun.

The 909 brings ideas directly from our Whyte Enduro team, from the thicker V-Grips to the use of 170mm cranks to bring the rider 5mm closer to the ground without compromising pedal clearance.

Dropout Code	DROPHWH17-2
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1161	430	30.9	120	406.2
M	1190	430	30.9	130	431
L	1224	430	30.9	140	457.2
XL	1260	430	30.9	150	482.6

529

Trail Hardtail 29er - 120mm

SRP - £999

Product Code - W529(size)V1



Colour	Matt Granite with Lime/Olive/Grey
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and 12mm X 148mm Boost Dropouts
Fork	RockShox Recon RL 29", 120mm Travel, 42mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster 29"x 2.35" Front, Maxxis Crossmark II 29" x 2.25" Rear
Shift Levers	Shimano Deore M6000, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
Cassette	Sunrace CSMS2, ED Black, 11-46, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	SR Suntour Zeron 1X, Forged Cranks 2pcs, Narrow wide 30T Chainring, 170mm, 10 Speed
Bottom Bracket	SR Suntour BSA Interface, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S 350mm, M/L/XL 400mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, 180mm Rotor
Rear Brakes	Tektro Auriga HD-M290, S/M 160mm, L/XL 180mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Our Alloy 29er hardtail frame is further developed with Boost 12mm dropouts being added for extra rear-end stiffness.

Our proprietary OTO & SCR technology bring increased balance and control to the 29er trail hardtail category.

The new frame bristles with UK design features such as the “Get A Grip” seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWH17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.5	609	300.0	794
M	66.5	74.5	628	300.0	819
L	66.5	74.5	648	300.0	840
XL	66.5	74.5	665	300.0	864

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1157	435	30.9	110	406.4
M	1177	435	30.9	115	444.5
L	1197	435	30.9	120	495.7
XL	1217	435	30.9	135	533.4



629

Trail Hardtail 29er - 120mm

SRP - £1,299

Product Code - W629(size)V1



Colour	Matt Bronze with Copper/Orange
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and 12mm X 148mm Boost Dropouts
Fork	RockShox Recon RL 29", 120mm Travel, 42mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 29"x 2.3" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Forecaster TR 29" x 2.35" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM NX Eagle, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM NX Eagle, X-SYNC Direct Mount 32T, 170mm, 12 Speed
Bottom Bracket	SRAM Power Spline, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S 350mm, M/L/XL 400mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	SRAM Guide T, 4 Pot, 180mm Rotor
Rear Brakes	SRAM Guide T, 4 Pot, S/M 160mm, L/XL 180mm Rotor, Internal Routing
Brake Levers	SRAM Guide T
Pedals	Fibre Reinforced Composite Platform

Our Alloy 29er hardtail frame is further developed with Boost 12mm dropouts being added for extra rear stiffness.

The new frame bristles with UK design features such as the 'Get A Grip' seat post clamp system. This allows quick adjustment, fantastic weather-proofing and an ergonomic lever which is easy to operate however cold your hands might be.

A full SRAM NX Eagle 1 by 12 groupset is specced on the 629, with its huge 480% range 11-50t cassette, you'll have the ability to tackle all types of terrain with the simplicity that only a 1 by set up can give.

Dropout Code	DROPHW17
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.5	609	300.0	794
M	66.5	74.5	628	300.0	819
L	66.5	74.5	648	300.0	840
XL	66.5	74.5	665	300.0	864

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1157	435	30.9	110	406.4
M	1177	435	30.9	115	444.5
L	1197	435	30.9	120	495.7
XL	1217	435	30.9	135	533.4

801

Trail Hardtail - 800 Series - 120mm

SRP - £899

Product Code - W801(size)V1



Colour	Matt Granite with Lime/Olive/Grey
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	RockShox Recon RL 27.5", 120mm Travel, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, TwistLoc Damper Adjust
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forecaster 27.5" x 2.35" Front, Maxxis Crossmark II 27.5" x 2.25" Rear
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Deraillleur	N/A
Rear Deraillleur	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
Cassette	Sunrace CSMS2, ED Black, 11-46, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	SR Suntour Zeron 1X, Forged 2pcs Cranks, Narrow wide 30T Chainring, 170mm, 10 Speed
Bottom Bracket	SR Suntour BSA Interface, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, S 160mm, M/L/XL 180mm Rotor
Rear Brakes	Tektro Auriga HD-M290, S/M/L 160mm, XL 180mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Our 800 hardtails have always offered a fine blend of fun, control and speed. Our SCR design, with no need for an inner chainring clearance, means our engineers were able to re-shape our custom chainstays for improved agility and a more dynamic ride.

The 800 Series frame uses the very latest Whyte geometry, based around a longer top tube, a short stem and wide 780mm bar. The 800 series bikes also feature a 120mm travel fork, for trail-bike levels of performance.

This new frame bristles with UK design features such as the “Get A Grip” seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	780
M	66.5	74	623	303.5	802
L	66.5	74	641	303.5	826
XL	66.5	74	660	303.5	855

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533

802

COMPACT-FIT

Trail Hardtail - 800 Series - 120mm

SRP - £899

Product Code - W802(size)V1



Colour	Matt Midnight with Magenta/Sky/Grey
Sizes Available	XS,S,M
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	RockShox Recon RL 27.5", 120mm Travel, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, TwistLoc Damper Adjust
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster 27.5" x 2.35" Front, Maxxis Crossmark II 27.5" x 2.25" Rear
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
Cassette	Sunrace CSMS2, ED Black, 11-46, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	SR Suntour Zeron 1X, Forged 2pcs Cranks, Narrow wide 28T Chainring, 170mm, 10 Speed
Bottom Bracket	SR Suntour BSA Interface, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS 740mm Wide, S/M 760mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

The 802 is available in the XS size. All sizes have more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach, suiting riders with shorter proportions.

The 800 Series frame uses the very latest Whyte geometry, based around a longer top tube, a short stem and wide 760mm bar. The 800 series bikes also feature a 120mm travel fork, for trail-bike levels of performance.

Our aluminium hardtails have always offered a fine blend of fun, control and speed. Our SCR design, with no need for an inner chainring clearance, means our engineers are able to further reduce the length of the chainstays for improved agility and a more dynamic ride.

Dropout Code	DROPSHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74.0	580	303.5	761
S	66.5	74.0	599	303.5	779
M	66.5	74.0	618	303.5	803

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444

805

Trail Hardtail - 800 Series - 120mm

SRP - £999

Product Code - W805(size)V1



Colour	Matt Lime with Eucalyptus/Olive/Grey
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	RockShox Recon RL 27.5", 120mm Travel, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, TwistLoc Damper Adjust, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster TR 27.5" x 2.35" 60TPI, EXO Sidewall Protection, Front, Maxxis Crossmark II TR 27.5" x 2.25" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
Cassette	Sunrace CSMS3, ED Black, 11-46, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow Wide Chaining, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, S 160mm, M/L/XL 180mm Rotor
Rear Brakes	Tektro Auriga HD-M290, S/M/L 160mm, XL 180mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

The 800 Series frame uses the very latest Whyte geometry, based around a longer top tube, a short stem and wide 780mm bar.

The BBX internal cable routing keeps cables clean and clear of grime whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine. It also allows the rider to easily upgrade to the Whyte Drop.it dropper post.

WTB STP i25 TCS System rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	780
M	66.5	74	623	303.5	802
L	66.5	74	641	303.5	826
XL	66.5	74	660	303.5	855

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533



806

COMPACT-FIT

Trail Hardtail - 800 Series - 120mm

SRP - £999

Product Code - W806(size)V1



Colour	Matt Midnight with Grey/Dark Red
Sizes Available	XS,S,M
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	RockShox Judy TK 27.5", 120mm Travel, Solo Air, Fast Black Coating, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster TR 27.5" x 2.35" 60TPI, EXO Sidewall Protection, Front, Maxxis Crossmark II TR 27.5" x 2.25" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6000-GS, Shadow Plus, 10 Speed
Cassette	Sunrace CSMS3, ED Black, 11-46, 10 Speed
Chain	Shimano HG-54, 10 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 30T Narrow Wide Chaining, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS 740mm Wide, S/M 760mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, 160mm Rotor
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

The 806 is available in the XS size. All sizes have more compact geometry than the 801 or 805. That means slightly less length for more comfortable reach, suiting riders with shorter proportions.

The 806 uses smooth Shimano Deore M6000 shifting, featuring the latest Shadow Plus clutch rear derailleur, combined with a Whyte 2pcs chainset with narrow-wide chain ring for perfect chain control.

WTB STP i25 TCS System rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74.0	580	303.5	761
S	66.5	74.0	599	303.5	779
M	66.5	74.0	618	303.5	803

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444

603

Sports/Trail Hardtail - 600 Series - 120mm

SRP - £599

Product Code - W603(size)V1



Colour	Matt Lime with Eucalyptus/Olive
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	SR Suntour XCM-LO 27.5", 120mm Travel, Hydro Lockout, Fixed Rebound Damping
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless compatible, 32 Hole
Tyres	WTB Trail Boss Comp 27.5" x 2.25" Front, WTB Ranger Comp 27.5" x 2.25" Rear
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Altus FD-M2000
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	SR Suntour XCM, Double 36-22, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, S 35mm, M/L/XL 45mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, S 160mm, M/L/XL 180mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Whyte’s design team have given the brand new 600 series frame the Trail treatment. A 120mm fork, wider 760mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips, make these the most trail-ready bikes in this price category.

You’ll find it hard to believe the 603 is Whyte’s entry level mountain bike: with carefully chosen, branded parts and a high quality, latest generation frame it has all the hallmarks of Whyte’s award winning DNA.

The new frame bristles with UK design features such as the “Get A Grip” seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.0	604	303.5	780
M	66.5	74.0	623	303.5	802
L	66.5	74.0	641	303.5	826
XL	66.5	74.0	660	303.5	864

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533

604

COMPACT-FIT

Sports/Trail Hardtail - 600 Series - 120mm

SRP - £599

Product Code - W604(size)V1



Colour	Matt Petrol with Reef/Magenta
Sizes Available	XS,S,M
Frame	6061 Alloy, Hydro Formed TB Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	SR Suntour XCM-LO 27.5", 120mm Travel, Hydro Lockout, Fixed Rebound Damping
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless Compatible, 32 Hole
Tyres	WTB Trail Boss Comp 27.5" x 2.25" Front, WTB Ranger Comp 27.5" x 2.25" Rear
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Deraillieur	Shimano Altus FD-M2000
Rear Deraillieur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	SR Suntour XCM, Double 36-22, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 740mm Wide
Stem	Whyte Alloy, XS/S 35mm, M 45mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, 160mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Our Compact MTBs feature shorter geometry and components to better fit a smaller rider. The 604 may be our entry level model, but with carefully chosen parts and an exceptional frame it remains distinctly Whyte.

Whyte’s design team have given the brand new 600 series frame the ‘Trail’ treatment. A 120mm fork, wider 740mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips, make these the most trail-ready bikes in this price category.

The new frame bristles with UK design features such as the “Get A Grip” seat post clamp system. This allows quick adjustment, fantastic weather proofing and a nice ergonomic lever which is easy to operate however cold your hands might be.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74.0	580	303.5	761
S	66.5	74.0	599	303.5	779
M	66.5	74.0	618	303.5	803

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444

605

Sports/Trail Hardtail - 600 Series - 120mm

SRP - £750

Product Code - W605(size)V1



Colour	Matt Midnight with Orange/Reef
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Get A Grip Seat Clamp System, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	RockShox XC-30 27.5", 120mm Travel, Adjustable Rebound, Turn Key Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless Compatible, 32 Hole
Tyres	WTB Trail Boss Comp 27.5" x 2.25" Front, WTB Ranger Comp 27.5" x 2.25" Rear
Shift Levers	Shimano Acera SL-M3000, 9 Speed
Front Derailleur	Shimano Altus FD-M2000
Rear Derailleur	Shimano Acera RD-M3000-SGS Shadow, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC. 9 Speed
Crankset	Shimano FC-MT210, Double 36-22, 2pcs, 9 Speed
Bottom Bracket	Sealed Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, S 35mm, M/L/XL 45mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga HD-M290, S 160mm, M/L/XL 180mm Rotor
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Whyte’s design team have given the brand new 600 series frame the Trail treatment. A 120mm fork, wider 760mm bar, shorter stem, wider grippier tyres and even our Enduro developed V-grips, make these the most trail-ready bikes in this price category.

The new frame bristles with UK design features such as the ‘Get A Grip’ seat post clamp system. This allows quick adjustment, fantastic weather-proofing and an ergonomic lever which is easy to operate however cold your hands might be.

The new 605 is fitted with Shimano’s all new 2 by 9 drive-train. This full Shimano groupset promises great reliability and should give the rider years of trouble-free riding.

Dropout Code	DROPWH6
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74.0	604	303.5	780
M	66.5	74.0	623	303.5	802
L	66.5	74.0	641	303.5	826
XL	66.5	74.0	660	303.5	864

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533



203

20" Junior Hardtail

Guide SRP - £499

Product Code - W203V1

AWAITING FINAL IMAGE



Colour	Matt Midnight with Lime/Sky
Sizes Available	11"
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX, IS Mount Dropouts
Fork	Whyte, 6061 Alloy, Rigid 20" Jr, IS dismount
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-203, 28 Hole
Tyres	Schwalbe Smart Sam 20" x 2.35"
Shift Levers	Sram X4 trigger shift 8-SPEED
Front Derailleur	N/A
Rear Derailleur	SRAM X4 Medium Cage, 8 speed
Cassette	Sunrace 8 Speed, 11-34T
Chain	KMC, 8 Speed
Crankset	Alloy 6061, 28T Narrow wide Chainring, Double Guard, 140mm Crank Length
Bottom Bracket	JIS Square Interface, Cartridge Bearings
Seatpost	Whyte Jr, 6061 Alloy, Single Bolt, 27.2x250mm
Seat	Whyte Jr Custom
Bar	Whyte 6061, Riser Bar, 31.8mm, 600mm Wide
Stem	Whyte Alloy, 35mm Extension
Grips	Whyte Custom
Front Brakes	Tektro M-275 hydraulic, 160mm Rotor
Rear Brakes	Tektro M-275 hydraulic, 140mm Rotor, Internal Routed
Brake Levers	Tektro M-275, Short Reach
Pedals	Jr Fibre Reinforced Composite Platform

Using the same design philosophy as the 400 series, Whyte have a designed a 20" wheeled bike gives great stability and confidence for even the smallest of trail rippers.

Hydraulic brakes with 140mm rotors, give smaller hands plenty of easy stopping power.

With a Whyte alloy rigid fork, Whyte's progressive geometry can be transferred down to our most Junior bike. Light-weight construction combined with high-air volume tyres give a quality ride with less trail chatter.

Dropout Code	DROPWH203
Mudguard Code	WHYMGJR
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
11"	67.0	77.0	450	238.0	555
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
11"	922	365	27.2	100	280.0

403

Youth 26er Trail Hardtail - 400 Series - 100mm

SRP - £599

Product Code - W403V1



Colour	Matt Lime with Eucalyptus/Olive
Sizes Available	13"
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	SR Suntour XCR, 100mm Travel, Hydro Lock-out, Air Spring, Adjustable Rebound, Post Mount
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-403, 28 Hole
Tyres	WTB Trail Boss Race 26" x 2.25" Front, WTB Nano 26" X 2.1" Rear
Shift Levers	Shimano Altus SL-M2000, Trigger Shifter, 9 Speed
Front Deraillieur	N/A
Rear Deraillieur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Sunrace CSM980, ED Black 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Alloy 6061, 28T Narrow wide Chainring, Single guard, 165mm Crank Length
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 640mm Wide
Stem	Whyte Alloy, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Promax Solve, 160mm Rotor
Rear Brakes	Promax Solve, 160mm Rotor, Internal Routing
Brake Levers	Promax Solve, Short Reach
Pedals	Fibre Reinforced Composite Platform

We’ve broken the mould with our kids bikes. By putting 26” wheels on a kids MTB we’ve given a boost in performance similar to an adult switching to a 650b/27.5” Trail Hardtail. More confidence, more control and easier riding.

Whyte spec a trigger shifter, which will help with the transition to an adult bike.

The 403 also comes with Whyte’s own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74.0	540	305.0	715
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1023	410	30.9	100	331.0

403

Youth 26er Trail Hardtail - 400 Series - 100mm

SRP - £599

Product Code - W403GV1



Colour	Matt Granite with Grey/Silver
Sizes Available	13"
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	SR Suntour XCR, 100mm Travel, Hydro Lock-out, Air Spring, Adjustable Rebound, Post Mount
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-403, 28 Hole
Tyres	WTB Trail Boss Race 26" x 2.25" Front, WTB Nano 26" X 2.1" Rear
Shift Levers	Shimano Altus SL-M2000, Trigger Shifter, 9 Speed
Front Deraillieur	N/A
Rear Deraillieur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Sunrace CSM980, ED Black 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Alloy 6061, 28T Narrow wide Chainring, Single guard, 165mm Crank Length
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 640mm Wide
Stem	Whyte Alloy, 35mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Promax Solve, 160mm Rotor
Rear Brakes	Promax Solve, 160mm Rotor, Internal Routing
Brake Levers	Promax Solve, Short Reach
Pedals	Fibre Reinforced Composite Platform

We’ve broken the mould with our kids bikes. By putting 26” wheels on a kids MTB we’ve given a boost in performance similar to an adult switching to a 650b/27.5” Trail Hardtail. More confidence, more control and easier riding.

Whyte spec a trigger shifter, which will help with the transition to an adult bike.

The 403 also comes with Whyte’s own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74.0	540	305.0	715
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1023	410	30.9	100	331.0

# 403

## Kid's / Youth Trail Bikes

SRP £599

Product Code - W403V2-2



<b>Colour</b>	Matt Petrol with Reef / Orange
<b>Sizes Available</b>	13"
<b>Frame</b>	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
<b>Fork</b>	SR Suntour XCR, 100mm Travel, Hydro Lock-out, Air Spring, Adjustable Rebound, Post Mount
<b>Rear Shock</b>	N/A
<b>Headset</b>	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
<b>Rear Hub</b>	Alloy, Cup & Cone, Double Seal, 28 Hole
<b>Front Hub</b>	Alloy, Cup & Cone, Double Seal, 28 Hole
<b>Spokes</b>	2.0mm, PG, Black Stainless, Brass Nipples
<b>Rims</b>	Whyte Trail-403, 28 Hole
<b>Tyres</b>	WTB Trail Boss Comp 26" x 2.25"
<b>Shift Levers</b>	Shimano Altus SL-M2000, Trigger Shifter, 9 Speed
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	Shimano Altus RD-M2000-SGS, 9 Speed
<b>Cassette</b>	Sunrace CSM90, ED Black 11-36, 9 Speed
<b>Chain</b>	KMC, 9 Speed
<b>Crankset</b>	Alloy 6061, 28T Narrow wide Chainring, Single guard, 152mm Crank Length
<b>Bottom Bracket</b>	Square Interface, Cartridge Bearings, 73mm
<b>Seatpost</b>	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Jr Mid Custom
<b>Bar</b>	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 660mm Wide
<b>Stem</b>	Whyte Alloy, 35mm Extension
<b>Grips</b>	Whyte Lock-on V Grip
<b>Front Brakes</b>	Tektro M-275, Hydraulic, 160mm Rotor
<b>Rear Brakes</b>	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
<b>Brake Levers</b>	Tektro HD-M275
<b>Pedals</b>	Fibre Reinforced Composite Platform

Whyte pioneered the 26" wheeled kids bikes at the same time adult bikes moved up to larger wheel sizes.

Award winning Whyte geometry gives the mini shredder more confidence and control along with a trigger shifter to ease the transition in to adult bikes.

The 403 also comes with Whyte's own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

<b>Dropout Code</b>	DROPWHRC
<b>Mudguard Code</b>	N/A
<b>Shock Stroke and Sag Setting</b>	N/A
<b>Reducer Bush Widths</b>	N/A
<b>Eye to Eye Length</b>	N/A
<b>Weight</b>	12.7

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74.0	540	305.0	715
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1023	410	30.9	100	331.0



405

Youth 26er Trail Hardtail - 400 Series - 100mm

SRP - £950

Product Code - W405V1



Colour	Matt Blue with Orange/Denim/Sky
Sizes Available	13"
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Get A Grip Seat Clamp System, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	SR Epixon, 100mm Travel, Black Alloy Stanchions, Alloy Steerer, Hydro Lockout, Air Spring, Adjustable Rebound
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte Trail-405, 28 Hole
Tyres	WTB Bronson Race, 26" X 2.1", 60TPI Folding Front, WTB Riddler, 26" X 1.95" Rear
Shift Levers	SRAM NX, 11 Speed, Trigger Shifter
Front Deraillieur	N/A
Rear Deraillieur	SRAM NX, 11 Speed
Cassette	SRAM GX-1130, 11-42, 11 Speed
Chain	SRAM PC-1130, 11 Speed
Crankset	SRAM NX Power Spline, X-SYNC Direct Mount 28T Chainring, 11 Speed Alloy, 165mm Crank Arms
Bottom Bracket	SRAM Power Spline, 73mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 680mm Wide
Stem	Whyte Gravity, 40mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Auriga, 160mm Rotor
Rear Brakes	Tektro Auriga, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga
Pedals	Fibre Reinforced Composite Platform

We’ve broken the mould with our kids bikes. By putting 26” wheels on a kids MTB we’ve given a boost in performance similar to an adult switching to a 650b/27.5” Trail Hardtail. More confidence, more control and easier riding.

With SRAM NX 1 by 11 spec and a trigger shifter, the 405 really is a scaled down version of our award winning 900 series bikes. We have specced an XSYNC Direct Mount chainring so multiple chainrings are available to tune this bike to the size of the rider.

The 405 also comes with Whyte’s own Get-a-Grip seat post clamping system. This easy to use clamp allows the post to be raised or lowered on the trail, even with small cold hands.

Dropout Code	DROPWH9
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	68.5	74.0	540	305.0	715

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1023	410	30.9	100	331.0

# FRISTON

Gravel/Adventure - GX Series

SRP - £1,699

Product Code - WFR(size)V1



Colour	Matt Petrol with Reef/Orange/Grey
Sizes Available	50,52,54,56,58
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DDX Cable Routing with Inter-Grip Seat Clamp System
Fork	Whyte Straight Bladed Carbon Fork, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts, 15mm x 100mm Stealth Through Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 100mm Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Resolute TCS System 700 x 42c, TCS Light/Fast front, WTB Riddler TCS System 700 x 37c Light/Fast rear , Tan Sidewall, Dual DNA Compound, Lightweight Tubeless Casing
Shift Levers	SRAM APEX 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM APEX 1, Long Cage, 11 Speed
Cassette	SRAM XG-1150, 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM APEX 1, X-SYNC, 40T Chainring, 50/52 170mm, 54 172.5mm, 56/58 175mm 11 Speed
Bottom Bracket	SRAM GXP, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte 500 by Controltech, 6061 Alloy, Gravel riser bar, 31.8mm x 500mm
Stem	Whyte Alloy, 7° Rise, 50cm 60mm, 52cm 70mm, 54cm 80mm, 56/58cm 90mm Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	SRAM APEX 1 Hydraulic, 160mm Rotor, Flat Mount, Internal Routing
Rear Brakes	SRAM APEX 1 Hydraulic, 160mm Rotor, Flat Mount, Internal Routing
Brake Levers	SRAM APEX 1, Hydraulic
Pedals	None

The Friston takes everything we’ve learnt from MTBs and puts that knowledge into a great value Gravel/Adventure bike package. With hydraulic discs, ground-breaking geometry and SRAM’s Apex 1 groupset.

We have applied our unique Whyte frame geometry to the Friston, creating a supremely versatile all-terrain bike. It’s equally at home riding your favourite bridle path, winter training or even commuting.

A straight bladed carbon fork with a tapered steerer tube, internal hose routing and 15mm through axle, give this bike great front end stiffness and steering precision.

Dropout Code	DROPWH17
Mudguard Code	WHYMG55
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	70.0	74.0	557	227.0	776
52	70.0	74.0	566	227.0	797
54	70.0	74.0	595	227.0	814
56	70.0	74.0	604	227.0	829
58	70.0	74.0	623	227.0	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	1037	425	30.9	130	500
52	1047	425	30.9	145	520
54	1077	425	30.9	160	540
56	1087	425	30.9	175	560
58	1107	425	30.9	190	580

# GISBURN

Gravel/Adventure - GX Series

SRP - £1,999

Product Code - WGIS(size)V1



Colour	Matt Lime with Eucalyptus/Olive
Sizes Available	50,52,54,56,58
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DDX Cable Routing with Inter-Grip Seat Clamp System
Fork	Whyte Straight Bladed Carbon Fork, Tapered Alloy Steerer, Internal Routing, Flat Mount Dropouts, 15mm x 100mm Stealth Through Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 100mm Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Resolute TCS System 700 x 42c, TCS Light/Fast front, WTB Riddler TCS System 700 x 37c Light/Fast rear , Tan Sidewall, Dual DNA Compound, Lightweight Tubeless Casing
Shift Levers	SRAM Force 1, Carbon Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Force 1, Long Cage, 11 Speed
Cassette	SRAM PG-1150, 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM Force 1, X-SYNC, 38T Chainring, 50/52 170mm, 54 172.5mm, 56/58 175mm, Carbon, 11 Speed
Bottom Bracket	SRAM GXP XR, 68mm
Seatpost	KS Speed Up Dropper Post, 30.9mm x 50mm Travel 50, 65mm Travel 52/54 , 100mm Travel 56/58, Saddle Nose Lever Control
Seat	Whyte Custom, Road, Lightweight Foam, CrMo Rails, Triple Panel Design
Bar	Whyte 500 by Controltech, 6061 Alloy, Gravel riser bar, 31.8mm x 500mm
Stem	Whyte Alloy, 7° Rise, 50cm 60mm, 52cm 70mm, 54cm 80mm, 56/58cm 90mm Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
Rear Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
Brake Levers	SRAM Force 1, Carbon
Pedals	None

A truly ground-breaking Gravel/Adventure bike with MTB-inspired geometry, tubeless ready wheels and tyres, hydraulic disc brakes and SRAM’s Force 1 groupset - and a dropper post so you can make the most out of the geometry on the descents.

Whyte geometry makes this bike exceptionally competent and controllable off-road. 1 x 11 gearing offers simplicity and efficiency that cannot be rivalled. Full hydraulic disc brakes add stopping power and control.

Whyte’s straight bladed carbon fork with its tapered steerer tube and 15mm through axle gives this bike great front end stiffness and steering precision. Combined with an ultra-wide “Whyte 500” riser bar which allows the rider to truly exploit the radical geometry.

Dropout Code	DROPWH17
Mudguard Code	WHYMG55
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	70.0	74.0	557	227.0	776
52	70.0	74.0	566	227.0	797
54	70.0	74.0	595	227.0	814
56	70.0	74.0	604	227.0	829
58	70.0	74.0	623	227.0	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	1037	425	30.9	130	500
52	1047	425	30.9	145	520
54	1077	425	30.9	160	540
56	1087	425	30.9	175	560
58	1107	425	30.9	190	580

# GLENCOE

RoadPLUS/Adventure

SRP - £1,299

Product Code - WGLE(size)V1



Colour	Matt Granite with Silver/Tan
Sizes Available	50,52,54,56,58
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DDX Cable Routing with Inter-Grip Seat Clamp System
Fork	Whyte Straight Bladed 6061 Alloy, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts, 12mm x 100mm Stealth Through Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, Centre-lock, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Through Axle, Centre-Lock, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless, Brass Nipples
Rims	WTB ST i23 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Horizon TCS System 27.5" x 47c, DNA Compound
Shift Levers	SRAM APEX 1, Mechanical, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM APEX 1, Long Cage, 11 Speed
Cassette	SRAM PC-1130, 11-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	Whyte, Forged Cranks, Direct Mount 44T Narrow Wide Chainring, 11 Speed
Bottom Bracket	Shimano SM-BB52, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte Gravel, 31.8mm, 500mm Wide
Stem	Whyte Alloy, 7° Rise, 50cm 60mm, 52cm 70mm, 54cm 80mm, 56/58cm 90mm Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Rear Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Brake Levers	SRAM APEX 1, Mechanical
Pedals	None

The Glencoe combines our Gravel/Adventure frame with Road Plus tyres. These high air volume 650b tyres have the same rolling circumference as a 700c X 28c setup and give huge levels of comfort and security on even the roughest road surfaces.

1 x 11 gearing offers simplicity and efficiency that cannot be rivalled. TRP mechanical/hydraulic disc brakes add stopping power and control.

Whether you're an inner-city, year-round commuter or a C or D back-road rider, the Glencoe is the perfect bike to give you control on unpredictable surfaces. The Glencoe is the most versatile all-round road bike we have ever made.

Dropout Code	DROPWH17
Mudguard Code	WHYMG55
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	70.0	74.0	557	270.0	776
52	70.0	74.0	566	270.0	797
54	70.0	74.0	595	270.0	814
56	70.0	74.0	604	270.0	829
58	70.0	74.0	623	270.0	850
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	1037	425	30.9	130	500
52	1047	425	30.9	145	520
54	1077	425	30.9	160	540
5658	1087	425	30.9	175	560
	1107	425	30.9	190	580



# WESSEX ONE

Carbon Performance Road - RDC7 Series

SRP - £1,999 - valid from 1/9/18

Product Code - WWESSCR(size)V1



Colour	Matt Lime with Eucalyptus/Olive
Sizes Available	50,52,54,56,58
Frame	Carbon, Uni-directional Multi Monocoque, One-By Specific, Flat Mount 160mm Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
Fork	Whyte Straight Bladed Carbon, Tapered Carbon Steerer, Internal Cable Routing, 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, XD Driver, 28 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Through Axle, 28 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless, Brass Nipples
Rims	WTB Asym i23, TCS System, 28 Hole
Tyres	Schwalbe G-ONE Speed 700 x 30c, TL-Easy Tubeless System, MicroSkin Puncture Protection
Shift Levers	SRAM APEX 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM APEX 1, Long Cage, 11 Speed
Cassette	SRAM PG-1150, 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	SRAM APEX 1, X-SYNC 44T Chainring
Bottom Bracket	SRAM GXP XR, BSA 68mm
Seatpost	Whyte 2014 Alloy, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Road, Lightweight Foam, CrMo Rails, Triple Panel Design
Bar	Whyte 6061 Alloy, Aero Road, 31.8mm, Compact "Wing" Bar, 50cm 400mm, 52/54cm 420mm, 56cm 440mm, 58cm 460mm
Stem	Whyte Alloy Road, -7° Rise, 50cm 90mm, 52cm 100mm, 54cm 110mm, 56/58cm 120mm Extension
Grips	Whyte Anti Slip with 3M Reflective Logos
Front Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
Rear Brakes	SRAM Force 1 Hydraulic, 160mm Flat Mount, Internal Routing
Brake Levers	SRAM APEX 1, Hydraulic
Pedals	None

When we set about designing this bike, we wanted to create an even simpler version of the Wessex. The 1 x 11 drive train gives 11 useable gears with no overlaps and utter simplicity.

30c Schwalbe G-One Speed tyres and WTB tcs 2.0 rims give all the advantages of tubeless tyres. The lower pressure creates both comfort and grip to give the security that creates the feeling of confidence in all weather and road conditions.

Hydraulic brakes give one finger control from either the hoods or the drops and the extra modulation allows for complete control in all situations and weather conditions.

Dropout Code	DROPWH17
Mudguard Code	WHYMG42W
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72.0	74.5	525	271.5	764
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73.0	570	271.5	814.5
58	73.0	73.0	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	993	425	27.2	130	500
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

# WESSEX

## Carbon Performance Road - RDC7 Series

SRP - £2,250 - valid from 1/9/18

Product Code - WWES(size)V1



<b>Colour</b>	Matt Zinc with Orange/Grey
<b>Sizes Available</b>	50,52,54,56,58
<b>Frame</b>	Carbon, Uni-directional Multi Monocoque, Flat Mount 160mm Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
<b>Fork</b>	Whyte Straight Bladed Carbon, Tapered Carbon Steerer, Internal Cable Routing, 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mudguards
<b>Rear Shock</b>	N/A
<b>Headset</b>	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, Centre-lock, 28 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Through Axle, Centre-Lock, 28 Hole
<b>Spokes</b>	DT Swiss Competition Butted, Black Sandvik Stainless, Brass Nipples
<b>Rims</b>	Easton AR-24, 21mm Wide, Tubeless Ready, 28 Hole
<b>Tyres</b>	Schwalbe G-ONE Speed 700 x 30c, TL-Easy Tubeless System, MicroSkin Puncture Protection
<b>Shift Levers</b>	Shimano Ultegra ST-R8020, 11 Speed
<b>Front Derailleur</b>	Shimano 105 FD-5800
<b>Rear Derailleur</b>	Shimano Ultegra RD-R8000-GS, 11 Speed
<b>Cassette</b>	Shimano 105 CS-5800, 11-32, 11 Speed
<b>Chain</b>	Shimano HG-601, 11 Speed
<b>Crankset</b>	Shimano 105 FC-R510, Double 50-34, 11 Speed, Hollowtech
<b>Bottom Bracket</b>	Shimano SM-BB52, BSA 68mm
<b>Seatpost</b>	Whyte 2014 Alloy, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Custom, Road, Lightweight Foam, CrMo Rails, Triple Panel Design
<b>Bar</b>	Whyte 6061 Alloy, Aero Road, 31.8mm, Compact "Wing" Bar, 50cm 400mm, 52/54cm 420mm, 56cm 440mm, 58cm 460mm
<b>Stem</b>	Whyte Alloy Road, -7° Rise, 50cm 90mm, 52cm 100mm, 54cm 110mm, 56/58cm 120mm Extension
<b>Grips</b>	Whyte Anti Slip with 3M Reflective Logos
<b>Front Brakes</b>	Shimano Ultegra BR-R8070 Hydraulic, 160mm Rotor, Centre-lock, Flat Mount, Internal Routing
<b>Rear Brakes</b>	Shimano Ultegra BR-R8070 Hydraulic, 160mm Rotor, Centre-lock, Flat Mount, Internal Routing
<b>Brake Levers</b>	Shimano Ultegra, ST-8020
<b>Pedals</b>	None

The Wessex was conceived to be the ideal contemporary British road bike. Built for all road surfaces, it uses the very latest in tubeless-ready, high air volume 30c Schwalbe G-One Speed tyres on 24mm wide Easton AR rims.

The 2017 road.cc Endurance Bike of the Year and recipient of a European Design and Innovation Award, the Wessex delivers previously unimaginable levels of grip, confidence and control, whatever the weather.

12mm through axles, tubeless tyres, disc brakes and the ability to fit full length mud guards makes the Wessex extremely versatile and capable - and perfect for tough UK conditions.

<b>Dropout Code</b>	DROPWH17
<b>Mudguard Code</b>	WHYMG42W
<b>Shock Stroke and Sag Setting</b>	N/A
<b>Reducer Bush Widths</b>	N/A
<b>Eye to Eye Length</b>	N/A
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72.0	74.5	525	271.5	764
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73.0	570	271.5	814.5
58	73.0	73.0	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	993	425	27.2	130	500
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

# WESSEX DI2

Carbon Performance Road - RDC7 Series

SRP - £3,650 - valid from 1/9/18

Product Code - WWESDI(size)V1



<b>Colour</b>	Forest Green with Reef/Orange/Sky
<b>Sizes Available</b>	50,52,54,56,58
<b>Frame</b>	Carbon, Uni-directional Multi Monocoque, Flat Mount 160mm Disc Mount, DOX Internal Cable Routing, Verti-Grip Integrated Seat Clamp System, Concealed Eyelets for Mud Guards and 142mm Rear Dropouts with 12mm Through Axle
<b>Fork</b>	Whyte Straight Bladed Carbon, Tapered Carbon Steerer, Internal Cable Routing, 12mm x 100mm Stealth Through Axle, Concealed Eyelets for Mudguards
<b>Rear Shock</b>	N/A
<b>Headset</b>	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Through Axle, Centre-lock, 24 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Through Axle, Centre-Lock, 24 Hole
<b>Spokes</b>	DT Swiss Competition Butted, Black Sandvik Stainless, Brass Nipples
<b>Rims</b>	Whyte Carbon, 21mm Wide, Tubeless Ready, 24 Hole
<b>Tyres</b>	Schwalbe Pro-ONE 700 x 28c, TL-Easy Tubeless System, MicroSkin Puncture Protection
<b>Shift Levers</b>	Shimano Ultegra Di2 ST-R8070, 11 Speed
<b>Front Derailleur</b>	Shimano Ultegra Di2 FD-R8050
<b>Rear Derailleur</b>	Shimano Ultegra Di2 RD-R8050-GS, 11 Speed
<b>Cassette</b>	Shimano Ultegra CS-R8000, 11-34, 11 Speed
<b>Chain</b>	Shimano HG-601, 11 Speed
<b>Crankset</b>	Shimano Ultegra FC-R8000, Double 50-34, 11 Speed, Hollowtech
<b>Bottom Bracket</b>	Shimano SM-BBR60, BSA 68mm
<b>Seatpost</b>	Whyte Carbon, 1pcs Carbon UD, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Custom, Road, Lightweight Foam, CrMo Rails, Triple Panel Design
<b>Bar</b>	Whyte Carbon, Aero Road, 31.8mm, Compact Carbon UD "Wing" Bar, 50cm 400mm, 52 420mm, 54/56/58cm 440mm
<b>Stem</b>	Whyte Alloy Road, -7° Rise, 50cm 90mm, 52cm 100mm, 54cm 110mm, 56/58cm 120mm Extension
<b>Grips</b>	Whyte Anti Slip with 3M Reflective Logos
<b>Front Brakes</b>	Shimano Ultegra BR-R8070 Hydraulic, 160mm Rotor, Centre-lock, Flat Mount, Internal Routing
<b>Rear Brakes</b>	Shimano Ultegra BR-R8070 Hydraulic, 160mm Rotor, Centre-lock, Flat Mount, Internal Routing
<b>Brake Levers</b>	Shimano Ultegra Di2, ST-8070
<b>Pedals</b>	None

Ultegra Di2 takes all year-round riding to a new level. With Tubeless tyres mounted on our own Whyte carbon rims and the all new Ultegra disk brakes, consistent control in all weather is guaranteed.

Shimano's new Di2 Ultegra gives the rider more control over shifting. The bar mounted junction box/display displays battery life and allows the rider to adjust shifting settings with ease.

12mm through axles, tubeless tyres, disc brakes and the ability to fit full length mud guards makes the Wessex extremely versatile and capable - and perfect for tough UK conditions.

<b>Dropout Code</b>	DROPWH17
<b>Mudguard Code</b>	WHYMG42W
<b>Shock Stroke and Sag Setting</b>	N/A
<b>Reducer Bush Widths</b>	N/A
<b>Eye to Eye Length</b>	N/A
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72.0	74.5	525	271.5	764
52	72.5	74	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73.0	570	271.5	814.5
58	73.0	73.0	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	993	425	27.2	130	500
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580

# DORSET

Sports Road/Commuter Disc - RD7 Series

SRP - £999

Product Code - WDOR(size)V1



Colour	Matt Granite with Bronze/Dark Red
Sizes Available	50,52,54,56,58
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc Mount
Fork	Whyte Straight Bladed Carbon Fork, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts with Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Schwalbe G-One Speed 700 x 30c, Race Guard
Shift Levers	Shimano Sora SL-R3000, 9 Speed
Front Deraillieur	Shimano Sora FD-R3000
Rear Deraillieur	Shimano Sora RD-R3000-GS, 9 Speed
Cassette	Shimano CS-HG-200, 11-32, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-R345, Double 50-34, 52 170mm, 54/56/58 175mm 9 Speed
Bottom Bracket	Shimano BB-ES300 Splined Hollow-Type, 68mm
Seatpost	Whyte 6061 Alloy, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, Road, 31.8mm, Compact "Wing" Bar, 50cm 380mm, 52/54cm 400mm, 56cm 420mm, 58cm 440mm
Stem	Whyte Alloy Road -6° Rise, 50cm 90mm, 52cm 100mm, 54/56cm 110mm, 58cm 120mm Extension
Grips	Whyte Anti Slip Comfort with 3M Reflective Logos
Front Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Rear Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Brake Levers	Shimano Sora ST-R3000
Pedals	Fibre Reinforced Composite Platform

The Dorset features Shimano’s 9-speed Sora groupset, with a wide-ratio cassette to make getting up the hills a breeze. On the descents, reliable TRP Flat Mount disc brakes will slow you down safely and easily.

Whether you’re commuting longer distances, winter training or entering summer sportifs, the Whyte Road Disc range offers Cyclo Cross durability with pure Road geometry.

A strong alloy 6061 frame, with mudguard and rack eyelets, combined with wide section Offset Rimmed RD-7 rims and TRP Hydro/Mechanical disc brakes will give years of reliable all-season performance.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46B
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50	72.0	74.5	525	271.5	764
52	72.5	74.0	540	271.5	781.5
54	73.0	73.5	555	271.5	798.5
56	73.0	73.0	570	271.5	814.5
58	73.0	73.0	585	271.5	830.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50	993.0	425	27.2	130	500.0
52	998.4	425	27.2	145	520
54	1003.3	425	27.2	160	540
56	1012.8	425	27.2	175	560
58	1027.8	425	27.2	190	580



DEVON

COMPACT-FIT

Sports Road/Commuter Disc - RD7 Series

SRP - £999

Product Code - WDEV(size)V1



Colour	Matt Midnight with Magenta/Grey
Sizes Available	47,49,51,53
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Flat Mount 160 Chainstay Disc Mount
Fork	Whyte Straight Bladed Carbon Fork, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts with Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Schwalbe G-One Speed 700 x 30c, Race Guard
Shift Levers	Shimano Sora SL-R3000, 9 Speed
Front Deraillieur	Shimano Sora FD-R3000
Rear Deraillieur	Shimano Sora RD-R3000-GS, 9 Speed
Cassette	Shimano CS-HG-200, 11-34, 9 Speed
Chain	KMC, 9 Speed
Crankset	FSA Vero Adventure Pro, Double 48-32, 47/49 170mm, 51 172.5mm, 53 175mm 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, Road, 31.8mm, Compact "Wing" Bar, 47/49/51cm 380mm, 53cm 400mm
Stem	Whyte Alloy Road -6° Rise, 47/49cm 80mm, 51cm 90mm, 53cm 100mm Extension
Grips	Whyte Anti Slip Comfort with 3M Reflective Logos
Front Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Rear Brakes	TRP HyRd Hydraulic, 160mm Rotor, Flat Mount, Linear Outer Cables with Kevlar Reinforcement, Internal Routing
Brake Levers	Shimano Sora ST-R3000
Pedals	Fibre Reinforced Composite Platform

Compact geometry makes for a more comfortable female-focused fit. The Devon's TRP HyRd disc brakes use an innovative hybrid cable/hydraulic system to provide powerful braking whatever the conditions.

A strong alloy 6061 frame with mudguard and rack eyelets, combined with wide-section offset rimmed RD-7 wheels, will give years of reliable all-season performance.

Whether you're commuting longer distances, winter training or entering summer sports, the Whyte Road Disc range offers Cyclo Cross durability with Road geometry.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46B
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
47	71.5	75	507	269.0	721
49	72	74.5	515	271.5	742.5
51	72.5	74	525	271.5	776.5
53	73	73.5	535	271.5	793.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
47	984.8	425	27.2	115	470
49	985	425	27.2	130	490
51	985.4	425	27.2	145	510
53	985.4	425	27.2	160	530

# WHITECHAPEL

Fast Urban/Commuter - R7 Series

SRP - £599

Product Code - WWH(size)V1



Colour	Matt Zinc with Grey/Blue
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed 6061 Alloy, Forged Crown, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Vittoria Zaffiro 700 x 32c, Puncture Protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Alloy, 42T Chainring with Alloy Chain Guard
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm, XL 70mm Extension
Grips	Whyte Custom with Extra-Thick Bar Plugs
Front Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

The Whitechapel is all about simplicity: a single chain ring and nine gears at the back will give years of reliable urban use.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46A
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	6.95	74.0	569.4	266.5	716.5
M	70.0	73.5	595.2	266.5	748.5
L	70.0	73.0	613	271.5	786
XL	70.0	73.0	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1061.4	430	27.2	145	406.4
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

# CARNABY COMPACT-FIT

Fast Urban/Commuter - R7 Series

SRP - £599

Product Code - WCAR(size)V1



Colour	Matt Blue with Orange/Sky
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed 6061 Alloy, Forged Crown, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Vittoria Zaffiro 700 x 32c, Puncture Protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Deraillieur	N/A
Rear Deraillieur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Alloy, 39T Chainring with Alloy Chain Guard
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 600mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm Extension
Grips	Whyte Custom with Extra-Thick Bar Plugs
Front Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

32c tyres on 21mm wide rims give the Carnaby both speed and comfort from the toughest urban commute to a open road adventure.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability, and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle for easy fitment of a rack or mudguards.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46A
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9

# SHOREDITCH

Fast Urban/Commuter - R7 Series

SRP - £699

Product Code - WSH(size)V1



Colour	Matt Petrol with Lime/Black
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed Carbon Fork, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Vittoria Zaffiro Pro 700 x 32c, Puncture Protection
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Deraillieur	N/A
Rear Deraillieur	Shimano Deore RD-M6000-SGS, Shadow Plus, 10 Speed
Cassette	Shimano Deore CS-HG-500, 11-42, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Alloy Narrow Wide 44T Chaining with Guard, 10 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm, XL 70mm Extension
Grips	Whyte Custom with Extra-Thick Bar Plugs
Front Brakes	Tektro HD-M290, 160mm Rotor, Internal Routing
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Featuring mountain bike clutch mech technology and the all-new Deore 11-42 wide range cassette, the Shoreditch has the right gear for any ride.

Based on our high performance mountain bike geometry, all our Fast Urban bikes have a long wheelbase and relaxed head angle for high speed stability and a shorter stem for excellent slow speed manoeuvrability.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required. 1 by 10 MTB gearing promises years of reliable urban use and hydro discs guarantee consistent performance.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46A
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	6.95	74.0	569.4	266.5	716.5
M	70.0	73.5	595.2	266.5	748.5
L	70.0	73.0	613	271.5	786
XL	70.0	73.0	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1061.4	430	27.2	145	406.4
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533



# PORTOBELLO PLUS

Fast Urban/Commuter - R7 Series

SRP - £799

Product Code - WPO(size)V1



Colour	Matt Bronze with Silver/Copper
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed 6061 Alloy, Alloy Tapered Steerer, Internal Cable Routing, Flat Mount with 160mm Post Adaptor, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road Plus 650b, Low Profile, 25mm Wide, Tubeless Compatible, 32 Hole Rear and 28 Hole Front
Tyres	WTB Horizon 650b x 47c, Tan Wall, Road Plus
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Deraillieur	N/A
Rear Deraillieur	Shimano Deore RD-M6000-SGS, Shadow Plus, 10 Speed
Cassette	Shimano Deore CS-HG-500, 11-42, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Alloy, Narrow Wide 44T Chainring with Guard, 10 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm, XL 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro Auriga HD-M290, 160mm Rotor, Flat Mount, Internal Routing
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Combining MTB geometry and parts with road bike wheels and tyres has always been the case with the R-7 line up - but the new Plus tyres takes this to a new level. These high-air volume/low-rolling-resistance tyres are perfect for dealing with ‘All Surface’ commutes and rides.

The Portobello features massive 650b x 47c tyres to smooth out the road chatter. These deep profile tyres, give the same rolling diameter as 700c x 28c tyres but the extra air volume make them super comfortable and pinch puncture resistant.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG55
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	6.95	74.0	569.4	266.5	716.5
M	70.0	73.5	595.2	266.5	748.5
L	70.0	73.0	613	271.5	786
XL	70.0	73.0	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1061.4	430	27.2	145	406.4
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

# VICTORIA PLUS

COMPACT-FIT

Fast Urban/Commuter - R7 Series

SRP - £799

Product Code - WVI(size)V1



Colour	Matt Bronze with Copper/Dark Red
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed 6061 Alloy, Alloy Tapered Steerer, Internal Cable Routing, Flat Mount with 160mm Post Adaptor, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road Plus 650b, Low Profile, 25mm Wide, Tubeless Compatible, 32 Hole Rear and 28 Hole Front
Tyres	WTB Horizon 650b x 47c, Tan Wall, Road Plus
Shift Levers	Shimano Deore SL-M6000, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6000-SGS, Shadow Plus, 10 Speed
Cassette	Shimano Deore CS-HG-500, 11-42, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Alloy, Narrow Wide 40T Chainring with Guard, 10 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 600mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro Auriga HD-M290, 160mm Rotor, Flat Mount, Internal Routing
Rear Brakes	Tektro Auriga HD-M290, 160mm Rotor, Internal Routing
Brake Levers	Tektro Auriga HD-M290
Pedals	Fibre Reinforced Composite Platform

Combining MTB geometry and parts with road bike wheels and tyres has always been the case with the R-7 line up - but the new Plus tyres takes this to a new level. These high-air volume/low-rolling-resistance tyres are perfect for dealing with ‘All Surface’ commutes and rides.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

The Victoria features massive 650b x 47c tyres to smooth out the road chatter. These deep profile tyres give the same rolling diameter as 700c x 28c tyres and the extra air volume make them super comfortable and pinch-puncture resistant.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG55
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9

# STIRLING

Fast Urban/Commuter - R7 Series

SRP - £999

Product Code - WST(size)V1



Colour	Matt Midnight with Grey/Dark Red
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed Carbon Fork, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Vittoria Zaffiro 700 x 32c, Puncture Protection
Shift Levers	Shimano Ultegra SL-RS700, Flat Bar, 11 Speed
Front Derailleur	Shimano 105 FD-R7000
Rear Derailleur	Shimano 105 RD-R7000-GS, 11 Speed
Cassette	Shimano 105 CS-R7000, 11-32, 11 Speed
Chain	Shimano CN-HG901, 11 Speed
Crankset	FSA Gossamer Compact MegaExo, 50-34, 2pcs, 11 Speed
Bottom Bracket	FSA MegaExo with Stainless Steel Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 2014 Alloy, 20mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm, XL 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Rear Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT400
Pedals	Fibre Reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x11spd Shimano drivetrain.

The Stirling features a carbon fork and 32c tyres to smooth out the road chatter. The fork has dropout eyelets to allow our custom mud guards to be easily fitted.

A custom rear dropout mounts the hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46A
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	6.95	74.0	569.4	266.5	716.5
M	70.0	73.5	595.2	266.5	748.5
L	70.0	73.0	613	271.5	786
XL	70.0	73.0	626.9	271.5	817

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1061.4	430	27.2	145	406.4
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

# PIMLICO

COMPACT-FIT

Fast Urban/Commuter - R7 Series

SRP - £999

Product Code - WPI(size)V1



Colour	Matt Midnight with Magenta/Grey
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts
Fork	Whyte Straight Bladed Carbon Fork, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 23, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 21mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 28 Hole Front
Tyres	Vittoria Zaffiro 700 x 32c, Puncture Protection
Shift Levers	Shimano Ultegra SL-RS700, Flat Bar, 11 Speed
Front Deraillieur	Shimano 105 FD-R7000
Rear Deraillieur	Shimano 105 RD-R7000-GS, 11 Speed
Cassette	Shimano 105 CS-R7000, 11-32, 11 Speed
Chain	Shimano CN-HG901, 11 Speed
Crankset	FSA Gossamer Compact MegaExo, 50-34, 2pcs, 11 Speed
Bottom Bracket	FSA MegaExo with Stainless Steel Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 2014 Alloy, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 600mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Rear Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT400
Pedals	Fibre Reinforced Composite Platform

A lightweight aluminium frame employs compact geometry to make this bike perfect for shorter riders who want a wide-ratio 2x11spd Shimano drivetrain.

A custom rear dropout allows us to mount the rear hydraulic disc brake caliper inside the rear triangle, clearing the way for any rack or mudguards that may be required.

Our shaped, butted and uniquely profiled rear stays give all our fast urban bikes a fantastically responsive and comfortable ride.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46A
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9



# RIDGEWAY

All Terrain/Leisure - C7 Series

SRP - £599

Product Code - WRI(size)V1



Colour	Matt Orange with Black/Grey
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Schwalbe SILENTO 700 x 35c, K-Guard puncture protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Acera FD-T3000
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, Triple 48-36-26, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, 160mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame, including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	592	278.0	765
M	69.0	73.5	617	278.0	774
L	69.0	73.0	632	278.0	805
XL	69.0	73.0	646.6	278.0	854
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099.0	435	30.9	115	457.0
M	1119.0	435	30.9	125	495.0
L	1129.0	435	30.9	135	546.0
XL	1144.0	435	30.9	145	585.0

# RIDGEWAY

All Terrain/Leisure - C7 Series

SRP - £599

Product Code - WRIB(size)V1



Colour	Matt Petrol with Mist/Lime
Sizes Available	S,M,L,XL
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Schwalbe SILENTO 700 x 35c, K-Guard puncture protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Acera FD-T3000
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, Triple 48-36-26, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, 160mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the RidgeWay is ready for adventure whenever you are. Its lightweight, comfortable chassis and full Shimano drivetrain will give years of unrivalled performance.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame, including our unique rear seat stays which really improve the comfort and performance, whatever the terrain. Puncture resistant tyres offer extra reliability and piece of mind.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	592	278.0	765
M	69.0	73.5	617	278.0	774
L	69.0	73.0	632	278.0	805
XL	69.0	73.0	646.6	278.0	854

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099.0	435	30.9	115	457.0
M	1119.0	435	30.9	125	495.0
L	1129.0	435	30.9	135	546.0
XL	1144.0	435	30.9	145	585.0

# RIDGEWAY WOMEN'S

All Terrain/Leisure - C7 Series

SRP - £599

Product Code - WRIL(size)V1



Colour	Matt Magenta with Black/Grey
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Schwalbe SILENTO 700 x 35c, K-Guard puncture protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Acera FD-T3000
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, Triple 48-36-26, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Women's Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, 160mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	570	278.0	718
M	69.0	74	587	278.0	737
L	69.0	73.5	612	278.0	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094.0	435	30.9	115	457.0
L	1114.0	435	30.9	125	495.0

# RIDGEWAY WOMEN'S

All Terrain/Leisure - C7 Series

SRP - £599

Product Code - WRILB(size)V1



Colour	Matt Petrol with Ice/Silver
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Schwalbe SILENTO 700 x 35c, K-Guard puncture protection
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Acera FD-T3000
Rear Derailleur	Shimano Altus RD-M2000-SGS, 9 Speed
Cassette	Shimano CS-HG-200, 11-36, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-M371, Triple 48-36-26, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Women's Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, 160mm Rotor
Rear Brakes	Tektro HD-M275, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

With hydraulic disc brakes and a comfort enhancing suspension fork, the Ridgeway is ready for adventure whenever you are. Its lightweight, comfortable women's specific chassis and full Shimano drivetrain will give years of unrivalled performance.

All the same key design features as the unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are flexi and offer less steering control). Puncture resistant tyres give extra reliability and piece of mind.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	570	278.0	718
M	69.0	74	587	278.0	737
L	69.0	73.5	612	278.0	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094.0	435	30.9	115	457.0
L	1114.0	435	30.9	125	495.0



# CALEDONIAN

All Terrain/Leisure - C7 Series

SRP - £850 - valid from 1/9/18

Product Code - WCA(size)V1



Colour	Matt Zinc with Lime/Grey
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Vittoria Randonneur Trail 700 x 35c, Double Shielding Puncture Protection
Shift Levers	Shimano Deore SL-T6000, 10 Speed
Front Derailleur	Shimano Deore FD-T6000
Rear Derailleur	Shimano Deore RD-T6000-SGS, 10 Speed
Cassette	Shimano Deore CS-HG500, 11-34, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Shimano FC-T521, Triple 48-36-26, 10 Speed
Bottom Bracket	Shimano BB-ES300 Splined Hollow-Type, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L 400mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano MT-400, 160mm Rotor
Rear Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT-400
Pedals	Fibre Reinforced Composite Platform

With wide ratio gearing taken from Shimano’s rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

Our custom built frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot that stops water spray from the rear wheel getting into the frame and the continuous outer cables that are internally routed to keep the gear shifts working smoother for longer.

The ride-feel of these bikes is second to none, with a fantastic quality lightweight frame including our unique rear seat stays which really improve the comfort and performance, whatever the terrain.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69.0	74.0	592	278.0	765
M	69.0	73.5	617	278.0	774
L	69.0	73.0	632	278.0	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099.0	435	30.9	115	457.0
M	1119.0	435	30.9	125	495.0
L	1129.0	435	30.9	135	546.0

# CALEDONIAN WOMEN'S

All Terrain/Leisure - C7 Series

SRP - £850 - valid from 1/9/18

Product Code - WCAL(size)V1



Colour	Matt Granite with Grey/Orange
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX , Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FSA No.10, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 700c, 32 Hole
Tyres	Vittoria Randonneur Trail 700 x 35c, Double Shielding Puncture Protection
Shift Levers	Shimano Deore SL-T6000, 10 Speed
Front Derailleur	Shimano Deore FD-T6000
Rear Derailleur	Shimano Deore RD-T6000-SGS, 10 Speed
Cassette	Shimano Deore CS-HG500, 11-34, 10 Speed
Chain	Shimano CN-HG54, 10 Speed
Crankset	Shimano FC-T521, Triple 48-36-26, 10 Speed
Bottom Bracket	Shimano BB-ES300 Splined Hollow-Type, 68mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Women's Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 17° Rise, 70mm Extension
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano MT-400, 160mm Rotor
Rear Brakes	Shimano MT-400, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT-400
Pedals	Fibre Reinforced Composite Platform

With wide ratio gearing taken from Shimano's rugged mountain bike line and high quality Vittoria trail tyres, the Caledonian is primed for a big adventure.

All the same key design features as the Unisex version, with the added benefit of a partially dropped top tube. This increases stand over height, while still keeping enough room inside the frame to comfortably fit a water bottle.

Another benefit of the partially dropped tube is the maintained stiffness of the frame (fully dropped top tube frames are more flexible and offer less steering control).

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	570	278.0	718
M	69.0	74	587	278.0	737
L	69.0	73.5	612	278.0	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094.0	435	30.9	115	457.0
L	1114.0	435	30.9	125	495.0

# STRAWBERRY HILL

Lightweight Classic/Leisure

SRP - £650

Product Code - WSTR(size)V1



Colour	Matt Granite with Grey/Gold
Sizes Available	S,M,L
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	Whyte 6061 Alloy, Curved Blade, Alloy Steerer
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Silver Stainless, Brass Nipples
Rims	Whyte Double Walled Alloy, 700c, 32 Hole
Tyres	Maxxis Roamer 700 x 42c, High Air Volume, Kevlar Puncture Guard
Shift Levers	Shimano Altus SL-M2000, 9 Speed
Front Derailleur	Shimano Acera FD-T3000
Rear Derailleur	Shimano Acera RD-T3000-SGS, 9 Speed
Cassette	Shimano Altus CS-HG-201, 11-34, 9 Speed
Chain	KMC, 9 Speed
Crankset	Shimano FC-T3010, Triple 48-36-26
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Women's Fit, Triple Panel Design
Bar	Whyte 6061 Alloy, Swept Bar, 45mm Sweep, 25.4mm, 600mm Wide
Stem	Whyte Alloy Custom, 20° High Rise
Grips	Ergon, Single Density For Swept Bar
Front Brakes	Tektro Forged V Brake
Rear Brakes	Tektro Forged V Brake
Brake Levers	Tektro V Brake Levers with Integrated Bell
Pedals	Alloy Body with Non Slip Grip

Whyte's take on a stylish, comfortable, lifestyle bike. Combining the elegance of a vintage machine with a 27 speed drivetrain and a remarkably lightweight frame, we've made it even easier to get up the hills, or just to lift up the stairs when you get home.

Comfort was given top priority with the Strawberry Hill. The Whyte saddle is highly cushioned but also lightweight. The grips are specifically designed to fit your palm on a swept handle bar and even the brake levers have a Kraton insert to add a tactile and comfortable feel.

Full mudguards, a chainset cover, kick stand and internal cable routing keep all the moving parts away from the rider.

Dropout Code	DROPWHLC
Mudguard Code	WHYMG50
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68.0	74.5	537.3	288.0	663
M	69.0	74	563	288.0	686
L	69.0	73.5	586.8	288.0	677

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1066	445	30.9	130	431.8
M	1079.8	445	30.9	160	457.0
L	1099.8	445	30.9	180	495.0

# HIGHGATE E-BIKE COMPACT-FIT

SHIMANO  
STEPS

Fast Urban/Commuter STEPS e-Bike - eR7 Series

SRP £2,350

Product Code - WHIG(size)V1



<b>Colour</b>	Matt Granite with Silver / Magenta
<b>Sizes Available</b>	S,M,L
<b>Frame</b>	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
<b>Fork</b>	Whyte Straight Bladed 6061 Alloy, Flat Mount, Single Eyelets for Mudguards and Internal Cable Routing
<b>Rear Shock</b>	N/A
<b>Headset</b>	FSA No. 42 B CUP for 1 1/2" Lower and 1 1/8" Upper
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 32 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 32 Hole
<b>Spokes</b>	2.0mm, Black Stainless with Brass Nipples
<b>Rims</b>	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
<b>Tyres</b>	WTB Byway, TCS System, DNA Compound, Folding, 650 x 47c
<b>Shift Levers</b>	Shimano SL-T6000, Deore, 10 Speed with STEPS SC-E6010 Display
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	Shimano RD-T6000, Deore, SGS 10-Speed, Shadow
<b>Cassette</b>	Shimano CS-HG500, 11-34, 10 Speed
<b>Chain</b>	Shimano STEPS E6090, e-Bike Specific, 10 Speed
<b>Crankset</b>	STEP's E8050 Hollowtech, 44T with Double Sided Chain Guard, 10 Speed
<b>Bottom Bracket</b>	STEPS Drive Unit E-6100 with Speed Sensor and Magnet
<b>Seatpost</b>	Whyte 6061 Alloy, 1pcs 3D Forged, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Custom
<b>Bar</b>	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 620mm Wide
<b>Stem</b>	Whyte Alloy 6061, S 60mm, M 70mm, L 80mm
<b>Grips</b>	Whyte Custom Dual Density Lock-on
<b>Front Brakes</b>	Tektro Auriga, 160mm Rotor, Flat Mount, Internal Routing
<b>Rear Brakes</b>	Tektro Auriga, 160mm Rotor, Internal Routing
<b>Brake Levers</b>	Tektro Auriga
<b>Pedals</b>	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Highgate is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling of this compact fit bike.

The Highgate comes fitted with 650b wheels and 47c RoadPlus, WTB Byway tyres, offering greater comfort, better grip and increased security on rough urban roads and light off-road rides.

Integrated lighting, controlled from your STEPS head unit gives you fingertip control of your lights for year-round usage. These powerful lights make night riding easy but also give you the ability to use them as daytime running lights for extra visibility

<b>Dropout Code</b>	DROPWHRC
<b>Mudguard Code</b>	
<b>Shock Stroke and Sag Setting</b>	N/A
<b>Reducer Bush Widths</b>	N/A
<b>Eye to Eye Length</b>	N/A
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	553	263	720
M	69.5	74	579	263	741
L	70	73.5	605	263	774
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1067	450	27.2	140	393.7
M	1078	450	27.2	160	431.8
L	1095	450	27.2	180	469.9



# CLIFTON E-BIKE

SHIMANO  
STEPS

Fast Urban/Commuter STEPS e-Bike - e7 Series

SRP £2,350

Product Code - WCL(size)V1



<b>Colour</b>	Matt Granite with Silver / Blue
<b>Sizes Available</b>	M,L,XL
<b>Frame</b>	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
<b>Fork</b>	Whyte Straight Bladed 6061 Alloy, Flat Mount, Single Eyelets for Mudguards and Internal Cable Routing
<b>Rear Shock</b>	N/A
<b>Headset</b>	FSA No. 42 B CUP for 1 1/2" Lower and 1 1/8" Upper
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 32 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 32 Hole
<b>Spokes</b>	2.0mm, Black Stainless with Brass Nipples
<b>Rims</b>	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
<b>Tyres</b>	WTB Byway, TCS System, DNA Compound, Folding, 650 x 47c
<b>Shift Levers</b>	Shimano SL-T6000, Deore, 10 Speed with STEPS SC-E6010 Display
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	Shimano RD-T6000, Deore, SGS 10-Speed, Shadow
<b>Cassette</b>	Shimano CS-HG500, 11-34, 10 Speed
<b>Chain</b>	Shimano STEPS E6090, e-Bike Specific, 10 Speed
<b>Crankset</b>	STEP's E8050 Hollowtech, 44T with Double Sided Chain Guard, 10 Speed
<b>Bottom Bracket</b>	STEPS Drive Unit E-6100 with Speed Sensor and Magnet
<b>Seatpost</b>	Whyte 6061 Alloy, 1pcs 3D Forged, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
<b>Seat</b>	Whyte Custom, Triple Panel Design
<b>Bar</b>	Whyte Alloy 6061, 31.8mm, 25mm Rise, 620mm Wide
<b>Stem</b>	Whyte Alloy 6061, M 70mm, L 80mm, XL 90mm
<b>Grips</b>	Whyte Custom Dual Density Lock-on
<b>Front Brakes</b>	Tektro Auriga, 160mm Rotor, Flat Mount, Internal Routing
<b>Rear Brakes</b>	Tektro Auriga, 160mm Rotor, Internal Routing
<b>Brake Levers</b>	Tektro Auriga
<b>Pedals</b>	Fibre Reinforced Composite Platform

Using Shimano's STEPS e-Bike Drive Unit the Clifton is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

The Clifton comes fitted with 650b wheels and 47c RoadPlus, WTB Byway tyres, offering greater comfort, better grip and increased security on rough urban roads and light off-road rides.

Integrated lighting, controlled from your STEPS head unit gives you fingertip control of your lights for year-round usage. These powerful lights make night riding easy but also give you the ability to use them as daytime running lights for extra visibility

<b>Dropout Code</b>	DROPWHRC
<b>Mudguard Code</b>	
<b>Shock Stroke and Sag Setting</b>	N/A
<b>Reducer Bush Widths</b>	N/A
<b>Eye to Eye Length</b>	N/A
<b>Weight</b>	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	74.0	600	263	755
L	70	74.0	614	263	791
XL	70	74.0	634	263	822
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1095	450	27.2	165	445.3
L	1110	450	27.2	185	495.3
XL	1125	450	27.2	205	533.4

# CONISTON E-BIKE

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP - £2,299

Product Code - W18CON(size)



Colour	Matt Granite with Grey/Blue
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Tapered Steerer Tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with Eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture Protection
Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
Front Deraillieur	N/A
Rear Deraillieur	Shimano RD-T670, 10 Speed
Cassette	Shimano CS-HG500-10, 11-34, 10 Speed
Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
Bottom Bracket	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano M425, 160mm Rotor
Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
Brake Levers	Shimano M395
Pedals	Fibre Reinforced Composite Platform

Using Shimano’s STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance, plus Whyte’s very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0	74	600	273.5	749
M	66.0	73.5	625	273.5	776
L	66.0	73	650	273.5	806
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1152	458	30.9	115	406.4
M	1172	458	30.9	125	444.5
L	1192	458	30.9	135	495.3

# CONISTON WOMEN’S E-BIKE

All Terrain/Leisure STEPS e-Bike - eC7 Series

SRP - £2,299

Product Code - W18CONL(size)



Colour	Matt Granite with Bronze/Magenta
Sizes Available	S,M,L
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Tapered Steerer Tube, Coil Spring and Hydro Lockout
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Sandvik Stainless Steel with Brass Nipples
Rims	WTB SX-17 700c, 32 Hole, with Eyelets
Tyres	Vittoria Randonneur Trail 700 x 35c, with Double Shielding Puncture Protection
Shift Levers	Shimano SL-M6000, Deore, 10 Speed with STEPS SC-E6010 Display
Front Derailleur	N/A
Rear Derailleur	Shimano SLX T670, 10 Speed
Cassette	Shimano CS-HG500-10, 11-34, 10 Speed
Chain	Shimano STEPS E6090, e-Bike Specific, 10 Speed
Crankset	Crankarms for Shimano STEPS, 44T with Double Sided Chain Guard, 10 Speed
Bottom Bracket	STEPS Drive Unit E-6001 with Speed Sensor and Magnet
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte Alloy 6061, S 70mm, M 80mm, L 90mm
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano M425, 160mm Rotor
Rear Brakes	Shimano M425, 160mm Rotor, Internal Routing
Brake Levers	Shimano M395
Pedals	Fibre Reinforced Composite Platform

Using Shimano’s STEPS e-Bike Drive Unit the Coniston is able to take advantage of the pedal assist without compromising the weight distribution and therefore the handling.

Our custom built e-Bike frames are loaded with unique design touches and British weatherproof features - such as the forward facing seat slot, continuous outer cables that keep the gear shifts working smoother for longer and optional custom matched mud guards.

The ride-feel of these e-Bikes is second to none, with a fantastic quality lightweight frame which includes our uniquely shaped rear seat stays for comfort and performance plus Whyte’s very own take on All Terrain geometry.

Dropout Code	DROPWHRC
Mudguard Code	WHYMG46
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	TBC

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0	74.5	581	273.5	677
M	66.0	74	605	273.5	691
L	66.0	73.5	630	273.5	702
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1137	458	30.9	107	406.4
M	1157	458	30.9	115	444.5
L	1177	458	30.9	125	495.3