

LBHS-1790D SERIES

銀箭牌

Computer-controlled, High-speed,
Lockstitch Buttonholing Machine

高速電子平頭鎖眼機



應用範圍

APPLICATIONS

採用新型旋梭，實現美觀線跡效果。高效
節能、舒適縫紉！


Machine with the new type rotary hook
gives smooth operation and maximize
sewing work efficiency!



 SIRUBA

特點


FEATURES



三角縫 Purl stitch
平縫 Whip stitch

採用新型旋梭，防止斷線，收線不良等縫紉跟問題。低張力線跡美觀，三角縫和平縫都能很好呈現。

The new type rotary hook helps to prevent thread breaks, uneven winding and other related issues. With low tension, machine makes a quality finish for purl stitch and whip stitch.



代表性的縫紉圖案
Standard and round end patterns

細小圖案也能呈現美觀的線跡。Beautiful stitches even in small patterns. 針擺最小分辨率每個脈衝提高 0.05mm，防止切刀後切開部位起毛。各種縫紉圖案都能準確縫製。Achieve minimum resolution of needle zigzag with 0.05 increment to prevent thread with fraying ends. It is capable to work on different type of sewing patterns.

四種打底縫紉形狀 Four types of underlay patterns



1 矩形 Rectangle

有效防止面料的鬆弛，保持線跡的柔軟性同時，提高扣眼的強度。

This type of underlay stitch is effective in preventing seams from unraveling and giving extra strength on buttonhole stitches.



2 山行 Mountain line

有效防止面料的鬆弛，防止打結部位的褶皺產生，有效防止脫線。

The type of underlay stitch is effective in preventing seams from unraveling and preventing seam puckering.



3 交叉縫 Cross seam

有效防止脫線，可以在矩形或山行後使用。

This type of underlay stitch is effective in preventing seams from unraveling and used after rectangle and mountain line underlay stitches.



4 之字形 Zigzag

鎖眼線跡形成前事先縫合開孔部位，事先壓平起毛面料的絨毛，使扣眼外觀更美觀。

Zig-zag underlay stitch gives an extra support to the buttonhole area before stitching and cutting to make a nice and beautiful buttonhole.



規格

SPECIFICATIONS

型號 Model	用途 Application	mm	DP×5	mm	S.P.M. (Max)	縫製區域 (X×Y) Sewing area (X×Y)	KG
LBHS-1790DS	標準品 Standard	6.4~	#11 -	34.6	4200	X:5mm, Y:41mm (選配件最大可縫製 Max.Y:120mm) (Y:120mm is max for optional device)	100.5kg / 106kg
LBHS-1790DK	針織布 For Knit	31.8mm	#14				
標準縫紉圖案 Number Of Standard Patterns						21	
存儲圖案數 Max. Number Of Stored Memory Patterns						50	
最大針數 / 1 個程序 Max. Number Of Stitches Per Program						999	
數據存儲方式 Data Storage Method						經由 USB 埠 USB port	
電源 Power Supply						單相 Single-phase 110V/220V 三相 Three-phase 220V/380V	



高林股份有限公司
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

