

bolting constitutes



2% Cost 80% headache



Squirter® DTIs (Direct Tension Indicators) take the headache out of bolting.

Try Squirter® DTIs on your next bolting project....you'll never go back.

SQUIRTER® DTIs the best way to bolt! www.allfast.co.nz



HobSpec orange is good







bolting Squirter® DTIs



SQUIRTER® DTIs (Direct Tension Indicators) are DTIs with flexible silicone embedded in the depressions under the bumps. To use them, simply tighten the bolt until the calibrated amount of orange silicone appears from under the DTIs squirt locations, then stop tightening. That's all there is to it.

Now you can see when the bolt assembly is tensioned correctly.

Easier & Better than Turn-of-nut

You don't have to remember to stop turning at 1/3rd, 1/2, or 2/3rds turn. No match marking necessary.

Saves Time

Enables correct tensioning as fast as the wrench can be moved to the next bolt, because the operator can see when to stop.

Works with All Bolt Lengths

Even when the bolts are extremely short or long, SQUIRTER® DTIs show you when the correct tension has been achieved.

Safe for Inspectors

Once calibrated, inspectors can easily see the orange squirts, they don't have to climb to all the connections or carry around a torque wrench to know the connection has been completed. Instead of sampling only some of the DTIs with a feeler gauge, squirters allow virtually 100% inspection.

Features

- ✓ Manufactured to ASTM F959M.
- Conforms to AS4100-1990 15.4.1 (b) Direct-tensioning indication device.
- ✓ Lot trace number on each washer.
- Test Certificates available online www.hobson.com.au.
- ✓ Visual tension indication by Orange Silicon.
- Enables efficient & accurate installation of AS1252 assemblies.

Sizes Available

M12

M16

M20

M22

M24

M27 M30

M36

Fabricators like them:

"They're easy and I know that I did it right."

Building certifiers like them:

"They're accurate, no torque wrenches or feeler gauges."

Project Managers like them:

"They're fast, we got the bolting approved in record time."

Since 1935

....because quality matters



Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.