

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

CARBON DIOXIDE, LIQUID

Synonyms

CARBONIC ACID; CARBON DIOXIDE LIQUID; CARBON DIOXIDE, REFRIGERATED LIQUID;
CARBONIC ANHYDRIDE, REFRIGERATED LIQUID; UN 2187; CO₂

Chemical Family inorganic liquid **Product Description**

Classification determined in accordance with Compressed Gas Association standards.

Product Use industrial. **Restrictions on Use** None known.

Details of the supplier of the safety data sheet

Lake Welding Supplies, Inc.
1415 W Ave A
Belle Glade, FL 33430
General Information: 561-996-6666
Emergency #: 1-800-633-8253 (PERS)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Gases Under Pressure - Refrigerated liquefied gas

Simple Asphyxiant

GHS Label Elements

Symbol(s)



Signal Word

Warning

Hazard Statement(s)

Contains refrigerated gas; may cause cryogenic burns or injury.

May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

Prevention

Wear cold insulating gloves/face shield/eye protection.

Response

Thaw frosted parts with lukewarm water. Do not rub affected area.

Get immediate medical advice/attention.

Storage

Store in a well-ventilated place. **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

May cause frostbite upon sudden release of liquefied gas.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
124-38-9	Carbon dioxide	100

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115°F; 41-46°C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute

May cause cryogenic burns, frostbite

Delayed no information on significant adverse effects.

Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use extinguishing agents appropriate for surrounding fire.

Unsuitable Extinguishing Media

Do not direct water at source of leak or safety devices; icing may occur.

Special Hazards Arising from the Chemical

Negligible fire hazard. Containers may rupture or explode if exposed to heat.

Hazardous Combustion Products

Oxides of carbon, Oxygen

Fire Fighting Measures

Move container from fire area if it can be done without risk. Damaged cylinders should be handled only by specialists. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Stay away from the ends of tanks. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Use extinguishing agents appropriate for surrounding fire. Cool containers with water spray until well after the fire is out. Do not get water directly on material. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. **Special Protective Equipment and Precautions for Firefighters**

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Do not touch or walk through spilled material. Stop leak if possible without personal risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Prevent entry into sewers, drains, ditches, underground or confined spaces and waterways. Damaged cylinders should be handled only by specialists.

Environmental Precautions

Avoid release to the environment. Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Wear cold insulating gloves/face shield/eye protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Conditions for Safe Storage, Including any Incompatibilities Store in a well-ventilated place.

Store in a well-ventilated area. Keep container tightly closed. Keep locked up. Store and handle in accordance with all current regulations and standards. Keep container tightly closed. Keep locked up. Protect from physical damage. Store in a well-ventilated area. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances. **Incompatible Materials**

combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases, potassium, sodium, ethyleneimine

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Carbon dioxide	124-38-9
ACGIH:	5000 ppm TWA
	30000 ppm STEL
NIOSH:	5000 ppm TWA ; 9000 mg/m ³ TWA
	30000 ppm STEL ; 54000 mg/m ³ STEL
	40000 ppm IDLH
Europe:	5000 ppm TWA ; 9000 mg/m ³ TWA
OSHA (US):	5000 ppm TWA ; 9000 mg/m ³ TWA
Mexico:	5000 ppm TWA [VLE-PPT]

	30000 ppm STEL [PPT-CT]
--	--------------------------

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI) There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Respiratory Protection

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA. 40,000 ppm. Any supplied-air respirator. Any self-contained breathing apparatus with a full facepiece. Emergency or planned entry into unknown concentrations or IDLH conditions -. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode. Escape -. Any appropriate escape-type, self-contained breathing apparatus.

Glove Recommendations Wear appropriate protective, cold insulating clothing.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	colorless gas	Physical State	gas
Odor	odorless	Color	colorless
Odor Threshold	Not available	pH	Not available
Melting Point	-70 - -56.56 °C (-94 - -70 °F)	Boiling Point	-78.5 - -61.7 °C (-109 - -79 °F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	(None)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	569 mmHg @ -82 °C
Vapor Density (air=1)	1.5	Specific Gravity (water=1)	1.101 at -37 °C
Water Solubility	(Soluble)	Partition coefficient: noctanol/water	Not available

Viscosity	7.01E-05 Pa.s	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form	compressed, liquefied gas	Sublimation	-78.5 °C (-109 °F)
Taste	acid taste	Volatility by Volume	100 %
Molecular Formula	C-02	Molecular Weight	44.01
triple point	-56.6 °C		

Solvent Solubility

Soluble

Hydrocarbons, organic solvents, acetone, alcohol

Section 10 - STABILITY AND REACTIVITY

Reactivity

Containers may rupture or explode if exposed to heat.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions Will

not polymerize.

Conditions to Avoid

Protect from physical damage and heat. Containers may rupture or explode if exposed to heat. Avoid contact with water or moisture. **Incompatible Materials**

combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases, potassium, sodium, ethyleneimine

Hazardous decomposition products

Oxides of carbon, Oxygen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma, changes in blood pressure, difficulty breathing, tremors, weakness, Unconsciousness

Skin Contact

blisters, frostbite

Eye

Contact frostbite,

blurred vision

Ingestion frostbite

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

Product Toxicity Data

Acute Toxicity Estimate No data available.

Immediate Effects

May cause cryogenic burns, frostbite

Delayed Effects no information on significant adverse effects.

Irritation/Corrosivity Data May cause cryogenic burns.

Respiratory Sensitization No data available.

Dermal Sensitization No data available.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Germ Cell Mutagenicity No data available.

Tumorigenic Data

No data available

Reproductive Toxicity No data available.

Specific Target Organ Toxicity - Single Exposure No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure No target organs identified.

Aspiration hazard Not applicable.

Medical Conditions Aggravated by Exposure heart or cardiovascular disorders, respiratory disorders

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

Persistence and Degradability

No data available.

Bioaccumulative Potential No data available.

Mobility No data available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: CARBON DIOXIDE, REFRIGERATED LIQUID

Hazard Class: 2.2

UN/NA #: UN2187

Required Label(s): 2.2

IMDG Information:

Shipping Name: CARBON DIOXIDE, REFRIGERATED LIQUID

Hazard Class: 2.2

UN#: UN2187

Required Label(s): 2.2

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Gas Under Pressure; Simple Asphyxiant

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Carbon dioxide	124-38-9	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Component Analysis - Inventory

Carbon dioxide (124-38-9)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

KR - REACH CCA	MX	NZ	PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 3 Fire: 0 Instability: 0 Other: SA

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Updated: 02/03/2017

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne - Nonspecific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information Disclaimer:

Continental Carbonic Products, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Continental Carbonic Products, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.