

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Propane – UN1075 Specific

Synonyms

INDUSTRIAL PROPANE; MTG MSDS 76; N-PROPANE; DIMETHYLMETHANE; PROPYL HYDRIDE; R290; PROPYLHYDRIDE; LIQUEFIED PETROLEUM GAS; LPG; >96% NATURAL GRADE; >99.9% PURE GRADE; UN 1978; C3H8

Chemical Family

Hydrocarbons, aliphatic

Product Description

Classification determined in accordance with Compressed Gas Association standards. **Product Use**

Industrial and Specialty Gas Applications.

Restrictions on Use None known.

Details of the supplier of the safety data sheet

Lake Welding Supplies, Inc.

1415 W Ave A

Belle Glade, FL 33430

General Information: 1-561-996-6666

Emergency #: 1-800-633-8253 (PERS)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Gases - Category 1

Gases Under Pressure - Liquefied gas

Simple Asphyxiant

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.

Storage

Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

May cause frostbite upon sudden release of liquefied gas.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
74-98-6	Propane	>96

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115°F; 41-46°C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention. **Eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Then get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute

frostbite, suffocation

Delayed

No information on significant adverse effects.

Indication of any immediate medical attention and special treatment needed

For inhalation, consider oxygen. Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media Suitable

Extinguishing Media

regular dry chemical, carbon dioxide, Large fires: water spray or fog **Unsuitable**

Extinguishing Media

Do not direct water at source of leak or safety devices; icing may occur.

Special Hazards Arising from the Chemical

Severe fire hazard. Severe explosion hazard. Gas/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Hazardous Combustion Products

Oxides of carbon

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Evacuation radius: 1600 meters (1 mile). Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Avoid heat, flames, sparks and other sources of ignition. All equipment used when handling the product must be grounded. Remove sources of ignition. Do not touch or walk through spilled material. Stop leak if possible without personal risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Do not direct water at spill or source of leak. Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Close valve after each use and when empty. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. **Conditions for Safe Storage,**

Including any Incompatibilities Protect from sunlight. Store in a well-ventilated place.

Store and handle in accordance with all current regulations and standards. Keep container tightly closed. Grounding and bonding required. Keep separated from incompatible substances. **Incompatible Materials** combustible materials, oxidizing materials

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Propane	74-98-6
ACGIH:	(See Appendix F: Minimal Oxygen Content, explosion hazard)
NIOSH:	1000 ppm TWA ; 1800 mg/m ³ TWA
	2100 ppm IDLH (10% LEL)

OSHA (US):	1000 ppm TWA ; 1800 mg/m ³ TWA
Mexico:	1000 ppm TWA [VLE-PPT]

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI) There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits. Use a back flow preventive device in the piping.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. **Skin Protection**

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Respiratory Protection

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA. 2100 ppm. Any supplied-air respirator. Any self-contained breathing apparatus with a full facepiece. Emergency or planned entry into unknown concentrations or IDLH conditions -. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode. Escape -. Any appropriate escape-type, self-contained breathing apparatus. **Glove Recommendations** Wear insulated gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	colorless gas	Physical State	gas
Odor	gasoline odor	Color	colorless
Odor Threshold	5000 - 20000 ppm	pH	Not available
Melting Point	-190 °C (-310 °F)	Boiling Point	-40 °C (-40 °F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Flammable gas
Autoignition Temperature	450 °C (842 °F)	Flash Point	-105 °C (-157 °F)
Lower Explosive Limit	2.1 %	Decomposition temperature	Not available

Upper Explosive Limit	9.5 % Vapor	Pressure	6398 mmHg @ 21.1 °C
Vapor Density (air=1)	1.55	Specific Gravity (water=1)	0.5853 at -45 °C
Water Solubility	(Very slightly soluble)	Partition coefficient: noctanol/water	Not available
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Log KOW	2.36	Physical Form	Liquefied gas
Molecular Formula	C-H3-C-H2-C-H3	Molecular Weight	44.11
Critical Temperature	96.74 °C		

Solvent Solubility

Soluble

absolute alcohol, ether, chloroform, benzene, turpentine

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions Will

not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat. **Incompatible Materials**

combustible materials, oxidizing materials

Hazardous decomposition products

Oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

nausea, suffocation, vomiting, irregular heartbeat, headache, drowsiness, dizziness, disorientation, mood swings, loss of coordination, convulsions, unconsciousness, coma **Skin Contact**

blisters, frostbite **Eye**

Contact frostbite,

blurred vision

Ingestion

ingestion of a gas is unlikely

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Propane (74-98-6)

Inhalation LC50 Rat >800000 ppm 15 min

Product Toxicity Data

Acute Toxicity Estimate

Inhalation - Gas	> 20000 ppm
------------------	-------------

Immediate Effects frostbite, suffocation

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data No data

available. **Respiratory Sensitization** No

data available. **Dermal Sensitization** No

data available.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Germ Cell Mutagenicity No

data available.

Tumorigenic Data

No data available

Reproductive Toxicity No

data available.

Specific Target Organ Toxicity - Single Exposure No

target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified. **Aspiration hazard** Not

applicable.

Medical Conditions Aggravated by Exposure None

known.

Additional Data

Stimulants such as epinephrine may induce ventricular fibrillation.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOEL ecotoxicity data are available for this product's components.

Persistence and Degradability This material is expected to

biodegrade.

Bioaccumulative Potential

Bioconcentration potential in aquatic organisms is low based on a BCF value of 13.

Mobility

Expected to have moderate mobility in soil.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. **Component**

Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: PETROLEUM GASES, LIQUEFIED

Hazard Class: 2.1

UN/NA #: UN1075

Required Label(s): 2.1

IMDG Information:

Shipping Name: PETROLEUM GASES, LIQUEFIED

Hazard Class: 2.1

UN#: UN1075

Required Label(s): 2.1

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Gas Under Pressure; Simple Asphyxiant

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Propane	74-98-6	No	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Component Analysis - Inventory

Propane (74-98-6)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

KR - REACH CCA	MX	NZ	PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 4 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Preparation Date

New SDS: 10/09/2018

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne-Nonspecific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada);

NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information Disclaimer:

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether



Safety Data Sheet
Material Name: Propane – UN1075 Specific

compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.