

Motorized Curtain

https://www.smartcurtainmotor.com/

A Contact : Merry Email:merry@zebrago.cc &+8613760363649

About us

It has been focusing on the research and development and manufacturing of window decoration products, and now it has become a benchmark brand that leads China's curtain rails and curtain rods.

Products include curtain opening and closing motors, tubular motors and their control systems, electric accessories and other intelligent indoor sunshade and smart home products. Provide numerous building shading and home automation solutions for business offices, public buildings, hotels, villas and high-end apartments.

The company guarantees a long-term stable supply of high-quality products with systematic, standardized and standardized operations. The products sell well in all provinces, municipalities directly under the central government, autonomous regions, cities and rural areas, and are exported to Southeast Asia, the Middle East, Europe and the United States and other markets. The product quality and professional services are well received and favored by customers.

As a leader in the curtain motor industry, we have been with you!









Open & Close Curtain package box with Fabric


A complete set of motorized curtains



Single- channel double-control emitter



Motorized Curtain Track System



 Motorized curtain track system including curtain motor, freely assembled curtain track, RF433 remote control & complete set accessories.

Track size: 2.2m, 3.2m, 4.2m, 5.2m, 6.2m, 7.2m, 8.2m
2.2m track set for window width < 2.16m
3.2m track set for window width 2.16m-3.16m
4.2m track set for window width 3.16m-4.16m
5.2m track set for window width 4.16m-5.16m
6.2m track set for window width 5.16m-6.16m
7.2m track set for window width 6.16m-7.16m
8.2m track set for window width 7.16m-8.16m

• 90°/ 135° track connectors available

Single track / double track optional

- Single open / double open (center open) optional
- Ceiling mount / wall mount optional
- Multiple controls: Handheld remote control, wall emitter control, switch control, smartphone control, voice control.

Motor Type:

Tuya WiFi/Tuya Zigbee/RS485/Z-wave/KNX/4-Wire/5-Wire etc.
 CN, EU, UK & US plug optional.


Motor Features:

- Manual start
- Manual operation if power cut
- Middle position set
- Automatically set the memory running point
- Tuya WiFi/Tuya Zigbee/RS485/Z-wave/KNX/5-Wire curtain motors support RF433 remote control. 4-wire motor no remote control.
- Only Tuya WiFi / Tuya Zigbee curtain motors work with Alexa & Google Home Voice Control & SmartLife APP.

Motor Specifications					
Rated Torque	1.2N.m/2.0N.m				
Rated Voltage	AC100-240V, 50/60Hz				
Rated Power	40W/80W				
Max Load	50KG/120KG				
Radio Distance	>50M				
Protection Class	IP20				

New version

Old version







Tuya WiFi Curtain Motor Tuya Zigbee Curtain Motor




KNX Curtain Motor



Z-wave Curtain Motor




5-wire Curtain Motor



Roller Blinds with Fabric

A complete set of motorized roller blinds



Electric Zebra Blinds



The above three kinds of curtains are suitable for three different types of motors.



25mm Tubular Motor





Roller Blinds

25mm Tuya WiFi / Zigbee Tubular Motor






- Rated Torque : 0.8N.m / 1.5N.m
- Rated Voltage : 100-240V, 50/60Hz
- With crown & adapte for 38mm groove tube.
- Suitable for zebra blind / roller blind / Shangri-La blind etc.
- Super quiet & precise motor

35mm Tuya WiFi / Zigbee Tubular Motor

E: Electronic Radio

Ø35 Electronic Limit + Built-in Wireless Receiver + The Third Limit + Jogging & Tilt Function + **Resistance And Stop Function**



- / roman blinds / projection Screen / honeycomb blinds / pleated blinds

Dimension Drawing



35mm Tuya WiFi Tubular Motor Technical Parameters

230V / 50Hz IP44								
Model Number	Rated Torque (N.m)	Rated Speed (rpm)	Motor Diameter (mm)	Rated Power (W)	Rated Current (A)	R unning Time (min)	L1/L2 Length (mm)	
Z-M35R-6/28	6	28	35	139	0.6	4	554/541	
Z-M35R-10/17	10	17	35	139	0.6	4	554/541	

120V / 60Hz IP44								
Model Number	Rated Torque (N.m)	Rated Speed (rpm)	Motor Diameter (mm)	Rated Power (W)	Rated Current (A)	R unning Time (min)	L1/L2 Length (mm)	
Z-M35R-6/33	6	33	35	128	1.06	4	554/541	
Z-M35R-10/21	10	21	35	128	1.06	4	554/541	



AC 120V/60HZ



Blue=Live White=Neutral Green=Earth

AC 230V/50HZ



Blue=Neutral Brown=Life Green/Yellow=Earth

45mm Tuya WiFi / Zigbee Tubular Motor

Ø45 E: Electronic Radio

Electronic Limit + Built-in Wireless Receiver + The Third Limit + Jogging & Tilt Function + Resistance And Stop Function



Dimension Drawing



45 mm Tuya WiFi Tubular Motor Technical Parameters

230V / 50Hz IP44								
Model Number	Rated Torque (N.m)	Rated Speed (rpm)	Motor Diameter (mm)	Rated Power (W)	Rated Current (A)	R unning Time (min)	L1/L2 Length (mm)	
Z-M45R-20/15	20	15	45	153	0.68	4	514/498	
Z-M45R-30/15	30	15	45	205	0.93	4	584/568	
Z-M45R-40/15	40	15	45	215	0.95	4	584/568	
Z-M45R-50/12	50	12	45	230	1.02	4	584/568	

120V / 60Hz IP44									
Model Number	Rated Torque (N.m)	Rated Speed (rpm)	Motor Diameter (mm)	Rated Power (W)	Rated Current (A)	R unning Time (min)	L1/L2 Length (mm)		
Z-M45R-20/19	20	19	45	214	1.85	4	514/498		
Z-M45R-30/13	30	13	45	213	1.83	4	584/568		
Z-M45R-40/13	40	13	45	235	1.95	4	584/568		
Z-M45R-50/13	50	13	45	270	2.30	4	584/568		



AC 120V/60HZ




Blue=Live White=Neutral Green=Earth

AC 230V/50HZ




Blue=Neutral Brown=Life Green/Yellow=Earth

A complete set of motorized roller blinds





Roman Blinds



Honeycomb Blinds




24E Electronic limit blinds motor (The above curtains can be used)

24E Electronic limit blinds motor









Motorized Venetian Blinds

Motorized Pleated blinds

Motorized Motorized Honeycomb blinds Roman blinds



24 tubular motor has the characteristics of small body, low noise, constant speed, etc. It is mainly used for electric blinds, Motorized roman blinds, motorized honeycomb blinds and electric ceiling honeycomb blinds, etc. It can be equipped with external intelligent mody le to achieve intelligent home system control; 24 The motor adopts external power adapter for power supply, electronic limit, easy and convenient debugging

- Constant speed function

Motor version



24 dual output shaft motor

• Wireless remote control • Electric limit • Connect with smart home system

Motor parameter								
Item No.	Input voltage	Max power	Rated frequency	Rated torque	Rated RPM	Working noise	Max load	
ZM24E-08/33-1	12VDC	12W	/	0.8N.m	33PRM	32- 35dB	6KG	
ZM24E-1/33-2	12VDC	12W	/	1N.m	33PRM	32- 35dB	8KG	

• Difference between single output shaft motor and dual output shaft motor

Single output shaft motor: single output shaft motor has only one side output head, it is installed on the side of the top slot, its body is short, suitable for the width of 0.5~1.5 meters of blinds, honeycomb blids, Roman blinds, etc., the maximum load is 6KG.

Dual output shaft motor: dual output shaft motor has bilateral output head, it is installed in the middle of the top slot, it has the characteristics of uniform and stable force, its body is longer than the single output, suitable for the width of ≥0.8m blinds, honeycomb blids, Roman blinds, etc., the maximum load is 8KG.

• Motor standard accessories

- 1、 Motor bracket*2
- 2、4-corner long shaft sleeve (single output*1, double output*2)
- 3、6-corner long shaft sleeve (single output*1, double output*2)
- 4、 fixing ring*2
- 5、Power adapter*1 (input voltage : 90-240V AC, output voltage : 12V DC current : 1A)



24 Motor power adapter






Motorized curtain matching fabric

One-stop shopping saves the trouble of separate configuration,

The zebrago curtain factory has a complete range of fabrics and is displayed as part of the hot selling fabrics If you have other requirements for different fabrics, you can contact us by email.







Opening and closing curtain fabric sheer curtain fabric



XY138-3







XY158-7

XY158-1

XY158-11


XY148-1

XY148-8





Opening and closing curtain fabric






Roller Blinds

- Shade Fabric
- Semi Shade Fabric




Sunshine Fabric







Hemp shade





Dream hemp shade

Double-coated shade



Pocked Silver Shade





Hemp Semi Shade

Float shade



Honeycomb Blinds

- Shade Fabric
- Semi Shade Fabric



JLL68-7



JLL68-29










JLL68-8

JLL68-10





JLL68-30

JLL68-31

JLL68-38



Zebra Blinds

- Shade Fabric
- Semi Shade Fabric



ZE-01







ZE-02

ZE-03








Shangrila Blinds


- Shade Fabric - Semi Shade Fabric








SH-05





SH-06



How to measure your window size for a curtain

Electric Roller Blind Installation Solution

01/



window side push Can be installed inside, can be installed externally

02/



window push out

Can be installed inside, can be installed externally

Installation Recommendations

03/



window push out Not recommended for installation



Internal requirements:

Width - measure the length of A. B and C,

take the smaller value - 1CM

Height - measure length of H1, H2

Note: The depth of the window should not be less than 10CM Interior features:

Space saving, slightly light transmission on both sides



Exterior

Internal requirements: Width - Length measuring C + 20CM Height - Length of measure D + 20CM Interior features: shading effect is good

Electric opening and closing curtain installation scheme

The ceiling does not cover the wall



Measurement method Width: Measure the length of A + 60CM Height: measure the length of the H

power reserve upper left or upper right corner of the window

Precautions During renovation, it is recommended to use the top of the window 5CM solid wood or 2 layers of 1.5CM Blockboard, gypsum board wall cannot be installed



Measurement method Width: measure A's length Height: measure the length of the H

power reserve upper left or upper right corner of the window

Precautions During renovation, it is recommended to use the top of the window 5CM solid wood or 2 layers of 1.5CM Blockboard, gypsum board wall cannot be installed

Top mounted on the wall

More Products under Development Thanks for Reading

Updated on 2022/01