

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

BRIGHT COAT - HULL DE-STAINER

Revision 0
Revision date 2015-08-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	BRIGHT COAT
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	August race worldwide Ltd
Address	UNIT 3 THE DART BUILDING DARTSIDE QUAY Galmpton Devon TQ50GA
Web	www.august-race.com
Telephone	+44 (0)1803 224363
Fax	N/A
Email	info@august-race.com
Email address of the competent person	info@august-race.com

1.4. Emergency telephone number


Emergency telephone number	01803 224363
Company	AUGUST RACE WORLDWIDE LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R21/22 Xi; R36 Symbols: Xn: Harmful.
Main hazards	Harmful in contact with skin and if swallowed. Irritating to eyes.
2.1.2. Classification - EC 1272/2008	Skin Corr. 1A: H314;

2.2. Label elements

Hazard pictograms	
Signal Word Hazard	Danger
Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Precautionary Statement:	P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

BRIGHT COAT - HULL DE-STAINER

Revision 0
Revision date 2015-08-12

2.2. Label elements

Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P363 - Wash contaminated clothing
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Oxalic acid	607-006-00-8	144-62-7	205-634-3		1 - 10%	Xn; R21/22	
BRIQUEST ADPA 60		2809-21-4		01-2119510391-53-0002		C; R34	
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0	01-2119456809-23			
Formaldehyde...% (Formaldehyde)	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. Cat. 3; R40 T; R23/24/25 C; R34 R43	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER							
SODIUM LAUROYL SARCOSINATE		137-16-6	205-281-5			Eye Dam. 1: H318; Acute Tox. 4: H332;	
SODIUM XYLENE SULPHONATE		1300-72-7				Eye Irrit. 2: H319;	
Oxalic acid	607-006-00-8	144-62-7	205-634-3		1 - 10%	Acute Tox. 4: H312; Acute Tox. 4: H302;	
BRIQUEST ADPA 60		2809-21-4		01-2119510391-53-0002		Met. Corr. 1: H290; Eye Dam. 1: H318;	
XANTHAN GUM		11138-66-2	234-394-2				
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0	01-2119456809-23			
ALCOHOL ETHOXYLATE		68439-46-3				Acute Tox. 4: H302; Eye Dam. 1: H318;	
Formaldehyde...% (Formaldehyde)	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. 1B: H350; Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; Skin Corr. 1B: H314; Skin Sens. 1: H317;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	No irritation expected. No Significant Hazard.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

BRIGHT COAT - HULL DE-STAINER

Revision 0

Revision date 2015-08-12

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon dioxide (CO2).
--	-----------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Wear suitable protective equipment. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

BRIGHT COAT - HULL DE-STAINER

Revision 0

Revision date 2015-08-12

8.1.1. Exposure Limit Values

Formaldehyde...% (Formaldehyde)	WEL 8-hr limit ppm: 2 WEL 15 min limit ppm: 2 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 2.5 WEL 15 min limit mg/m3: 2.5 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Oxalic acid	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 1 WEL 15 min limit mg/m3: 2 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
PROPYLENE GLYCOL (Propane-1,2-diol particulates)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)	WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 474 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.

No data is available on this product.

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Not normally required.
8.2.2. Individual protection measures	Wear suitable protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
n	Not normally required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aqueous solution
Colour	Various
Odour	Mild
pH	1
Relative density	1.03 - 1.06
Solubility	Soluble in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

BRIGHT COAT - HULL DE-STAINER

Revision 0
Revision date 2015-08-12

11.1. Information on toxicological effects

Skin corrosion/irritation	May cause severe irritation to skin, eyes and mucous membranes.
---------------------------	---

SECTION 12: Ecological information

12.2. Persistence and degradability

	DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts.
--	---

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.2. Chemical safety assessment

	No chemical Safety assessment has been carried out by the supplier.
--	---

SECTION 16: Other information

Other information

Text of risk phrases in Section 3	R21/22 - Harmful in contact with skin and if swallowed. R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed. R34 - Causes burns. R40 - Limited evidence of a carcinogenic effect. R43 - May cause sensitisation by skin contact.
Text of Hazard Statements in Section 3	Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H332 - Harmful if inhaled. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H302 - Harmful if swallowed.

BRIGHT COAT - HULL DE-STAINER

Revision 0

Revision date 2015-08-12

Other information

Acute Tox. 4: H312 - Harmful in contact with skin.
Met. Corr. 1: H290 - May be corrosive to metals.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.