# PRODUCT DATASHEET
## DST STICK 14 W/4000 220...240 V B22d

### OSRAM DULUXSTAR STICK | Compact fluorescent integrated, stick shape

#### AREAS OF APPLICATION

– General illumination
– Domestic applications
– Wherever compact and efficient lamps are needed
– Wherever cold light colors are needed
– Outdoor use in enclosed and ventilated luminaires only

#### PRODUCT BENEFITS

– Fast return on investment
– Up to 80 % less energy consumption compared with ordinary light bulbs

#### PRODUCT FEATURES

– Available in 2 light colors: 827 and 865
– Also available in activating light color LUMILUX Cool Daylight
– Average life: up to 8,000 h

---

## TECHNICAL DATA

### Electrical data

| | |
|---|---|
| **Nominal wattage** | 14.00 W |
| **Rated wattage** | 14.00 W |
| **Nominal voltage** | 220...240 V |
| **Power factor λ** | ≥ 0.55 |
| **Nominal current** | 0.14 A |
| **Operating frequency** | 50...60 Hz |

### Photometrical data

| | |
|---|---|
| **Nominal luminous flux** | 800 lm |
| **Rated luminous flux** | 800 lm |
| **Rated color temperature** | 4000 K |
| **Light color** | 4000 |
| **Color rendering index Ra** | ≥80 |
| **Color temperature** | 4000 K |
| **Luminous flux** | 800 lm |
| **Color rendering index Ra** | ≥80 |

### Light technical data

| | |
|---|---|
| **Starting time** | ≤ 0.3 s |

### Dimensions & weight

| | |
|---|---|
| **Maximum diameter** | 41.0 mm |
| **Overall length** | 133.0 mm |
| **Product weight** | 65.00 g |
| **Length** | 133.0 mm |

### Lifespan

| | |
|---|---|
| **Nominal lamp life time** | 10000 h |
| **Rated lamp life time** | 10000 h |
| **Number of switching cycles** | 10000 |

### Additional product data

| | |
|---|---|
| **Base (standard designation)** | B22d |
| **Mercury content** | 2.0 mg |
| **Show WEEE picto** | Yes |

### Certificates & standards

| | |
|---|---|
| **Cleaning instruction in case of breakage** | What to do if a lamp containing mercury breaks? |

---

## SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp
Not for use with external dimmers or electronic switches.

## LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---|---|---|---|---|---|
| 4052899449534 | DST STICK 14 W/4000 220...240 V B22d | Shipping carton box 10 | 226 mm x 95 mm x 156 mm | 3.35 dm³ | 921.00 g |
| 4052899449534 | DST STICK 14 W/4000 220...240 V B22d | Shipping carton box 10 | 226 mm x 95 mm x 156 mm | 3.35 dm³ | 923.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

—