

# **PRODUCT DATASHEET**DST STICK 20 W/840 B22D

OSRAM DULUXSTAR COMPACT | CFLi, stick shape, with screw base





# **TECHNICAL DATA**

# Electrical data

Nominal wattage	20.00 W
Rated wattage	20.00 W
Nominal voltage	220240 V
Power factor λ	≥ 0.50
Nominal current	0.2 A
Operating frequency	5060 Hz


# Photometrical data

Nominal luminous flux	1180 lm
Rated luminous flux	1180 lm
Rated color temperature	4000 K
Light color	4000
Light color (designation)	LUMILUX Cool White
Color rendering index Ra	≥80
Color temperature	4000 K
Luminous flux	1180 lm
Color rendering index Ra	≥80
Color rendering group	1B

# Light technical data

Warm-up time (60 %)	≤ 60.00 s	
Starting time	≤ 2.0 s	

# Dimensions & weight



Maximum diameter	49.0 mm
Overall length	159.0 mm
Product weight	85.00 g

|--|

# Lifespan

Nominal lamp life time	8000 h	
Rated lamp life time	8000 h	
Number of switching cycles	4000	

## Additional product data

Base (standard designation)	B22d	
Mercury content	2.0 mg	
Show WEEE picto	Yes	

## Capabilities

Dim	mable	No

#### Certificates & standards

Cleaning instruction in case of breakage	What to do if a lamp containing mercury breaks?
--	---

## Country-specific categorizations

ILCOS	FBT-20/40/1B-220/240-B22D
-------	---------------------------

#### **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899262997	DST STICK 20 W/840 B22D	Shipping carton box 20	254 mm x 204 mm x 172 mm	8.91 dm³	2415.00 g
4052899262997	DST STICK 20 W/840 B22D	Shipping carton box 10	268 mm x 111 mm x 179 mm	5.32 dm <sup>3</sup>	1112.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.