

# **PRODUCT DATASHEET** DULUX D 13 W/840 GX23-2

## OSRAM DULUX D | CFLni, 2 tubes, with 2-pin base for CCG operation



## **AREAS OF APPLICATION**

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

## **PRODUCT BENEFITS**

- Extremly economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

#### **PRODUCT FEATURES**

- Average life: 10,000 h
- Color rendering index R<sub>a</sub>: 80...89
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



## **TECHNICAL DATA**


## Electrical data


| Nominal wattage | 13.00 W |
|-----------------|---------|
| Rated wattage   | 13.00 W |


#### Photometrical data

| Nominal luminous flux     | 900 lm             |
|---------------------------|--------------------|
| Light color (designation) | LUMILUX Cool White |
| Luminous flux at 25 °C    | 900 lm             |
| Rated luminous flux       | 900 lm             |
| Rated color temperature   | 4000 K             |
| Color rendering index Ra  | >78                |
| Rated LLMF at 2,000 h     | 0.85               |
| Rated LLMF at 4,000 h     | 0.78               |
| Rated LLMF at 6,000 h     | 0.76               |
| Rated LLMF at 8,000 h     | 0.75               |
| Color temperature         | 4000 К             |
| Luminous flux             | 900 lm             |
| Color rendering index Ra  | >78                |

## - Dimensions & weight







| Diameter                                    | 11.0 mm   |
|---|-----------|
| Overall length                              | 136.0 mm  |
| Length                                      | 138.0 mm  |
| Length acc. to IEC standard                 | 130 mm    |
| Length with base excl. base pins/connection | 115.00 mm |
| Outer bulb                                  | T11       |
| Maximum diameter                            | 11.0 mm   |

#### Lifespan

| Nominal lamp life time                | 8000 h                |  |
|---------------------------------------|-----------------------|--|
| Rated lamp life time                  | 8000 h                |  |
| Rated lamp survival factor at 2,000 h | 0.99                  |  |
| Rated lamp survival factor at 4,000 h | 0.99                  |  |
| Rated lamp survival factor at 6,000 h | 0.95                  |  |
| Rated lamp survival factor at 8,000 h | 0.81                  |  |
| Operation mode LLMF/LSF               | 50 Hz                 |  |
| Lifespan                              | 10000 h <sup>1)</sup> |  |
|                                       |                       |  |

<sup>1)</sup> With CCG/LLCG

#### Additional product data

| Base (standard designation) | G24d-1 |
|-----------------------------|--------|
| Mercury content             | 5.0 mg |

#### Capabilities

| Suitable for indoor | Yes |
|---------------------|-----|
|---------------------|-----|

#### Certificates & standards

| Energy efficiency class | A            |
|-------------------------|--------------|
| Energy consumption      | 17 kWh/1000h |
| Energy efficiency class | A            |

#### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on conventional control gear

## **SAFETY ADVICE**

In case of lamp breakage: www.ledvance.com/brokenlamp

#### LOGISTICAL DATA

| Product code  | Product description        | Packaging unit<br>(Pieces/Unit) | Dimensions (length x<br>width x height) | Volume   | Gross weight |
|---------------|----------------------------|---------------------------------|---|----------|--------------|
| 4008321830814 | DULUX D 13 W/840<br>GX23-2 | Shipping carton box<br>10       | 187 mm x 81 mm x<br>163 mm              | 2.47 dm³ | 583.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.