

PRODUCT DATASHEET L 36 W/4000

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases





June 12, 2018, 14:05:30 L 36 W/4000

TECHNICAL DATA

Electrical data


Nominal voltage	230 V
Nominal wattage	36.00 W
Rated wattage	36.00 W
Lamp current	0.43 A

Photometrical data

Rated luminous flux	2850 lm
Light color	4000
Rated color temperature	4000 К
Nominal luminous flux	2850 lm
Color temperature	4000 К
Luminous flux	2850 lm

Dimensions & weight





IEC 7004-51 DIN 49653 T1

Tube diameter	26 mm	
Length	1200 mm	
Length with base excl. base pins/connection	1200.00 mm	
Diameter	26.0 mm	

Lifespan

Service life	5000 h
Lifespan	13000 h ¹⁾
Rated lamp life time	13000 h
Nominal lamp life time	13000 h


 $^{1)}$ With CCG/LLCG $\,$

Additional product data

Base (standard designation) G13	C 4 7
---------------------------------	-------

PRODUCT DATASHEET

Mercury content	8.0 mg
Show WEEE picto	Yes



Circuit diagram

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321959713	L 36 W/4000	Shipping carton box 25	142 mm x 145 mm x 1242 mm	25.57 dm³	5450.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.