# SAFETY DATA SHEET

# SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID:	DOUBLE B BLOOMCO QUICK DETAIL			
Product Name:	DOUBLE B BLOOMCO QUICK DETAIL			
Revision Date:	Feb 06, 2019			
Version:	1.0			
Distributor's Name:	DOUBLE B AUTOMOTIVE			
Address:	5035 N SUE RD - B-1 - BURLINGTON, ON L7L5V2			
Emergency Phone:	1-800-535-5053			
Information Phone Number: (905) 332-8070				

Date Printed:Feb 27, 2019Supersedes Date:N.A.

## Product/Recommended Uses:

Fax:

# **SECTION 2) HAZARDS IDENTIFICATION**

# Classification

Aerosols Category 1 Aspiration Hazard - Category 1 Carcinogenicity - Category 1B Eye Irritation - Category 2 Gases Under Pressure Liquefied Gas Germ Cell Mutagenicity - Category 1B Reproductive Toxicity - Category 2 Skin Irritation - Category 2 Specific Target Organ Toxicity - Repeated Exposure - Category 2 Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3 Pictograms Signal Word Danger Hazardous Statements - Physical H222 - Extremely flammable aerosol H280 - Contains gas under pressure; may explode if heated **Hazardous Statements - Health** H304 - May be fatal if swallowed and enters airways H350 - May cause cancer. H319 - Causes serious eye irritation

- H340 May cause genetic defects.
- H361 Suspected of damaging fertility or the unborn child.
- H315 Causes skin irritation

DOUBLE B BLOOMCO QUICK DETAIL

H373 - May cause damage to organs through prolonged or repeated exposure. H336 - May cause drowsiness or dizziness

# **Precautionary Statements - General**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

#### **Precautionary Statements - Prevention**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves, protective clothing, eye protection, and face protection.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe mist, vapors, or spray.
- P271 Use only outdoors or in a well-ventilated area.

#### **Precautionary Statements - Response**

P308 + P313 - IF exposed or concerned: Get medical attention.

P314 - Get medical attention if you feel unwell.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

# **Precautionary Statements - Storage**

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

#### **Precautionary Statements - Disposal**

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

# SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight				
0064742-49-0	NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	25% - 50%				
0000110-54-3	n-HEXANE	25% - 50%				
0000074-98-6	PROPANE	10% - 20%				
0000106-97-8	BUTANE	5% - 10%				
0063148-62-9	POLYDIMETHYLSILOXANE	5% - 10%				
Specific chemical identit	Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.					

# **SECTION 4) FIRST-AID MEASURES**

#### Inhalation

Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

#### **Eye Contact**

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

## Skin Contact

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

## Ingestion

Ingestion is not a likely route of exposure.

If ingestion occurs rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

# **SECTION 5) FIRE-FIGHTING MEASURES**

# Suitable Extinguishing Media

Foam, alcohol foam, carbon dioxide, dry chemical, water fog.

#### **Unsuitable Extinguishing Media**

Water spray may be ineffective.

#### Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

#### **Fire-Fighting Procedures**

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

#### **Special Protective Actions**

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure**

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

#### **Recommended Equipment**

Clean up with an absorbent material and place in closed containers for disposal.

#### **Personal Precautions**

Wear safety glasses and gloves.

#### **Environmental Precautions**

Stop spill/release if it can be done safely.

# **SECTION 7) HANDLING AND STORAGE**

# General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in

eyes. Do not take internally.

# **Ventilation Requirements**

Use in a well-ventilated place.

## **Storage Room Requirements**

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

# **SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION**

# **Eye Protection**

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

#### **Skin Protection**

Use solvent-resistant protective gloves for prolonged or repeated contact.

## **Respiratory Protection**

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

## **Appropriate Engineering Controls**

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinog en	OSHA Skin designati on	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinog en
BUTANE								800	1900			
n-HEXANE	500	1800			1			50	180			
PROPANE	1000	1800			1			1000	1800			
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	500	2000			1				350			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BUTANE			1000 (EX)	
n-HEXANE	50			
PROPANE			Simple asphyxia nt (D), explosion hazard (EX)	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	(L)	[(L)]; [5 (I)];		

(L) - Exposure by all routes should be carefully controlled to levels as low as possible

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

Physical and Chemical Properties

Density5.08740 lb/galDensity VOC4.8325 lb/gal% VOC94.99041%AppearanceAerosol ProductOdor ThresholdN.A.Odor DescriptionSolventpHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.Usper Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Freezing PointN.A.Lowe Diffusion LevelN.A.Low Boiling PointN.A.Ketting PointN.A.Na	
% VOC94.99041%AppearanceAerosol ProductOdor ThresholdN.A.Odor DescriptionSolventpHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.Kana Markan M	
AppearanceAerosol ProductOdor ThresholdN.A.Odor DescriptionSolventpHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Kustow Boiling PointN.A.Kustow Boiling PointN.A.Kustow Boiling PointN.A.Kustow Boiling PointN.A.Kustow Boiling PointN.A.	
No.Odor ThresholdN.A.Odor DescriptionSolventpHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Vapor DensityN.A.Vapor DensityN.A.Freezing PointN.A.Kong PointN.	
Odor DescriptionSolventpHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Vapor DensityN.A.Vapor DensityN.A.Metting PointN.A.Freezing PointN.A.Low Boiling PointN.A.NAN.A.Kater Stater State	
pHN.A.Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.NameN.A.Na	
Water SolubilityN.A.FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.NAN.A.Kathara MarkN.A.NA <td< td=""><td></td></td<>	
FlammabilityFlash point below 73°F/23°CVapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Vapor DensityN.A.Vapor DensityN.A.Freezing PointN.A.Low Boiling PointN.A.NAN.A.	
Vapor PressureN.A.Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Flash PointN.A.ViscosityN.A.Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
ViscosityN.A.Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Lower Explosion LevelN.A.Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Upper Explosion LevelN.A.Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Vapor DensityN.A.Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Melting PointN.A.Freezing PointN.A.Low Boiling PointN.A.	
Freezing PointN.A.Low Boiling PointN.A.	
Low Boiling Point N.A.	
-	
Line Delle Delle	
High Boiling Point N.A.	
Decomposition Pt N.A.	
Auto Ignition Temp N.A.	
Evaporation Rate N.A.	

# SECTION 10) STABILITY AND REACTIVITY

## Stability

The product is stable under normal storage conditions.

#### **Conditions to Avoid**

High temperatures.

# **Incompatible Materials**

No data available.

## Hazardous Reactions/Polymerization

None known.

# **Hazardous Decomposition Products**

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

# SECTION 11) TOXICOLOGICAL INFORMATION

## Skin Corrosion/Irritation

Causes skin irritation

## Classification of the substance or mixture

No data available

# Serious Eye Damage/Irritation

Causes serious eye irritation

## Carcinogenicity

No data available

## Germ Cell Mutagenicity

No data available

# **Reproductive Toxicity**

Suspected of damaging the unborn child.

## **Respiratory/Skin Sensitization**

No data available

# Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

# Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

# **Aspiration Hazard**

May be fatal if swallowed and enters airways

## Acute Toxicity

#### 0000110-54-3 n-HEXANE

LC50 (male rat): 38500 ppm (4-hour exposure); cited as 77000 ppm (271040 mg/m3) (1-hour exposure) (15) LC50 (rat): 48000 ppm (4-hour exposure) (16) LC50 (rat): 73680 ppm (260480 mg/m3) (4-hour exposure) (n-hexane and isomers) (1,3) LD50 (oral, 14-day old rat): 15840 mg/kg (3) LD50 (oral, young rat): 32340 mg/kg (3) LD50 (oral, adult rat): 28700 mg/kg (3,16) 0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9) LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)

# SECTION 12) ECOLOGICAL INFORMATION

## Toxicity

No data available

## Persistence and Degradability

No data available.

# **Bio-Accumulative Potential**

No data available.

# Mobility in Soil

No data available.

# **Other Adverse Effects**

No data available.

# SECTION 13) DISPOSAL CONSIDERATIONS

# Waste Disposal

DOUBLE B BLOOMCO QUICK DETAIL

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 14) TRANSPORT INFORMATION**

## **U.S. DOT Information**

UN number: UN1950

Proper shipping name: Aerosols, flammable

Hazard class: 2.1

Packaging group: NA

Hazardous substance (RQ): No Data Available

Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision:(each not exceeding 1 L capacity) (LTD QTY)

## **IMDG** Information

UN number: UN1950

Proper shipping name: Aerosols, flammable

Hazard class: 2.1

Packaging group: NA

Marine Pollutant: No Data Available

Note / Special Provision:(each not exceeding 1 L capacity) (LTD QTY)

# **IATA Information**

UN number: UN1950 Hazard class: 2.1 Packaging group: NA Proper shipping name: Aerosols, flammable Note / Special Provision: (each not exceeding 1 L capacity) (LTD QTY)


# **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0064742-49-0	NAPHTHA (PETROLE- UM),HYDROTREATED LIGHT	25% - 50%	SARA312,VOC,TSCA,ACGIH,OSHA
0000110-54-3	n-HEXANE	25% - 50%	SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, CA_Prop65 - California Proposition 65, OSHA
0000074-98-6	PROPANE	10% - 20%	SARA312,VOC,TSCA,ACGIH,OSHA
0000106-97-8	BUTANE	5% - 10%	SARA312,VOC,TSCA,ACGIH
0063148-62-9	POLYDIMETHYLSILO XANE	5% - 10%	SARA312,TSCA

#### Glossary

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Material Information System.



#### (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

# DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.