

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

SECTION 1: Identification

- 1.1 Product identifier**
Trade name **Jade Fabric Guard**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Relevant identified uses Fabric waterproofing
Textile treatment
HS code 3809.91.00.
- 1.3 Details of the supplier of the safety data sheet**
B&B Blending, LLC
10963 Leroy Drive
Northglenn
CO 80233
United States

telephone 1.800.875.6320, 1.303.289.6320
e-mail: info@bbblending.com
website bbblending.com
e-mail (competent person) Btirrell@bbblending.com
- 1.4 Emergency telephone number**
Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard identification

- 2.1 Classification of the substance or mixture**
Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.7	Reproductive toxicity	2	Repr. 2	H361f

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

- 2.2 Label elements**

Labeling

Signal word **Danger**

Pictograms

GHS02, GHS08



Hazard statements

H225 Highly flammable liquid and vapour.
H361f Suspected of damaging fertility.



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Precautionary statements

- P202** Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P308+P313 IF exposed or concerned: Get medical advice/ attention.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling

Octamethylcyclotetrasiloxane

2.3 Other hazards

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
tert-butyl acetate	CAS No 540-88-5	≥ 6	Flam. Liq. 2 / H225	C(c)
octamethylcyclotetrasiloxane	CAS No 556-67-2	≥ 0.1	Flam. Liq. 3 / H226 Repr. 2 / H361f	PBT vPvB
menthone	CAS No 89-80-5 10458-14-7 1074-95-9	< 100	Flam. Liq. 4 / H227	
dl-limonene (racemic)	CAS No 138-86-3	< 0.1	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 Skin Sens. 1 / H317	
alpha-Pinene	CAS No 80-56-8	< 0.1	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Asp. Tox. 1 / H304	

Notes

C(c): The substance is a specific isomer. Other isomers see Part 3 of the Regulation (EC) No 1272/2008

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic)

vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

For full text of abbreviations: see SECTION 16.

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray. BC-powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x). Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). collect spillage

sawdust

kieselgur (diatomite)

sand

universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

General rule

Do not use for squirting or spraying.

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
CA	tert-butyl acetate	540-88-5	OEL (AB)	200	950						OHS Code
CA	tert-butyl acetate	540-88-5	OEL (BC)	200							"BC Regulation"
CA	tert-butyl acetate	540-88-5	OEL (ON-MoL)	200							MoL
CA	tert-butyl acetate	540-88-5	PEV/VEA	200	950						Regulation OHS
CA	2-pinene	80-56-8	OEL (ON-MoL)	20							MoL
CA	pin-2(3)-ene	80-56-8	OEL (BC)		20						"BC Regulation"
CA	pin-2(3)-ene (selected monoterpene)	80-56-8	OEL (AB)	20	111						OHS Code
CA	α-pinene	80-56-8	PEV/VEA	20	112						Regulation OHS

Notation

- Ceiling-C Ceiling value is a limit value above which exposure should not occur
- STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
tert-butyl acetate	540-88-5	DNEL	159 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
tert-butyl acetate	540-88-5	DNEL	714 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
tert-butyl acetate	540-88-5	DNEL	22.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
menthone	89-80-5 10458-14-7 1074-95-9	DNEL	6.99 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
menthone	89-80-5 10458-14-7 1074-95-9	DNEL	1.98 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
alpha-Pinene	80-56-8	DNEL	5.98 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
tert-butyl acetate	540-88-5	PNEC	0.016 mg/l	aquatic organisms	freshwater	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.002 mg/l	aquatic organisms	marine water	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.15 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.172 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.017 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.025 mg/kg	terrestrial organisms	soil	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediments	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediments	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	28.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	2.82 µg/l	aquatic organisms	marine water	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	1 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	1.3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	0.13 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
menthone	89-80-5 10458-14-7 1074-95-9	PNEC	0.244 mg/kg	terrestrial organisms	soil	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	4 µg/l	aquatic organisms	freshwater	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	0.4 µg/l	aquatic organisms	marine water	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	3.26 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	1.033 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	0.103 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	1.35 mg/kg	aquatic organisms	water	short-term (single instance)
alpha-Pinene	80-56-8	PNEC	0.539 mg/kg	terrestrial organisms	soil	short-term (single instance)



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid
Color	Colorless
Particle	Not relevant Liquid
Odor	Mint - Like solvent

Other safety parameters

PH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	97.8 °C
Flash point	22 °C at 101.3 kPa 72 °F at 1 atm
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant Fluid
Vapor pressure	42 Torr at 20 °C
Density	0.916 g/ml at 25 °C 7.64 lb/gal at 25 °C
Vapor density	This information is not available



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Solubility(ies)	Not determined
Partition coefficient	
- n-octanol/water (log KOW)	This information is not available
Auto-ignition temperature	384 °C Auto-ignition temperature (liquids and gases)
Viscosity	Not determined
Explosive properties	Not explosive GHS of the United Nations, annex 4
Oxidizing properties	None

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 Maximum permissible surface temperature on the equipment: 300 °C
---	--

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated

Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed or in contact with skin.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
tert-butyl acetate	540-88-5	LC50	240 mg/l	fish	96 h
tert-butyl acetate	540-88-5	EC50	410 mg/l	aquatic invertebrates	24 h
tert-butyl acetate	540-88-5	ErC50	64 mg/l	algae	96 h
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
menthone	89-80-5 10458-14-7 1074-95-9	EC50	74.7 mg/l	aquatic invertebrates	48 h



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
menthone	89-80-5 10458-14-7 1074-95-9	ErC50	172.9 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
tert-butyl acetate	540-88-5	EC50	410 mg/l	aquatic invertebrates	24 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks


Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

SECTION 14: Transport information

14.1 UN number	1123
UN RTDG	UN 1123
IMDG-Code	UN 1123
ICAO-TI	UN 1123
14.2 UN proper shipping name	BUTYL ACETATES
UN RTDG	BUTYL ACETATES
IMDG-Code	BUTYL ACETATES
ICAO-TI	Butyl acetates
14.3 Transport hazard class(es)	
UN RTDG	3
IMDG-Code	3
ICAO-TI	3
14.4 Packing group	II Substance presenting medium danger
UN RTDG	II
IMDG-Code	II
ICAO-TI	II
14.5 Environmental hazards	Non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
	There is no additional information.
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.
14.8 Information for each of the UN Model Regulations	
	Transport information
	National regulations
	Additional information(UN RTDG)
UN number	1123
Class	3
Packing group	II
Danger label(s)	3
	
Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -
Danger label(s) 3



Special provisions (SP) -
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
EmS F-E, S-D
Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
tert-butyl acetate	540-88-5		1	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
tert-butyl acetate	540-88-5				1.0 %



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
tert-butyl acetate	540-88-5	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
tert-butyl acetate	540-88-5		F3
dl-limonene (racemic)	138-86-3		F2
alpha-Pinene	80-56-8		F3

Legend

- F2 Flammable - Second Degree
- F3 Flammable - Third Degree

Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ACETIC ACID, 1,1-DIMETHYLETHYL ESTER	540-88-5	E

Legend

- E Environmental hazard

Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
tert-butyl acetate	540-88-5	T

Legend

- T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
(+)-Pulegone	89-82-7	0.0056		cancer

VOC content

Regulated Volatile Organic Compounds (VOC-EPA)	0.2002 %
Regulated Volatile Organic Compounds (VOC-Cal ARB)	0.2002 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



Safety Data Sheet

acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation. Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
ACGIH®	American Conference of Governmental Industrial Hygienists
Asp. Tox.	Aspiration hazard
Cal ARB	California Air Resources Board



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin



Safety Data Sheet
acc. to Hazardous Products Regulations
(HPR)

Jade Fabric Guard

version number GHS 1.0.

Date of compilation. 2022-01-19.

Abbr.	Descriptions of used abbreviations
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.
Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.