



18229-4070

Spec: 20/410, 22/410, 24/410,
28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18229-7070

Spec: 20/410, 22/410, 24/410,
28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18229-8070

Spec: 22/410, 24/410, 28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18229-33070

Spec: 24/410, 28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18229-35070

Spec: 24/410, 28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18229-36070

Spec: 24/410, 28/410
Discharge Rate: 0.5-0.7CC, 1.0CC



18227-1040

Spec: 18/410, 18/415, 20/410,
20/415, 24/410
Discharge Rate: 0.2-0.4CC



18227-1J040

Spec: 18/415
Discharge Rate: 0.4CC



Ribbed/Smooth + AS overcap

18227-2040

Spec: 20/410, 24/410
Discharge Rate: 0.4CC



18227-3040

Spec: 20/410, 24/410
Discharge Rate: 0.2-0.4CC



18229-1040

Spec: 18/415, 20/410, 24/410
Discharge Rate: 0.4CC



18229-2040

Spec: 20/410, 24/410
Discharge Rate: 0.4CC



Smooth + AS overcap

18229-3040

Spec: 20/410, 24/410
Discharge Rate: 0.4CC



18229-6020

Spec: 20/410, 24/410
Discharge Rate: 0.2CC



18229-9040

Spec: 18/410, 18/415, 20/410,
20/415, 24/410
Discharge Rate: 0.2-0.4CC



Double Wall

18229-11040

Spec: 24/410
Discharge Rate: 0.4CC



18229-10040

Spec: 18/415, 20/410, 24/410
Discharge Rate: 0.4CC



18229-12040

Spec: 20/410, 24/410
Discharge Rate: 0.4CC



18229-15040

Spec: 18/410, 18/415
Discharge Rate: 0.2-0.4CC



External diptube

18229-15T040

Spec: 18/410, 18/415
Discharge Rate: 0.2-0.4CC



18229-16040

Spec: 18/410, 20/410, 20/415,
24/410
Discharge Rate: 0.2-0.4CC



18229-17020

Spec: 18/415, 20/410
Discharge Rate: 0.2CC



18229-18040

Spec: 20/410
Discharge Rate: 0.4CC



18229-19040

Spec: 20/410, 24/410
Discharge Rate: 0.4CC



18229-20025

Spec: 20/410
Discharge Rate: 0.25CC



18229-21025

Spec: 20/410
Discharge Rate: 0.25CC



18229-22025

Spec: 20/410
Discharge Rate: 0.25CC



18229-23025

Spec: 20/410
Discharge Rate: 0.25CC



18229-24025

Spec: 20/410
Discharge Rate: 0.25CC



18229-25025

Spec: 20/410
Discharge Rate: 0.25CC



18229-26025

Spec: 20/410, 24/410
Discharge Rate: 0.25CC



18229-27025

Spec: 18/410, 20/410
Discharge Rate: 0.25CC



18229-28040

Spec: 24/410
Discharge Rate: 0.4CC



18229-30040

Spec: 18/415, 20/410, 24/410
Discharge Rate: 0.4CC



18229-37P025

Spec: 18/410, 20/410, 24/410, 28/410
Discharge Rate: 0.2-0.25CC