

T8 Plus

F32T8/TL841 PLUS ALTO HV 30PK

Philips PLUS T8 lamps are energy-efficient lighting solutions and offer long life.

Product data

| General Information Base G13 [Medium Bi-Pin Fluorescent] Life 12-Hr Programstart [Hrs] 44000 h Life 12-Hr Instant Start [Hrs] 36000 h Life 3-Hr Program Start [Hrs] 38000 h Life 3-Hr Instant Start [Hrs] 30000 h Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical Power (Rated) (Nom) 32 W | | |
|---|------------------------------------|---|
| Life 12-Hr Programstart [Hrs] 44000 h Life 12-Hr Instant Start [Hrs] 36000 h Life 3-Hr Program Start [Hrs] 38000 h Life 3-Hr Instant Start [Hrs] 30000 h Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | General Information | |
| Life 12-Hr Instant Start [Hrs] 36000 h Life 3-Hr Program Start [Hrs] 38000 h Life 3-Hr Instant Start [Hrs] 30000 h Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Base | G13 [Medium Bi-Pin Fluorescent] |
| Life 3-Hr Program Start [Hrs] 38000 h Life 3-Hr Instant Start [Hrs] 30000 h Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Life 12-Hr Programstart [Hrs] | 44000 h |
| Life 3-Hr Instant Start [Hrs] 30000 h Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Life 12-Hr Instant Start [Hrs] | 36000 h |
| Features ALTO® Plus Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 | Life 3-Hr Program Start [Hrs] | 38000 h |
| Footnotes Fluorescent/CFL 1 Circle E- The encircled E means this bulb meets Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Life 3-Hr Instant Start [Hrs] | 30000 h |
| Federal minimum efficiency standards. Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Features | ALTO® Plus |
| Light Technical Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Footnotes Fluorescent/CFL 1 | Circle E- The encircled E means this bulb meets |
| Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | | Federal minimum efficiency standards. |
| Color Code TL841 [CCT of 4100K (841)] Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | | |
| Initial lumen (Nom) 2950 lm Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Light Technical | |
| Color Designation TL841 Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Color Code | TL841 [CCT of 4100K (841)] |
| Design Mean Lumens 2800 lm Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Initial lumen (Nom) | 2950 lm |
| Correlated Color Temperature (Nom) 4100 K Color Rendering Index (Nom) 85 Operating and Electrical | Color Designation | TL841 |
| Color Rendering Index (Nom) 85 Operating and Electrical | Design Mean Lumens | 2800 lm |
| Operating and Electrical | Correlated Color Temperature (Nom) | 4100 K |
| | Color Rendering Index (Nom) | 85 |
| | | |
| Power (Rated) (Nom) 32 W | Operating and Electrical | |
| | Power (Rated) (Nom) | 32 W |
| | | |

| Mechanical and Housing | |
|---------------------------------|-------------------------------|
| Cap-Base Information | Green Base |
| Nominal Length (Inch) | 48 |
| | |
| Approval and Application | |
| Energy Saving Product | Energy Saving |
| Picogram Per Lumen Hour | 20 pg/lm.h |
| Mercury (Hg) Content (Nom) | 1.7 mg |
| | |
| Product Data | |
| Order product name | F32T8/TL841 PLUS ALTO HV 30PK |
| EAN/UPC - Product | 046677281793 |
| Order code | 281790 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 30 |
| Material Nr. (12NC) | 927852084104 |
| Net Weight (Piece) | 0.136 kg |
| | |
| | |

Warnings and Safety

• Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Datasheet, 2019, January 17 data subject to change

T8 Plus

Dimensional drawing

Product

F32T8/TL841 PLUS ALTO HV 30PK



F32T8/841 48 ALTO Plus ES



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.