

By grower's choice

1000W CMH SYSTEM


Installation and Operating Instructions



TECHNICAL SPECIFICATIONS:

Rated Main Voltage:	208V 240V 277V 347V
Input Current:	4.8A 4.2A 3.6A 2.9A
Input Frequency:	50/60 Hz
Power Factor:	>0.98
THD:	<10%
Required Lamp Voltage:	110V ~ 140V
Illumination Surface:	5' X 5'

State	Off-DB	On-DB	Off-Rem	On-Rem	Open	Short	HTP	LVP	HVP
Green	Off	Off	Flash	On	On	Off	On	Flash	Flash
Red	Flash	On	Off	Off	Flash	Strobo	On	Flash	On



Off-DB =Ballast is switched off by dim button.

On-DB = Ballast is switched on by dim button.

Off-Rem = Ballast is switched off by remote.

On-Rem =Ballast is switched on by remote.

Open =Ballast is off because of an open contact or defect bulb

Short =Ballast is off because of short-circuit or defect bulb

Short =Ballast is off because of short-circuit or defect bulb

HTP =Ballast is off because of High Temperature Protection (Ballast is too hot)

LVP =Ballast is off because of Low Voltage Protection

=Ballast is off because of High Voltage Protection

When both LED's are off, check fuse and power supply.

• Strobo is a very fast flash



SAFETY WARNINGS:

Grower's Choice Master Pursuit 1000W CMH System is special designed and tested pairing with Grower's Choice 500W MP CMH Lamps. Using other lamps in this system may cause harm to the system or the lamps and void warranty.

- Always adhere to the local rules and regulations when installing or using the fixture.
- Do not open the ballast or disassemble the fixture, it contains no service parts inside. Doing so will void the warranty.
- Wearing protective gloves is recommended during installation, servicing lamps and replacing reflectors.
- Always disconnect from the mains before performing any maintenance to the fixture.
- This fixture is designed and tested for damp indoor location only. Do not use in wet environment or outdoors.
- The fixture and lamps will get hot during operation. Do not touch while light is on. Keep this product away from children.
- Always allow at least 20 minutes for lamps to cool before handling.

- Keep power cord away from hot surface
- Do not use the fixture when either its lamp or power cord are damaged. Contact us immediately.
- Do not plug this system into a supply voltage other than what is instructed on the fixture.
- This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation systems operating between 0.45-30 MHz.
- Do not expose fixture to condensing humidity, heavy mist, fog or direct spray.
- Do not expose fixture to direct sunlight during use or other light that could heat up the fixture.
- Wearing protective glasses is highly recommended working under white light is on.



500W MP CMH Lamps

CONTENTS:

- Fixture with the one set of power cord attached.
- 2x C182/O CMH Lamps
- Gloves

Not Included:

- RJ cord
- Controller
- Hanging kit
- Protection glasses

INSTALLATION:



- Switch off mains power.
- Remove the system from the box along with all additional parts.
- Make sure the end wires are straight.
- Remove the lamp-holder covers.



• Using the gloves provided, carefully install the lamps.



• Always disconnect from the mains before performing any maintenance to the fixture.



• Allow at least 20 minutes for the lamps to cool before handling.




• Wearing protective gloves and glasses are recommended.





INSTALL LAMPS

• Line up the correct pins with the lamp-holder.



• Carefully press down and turn 30-45 degrees clockwise until lamp locks in. The lamp holder will give a snap-in sensation to confirm proper insertion.







• Close the lamp holder covers.

REPLACEMENT OF LAMPS

• Open the lamp holder covers.




• Replacement of the lamp.



• Carefully turn 30-45 degrees counter clockwise until the lamp losen up.


REPLACEMENT OF REFLECTOR




• Hang the fixture per light distribution plan: (different ways of hanging)



"C" shaped hook installation



Intermediate sling installation



Sling installation

CONNECTING THE FIXTURE TO THE MAINS

• For 208V-240V to NEMA L6-15P

• Straight NEMA L6-15P



• For 277V to NEMA L7-15P

• Straight NEMA L7-15P






• For 347V to NEMA L24-20P

• Straight NEMA L24-20P



• Pigtail Wiring (Certified electrician installation required)









NEMA L6-15P

NEMA L7-15P

NEMA L24-20P

Wire	277V/347V
White	Neutral (N)
Black	Phase (L)
Green	Ground (🍚)

WARRANTY:

GROWER'S CHOICE warrants the mechanical and electronic components of their product to be free of defects in material and workmanship if used under normal operating conditions for a period of three (3) years from the original date of purchase. If the product shows any defects within this period and that defect is not due to user error or improper use, GROWER'S CHOICE shall, at its discretion, either replace or repair the product using suitable new or reconditioned products or parts. For HID lamps, the warranty period is one (1) year from the original date of purchase. GROWER'S CHOICE warranty liability extends only to the replacement cost of the product. In case GROWER'S CHOICE decides to replace the entire product, the limited warranty shall apply to the replacement product for the remaining initial warranty period.

GROWER'S CHOICE shall not be held responsible for any damage caused by the operation of the unit, be it incidental or consequential or any type including, without limitation, damage or injury caused to other products or machinery or buildings. Nor will responsibility be accepted for loss of time or profit, loss of finished product, or for any inconvenience caused in any way whatsoever.



Aste. Pussuit By grower's choice

Tel: (909) 972-8419

E-mail: info@growersc.com **Website:** www.growersc.com

Address: 1500 S Milliken Ave, Suite B, Ontario, CA, 91761

