
## SSS16B4-4-\*\*

Mounting Height Alum. Pole Cap With Stainless Steel Screws

→ "B" Wall Carbon Steel With Painted Finish





- (4) NC Galvanized Steel Anchor Bolts, AASHTO M314-90 Grade 55, 10" of Threaded End Galvanized Per ASTM A153.
- (4) NC Galvanized Steel Hex. Nuts
- (4) Galvanized Steel Lockwashers
- (4) Galvanized Steel Flatwashers

## Reinforced Handhole (3" x 5") With Steel Cover And Stainless Steel Screws "C" Butt Diameter ABS Plastic Base Cover



## STANDARD FINISHES: (add as suffix)

BA Black Powder Paint BH White Powder Paint BM Bronze Powder Paint BV Dark Green Powder Paint

General Shaft Assembly	Α	В	С	D	Е	F	Э				Н					
	Mtg	Gauge	Butt	Top	Base		_Bolt _	Net	Lum .	Anchor	. Arm					
Assembly	Hgt		Dia.	Dia.	Dia.		Project	Weight	Weight	Bolts	Length	70	80	90	100	110
SSS	16	11	4	4	10	8 - 10	2.75	113	150	.75 x 17 x 3		19.2	14.4	10.9	8.3	6.4