

Item#: WL55436

INTERIOR COMMERCIAL SPACES

High Efficiency, Energy Saving
Up to 36% Savings vs. T8 Fluorescent
Low glare, bright consistent lighting

For covered ceilings onlyEarthquake proof hooks included

2X4 LUMINARIES FOR AMBIENT LIGHTING OF

Ideal for offices, conference rooms, hospitals, lobbies, hotels, classrooms, workshops, cafeterias and other

LED 2X4 PANEL

FEATURES

APPLICATION


common areas.

INDUSTRIAL AND COMMERCIAL LIGHTING MFR SINCE 2003 PROJECT NAME:

ITEM #: ______ FIXTURE SCHEDULE: _____

NOTES: __

ELECTRICAL		
Wattage	75W	
Voltage	100-277V	
Current	1700mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	9.8	
LIGHTING PERFORMANCE		
Lumens	8300	
Lumens Per Watt (LPW)	111	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	83	
R9 (Red Value)	10	
R13 (Skin Tones)	85	
Beam Angle	120°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B3 - U1 - G1	
Dimmable Lighting Control	(Dimmable 1-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Seoul	
Driver	554366	
CONSTRUCTION		
Housing	Aluminum	
Lens		
Base / Power Supply	Hard Wired	
Finish	White	
QUALIFICATIONS		
NTERTER.		



Rohs

compliant



Warehouse-Lighting.com 2750 South 163th St New Berlin, WI 53151

(4)

CERTIFIED

Warehouse-Lighting.com Phone: 888-454-4480 Requests@warehouse-lighting.com

Item#: WL55436

DIMENSIONS (Inches)

Install Instructions

LM79

LM80

IES Download from Web Item


Length	47.8"		
Width	23.7"		
Height	1.7"		
Net Weight (Lbs)	13.7		
SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		

VIEW

VIEW

VIEW

VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768023401	49.5" x 25.6" x 4.5"	32.9
Individual Box	1	811768023404		16.5
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
WL55436	LED 2X4 PANEL/75W/50K/DIMM/120-277V - DLC °	2
ACCESSORIES	5	
WL55129	2X4 FLANGE KIT FOR PANEL & TROFFER/WHT	1
WL55442	2X4 SURFACE MOUNT KIT FOR LED PANEL/WHT	25
WL55445	SUSPENDED CABLE MOUNTING KIT FOR LED PANEL	100
WL55449	EMERGENCY PACK FOR LED PANEL 15W/90 MIN - T20C	6
WL55450	EMERGENCY PACK FOR LED PANEL 25W/90 MIN - T20C	6
REPLACEMEN	IT PARTS	
WL554366	75W REPLACEMENT DRIVER	1

ADDITIONAL INFORMATION:

Family Item: WL55434/3500K • WL55435/4000K



Warehouse-Lighting.com 2750 South 163th St New Berlin, WI 53151