

Item#: 57742 LED 48" VAPOR TIGHT - 3 LAMP LED READY FIXTURE

FEATURES

- · Diffusing lens for uniform light.
- Gasket formed to housing provides a seamless seal and protects lamps from dust and humidity.
- Die formed galvanized steel mounting brackets.
- · Stainless steel clips
- 18 AWG 3 Conductor (10A /-40°C ~ 90°C /Dia .305")

MOUNTING

Surface or suspended mounting.

APPLICATION

Ideal for commercial and industrial environments; tunnels, stairwells, parking garages, cold storage, and airports. *Not designed for use in car washes, truck wash bays, or where exposed to harsh chemicals.*



ELECTRICAL

Lamps Type (Not included)	Т8
Number of Lamps	3
Voltage	120-277V
ENVIRONMENT	
Operating Temperature	-4° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65
LIFESPAN	
Warranty (Years)	2

CONSTRUCTIONS

Housing	Polycarbonate
Lens	Vandal Resistant / PC
Sockets	Non-Shunted
Base / Power Supply	Hard Wired
Clips	Stainless Steel
Finish	White

CERTIFICATIONS



Operating temperature may vary depending on the lamps used. • Specifications are subject to change without notice.



Item#: **57742 LED 48" VAPOR TIGHT - 3 LAMP**

DIMENSIONS (Inches)	
Length	50"
Width	10"
Height	4.1"
Weight (Lbs)	

Length	50"
Width	10"
Height	4.1"
Weight (Lbs)	

Û Û 50"

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768025170	50.8" x 10.4" x 3.3"	12.6
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
57742	LED 4FT VAPOR TIGHT FOR 3 T8	1
REPLACEM	ENT PARTS	
REPLACEM 57730	ENT PARTS STAINLESS STEEL CLIPS	1

ADDITIONAL INFORMATION:

• Pairs with Direct Wire Single-End or Double-End UL Type B Lamps. Single-end pre-wired fixtures can also be wired double-end by the end- user if needed. Follow specific lamp installation wiring instructions for correct wiring.

