



**PRODUCT DESCRIPTION**

Reducing the scale of the classic cylinder sconce is intended for use in applications needed to meet ADA requirements. The sconce profiles extend vertically casting ample light both upwards and downwards. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.

**MEASUREMENTS**

DIMENSION : 2.5" W x 14.5" H x 3.25" Ext  
 BACK PLATE : 4.5" W x 4.5" H x 7.25" HCO  
 HANGING WEIGHT : 2.74 lb

**LAMPING**

INPUT VOLTAGE : 120-277V  
 LUMENS : 1,400 Rated (1,190 Del.)  
 BULB : 2 x 7W LED DC Integrated , 14W Total  
 BULB INCLUDED : (Integrated)  
 DIMMABLE : Triac  
 CRI : 90 CRI  
 COLOR\_TEMP : 3000K  
 LIGHTING\_DIRECTION : Up & Down

**FINISHES OPTION**

 Black (BK)

**MATERIAL**

Aluminum, Glass

**RATINGS**

cETLus  
 Wet Location  
 ADA  
 DARKSKY



**ADDITIONAL**

INSTALL UP/DOWN: Up  
 RATED LIFE 25000 Hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746  
 EASTERN DISTRIBUTION CENTER  
 101 GARDNER PARK | PEACHTREE CITY, GA 30269  
 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com