

PROJECT NAME:	
CATALOG NUMBER:	
NOTES:	
FIXTURE SCHEDUILE:	

## **LED Frosted Linear Fixture**



This Frosted Translucent linear down light fixture can fulfil several lighting needs. It is available in 4-foot and 8-foot lengths and in white body surrounded by durable acrylic. It can be surface mounted as well suspended with included aircraft cables and power feed. A switch inside the fixture allows the selectable CCT (3500K / 4000K / 5000K) to be set in the field. The main body is constructed of extruded aluminum and has a side in polycarbonate diffuser between two translucent pieces of acrylic to help reduce glare.

## Features:

- Includes 10' adjustable aircraft cables
- Includes 10', 5 wire power feed cable and canopy
- Wattage:

4 Foot: 40W8 Foot: 80W

- CCT Selectable: 3500K / 4000K / 5000K

Voltage: 120-277V0-10V Dimmable

- Lifetime: 50000+ hours

- Operating Temp: -22°F to 104°F (-30°C to 40°C)

cULus Listed5 Year Warranty








SKU	Dimensions	Finish	Lumens
	47 5/16" L x 2 3/8" W x 2 3/4" H	Frosted	3500K = 4400
BEAMLED4-TPFR-40W-3CT-DMV			4000K = 4500
			5000K = 4600
	95 9/32" L x 2 3/8" W x 2 3/4" H	Frosted	3500K = 8800
BEAMLED8-TPFR-80W-3CT-DMV			4000K = 8900
			5000K = 9200

Series	Length	Finish	Wattage	ССТ	Dimming
DEANALED	4 = 4 foot	TPFR	40W	3CT = CCT Selectable: 3500K / 4000K / 5000K DMV =	DMV = 0-10V Dimmable
BEAMLED	8 = 8 foot	(Frosted) 8	80W		PINIA – 0-10A DILILIUADIE

## **LED Frosted Linear Fixture**

## **Photometrics**



Luminaire	3500K
Input Voltage(VAC)	119
Power (W)	43.22W
Delivered Lumen(Lm)	4733.6LM
Efficacy(Lm/W)	112Lm/W
Beam Angle	H99.1 V139.2
Power Factor(PF)	>99.8
Color Rendering Index(CRI)	>80