




INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Beam Direct Series



This linear down light fixture can fulfill a number of lighting needs. It is available in 2 foot, 4 foot, 6 foot and 8 foot lengths and in white, black, or silver finishes. It can be surface, wall*, recessed* and pendant mounted. Mix and match fixture lengths with L, X, Y, and T shaped connectors.

Specifications – 6 Foot

CRI	>80	Ratings & Certifications	cULus, Damp Location
Light Source	Integrated LED	Beam Angle	Wide
Dimmable	0-10v	Linkable	600 watt maximum
Color Temperature	3000K - 3500K - 4000K - 5000K	Mounting Options	Surface, Suspended, Wall*, Recess*
Wattage	60W	Operating Temperature	-20° C to 40° C (-4° F to 104° F)
LPW	110	Lumens	6600
Voltage	120-277v	Lens	Polycarbonate Frosted
Product Dimensions	70.71" L x 2.76" W x 3.35" H	Product Weight	8.81 lbs.
Shipping Dimensions	71.85" L x 2.99" W x 3.74" H	Shipping Weight	9.92 lbs.
Finish	Black or White	Warranty	5 Years

*Hardware purchased separately.





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

Beam Direct G2				Example: BEAMLED8-80W-4CT-DMV-BK-G2		
Series	Length	Wattage	CCT	Voltage	Finish	Generation
BEAMLED	2 4 Foot	20W 20 Watt	4CT 30K-35K-40K-50K	DMV Universal Voltage (120-277) 0-10v dimming	BK Black	G2
	4 4 Foot	40W 40 Watt			WH White	
	6 6 Foot	60W 60 Watt			SV Silver *4' and 8' only	
	8 8 Foot	80W 80 Watt				

Mount Options

Suspended (Included)



Wall Mount Kit




Surface Mount Kit (Included)



Mud Flange Kit



Recessed Flange Kit





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____


DLC Information

Item	DLC Version	DLC ID	Wattage	Lumens*
beamled4-40w-4ct-dmv-wh-g2	5.1 Premium	S-ZIAU9W	40W	4608
beamled8-80w-4ct-dmv-wh-g2	5.1 Premium	S-T11QSR	80W	9263

Dimensions

Item	Length	Width	Height	Weight
beamled2-20w-4ct-dmv- [bk, wh]-g2	23.9"	2.76"	3.35"	3.74 lbs.
beamled4-40w-4ct-dmv- [bk, wh, sv]-g2	47.32"	2.76"	3.35"	6.61 lbs.
beamled6-60w-4ct-dmv- [bk, wh]-g2	70.71"	2.76"	3.35"	8.81 lbs.
beamled8-80w-4ct-dmv- [bk, wh, sv]-g2	94.17"	2.76"	3.35"	12.13 lbs.


BEAMLED2




BEAMLED4



BEAMLED6



BEAMLED8






INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Connector Options



Our Linear Architectural Beam G2 series fixtures are now available with innovative connector pieces that let you arrange them in a practically limitless selection of shapes, configurations, and even patterns.



Item	Joint Type	Dimensions	Weight
BEAM-4CCT-L-CNTR-BK-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs
BEAM-4CCT-L-CNTR-WH-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs
BEAM-4CCT-X-CNTR-BK-G2	X	8.82" L x 8.82" W x 3.35" H	2.2 lbs
BEAM-4CCT-X-CNTR-WH-G2	X	8.82" L x 8.82" W x 3.35" H	2.2 lbs
BEAM-4CCT-Y-CNTR-BK-G2	Y	7.91" L x 6.85" W x 3.35" H	1.1 lbs
BEAM-4CCT-Y-CNTR-WH-G2	Y	7.91" L x 6.85" W x 3.35" H	1.1 lbs
BEAM-4CCT-T-CNTR-BK-G2	T	8.82" L x 5.79" W x 3.35" H	1.76 lbs
BEAM-4CCT-T-CNTR-WH-G2	T	8.82" L x 5.79" W x 3.35" H	1.76 lbs



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Compatible Dimmer List

Brand	Model
Lutron	DVSTV-WH Diva 8 Amp 3-way/Single-Pole 0-10V Dimmer
Eaton	Controls DF10P-C1 Decorator 0-10V Dimmer
Cooper	SF10P-W Slide 0-10V Dimmer
LuxDrive	Dimming Control - 0-10V Low Voltage Wall Mount
Lutron	DVTV-WH Diva 30mA Single Pole 0-10V Fluorescent
Leviton	DS710-10Z