EasyLED Series

EasyLED Flat Top Bollard with LED Cone Reflector



Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance Reflector:

Specially Designed Aluminum Cone Reflector for LED.

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included).

LumaFit LED: Array Lumens: 2,089

Delivered Lumens: 1,384 CRI: 83 CCT: 4000K, 5000K Rated Life: 50,000 Hours 5-Year Warranty

Aluminum Boards

Wattage:

Array: 14.5w, System: 17w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Dimmable Driver Listing & Ratings:

CSA: Listed for Wet Locations. IP65 Operating Temperatures: -40°C to +40°C


Options:

Surge Protection Battery Backup

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths Upon Request.





WAREHOUSE-LIGHTING, COM

| EasyLED Flat Top Bollard with LED Cone Reflector | | | |
|--|----------------------|----------------------------|--|
| Catalog # | | Description | |
| Complete Units Ordering Information Example: BOFRLQF1X15U5KZSP | | | |
| BOFRL | Model: | BOFRL | |
| Q | LED Mfr: | Q=QSSI | |
| F | Optics: | F=Medium Beam Spread | |
| 1X | Number of Arrays: | 1X=One | |
| 15 | Wattage: | 15=15w | |
| U | Ballast: | U=120-277V | |
| 5K | CCT: | 4K=4000K, 5K=5000K | |
| Z | Color: | Z=Bronze, W=White, B=Black | |
| - | Mounting: | N/A | |
| | | | |


SF=Single Fuse, DF=Double Fuse,

SP=Surge Protection

DIMENSIONS

SP

Options:



BOFRLQ



WAREHOUSE-LIGHTING.COM

| Catalog # | Description |
|------------|---|
| BOLAN4 | Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts |
| BOLAN8 | Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts |
| BOLAN12 | Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts |
| BOLAN15 | Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts |
| BOLPC | Replacement Polycarbonate Lens |
| BOLRM | Root Mount Kit |
| 3EBL120277 | Provides 90 Minutes of Backup Power. |


LD

To Disease In Unit Of Managing Height Disease In Unit Of Managing Height A Disease Control These Street And Destract Curve (1) Managing Control These Street And Destract Curve (1) Managing Control These Street And Destract Curve


BOFRLQF1X15U5K

EasyLED Series


EasyLED Flat Top Bollard with LED Cone Reflector



BOLAN



BOLPC



BOLRM



3EBL120277

