LED COMPASS HIGH BAY - 100-277V

INSTALL INSTRUCTIONS



PLEASE FIND A QUALIFIED ELECTRICIAN FOR INSTALLATION. Please read the instructions before you install and use the luminaire.

WARNING, CAUTIONS AND OPERATING INSTRUCTIONS

- To reduce the risk of death, personal injury or property damage from fire, electric shock, falling parts, cuts/abrasions, and other hazards read all warnings and instructions included with and on the fixture box and all fixture labels.
- Before installing, servicing, or performing routine maintenance upon this equipment, follow these general precautions.
- · Commercial installation, service and maintenance of luminaires should be performed by a qualified licensed electrician.
- For the installation: If you are unsure about the installation or maintenance of the luminaires, consult a qualified licensed electrician and check your local electrical code.
- To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.
- · Do not make or alter any open holes in an enclosure of wiring or electrical components during kit installation.

WARNING: RISK OF FIRE OR ELECTRICAL SHOCK

- Turn off electrical power at fuse or circuit breaker box before wiring fixture to the power supply.
- Turn off the power when you perform any maintenance.
- · Verify that supply voltage is correct by comparing it with the luminaire label information.
- · Make all electrical and grounded connections in accordance with the National Electrical Code and any applicable local code requirements.
- · All wiring connections should be capped with UL approved wire connectors.


CAUTION: RISK OF INJURY

- Avoid direct eye exposure to the light source while it is on.
- Account for small parts and destroy packing material, as these may be hazardous to children.
- The external flexible cable or cord of this luminaire cannot be replaced.
- Mounting surface should be of sufficient strength to hold more than the weight of the fixture.
- · Suitable for Wet locations.



WARNING DISCONNECT POWER BEFORE INSTALLING OR SERVICING.


GENERAL WIRING DIAGRAM




*Note: For non-dimming applications, cap the purple and pink (or gray) dimming wires separately. Failure to do so may cause malfunctioning and void warranty. • 12V DC AUX wire must be capped if unused.

SAFETY CABLE

(Not included, must be provided by installer.)



500W-600W



LED COMPASS HIGH BAY - 100-277V

INSTALL INSTRUCTIONS







WARNING DISCONNECT POWER BEFORE INSTALLING OR SERVICING.


EYELET INSTALLATION


For: 100W / 150W / 200W 240W / 300W / 400W

- 1. Drill a hole into the ceiling for the appropriate size hook (provided by installer).
- 2. Secure hook to the ceiling and hang the fixture from the hook.
- 3. Install safety cable and secure fixture to it (safety cable provided by installer).
- Connect the electrical cables (see general wiring diagram). If using in wet locations, ensure all electrical connections and installation holes have a water tight seal.












BRACKET INSTALLATION


Bracket included: 500W / 600W (Bracket sold separately for 100W-400W)

- 1. Drill a hole into the ceiling and install expansion screws (provided by installer).
- 2. Attach the bracket to the mounting surface.
- Install safety cable and secure fixture to it (safety cable provided by installer).
- Connect the electrical cables (see general wiring diagram). If using in wet locations, ensure all electrical connections and installation holes have a water tight seal.











BRACKET MOUNTING DIAGRAM



100W / 150W / 200W / 240W / 300W / 400W



500W / 600W