CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC6-40W-MCTP-SA-D CRLC6-40W-MCTP-SA-D-WH

6" LED COMMERCIAL SQUARE & WALL WASH RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name:

Project Name:



8"(H) X 4 1/7"(W) X 7 1/2"(D)

Features

- 6" Haze & White Finish TRIM
- MCTP: The switch is on the light engine
- · Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

• Voltage: 120-277VAC 50/60Hz

Wattage: 27W/34W/40WPower factor: >0.90Efficacy: 80 LPW

Mechanical:

- 6" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 3200LM Max.
- Color temperature: 3000K/3500K/4000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 40W | 3200LM | CRLC6-40W-MCTP-SA-D
- 40W | 3200LM | CRLC6-40W-MCTP-SA-D-WH













Photometrics: CRLC6-40W-MCTP-SA-D





20 15 10 5 2fc 1fc 0.5fc 0.1fc o 5 10 25


BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









CRLC-TRM-6S



CRLC6-40W-MCTP-S-D

White



CRLC-EGN-40W-MCTP-D



CRLC-TRM-6S-WH



CRLC6-40W-MCTP-S-D-WH

Performance Table: CRLC6-40W-MCTP-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC6-40W-MCTP-SA-D	27W	120-277V	2160LM	3000K 3500K 4000K	B1-U1-G0	80
CRLC6-40W-MCTP-SA-D-WH	34W		2720LM			
	40W		3200LM			

Sample Ordering

Watt Color Temp Shape Dimming Housing Model



WH = WHITE

Accessory:

SSL6-RI 6" SQUARE ROUGH-IN PLATE, 26" LONG



SSL6-RI 26"(W) x 8 1/4"(H)

Factory-Installed Option:



EXTERNAL EMERGENCY BACK UP BATTERY

Accessory:

Blank = No Option For Accessories SSL6-RI = 6" SQUARE ROUGH-IN PLATE, 26" LONG

Factory-Installed Option:

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Example:

OPT-EM-HB1EXT

1. CRLC6-40W-MCTP-SA-D 1. CRLC6-40W-MCT-PSA-D

(FOR 40W CRLC6 MCTP 120-277V)

(FOR 40W CRLC6 MCTP 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





