CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC8-15W-MCT-D CRLC8-15W-MCT-D-WH

8" LED COMMERCIAL RECESSED LIGHT



Type:



6" 3 1/2" 9 1/4" 4 1/7"

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

9 1/4"(L) X 6" (H)

Features

- 8" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- Mounting Options: Recessed

5-Year Warranty

Note:

Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz

Wattage: 15WPower factor: >0.90Efficacy: 85 LPW

Mechanical:

- 8" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1275LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 20W | 1720LM | CRLC4-20W-MCT-A-D
- 20W | 1720LM | CRLC4-20W-MCT-A-D-WH













Photometrics: CRLC8-15W-MCT-D





25 20 15 10 5 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25

BUG Rating: B1-U1-G0

15W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









=




CRLC-TRM-8

CRLC8-20W-MCT-D

Whitev









CRLC-TRM-8-WH



CRLC8-20W-MCT-D-WH

Performance Table: CRLC8-15W-MCT-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC8-15W-MCT-D	15W	120-277V	1275LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC8-15W-MCT-D-WH						

Sample Ordering

Model Watt Dimming Housing

CRLC8 = 15W = MCT = D = Blank

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



Example:

1. CRLC8-15W-MCT-D

(FOR 15W CRLC8 MCT 120-277V)

1. CRLC8-15W-MCT-D OPT-EM-HB1EXT (FOR 15W CRLC8 MCT 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)

WH = WHITE





